

CO1 - Assessment Tool - 1 – MCQ

CSA0203 – C Programming

Q1 Operators and Expressions

1 mark

A programmer wants to display the octal equivalent of a decimal number stored as 25 using printf. Which output will the program produce?

A. 31

B. 25

C. 32

D. Error

 Save Answer

Next →

Q2 Operators and Expressions

1 mark

A developer prints an integer value 26 using the %x format specifier. Considering lowercase hexadecimal representation in C, what will be the output?

```
int n = 26;  
printf("%x", n);
```

A. 1A

B. 1a

C. 26

D. Error

 Save Answer

Next →

Q3 Operators and Expressions

1 mark

Nerd initializes a variable using 017 and prints it using %d. Since the value is stored in a different number system, what will be the resulting output?

```
int n = 017;  
printf("%d", n);
```

A. 17

B. 15

C. 16

D. Error

 Save Answer

Next →

Q4 Operators and Expressions

1 mark

A variable is assigned a hexadecimal constant 0xA5 and printed using %d. After decimal conversion, what value will be displayed?

```
int n = 0xA5;  
printf("%d", n);
```

A. 155

B. 165

C. 150

D. Error

 Save Answer

Next →

Q5 Operators and Expressions

1 mark

Geek uses 010 as the value of an integer and prints it using %x. After converting the value appropriately, what will be the final output?

```
int n = 010;  
printf("%x", n);
```

A. 8

B. A

C. 10

D. Error

 Save Answer

Next →

Q6 Operators and Expressions

1 mark

A technician adds a hexadecimal value 0x10 and an octal value 010, then prints the result using %d. What will be the output?

```
printf("%d", 0x10 + 010);
```

A. 24

B. 18

C. 20

D. 16

 Save Answer

Next →

Q7 Operators and Expressions

1 mark

A variable with value 20 is printed using both %o and %x format specifiers in the same statement. What will be the output?

```
int n = 20;  
printf("%o %x", n, n);
```

A. 24 14

B. 20 20

C. 24 20

D. Error

 Save Answer

Next →

Q8 Operators and Expressions

1 mark

A macro #define A 10+5 is used in an expression A*2 without parentheses. What will be the output?

```
#define A 10+5  
printf("%d", A*2);
```

A. 30

B. 25

C. 40

D. Error

 Save Answer

Next →

Q9 Operators and Expressions

1 mark

A macro `#define X 10` is defined, and later a variable with the same name `int X = 5;` is declared. What will happen when printing X?

```
#define X 10  
int X = 5;  
printf("%d", X);
```

A. 10

B. 5

C. Error

D. Garbage

 Save Answer

Next →

Q10 Operators and Expressions

1 mark

A constant variable is declared as `"const int x = 10"` and then reassigned using `"x = x + 5"`. What will be the result?

```
const int x = 10;  
x = x + 5;
```

A. 15

B. 10

C. Error

D. Garbage

 Save Answer

Next →

Q11 Operators and Expressions

1 mark

A student divides an integer (5) by a float (2) and prints the result using %f. What will be the output?

```
int a = 5;  
float b = 2;  
printf("%f", a/b);
```

A. 2.5

B. 2

C. 0.2

D. Error

 Save Answer

Next →

Q12 Operators and Expressions

1 mark

A float variable is initialized as float x = 5/2 and then printed using %f. What will be the output?

```
float x = 5/2;  
printf("%f", x);
```

A. 2.5

B. 2

C. 5

D. Error

 Save Answer

Next →

Q13 Operators and Expressions

1 mark

A character variable is assigned the value 100 and printed using %c. What will be displayed?

```
char c = 100;  
printf("%c", c);
```

A. 100

B. d

C. Error

D. Garbage

 Save Answer

Next →

Q14 Operators and Expressions

1 mark

A macro, A, is defined and then undefined using #undef. What will happen when attempting to print A?

```
#define A 5  
#undef A  
printf("%d", A);
```

A. 5

C. Error

D. Garbage

 Save Answer

Next →

Q15 Operators and Expressions

1 mark

A variable is declared but not initialized, and then printed. What will be the output?

```
int a;  
printf("%d", a);  
Output?
```

B. Error

C. Garbage Value

D. 1

 Save Answer

Next →

Q16 Operators and Expressions

1 mark

A character, 'A', is stored in a variable, and 1 is added to it before printing the result as an integer. What will be the output?

```
char a = 'A';  
int b = a + 1;  
printf("%d", b);
```

A. 66

B. 65

C. A

D. Error

 Save Answer

Next →

Q17 Operators and Expressions

1 mark

A macro #define B 2+3 is used in the expression B + 4. What will be the output?

```
#define B 2+3  
printf("%d", B+4);
```

A. 9

B. 10

C. 11

D. Error

 Save Answer

Next →

Q18 Operators and Expressions

1 mark

A macro `#define X 3+2` is used in the expression `X*X` without parentheses. What will be the output?

```
#define X 3+2
printf("%d", X*X);
```

A. 25

B. 11

C. 19

D. Error

 Save Answer

Next →

Q19 Operators and Expressions

1 mark

An integer is divided by a float and printed using `%f`. What will be the output of `10/3`?

```
int a = 10;
float b = 3;
printf("%f", a/b);
```

A. 3.333333

B. 3

C. 3.01

D. Error

 Save Answer

Next →

Q20 Operators and Expressions

1 mark

A character 'A' is printed using `%d`. What will be the output?

```
char ch = 'A';
printf("%d", ch);
```

A. A

B. 65

C. Error

D. Garbage

 Save Answer