

## DP 3545-20 Direct-Plug-in Spool Gun



For use with IronMan® 230

243750 March 2011



Great for aluminum MIG welding to eliminate feeding problems associated with soft aluminum wire. Quick and easy to install on the IronMan 230. For applications requiring extended reach the DP 3545-20 comes with a 20 ft (6 m) cable lead.

MIG weld 18 ga. –1/2 in. (1.2–12.7 mm) aluminum with the IronMan 230. Also for use with mild and stainless steel wires. Rated 200 amps at 60% duty cycle.

## **Applications:**

- Aluminum Fabrication/Repair
- Trailer Fabrication/Repair
- Auto and Marine Repair
- Sign Manufacturing





Spool Size

4 in. (102 mm)

**Dimensions** 

H: 11-1/2 in. (291 mm)

W: 2-1/4 in. (57 mm)

L: 8 in. (203 mm)

Capacity



Net Weight with

Cable Assembly

8 lb. (3.6 kg)



Weldina

200 A at

**Output Rating** 

60% Duty Cycle

**Electrode Wire** 

**Diameter Capacity** 

.030 - .047 in. (0.8-1.2 mm)

aluminum, steel and stainless steel

Hobart DP 3545-20



Wire Speed


0-1200 IPM

(0-30.5 MPM)

## **Consumables**

Note: DP 3545-20 is shipped with two .030 in., two .035 in., and two .047 in. contact tips.





**#199387** For .030 in. (0.8 mm) wire. **#199388** For .035 in. (0.9 mm) wire.

**#199389** For .047 in. (1.2 mm) wire.



Nozzle #199386



**Drive Roll (1)** #199396 For .047 in. (1.2 mm) wire. #186413 For .030/.035 in. (0.8/0.9 mm) wire.



**Push Roll (1) #199397** For .047 in. (1.2 mm) wire. **#186414** For .030/.035 in. (0.8/0.9 mm) wire.

## Typical Installation for DP 3545-20 Spool Gun to IronMan® 230

It's quick and easy to install the DP 3545-20 Spool Gun on the IronMan® 230. Just plug the power pin of the spool gun into the feedhead, attach the trigger lead and flip the switch on the inside panel for spool gun operation. Install the correct wire and gas for the job and its ready to go.

