

Program Testing. Refactoring.

Arthur Molnar

Babes-Bolyai University

arthur@cs.ubbcluj.ro

September 19, 2015

Overview

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- 1 Program testing
 - Testing Methods
 - PyUnit
 - Debugging

- 2 Refactoring
 - Coding style
 - Refactoring
 - How to refactor

Program testing

Lecture 10

Arthur Molnar

Program testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- **Testing** is observing the behavior of a program in many executions.
- Execute the program for some input data and observe if the results are correct for these inputs.
- Testing does not prove program correctness (only give us some confidence). On the contrary, it may prove its incorrectness if one execution give wrong results.
- Testing can never completely identify all the defects within software.

Testing methods

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

Exhaustive testing

- Check the program for all possible inputs.
- Impractical so we need to choose a finite number of test cases.

Black box testing

- The selection of input data for testing is decided by analyzing the specification.
- Distinct cases of the problem are decided and we use a test input data for each case

White box testing

- Select the test data by analyzing the text of the program. We select test data such that all the execution paths are covered.
- We test a function such that each statement is executed.

White box vs Black Box testing

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

```
def isPrime(nr):  
    """  
        Verify if a number is prime  
        return True if nr is prime False if not  
        raise ValueError if nr<=0  
    """  
    if nr<=0:  
        raise ValueError("nr need to be positive")  
    if nr==1:#1 is not a prime number  
        return False  
    if nr<=3:  
        return True  
    for i in range(2,nr):  
        if nr%i==0:  
            return False  
    return True
```

White box vs Black Box testing

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

Black Box

- test case for a prime/not prime
- test case for 0
- test case for negative number

```
def blackBoxPrimeTest():  
    assert (isPrime(5)==True)  
    assert (isPrime(9)==False)  
    try:  
        isPrime(-2)  
        assert False  
    except ValueError:  
        assert True  
    try:  
        isPrime(0)  
        assert False  
    except ValueError:  
        assert True
```

White Box (cover all the paths)

- test case for 0
- test case for negative
- test case for 1
- test case 3
- test case for prime (no divider)
- test case for not prime

```
def whiteBoxPrimeTest():  
    assert (isPrime(1)==False)  
    assert (isPrime(3)==True)  
    assert (isPrime(11)==True)  
    assert (isPrime(9)==True)  
    try:  
        isPrime(-2)  
        assert False  
    except ValueError:  
        assert True  
    try:  
        isPrime(0)  
        assert False  
    except ValueError:  
        assert True
```

Testing levels

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring
Coding style
Refactoring
How to refactor

Tests are frequently grouped by where they are added in the software development process, or by the level of specificity of the test.

Unit testing

- Unit testing refers to tests that verify the functionality of a specific section of code, usually at the function level.
- Testing unit of code in isolation (functions). Test small parts of the program independently

Integration testing

- Considers the way program works as a whole.
- After all modules have been tested and corrected we need to verify the overall behavior of the program

Automated testing

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

Automated testing

- Test automation is the process of writing a computer program to do testing that would otherwise need to be done manually.
- Use of software to control the execution of tests, the comparison of actual outcomes to predicted outcomes, the setting up of test preconditions

Test Driven Development (TDD)

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

TDD Steps:

- 1 Automated test cases
- 2 Writing specification (invariants, pre/post)
- 3 Throwing or not exceptions
- 4 Production code

Python unit testing framework (PyUnit)

Lecture 10

Arthur Molnar

Program
testing

Testing Methods

PyUnit

Debugging

Refactoring

Coding style

Refactoring

How to refactor

unittest module supports:

- Test automation
- Sharing of setup and shutdown code for tests
- Aggregation of tests into collections
- Independence of the tests from the reporting framework

Python unit testing framework (PyUnit)

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

```
import unittest
class TestCase(unittest.TestCase):
    def setUp(self):
        #code executed before every testMethod
        val=StudentValidator()
        self.ctr=StudentController(val, StudentRepository())
        st = self.ctr.create("I", "Ion", "Adr", 1, "Cluj")

    def tearDown(self):
        #cleanup code executed after every testMethod

    def testCreate(self):
        self.assertTrue(self.ctr.getNrStudents()==1)
        #test for an invalid student
        self.assertRaises(ValidationEx,self.ctr.create,"I", "", "", 1, "Cj")

        #test for duplicated id
        self.assertRaises(DuplicatedIDException,self.ctr.create,"I", "I",
                                                                    "A", 1, "j")
```

Python unit testing framework (PyUnit)

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

```
def testRemove(self):
    #test for an invalid id
    self.assertRaises(ValueError, self.ctr.remove, "2")

    self.assertTrue(self.ctr.getNrStudents() == 1)

    st = self.ctr.remove("1")
    self.assertTrue(self.ctr.getNrStudents() == 0)
    self.assertEqual(st.getId(), "1")
    self.assertTrue(st.getName() == "Ion")
    self.assertTrue(st.getAdr().getStreet() == "Adr")

if __name__ == '__main__':
    unittest.main()
```

Debugging

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

Debugging - the activity that must be performed when testing indicates the presence of errors, to find errors, and rewrite the program with the purpose of eliminating the errors.

- Using print statements
- Using the IDE

Debugging is the most unpleasant activity. Debugging must be avoided!

Eclipse debug perspective - Example

Lecture 10


Arthur Molnar

Program testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor



Eclipse debug perspective

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

Debug view

- View the current execution trace (stack trace)
- Execute step by step, resume/pause execution

Variables view

- View variable values

Program inspection

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- Anyone can write code that a computer can understand.
Good programmers
- Write code that humans can understand!
- Programming style consist of all the activities made by a programmer for producing products easy to read, and easy to understand, and the way in which these qualities are achieved

Program inspection

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- Readability is considered the main attribute of style.
- A program, like any publication, is a text must be read and understand by another programmer. The element of coding style are:
 - Comments
 - Text formatting (indentation, white spaces)
 - Specification
 - Good names for entities (classes, functions, variables) of the program
 - Meaningful names
 - Use naming conventions

Naming conventions

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- Class names: Student, StudentRepository
- Variable names: student, nrElem (nr_elem)
- Function names: getName, getAddress, storeStudent
(get_name, get_address, store_student)
- constants: MAX

Whatever convention you use, use it **consistently**.

Refactoring

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- Refactoring is the process of changing the software system in such a way that it does not alter the external behavior of the code yet improves its internal structure.
- It is a disciplined way to clean up the code that minimizes the chances of introducing bugs.
- When you need to add a new feature to the program, and the program's code is not structured in a convenient way for adding the new feature, first refactor the code to make it easy to add a feature, then add the feature

Why refactoring

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- Refactoring improves the design of the software
- Refactoring makes software easier to understand
- Refactoring helps you find bugs
- Refactoring helps you program faster

Bad smells

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

When we need to refactor the code

- Duplicated code
- Long method
- Large class
- Long parameter list
- Comments
- Divergent change - One class is commonly changed in different ways for different reasons

Refactoring methods

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- **Rename Method** - *The name of a method does not reveal its purpose.*
- **Consolidate Conditional Expression** - *You have a sequence of conditional tests with the same result.*
Combine them into a single conditional expression and extract it.
- **Consolidate Duplicate Conditional Fragments** - *The same fragment of code is in all branches of a conditional expression.* Move it outside of the expression.

Refactoring methods

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- **Decompose Conditional** - *You have a complicated conditional (if-then-else) statement.* Extract methods from the condition, then part, and else parts.
- **Inline Temp** - *You have a temp that is assigned to once with a simple expression, and the temp is getting in the way of other refactorings.* Replace all references to that temp with the expression.
- **Introduce Explaining Variable** - *You have a complicated expression.* Put the result of the expression, or parts of the expression, in a temporary variable with a name that explains the purpose.

Refactoring methods

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- **Remove Assignments to Parameters** - *The code assigns to a parameter. Use a temporary variable instead.*
- **Remove Control Flag** - *You have a variable that is acting as a control flag for a series of boolean expressions. Use a break or return instead.*
- **Remove Double Negative** - *You have a double negative conditional. Make it a single positive conditional*

Refactoring methods

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- **Replace Nested Conditional with Guard Clauses** - *A method has conditional behavior that does not make clear what the normal path of execution is. Use Guard Clauses for all the special cases.*
- **Replace Temp with Query** - *You are using a temporary variable to hold the result of an expression. Extract the expression into a method. Replace all references to the temp with the expression. The new method can then be used in other methods.*

Refactoring classes

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- **Encapsulate Field** - *There is a public field.* Make it private and provide accessors.
- **Replace Magic Number with Symbolic Constant** - *You have a literal number with a particular meaning.* Create a constant, name it after the meaning, and replace the number with it.
- **Extract Method** - *You have a code fragment that can be grouped together.* Turn the fragment into a method whose name explains the purpose of the method.

Refactoring classes

Lecture 10

Arthur Molnar

Program
testing

Testing Methods
PyUnit
Debugging

Refactoring

Coding style
Refactoring
How to refactor

- **Move Method** - *A method is, or will be, using or used by more features of another class than the class on which it is defined.* Create a new method with a similar body in the class it uses most. Either turn the old method into a simple delegation, or remove it altogether.
- **Move Field** - *A field is, or will be, used by another class more than the class on which it is defined.* Create a new field in the target class, and change all its users.