

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods,
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

User Defined Types

Arthur Molnar

Babes-Bolyai University

arthur@cs.ubbcluj.ro

October 28, 2015

Overview

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

1 User defined types

- Why define new types?
- Classes
- Objects
- Fields
- Methods
- Special methods. Overloading

2 Python scope and namespace

- Class attributes vs instance attributes

3 Principles when defining new data types

User defined types - classes and objects

Lecture 07

Arthur Molnar

User defined types

Why define new types?
Classes
Objects
Fields
Methods
Special methods.
Overloading

Python scope and namespace

Class attributes vs instance attributes

Principles when defining new data types

- **Object oriented programming** - a programming paradigm that uses objects to design applications.
- **Remember! - Types** classify values. A type denotes a **domain** (a set of values) and **operations** on those values.

Let's review modular calculator

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods,
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

Issues with the global variables version:

- You can easily break global vars!
- They make testing difficult
- The relation between them is difficult

Issues with the no-global variables version:

- The state of the calculator is exposed to the world
- The state has to be transmitted as parameter to every function

User defined types - classes

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods,
Overloading

Python scope and namespace

Class attributes
vs instance
attributes

Principles when defining new data types

Class - a construct that is used as a template to create instances of itself - referred to as class instances, class objects, instance objects or simply **objects**. A class defines constituent members which enable these class instances to have *state* and behaviour.

Classes in Python

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

```
class MyClass:  
    <statement 1>  
    ....  
    <statement n>
```

- The class definition is an executable statement.
- The statements inside a class definition are usually function definitions, but other statements are allowed
- When a class definition is entered, a new namespace is created, and used as the local scope - thus, all assignments to local variables go into this new namespace. In particular, function definitions bind the name of the new function here.

User defined types - objects

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods,
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

Object - a collection of data and functions that operates on that data. Class instances are of the type of the associated class. Objects support two kinds of operations: attribute (data or method) references and instantiation.

User defined types - objects

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

Creating instances of a class (`--init--`) Class *instantiation* uses function notation.

```
x = MyClass()
```

- The instantiation operation (calling a class object) creates an empty object. `x` will be an instance of type `MyClass`

User defined types - objects

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

- A class may define a special method named `__init__`

```
class MyClass:  
    def __init__(self):  
        self.someData = []
```

`__init__`

- Create an instance
- Use `self` to refer to that instance

User defined types - objects

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

```
class RationalNumber:
```

```
    """
```

```
        Abstract data type for rational numbers
```

```
        Domain: {a/b where a and b are integer numbers b!=0}
```

```
    """
```

```
    def __init__(self, a, b):
```

```
        """
```

```
            Creates a new instance of RationalNumber
```

```
        """
```

```
        self.n = a
```

```
        self.m = b
```

```
r1 = RationalNumber(1,3)  #create the rational number 1/3
```

self.n = a vs n = a

- 1 Creates an attribute for the current instance
- 2 Creates a function local variable

Fields

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

```
x = RationalNumber(1,3)
y = RationalNumber(2,3)
x.m = 7
x.n = 8
y.m = 44
y.n = 21
```

Fields

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

```
class RationalNumber:
    """
        Abstract data type for rational numbers
        Domain: {a/b where a and b are integer numbers b!=0}
    """

    def __init__(self, a, b):
        """
            Creates a new instance of RationalNumber
        """
        #create a field in the rational number
        #every instance (self) will have this field
        self.n = a
        self.m = b
```

$\text{self.n} = a$ vs $n = a$

- 1 Creates an attribute for the current instance
- 2 Creates a function local variable

Methods

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?
Classes
Objects
Fields

Methods
Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

- **Methods** - functions in a class that can access values from a specific instance.
- In Python the method will automatically receive a first argument: the current instance
- All the methods need to have an argument (self)

```
def testCreate() :  
    """  
        Test function for creating rational numbers  
    """  
    r1 = RationalNumber(1,3)  #create the rational number 1/3  
    assert r1.getNominator()==1  
    assert r1.getDenominator()==3  
    r1 = RationalNumber(4,3)  #create the rational number 4/3  
    assert r1.getNominator()==4  
    assert r1.getDenominator()==3
```

Methods

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

```
class RationalNumber:
    """
        Abstract data type rational numbers
        Domain: {a/b where a,b integer numbers, b!=0, greatest common divisor
a, b =1}
    """
    def __init__(self, a, b):
        """
            Initialize a rational number
            a,b integer numbers
        """
        self.__nr = [a, b]

    def getDenominator(self):
        """
            Getter method
            return the denominator of the rational number
        """
        return self.__nr[1]

    def getNominator(self):
        """
            Getter method
            return the nominator of the method
        """
        return self.__nr[0]
```

Special methods

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

`__str__` - convert into a string type (print representation)

```
def __str__(self):  
    """  
        provide a string representation for the rational number  
        return a string  
    """  
    return str(self.__nr[0])+"/"+str(self.__nr[1])
```

Special methods

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

Comparisons - $<$, $>$, \leq , \geq

```
def testCompareOperator():  
    """  
    Test function for < >  
    """  
    r1 = RationalNumber(1, 3)  
    r2 = RationalNumber(2, 3)  
    assert r2>r1  
    assert r1<r2
```

```
def __lt__(self, ot):  
    """  
    Compare 2 rational numbers (less than)  
    self the current instance  
    ot a rational number  
    return True if self<ot, False otherwise  
    """  
    if self.getFloat()<ot.getFloat():  
        return True  
    return False
```


Special methods

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

`__eq__` - verify if equals

```
def testEqual():  
    """  
        test function for ==  
    """  
    r1 = RationalNumber(1, 3)  
    assert r1==r1  
    r2 = RationalNumber(1, 3)  
    assert r1==r2  
    r1 = RationalNumber(1, 3)  
    r1 = r1.add(RationalNumber(2, 3))  
    r2 = RationalNumber(1, 1)  
    assert r1==r2
```

```
def __eq__(self, other):  
    """  
        Verify if 2 rational are equals  
        other - a rational number  
        return True if the instance is  
        equal with other  
    """  
    return self.__nr==other.__nr
```

Operator overloading

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

Overload `--add--(self, other)` - to be able to use `" + "` operator

```
def testAddOperator():  
    """  
        Test function for the + operator  
    """  
    r1 = RationalNumber(1,3)  
    r2 = RationalNumber(1,3)  
    r3 = r1+r2  
    assert r3 == RationalNumber(2,3)
```

```
def __add__(self,other):  
    """  
        Overload + operator  
        other - rational number  
        return a rational number,  
        the sum of self and other  
    """  
    return self.add(other)
```

Operator overloading

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

- Overload **`__mul__(self, other)`** - to be able to use the "*" operator
- Overload **`__setitem__(self, index, value)`** - to make a class behave like an array/dictionary, use the "[]"
 $a = A()$
 $a[index] = value$
- **`__getitem__(self, index)`** - to make a class behave like an array
 $a = A()$
for el *in* a :
pass

Operator overloading

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

- **`__len__(self)`** - overload `len`
- **`__getslice__(self,low,high)`** - overload slicing operator
 $a = A()$
 $b = a[1 : 4]$
- **`__call__(self, arg)`** - to make a class behave like a function, use the "`()`"
 $a = A()$
 $a()$

Python scope and namespace

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

- A *namespace* is a mapping from names to objects.
- Namespaces are implemented as Python dictionaries
 - Key: name
 - Value - Object
- A class introduce a new name space
- Methods and fields of a class are in a separate namespace (the namespace of the class)
- All the rules (bound a name, scope/visibility, formal/actual parameters, etc.) related to the names (function, variable) are the same for class attributes (methods, fields). Just keep in mind that the class have it's own namespace

Data members (fields)

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

```
class RationalNumber:
    """
        Abstract data type for rational numbers
        Domain: {a/b where a and b are integer numbers b!=0}
    """
    #class field, will be shared by all the instances
    numberOfInstances = 0

    def __init__(self, a, b):
        """
            Creates a new instance of RationalNumber
        """
        self.n = a
        self.m = b
        RationalNumber.numberOfInstances+=1    # accessing class fields

    numberOfInstances = 0
    def __init__(self,n,m):
        self.n = n
        self.m = m
        RationalNumber.numberOfInstances+=1
```

Data members (fields)

Lecture 07

Arthur Molnar

User defined types

Why define new types?
Classes
Objects
Fields
Methods
Special methods.
Overloading

Python scope and namespace

Class attributes
vs instance
attributes

Principles when defining new data types

```
def testNumberInstances():  
    assert RationalNumber.numberOfInstances == 0  
    r1 = RationalNumber(1,3)  
    #show the class field numberOfInstances  
    assert r1.numberOfInstances==1  
    # set numberOfInstances from the class  
    r1.numberOfInstances = 8  
    assert r1.numberOfInstances==8 #access to the instance field  
    assert RationalNumber.numberOfInstances==1 #access to the class field  
  
testNumberInstances()
```

Class Methods

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?
Classes
Objects
Fields
Methods
Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

```
class RationalNumber:
    #class field, will be shared by all the instances
    numberOfInstances = 0

    def __init__(self, n, m):
        """
        Initialize the rational number
        n, m - integer numbers
        """
        self.n = n
        self.m = m
        RationalNumber.numberOfInstances += 1

    @staticmethod
    def getTotalNumberOfInstances():
        """
        Get the number of instances created in the app
        """
        return RationalNumber.numberOfInstances
```


Class Methods

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?
Classes
Objects
Fields
Methods
Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

```
def testNumberOfInstances():  
    """  
        test function for getTotalNumberOfInstances  
    """  
    assert RationalNumber.getTotalNumberOfInstances() == 0  
    r1 = RationalNumber(2, 3)  
    assert RationalNumber.getTotalNumberOfInstances() == 1  
  
testNumberOfInstances()
```

- *ClassName.attributeName* - used to access the class attributes (fields, methods)
- The *staticmethod* form is a function decorator. A static method does not receive an implicit first argument.

Encapsulation

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope and namespace

Class attributes
vs instance
attributes

Principles when defining new data types

- The data that represents the state of the object and the methods that manipulate that data are stored together as a cohesive unit. State and behaviour are kept together, they are encapsulated.

Information hiding

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope and namespace

Class attributes
vs instance
attributes

Principles when defining new data types

- The internal representation of an object need to be hidden from view outside of the object's definition
- Hiding the internals of the object protects its integrity by preventing users from setting the internal data of the component into an invalid or inconsistent state
- Divide the code into a public interface, and a private implementation of that interface

Information hiding

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods,
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

Why?

- Defining a specific interface and isolate the internals to keep other modules from doing anything incorrect to your data
- Limit the functions that are visible (part of the interface), so you are free to change the internal data without breaking the client code
- Write to the Interface, not the the Implementation
- If you are using only the public functions you can change large parts of your classes without affecting the rest of the program

Public and private members - Data hiding in Python

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope and namespace

Class attributes vs instance attributes

Principles when defining new data types

- We need to protect (hide) the internal representation (the implementation) Provide accessors (getter) to the data
- Encapsulations is particularly important when the class is used by others
- Nothing in Python makes it possible to enforce data hiding - it is all based upon convention. use the convention: `_name` or `__name` for fields, methods that are "private"
- A name prefixed with an underscore (e.g. `_spam`) should be treated as a non-public part of the API (whether it is a function, a method or a data member). It should be considered an implementation detail and subject to change without notice.

Guidelines

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods,
Overloading

Python scope and namespace

Class attributes
vs instance
attributes

Principles when defining new data types

- Client code does not have to know about the implementation details of the methods or the internal data representation (abstraction, the class is a black box)
- Client code needs to work even if we change the implementation or data representation
- Function and class specification have to be independent of the data representation and the method's implementation (Data Abstraction)

Abstract data types

Lecture 07

Arthur Molnar

User defined types

Why define new types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope and namespace

Class attributes
vs instance
attributes

Principles when defining new data types

- Operations are specified independently of their implementation
- Operations are specified independently of the data representation
- Abstract data type is a Data type + Data Abstraction + Data Encapsulation

SimplestClassExample

Lecture 07

Arthur Molnar

User defined
types

Why define new
types?

Classes

Objects

Fields

Methods

Special methods.
Overloading

Python scope
and
namespace

Class attributes
vs instance
attributes

Principles
when defining
new data
types

Try to run the code in the provided example (same directory as Lecture Notes).

```
class FirstClass:  
    pass
```

```
class SecondClass:  
    def __init__(self):  
        self.testOne = "Test One"  
        self._testTwo = "Test Two"  
        self.__testThree = "Test Three"
```