PRACTICAL 3 – EXTENDED ACL

R1

```
enable
configure terminal
hostname R1
interface g0/0
ip address 172.22.34.65 255.255.255.224
no shutdown
interface g0/1
ip address 172.22.34.97 255.255.255.240
no shutdown
interface g0/2
ip address 172.22.34.1 255.255.255.192
no shutdown
line console 0
password conpa55
login
line vty 0 4
password vtypa55
login
enable secret enpa55
access-list 100 permit tcp 172.22.34.64 0.0.0.31 host 172.22.34.62 eq ftp
access-list 100 permit icmp 172.22.34.64 0.0.0.31 host 172.22.34.62
interface g0/0
ip access-group 100 in
ip access-list extended HTTP_ONLY
permit tcp 172.22.34.96 0.0.0.15 host 172.22.34.62 eq www
permit icmp 172.22.34.96 0.0.0.15 host 172.22.34.62
interface g0/1
```

```
ip access-group HTTP_ONLY in
end
write memory
```

PRACTICAL 3 – PART B (SSH + ACL)

RTA

```
enable
configure terminal
hostname RTA
interface g0/0
ip address 10.101.117.49 255.255.255.248
no shutdown
interface g0/1
ip address 10.101.117.33 255.255.255.240
no shutdown
interface g0/2
ip address 10.101.117.1 255.255.255.224
no shutdown
enable secret enpa55
line console 0
password tyit
login
ip domain-name ccnasecurity.com
username admin secret adminpa55
crypto key generate rsa
1024
line vty 0 4
login local
transport input ssh
```

```
access-list 199 permit tcp 10.101.117.32 0.0.0.15 10.101.117.0 0.0.0.31 eq 22
access-list 199 permit icmp any any
interface g0/2
ip access-group 199 out
end
write memory
```

SWA

```
enable
configure terminal
interface vlan 1
ip address 10.101.117.50 255.255.255.248
no shutdown
ip default-gateway 10.101.117.49
enable secret enpa55
line console 0
password tyit
login
ip domain-name ccnasecurity.com
username admin secret adminpa55
crypto key generate rsa
1024
line vty 0 4
login local
transport input ssh
end
```

SWB

```
enable
```

```
configure terminal
interface vlan 1
ip address 10.101.117.34 255.255.255.240
no shutdown
ip default-gateway 10.101.117.33
enable secret enpa55
line console 0
password tyit
login
ip domain-name ccnasecurity.com
username admin secret adminpa55
crypto key generate rsa
1024
line vty 0 4
login local
transport input ssh
end
SWC
enable
configure terminal
interface vlan 1
ip address 10.101.117.2 255.255.255.224
no shutdown
ip default-gateway 10.101.117.1
enable secret enpa55
line console 0
password tyit
login
ip domain-name ccnasecurity.com
```

```
username admin secret adminpa55
crypto key generate rsa
1024
line vty 0 4
login local
transport input ssh
end
```