

## **Xalan-J XSLT 3.0 specification implementation status**

Document last modified : 2025-07-18

Authors:

Gary Gregory <gggregory@apache.org>  
Joseph Kesselman <keshlam@alum.mit.edu>  
Mukul Gandhi <mukulg@apache.org>

### **(1) XSL Transformations (XSLT) 3.0 and XML Path Language (XPath) 3.1**

The XSLT 3.0 specification defines the following conformance features, and the level to which Xalan-J implements them.

- |                                   |  |
|-----------------------------------|--|
| a) Basic XSLT processor           | Supported  |
|                                   | XSLT 3.0 instructions and XPath language features, whose implementations are available are described in subsequent sections of this document, below.   |
| b) Schema aware XSLT processor    | Supported  |
|                                   | An XML Schema document can be imported into an XSL stylesheet using <code>xsl:import-schema</code> instruction, and schema's global type definitions and element & attribute declarations can be used within the stylesheet. |
|                                   | Schema aware feature where XML input document, resulting in node tree having detailed type annotations on all possible nodes is not supported. i.e, XPath processor is natively not schema aware.                            |
| c) Serialization feature          | Supported  |
|                                   | A new support for <code>xsl:output method="json"</code> is available, in addition to existing <code>xsl:output method</code> values.   |
| d) Streaming feature              | Partially supported  |
| e) Dynamic evaluation feature     | Supported  |
| f) XPath 3.1 feature, for arrays  | Supported  |
| g) Higher-order functions feature | Supported  |

Following are details of XSL 3.0 family of language features, whose working implementation is available on Xalan-J's dev repos branch 'xalan-j\_xslt3.0\_mvn':

## 1.1) XSLT 3.0

**XSLT version 3.0 specification :** <https://www.w3.org/TR/xslt-30/>

- 1) `xsl:for-each-group` instruction
- 2) `xsl:analyze-string` instruction
- 3) `xsl:iterate` instruction
- 4) `xsl:for-each` instruction implementation improvements, for new XSLT 3.0 requirements. Particularly, `xsl:for-each` instruction being able to iterate XPath atomic values in addition to nodes.
- 5) `xsl:evaluate` instruction
- 6) `xsl:function` instruction
- 7) `xsl:sequence` instruction
- 8) The following XSL stylesheet elements can now have attributes ‘type’ and ‘validation’ : `xsl:element`, literal result element (`xsl:validation` and `xsl:attribute`), `xsl:attribute`, `xsl:copy-of`, `xsl:copy`.
- 9) `xsl:attribute` element can now have both, "select" attribute and child sequence constructor. But only one of these is allowed to be present on `xsl:attribute` instruction as specified by XSLT 3.0 specification.
- 10) `xsl:import-schema` instruction
- 11) `xsl:variable` instruction evaluation to node set instead of result tree fragment (RTF). This XSLT specification change was first introduced in XSLT 2.0. With XSLT 1.0, if RTF has to be used as node set, then it has to be converted to node set using node-set extension function.
- 12) The sequence type expression "as" attribute on XSLT elements `xsl:variable`, `xsl:template`, `xs:function`, `xsl:param`, `xsl:with-param`, `xsl:evaluate`.
- 13) XSL template tunnel parameters
- 14) `xsl:value-of` instruction can now produce result either via its “select” attribute, or by `xsl:value-of` instruction’s child sequence constructor. `xsl:value-of` instruction can now have an attribute named ‘separator’ as well.
- 15) `xsl:merge` instruction
- 16) `xsl:fork` instruction
- 17) `xsl:source-document` instruction
- 18) `xsl:try` and `xsl:catch` instructions

- 19) `xsl:character-map` instruction
- 20) Specifying XSL transformation's initial template name and support for initial template's default name `xsl:initial-template`.
- 21) XSLT function implementations
  - a) New function implementations : `fn:current-grouping-key`, `fn:current-group`, `fn:regex-group`, `fn:current-merge-group`, `fn:current-merge-key`
  - b) Function implementation enhancements : `fn:system-property`
- 22) Implementation of XSLT 3.0 attribute `xpath-default-namespace`

**Support for following new Xalan-J XSL transformation properties:**

`http://apache.org/xalan/validation` (used to enable XML input document validation when `xsl:import-schema` instruction is used within an XSL stylesheet, with default value false)

`http://apache.org/xalan/xslevaluate` (used to enable XSL stylesheet instruction `xsl:evaluate`, with default value false)

These new XSL transformation properties can be set, using Xalan-J's class `TransformerImpl` when XSL transformation is invoked via API, or via Xalan-J command line.

## 1.2) XPath 3.1

**XPath version 3.1 specification** : <https://www.w3.org/TR/xpath-31/>

- 1) Range "to" expression
- 2) Value comparison operators `eq`, `ne`, `lt`, `le`, `gt`, `ge`
- 3) Function item "inline function expression"
- 4) Dynamic function calls
- 5) "if" expression
- 6) "for" expression
- 7) Quantified expressions 'some', 'every'
- 8) "let" expression
- 9) Sequence constructor expression, using comma operator

- 10) String concatenation operator "||"
- 11) Node comparison operators "is", "<<", ">>"
- 12) Simple map operator '!'
- 13) Instance Of expression
- 14) Implementation of various new XML Schema built-in data types for use in XSLT 3.0 stylesheets and XPath 3.1 expressions. Implementation of, XPath constructor function calls (for e.g, xs:string('hello'), xs:date('2005-10-07') etc) for these supported XML Schema data types.

Following XML Schema built-in types are supported (depicted with XML Schema data type and subtype hierarchy as specified by W3C XML Schema data types specification):

```
xs:anyType
  xs:anySimpleType
    xs:anyAtomicType
      xs:anyURI
      xs:base64Binary
      xs:boolean
      xs:decimal
      xs:integer
        xs:long
        xs:int
        xs:short
        xs:byte
      xs:nonNegativeInteger
        xs:positiveInteger
        xs:unsignedLong
        xs:unsignedInt
        xs:unsignedShort
        xs:unsignedByte
      xs:nonPositiveInteger
        xs:negativeInteger
      xs:double
      xs:float
      xs:date
      xs:dateTime
      xs:time
      xs:duration
        xs:dayTimeDuration
        xs:yearMonthDuration
      xs:gDay
      xs:gMonth
      xs:gMonthDay
      xs:gYear
      xs:gYearMonth
```

- xs:hexBinary
- xs:QName
- xs:string
  - xs:normalizedString
  - xs:token
    - xs:language
    - xs:Name
      - xs:NCName
      - xs:ID
      - xs:IDREF
      - xs:NMTOKEN

In addition to above mentioned XML Schema built-in data types, an XML Schema type xs:untyped specified by XPath 3.1 specification has also been implemented.

## 15) Collation support

Within the context of XSL languages, a collation is a method by which text information is compared and sorted.

As specified by XPath 3.1 F&O spec, implementations of following collations are available:

### 15.1) The Unicode Codepoint Collation

### 15.2) The Unicode Collation Algorithm

Support for following collation uri query parameters is available : 'fallback', 'lang', 'strength'

For the collation's query "lang" parameter, all languages as those supported by Java's 'java.util.Locale' class are available within Xalan-J's XSLT 3.0 implementation (ref, <https://docs.oracle.com/javase/8/docs/api/java/util/Locale.html>).

For the collation's query "strength" parameter, following values are supported : 'primary', 'secondary', 'tertiary', 'identical'.

### 15.3) The HTML ASCII Case-Insensitive Collation

## 16) Sequence type expression

## 17) Map expression

## 18) Array expression

## 19) Cast expression

## 20) Castable expression

## 21) Treat expression

- 22) Named function reference
- 23) Map and array lookup using function call syntax,  
Map and array lookup using unary lookup operator “?”
- 24) Arrow operator (=>)
- 25) Node combination operators union, intersect and except

### 1.3) XPath 3.1 functions

**XPath version 3.1 F&O specification :** <https://www.w3.org/TR/xpath-functions-31/>

Implementation of XPath built-in default functions namespace : <http://www.w3.org/2005/xpath-functions>

Implementation of XPath built-in math functions namespace : <http://www.w3.org/2005/xpath-functions/math>

Implementation of XPath built-in map functions namespace : <http://www.w3.org/2005/xpath-functions/map>

Implementation of XPath built-in array functions namespace : <http://www.w3.org/2005/xpath-functions/array>

#### 1) Functions on numeric values

fn:abs

fn:round (implementation of an optional second argument, that's used to specify 'precision')

#### 2) Context functions

fn:current-dateTime

fn:current-date

fn:current-time

fn:implicit-timezone

fn:default-collation

#### 3) Functions giving access to external information

fn:doc

fn:doc-available

fn:collection

fn:unparsed-text

fn:unparsed-text-lines

#### 4) Functions on strings

fn:string-join  
fn:upper-case  
fn:lower-case  
fn:codepoints-to-string  
fn:string-to-codepoints  
fn:compare (with support for collation argument)  
fn:codepoint-equal  
fn:contains-token (with support for collation argument)  
fn:contains (added support for collation argument)  
fn:starts-with (added support for collation argument)  
fn:ends-with (with support for collation argument)  
fn:substring-before (added support for collation argument)  
fn:substring-after (added support for collation argument)

#### 5) String functions that use regular expressions

fn:matches  
fn:replace  
fn:tokenize  
fn:analyze-string

#### 6) Functions that compare values in sequences

fn:distinct-values (with support for collation argument)  
fn:index-of (with support for collation argument)  
fn:deep-equal (with support for collation argument)

#### 7) Maths trigonometric and exponential functions

math:pi  
math:exp  
math:exp10  
math:log  
math:log10  
math:pow  
math:sqrt  
math:sin  
math:cos  
math:tan  
math:asin  
math:acos  
math:atan  
math:atan2

#### 8) Component extraction functions on durations

fn:years-from-duration  
fn:months-from-duration

fn:days-from-duration  
fn:hours-from-duration  
fn:minutes-from-duration  
fn:seconds-from-duration

## 9) Constructing xs:dateTime value

fn:dateTime

## 10) Component extraction functions on dates and times

fn:year-from-dateTime  
fn:month-from-dateTime  
fn:day-from-dateTime  
fn:hours-from-dateTime  
fn:minutes-from-dateTime  
fn:seconds-from-dateTime  
fn:timezone-from-dateTime  
fn:year-from-date  
fn:month-from-date  
fn:day-from-date  
fn:timezone-from-date  
fn:hours-from-time  
fn:minutes-from-time  
fn:seconds-from-time  
fn:timezone-from-time

## 11) Built-in higher-order functions

fn:for-each  
fn:filter  
fn:fold-left  
fn:fold-right  
fn:for-each-pair  
fn:sort (with support for collation argument)  
fn:apply

Dynamic loading and execution, of XSLT stylesheets:

fn:transform

## 12) Functions on sequences

### 12.1 General functions on sequences

fn:empty  
fn:exists  
fn:head  
fn:tail  
fn:insert-before  
fn:remove



fn:reverse  
fn:subsequence  
fn:unordered

## 12.2 Aggregate functions

fn:avg  
fn:max  
fn:min

## 13) Parsing and serializing

fn:parse-xml  
fn:parse-xml-fragment

## 14) Accessors

fn:node-name  
fn:string  
fn:data  
fn:base-uri  
fn:document-uri

## 15) Functions related to QNames

fn:resolve-QName  
fn:QName

## 16) Functions related to maps

map:merge  
map:size  
map:keys  
map:contains  
map:get  
map:find  
map:put  
map:entry  
map:remove  
map:for-each

## 17) Functions related to arrays

array:size  
array:get  
array:put  
array:append  
array:subarray  
array:remove  
array:insert-before

array:head  
array:tail  
array:reverse  
array:join  
array:for-each  
array:filter  
array:fold-left  
array:fold-right  
array:for-each-pair  
array:sort (with support for collation argument)  
array:flatten

#### 18) Functions on JSON data

fn:parse-json  
fn:json-doc  
fn:json-to-xml  
fn:xml-to-json

**Other than the above mentioned newly implemented XPath 3.1 functions, all the functions that are specified for XPath 1.0 are available with Xalan-J's XPath 3.1 implementation as well.**

Please refer to the link <https://www.w3.org/TR/1999/REC-xpath-19991116/> (section "4 Core Function Library") for the details about XPath 1.0 functions.

#### **(2) Features yet not implemented, or partially implemented**

##### **XSLT 3.0 instructions**

Not yet implemented:

- a) xsl:package
- b) xsl:mode

Within Xalan-J, a partial workaround is to use template's mode name as follows: xsl:template match="..." mode="mode name" with an XSLT 1.0 defined semantics.

- c) Conditional content construction instructions xsl:where-populated, xsl:on-empty, xsl:on-non-empty
- d) Various aspects of XSLT 3.0 streaming specifications

Partial implementation:

- a) xsl:sort instruction's data-type value eqname, and 'collation' attribute are yet not implemented

##### **XPath 3.1 features**

Partial implementation:

- a) Few XML Schema data types, for use with XPath 3.1 constructor function calls and sequence types are yet not supported

The list of supported XML Schema data types with Xalan-J, are described within this document's section 1.2) XPath 3.1 point 14) above.

### **(3) Xalan-J's XSLT 3.0 and XPath 3.1 test suite details**

Xalan-J XSLT 3.0 development code's latest conformance results with W3C XSLT 3.0 test suite is available here : [https://github.com/apache/xalan-java/blob/xalan-j\\_xslt3.0\\_mvn/src/test/java/org/apache/xalan/tests/w3c/xslt3/result/w3c\\_xslt3\\_testsuite\\_xalan-j\\_result.xml](https://github.com/apache/xalan-java/blob/xalan-j_xslt3.0_mvn/src/test/java/org/apache/xalan/tests/w3c/xslt3/result/w3c_xslt3_testsuite_xalan-j_result.xml)

Xalan-J XSLT 3.0 development code's own test suite is available here : [https://github.com/apache/xalan-java/tree/xalan-j\\_xslt3.0\\_mvn/src/test](https://github.com/apache/xalan-java/tree/xalan-j_xslt3.0_mvn/src/test) and the results of these XSL tests are available at locations [https://xalan.apache.org/xalan-j/xsl3/tests/xalan-j\\_xsl3\\_test\\_suite\\_result.xml](https://xalan.apache.org/xalan-j/xsl3/tests/xalan-j_xsl3_test_suite_result.xml) & [https://xalan.apache.org/xalan-j/xsl3/tests/xalan-j\\_xsl3\\_test\\_suite\\_result.html](https://xalan.apache.org/xalan-j/xsl3/tests/xalan-j_xsl3_test_suite_result.html)

Apache Xalan-J site  
<https://xalan.apache.org/xalan-j/>

Copyright © 1999-2025 The Apache Software Foundation