buildandteach

SQL EDITOR · PART 1 QUICK REFERENCE

SELECT · WHERE · CASE · NULLs

SQL Editor on the Free Edition serverless SQL warehouse. Read-only: VALUES CTEs, nothing created.
8 fictional orders; 105 no customer, 106 no quantity, 107 no unit_price. Baseline: 6 valid, 142.50.

1. Valid rows (reconcile everything to this)

```
valid AS (SELECT order_id, customer, region, category,
    CAST(quantity * unit_price AS DECIMAL(12,2)) AS order_total
  FROM orders WHERE quantity IS NOT NULL AND unit_price IS NOT NULL)
SELECT COUNT(*) AS valid_orders, SUM(order_total) AS valid_revenue FROM valid;
```

Observed: valid_orders 6 · valid_revenue 142.50. NULL * anything = NULL, so 106/107 totals are NULL.

2. WHERE + IN + ORDER BY

```
SELECT order_id, customer, region, category, order_total FROM valid
WHERE category = 'Books' AND region IN ('NORTH', 'WEST')
ORDER BY order_id;
```

Observed: 101 Ana 20.00 · 103 Cy 25.50 (sum 45.50). AND binds before OR; IN avoids parentheses bugs.

3. CASE (first match wins)

```
CASE WHEN order_total >= 30 THEN 'premium'
     WHEN order_total >= 25 THEN 'high'
     ELSE 'standard' END AS value_band
-- WHERE order_total >= 25  ORDER BY order_total DESC, order_id DESC
```

Observed: 108 premium 30.00 · 104 premium 30.00 · 103 high 25.50 · 102 high 25.00.

buildandteach

SQL EDITOR · PART 1 QUICK REFERENCE

NULL handling + practice

4. Count NULLs before cleaning (data quality check)

```
SELECT COUNT(*) AS total_orders,
  SUM(CASE WHEN customer IS NULL THEN 1 ELSE 0 END) AS null_customer,
  SUM(CASE WHEN quantity IS NULL THEN 1 ELSE 0 END) AS null_quantity,
  SUM(CASE WHEN unit_price IS NULL THEN 1 ELSE 0 END) AS null_unit_price FROM orders;
```

Observed: 8 · 1 · 1 · 1.

5. COALESCE for display only

```
SELECT order_id, COALESCE(customer, '(missing)') AS customer_display, region, category
FROM orders WHERE customer IS NULL OR quantity IS NULL OR unit_price IS NULL;
```

Observed: 105 (missing) · 106 Fay · 107 Gus. Never fill a missing price with 0.

Rules: = NULL is never true · SUM and COUNT(col) skip NULLs · COUNT(*) counts rows.

Run one statement: clear Run all statements, then Ctrl/Cmd + Enter.
Serverless SQL warehouse = managed, fast-starting compute for interactive SQL.

Practice challenge

Over all 8 orders, how many rows does WHERE customer <> 'Ana' keep? Answer: 6. 101 is FALSE and 105 (NULL) is UNKNOWN. For 7, add OR customer IS NULL, or use customer IS DISTINCT FROM 'Ana'.

Associate prep: Section 1 compute, Section 3 cleaning nulls and data quality checks. No exam guarantee.
Independent education, not affiliated with Databricks. Fictional data. Part 1 of 3.