SGPC Programmer's Manual

Steven Vroom

November 2016

Contents

Co	onter	nts	i
Li	st of	Figures	iv
Li	st of	Tables	\mathbf{v}
Αl	oout	This Manual	vi
	Rela	ted Documentation	vi
		anization	vi
	Con	ventions	vi
	Acro	onyms and Abbreviations	vi
1	Ove	erview	1
	1.1	SGPC Architecture Overview	1
	1.2	Registers	1
		User-accessible Registers	1
		Internal Registers	1
	1.3	Instruction Conventions	1
		Instruction Layout	1
		Addressing Modes	1
	1.4	Instruction Set	1
	1.5	Interrupt Model	1
	1.6	Memory Management Model	1
2	Reg	ister Set	2
	2.1	Foreground Registers	2
		General-Purpose Registers (GPRs)	2
		Temporary Data Register	3
		Stack Pointer Register (SP)	3
		Program Counter Register (PC)	3
	2.2	Background Registers	3
		Backup Registers	3
		Interrupt Registers	4
	2.3	Indirect Registers	4
		Flags Register	4
		Section Registers	4
	2.4	Output Registers	4
3	Ope	erand Conventions and Addressing Modes	5

CONTENTS	i	i

В	Sim	plified Mnemonics
\mathbf{A}	Inst	ruction Set Listings
8	Inst	ruction Set
7	I/O 7.1 7.2	Conventions Reading Input
		Switch Context
		Return to Context
	6.3	Interrupt Service Routine (ISR)
		Full Restore
		Backup
	6.2	Programmable Interrupt Controller (PIC)
		Interrupt Enabled Flag
6	6.1	rrupts Interrupt Enabling/Disabling
•	0.0	
	5.4 5.5	Segment Switching
	5.3	Data Segment (DS)
	5.2	Limit
5	Mer 5.1	nory Management Segments
		exceptions
	4.2	Instruction Format
		Reserved Instructions
		Arithimic Instructions
•	4.1	Instruction Types
4	Inst	ruction Set Summary
		Not From Memory
	3.2	Aligned and Misaligned Memory Access
	0.1	Bit and Byte Ordering
	3.1	Operand Conventions

CONTENTS	iii
----------	-----

\mathbf{C}	Common Procedures	14
D	Standard Peripherals	15
	D.1 Programmable Interrupt Controller (PIC)	15
	D.2 Keyboard	15
	D.3 Programmable Interrupt Timer (PIT)	15
	D.4 Sound Card	15
	D.5 Graphical Card	15
	D.6 Memory Control Hub (MCH)	15
	D.7 Segements and Out Of Bounds Exception	15

List of Figures

List of Tables

2.1	List of Foreground Registers	 	 	2
2.2	List of Background Registers	 	 	3
2.3	List of Flags	 	 	4
A.1	List of instructions sorted by opcode	 	 	11
A.1	List of instructions sorted by opcode	 	 	12

About This Manual

Related Documentation

Organization

Conventions

Acronyms and Abbreviations

Overview

- 1.1 SGPC Architecture Overview
- 1.2 Registers

User-accessible Registers

Internal Registers

1.3 Instruction Conventions

Instruction Layout

Addressing Modes

- 1.4 Instruction Set
- 1.5 Interrupt Model
- 1.6 Memory Management Model

Register Set

This chapter describes the registers seperated in four groups based on accessability. however, the internal registers are omitted from this chapter since these are implementation specific.

2.1 Foreground Registers

The foreground registers are the registers all regular instructions can read from and write to. There are eight 8-bit and eight 16-bit foreground registers. These registers are preserved in interrupts.

Table 2.1: List of Foreground Registers

ID	Mnonic	Descriptive Name	Length in bits
0x0	al	The lower byte of ax	8
0x1	ah	The higher byte of ax	8
0x2	bl	The lower byte of bx	8
0x3	$_{ m bh}$	The higher byte of bx	8
0x4	cl	The lower byte of cx	8
0x5	ch	The higher byte of cx	8
0x6	dl	The lower byte of dx	8
0x7	$\mathrm{d}\mathrm{h}$	The higher byte of dx	8
0x8	ax	The first GPR	16
0x9	bx	The second GPR	16
0xA	cx	The third GPR	16
0xB	dx	The fourth GPR	16
0xC	ex	The fifth GPR	16
0xD	${ m tm}$	Temporary data	16
0xE	sp	Stack pointer	16
0xF	pc	Program counter	16

General-Purpose Registers (GPRs)

These registers are meant for computing storage. The first four 16-bit registers are all splitted into two 8-bit registers. So software can directly access the upper and lower byte of these 16-bit registers.

Temporary Data Register

This registers is meant to facilitate call procedures. So it won't be preserved in a function call. However this nothing more than a suggestion to the user, software can use this register as a regular GPR.

Stack Pointer Register (SP)

This register is meant to keep track of the end of the stack. However this nothing more than a suggestion to the user, software can use this register as a regular GPR.

Program Counter Register (PC)

This register holds the address of the next instruction to run. Writing to this registers means jumping to other code.

2.2 Background Registers

Background registers can only accessed with the instructions BSTR and BLD.

ID	Mnonic	Descriptive Name	Length in bits
0x0	n/a	Reserved	8
0x1	n/a	Reserved	8
0x2	n/a	Reserved	8
0x3	n/a	Reserved	8
0x4	n/a	Reserved	8
0x5	n/a	Reserved	8
0x6	n/a	Reserved	8
0x7	n/a	Reserved	8
0x8	bpc	Program counter backup	16
0x9	bsf	Segments and flags backup	16
0xA	ipc	Interrupt program counter	16
0xB	is	Interrupt segments	16
0xC	n/a	Reserved	16
0xD	n/a	Reserved	16
0xE	n/a	Reserved	16
0xF	n/a	Reserved	16

Table 2.2: List of Background Registers

Backup Registers

The backup registers are used to backup the state of the CPU (see section 6.2). The foreground registers, segment registers and flags register all have their own backup register. However, most backup register aren't background registers. Only the segment registers, program counter register and flags register have directly accessable backup registers. Note that both segment registers and the flag register share one 16-bit backup register.

Interrupt Registers

The Interrupt registers hold the new state the CPU should jump to when an interrupt is triggered (see chapter 6). Only the segement registers and the program counter have an interrupt register.

2.3 Indirect Registers

Indirect registers are registers that software can't directly read nor write to with any instruction. All the backup registers that aren't background registers fall under this catogory. All the indirect registers can only be written to and read from via the state preservation system (see section 6.2).

Flags Register

The flags register holds multiple flags (see Table 2.3). There are two types of flags: status flags and control flags. Status flags give software extra information about the last computation made, while control flags control how the cpu behaves. There is only one control flag in the [insert name here] processor, the interrupts enabled flag. If this flag is set to zero interrupt requests will be ignored (see section 6.1)

Mnonic **Descriptive Name** Type of flag Length in bits Ζ Zero flag Status flag S Sign flag Status flag 1 Ρ Parity flag Status flag 1 O Overflow flag Status flag 1 \mathbf{C} Carry flag Status flag 1 Ι Interrupts enabled flag Control flag 1

Table 2.3: List of Flags

Section Registers

2.4 Output Registers

Operand Conventions and Addressing Modes

3.1 Operand Conventions

Bit and Byte Ordering

Aligned and Misaligned Memory Access

3.2 Addressing Modes

Not From Memory

Register Direct

Absolute

Register with displacement

From Memory

Direct

Base Plus Displacement

Instruction Set Summary

4.1 Instruction Types

Move Instructions

Arithmmic Instructions

Control Instructions

Reserved Instructions

Artifact Instructions

4.2 Instruction Format

exceptions

Memory Management

5.1 Segments

Base

Limit

- 5.2 Code Segment (CS)
- 5.3 Data Segment (DS)
- 5.4 Segment Switching
- 5.5 Changing Segments

Interrupts

6.1 Interrupt Enabling/Disabling

Interrupt Enabled Flag

Internal Interrupt Mask

Programmable Interrupt Controller (PIC)

6.2 State Preservation

Backup

Full Restore

Partial Restore

6.3 Interrupt Service Routine (ISR)

Interrupt Far Jump

Return to Context

Switch Context

I/O Conventions

- 7.1 Reading Input
- 7.2 Writing Output

Problem with Interrupts

Instruction Set

0x00: MOVZ

0x01: MOVNZ

0x02: MOVS

0x03: MOVNS

...

Appendix A

Instruction Set Listings

Table A.1: List of instructions sorted by opcode

Opcode			3.4	0 1 4	0 10
Decimal	Hex	Binary	Memnonic	Operand A	Operand B
0	0x00	000000	MOV	W?	R?
1	0x01	000001	MOV	W?	R?
2	0x02	000010	MOV	W?	R?
3	0x03	000011	MOV	W?	R?
4	0x04	000100	MOV	W?	R?
5	0x05	000101	MOV	W?	R?
6	0x06	000110	MOV	W?	R?
7	0x07	000111	MOV	W?	R?
8	0x08	001000	MOV	W?	R?
9	0x09	001001	MOV	W?	R?
10	0x0A	001010	MOV	W?	R?
11	0x0B	001011	MOV	W?	R?
12	0x0C	001100	MOV	W?	R?
13	0x0D	001101	MOV	W?	R?
14	0x0E	001110	MOV	W?	R?
15	0x0F	001111	MOV	W?	R?
16	0x10	010000	MOV	W	R
17	0x11	010001	n/a	n/a	n/a
18	0x12	010010	WRI	-	R
19	0x13	010011	n/a	n/a	n/a
20	0x14	010100	STRB	O	R
21	0x15	010101	LDB	W	O
22	0x16	010110	OUT	O	R
23	0x17	010111	IN	W	О
24	0x18	011000	BACK	_	_
25	0x19	011001	FRET	-	-
26	0x1A	011010	PRET	-	-
27	0x1B	011011	FJMP	_	-
28	0x1C	011100	$_{ m HLT}$	_	-
29	0x1D	011101	NOP	_	_
30	0x1E	011110	CMP	R	R

Table A.1: List of instructions sorted by opcode

\mathbf{Opcode}			Μ	O	O 1 D
Decimal	Hex	Binary	Memnonic	Operand A	Operand B
31	0x1F	011111	TEST	R	R
32	0x20	100000	OR	R&W	R
33	0x21	100001	OR	!R&W	R
34	0x22	100010	OR	R&W	!R
35	0x23	100011	OR	!R&W	!R
36	0x24	100100	AND	R&W	R
37	0x25	100101	AND	!R&W	R
38	0x26	100110	AND	R&W	!R
39	0x27	100111	AND	!R&W	!R
40	0x28	101000	XOR	R&W	R
41	0x29	101001	XOR	!R&W	R
42	0x2A	101010	XOR	R&W	!R
43	0x2B	101011	XOR	!R&W	!R
44	0x2C	101100	ADD	R&W	R
45	0x2D	101101	ADD	!R&W	R
46	0x2E	101110	ADD	R&W	!R
47	0x2F	101111	ADD	!R&W	!R
48	0x30	110000	ADD1	R&W	R
49	0x31	110001	ADD1	!R&W	R
50	0x32	110010	ADD1	R&W	!R
51	0x33	110011	ADD1	!R&W	!R
52	0x34	110100	ADDC	R&W	R
53	0x35	110101	ADDC	!R&W	R
54	0x36	110110	ADDC	R&W	!R
55	0x37	110111	ADDC	!R&W	!R
56	0x38	111000	SHL	W	R
57	0x39	111001	SHL1	W	R
58	0x3A	111010	RCL	W	R
59	0x3B	111011	ROL	W	R
60	0x3C	111100	SHR	W	R
61	0x3D	111101	SHR1	W	R
62	0x3E	111110	RCR	W	R
63	0x3F	111111	ROR	W	R

Appendix B

Simplified Mnemonics

Appendix C

Common Procedures

Appendix D

Standard Peripherals

- D.1 Programmable Interrupt Controller (PIC)
- D.2 Keyboard
- D.3 Programmable Interrupt Timer (PIT)
- D.4 Sound Card
- D.5 Graphical Card
- D.6 Memory Control Hub (MCH)
- D.7 Segements and Out Of Bounds Exception