

One event. Two deliveries. One simulated write.

A small, runnable example of how a webhook can be authenticated, checked for duplicate data, and retried without silently starting over.

FIRST DELIVERY

1 attempt

+

EXACT REDELIVERY

0 attempts

=

TOTAL

1 attempt

Seven observed runs

EVENT OR ACTION	OBSERVED DECISION	ATTEMPTS
First valid delivery	Would write to simulated CRM	1
Same event and data, new process	Duplicate suppressed	0
Same event ID, changed company	Payload conflict; no retry	0
CRM simulation keeps returning 500	Stops at the attempt limit	3
New process, same exhausted event	Still stopped	0
Explicit replay of that event	Would write to simulated CRM	1
Incorrect signature	Rejected before event processing	0

The useful boundary

After the retry limit is reached, restarting the process does not start another round of attempts. The original event stays stopped until an operator explicitly requests a replay.

What this demonstrates - and what it does not

The duplicate/conflict and exhaustion/replay sequences each reuse a SQLite file across separate CLI processes. The contact is fictional and the CRM is simulated. No CRM request was sent; retry delays were recorded, not slept. The public preview API has a separate, request-scoped ledger, so these restart results apply to the CLI only.

This is evidence about one inspected sample, not client work, production reliability, avoided losses, customer acceptance or earnings.