Sentiment Analysis and Issue Extraction for E-commerce Reviews with Classic NLP and Transformer Extensions

Paper-form Report Aligned with Current Code State

Team: Team SkyDom+

Group members:

Nguyen Nhu Tien Tuan	22BA13314
Tran Hien Chuong	22BA13056
Do Gia Bao	22BA13042
Bui The Anh	22BA13007
Le Duc An	22BA13002
Pham Quang Tung	22BA13320
Khuong Bao Duc	22BA13077

Updated on March 12, 2026

Abstract

This report rewrites the project paper in strict alignment with the current repository state (commit `d9c7e6f`) while preserving a formal NLP paper structure. The project addresses three tasks: binary sentiment classification with uncertainty control, multi-label issue extraction, and transformer-based extension. The source corpus contains 152,410 reviews; the issue annotation set contains 19,000 rows. In classic sentiment, variant V6 (word 1–2 + char 3–5 + negation, class weight w10) reaches test `precision_0=0.677`, `recall_0=0.932`, and `F2_0=0.867`, with selective coverage 0.885 under threshold band 0.40/0.60. The transformer sentiment extension reaches `accuracy=0.967`, `precision_0=0.822`, `recall_0=0.833`, and `F2_0=0.831`, with coverage 0.910. For issue extraction on the 3,800-row split, OVR Logistic reaches `micro-F1=0.780` and `macro-F1=0.387`, OVR LinearSVM reaches `micro-F1=0.771` and `macro-F1=0.405`, while dummy labelset baselines show high micro-F1 (`0.809`) but very low macro-F1 (`0.101`) due to majority-label dominance. The no-new-data upgrade package adds syllabus baselines, n-gram language modeling, evaluation-rigor artifacts, and transformer issue-routing experiments. All quantitative statements are sourced from saved files under `results/`.

Contents

1 Introduction **1**

2 NLP Problem Definition **1**

2.1 Task A: Sentiment Understanding 1

2.2 Task B: Issue Extraction 1

2.3 Task C: Deep Context Extension 1

3 Dataset and Language Characteristics **1**

3.1 Data Source and Scale 1

3.2 Observed Language Noise 2

3.3 Issue Label Data 2

4 Text Processing Design **3**

4.1 Normalization 3

4.2 Negation Handling 3

4.3 Contrast Handling 3

4.4 Character-level Modeling 3

5 Feature Engineering **3**

5.1 Classic Sparse Representation 3

5.2 Lexicon Feature Block 3

6 Modeling Approach **4**
6.1 Sentiment Classifiers 4
6.2 Issue Extraction Model 4
6.3 Transformer Extension 4

7 Experimental Setup **4**
7.1 Split and Protocol 4
7.2 Main Metrics 4
7.3 Uncertainty Rule 4

8 No-New-Data Syllabus Upgrade Package **5**

9 Results for Classic NLP Sentiment Model **5**
9.1 Baseline Selection by K 5
9.2 Variant Comparison 6
9.3 Threshold and Uncertainty Behavior 6

10 Results for Transformer NLP Extension **6**
10.1 Transformer Metrics 6
10.2 Transformer Threshold Sweep 7
10.3 Hard-case Comparison 7

11 Results for NLP Issue Extraction **7**
11.1 Overall Multi-label Results 7
11.2 Per-label Improvement 8
11.3 Threshold Strategy in Multi-label Setting 8

12 Results for Syllabus Upgrade Package **9**
12.1 Classic Baselines for Core Course Algorithms 9
12.2 Selective Behavior in the Added Baselines 10
12.3 N-Gram Language Model Results 10
12.4 Updated Course-Fit Matrix 10

13 Classic Versus Transformer Discussion **11**

14 Error Analysis and Failure Modes **12**

15 Practical Value for NLP Course **12**

16 Limitations and Future Work **12**

17 Conclusion **12**

References **14**

Appendix A: Sentiment Figures **15**

Appendix B: Issue Extraction Figures **20**

Appendix C: Syllabus Upgrade Figures **22**

1 Introduction

User reviews are short, noisy, and often mix praise and complaints in the same sentence. This project treats review understanding as a complete NLP pipeline problem rather than a single classifier benchmark [1, 2]. The system is designed for practical support triage where missing negative feedback has higher operational risk than over-flagging.

The paper is rewritten to follow the established course report format while synchronizing every reported metric with current artifacts in the repository. The scope is constrained to no-new-data upgrades: modeling, evaluation, calibration, and analysis improvements are performed on existing data only.

2 NLP Problem Definition

2.1 Task A: Sentiment Understanding

Task A is binary sentiment classification from review text. Ratings 1–2 are mapped to class 0 (negative), ratings 4–5 to class 1 (positive), and rating 3 is reserved as uncertain analysis data. Due to severe imbalance (about 9.5:1 positive to negative), model selection follows a negative-first ordering: maximize `recall_0`, then `F2_0`, then `precision_0`.

2.2 Task B: Issue Extraction

Task B maps review text to a multi-label issue vector with nine labels (delivery, redemption, product quality, customer service, refund, usability, value/price, fraud/scam, other). This converts unstructured text into actionable support categories [4, 5].

2.3 Task C: Deep Context Extension

Task C extends the classic pipeline with transformer fine-tuning for deeper contextual modeling, hard-case comparison, and threshold-behavior analysis [6, 7].

3 Dataset and Language Characteristics

3.1 Data Source and Scale

The source file contains 152,410 reviews. Rating distribution is shown in Table 1.

Table 1: Rating distribution in source data

Rating	Count
1	12,326
2	1,873
3	3,271
4	6,692
5	128,248

Strong-label sentiment rows (ratings 1,2,4,5) total 149,139, with 14,199 negatives and 134,940 positives.

3.2 Observed Language Noise

The corpus includes abbreviations (for example *gr8*, *thx*, *idk*), short fragments, typos, and mixed-polarity constructions such as *good but late delivery*. Negation and contrast markers are frequent and motivate dedicated handling in preprocessing and feature design.

3.3 Issue Label Data

The merged issue dataset contains 19,000 annotated rows. Label frequency is shown in Table 2.

Table 2: Issue label frequency in manual annotation set

Label	Count	Share
delivery_shipping	972	0.0512
redemption_activation	284	0.0149
product_quality	1,251	0.0658
customer_service	182	0.0096
refund_return	93	0.0049
usability	873	0.0459
value_price	558	0.0294
fraud_scam	144	0.0076
other	15,960	0.8400

4 Text Processing Design

4.1 Normalization

The default cleaner applies lowercasing, URL removal, punctuation spacing, and whitespace normalization. The goal is to reduce sparsity while preserving sentiment-bearing tokens.

4.2 Negation Handling

The classic sentiment and issue pipelines support negation propagation with a local window (current issue config: window size 3). This is critical for polarity flips in short reviews.

4.3 Contrast Handling

Contrast cues such as *but*, *however*, and clause-level polarity shifts are handled indirectly through n-gram features, including phrase patterns that encode polarity transitions.

4.4 Character-level Modeling

Character n-grams (3–5) are combined with word n-grams in selected variants to improve robustness to misspellings, abbreviations, and non-standard surface forms.

5 Feature Engineering

5.1 Classic Sparse Representation

The main sentiment representation is TF-IDF over word n-grams (1–2) and character n-grams (3–5), followed by Chi-square feature selection. The selected best variant (V6) uses `k=10000`.

For issue extraction, TF-IDF with optional character support and Chi-square filtering (selected `k=2000`) is used before one-vs-rest classification.

5.2 Lexicon Feature Block

The current default best models are data-driven sparse models. Lexicon-oriented analyses are retained as optional diagnostic components in the extension package rather than as mandatory blocks in the final deployment path.

6 Modeling Approach

6.1 Sentiment Classifiers

The classic sentiment backbone is Logistic Regression. Class-weight modes are searched across `none`, `balanced`, `w2`, `w5`, and `w10`. Variant search over preprocessing and feature toggles (V0–V7) determines the final configuration.

6.2 Issue Extraction Model

Issue extraction uses calibrated one-vs-rest Logistic Regression with per-label threshold tuning. One-vs-rest LinearSVM and a probability-level blend (`ovr_blend_lr_svm`) are retained as strong classical comparators. Two dummy baselines (`dummy_labelset_majority`, `dummy_label_prior`) are also reported as sanity checks. Current train configuration includes per-label class-weight search and sigmoid calibration (CV=3).

6.3 Transformer Extension

The transformer extension uses HuggingFace sequence-classification fine-tuning (default base family: DistilBERT in current scripts). It is evaluated with the same threshold-band policy to enable direct comparison with classic selective behavior.

7 Experimental Setup

7.1 Split and Protocol

Sentiment training uses strong-label data (ratings 1,2,4,5) with held-out validation and test sets; rating 3 is kept for uncertainty analysis. Issue extraction uses a fixed random split of 13,300/1,900/3,800 (train/val/test). The issue-transformer extension reports on 3,000/1,000/2,000.

7.2 Main Metrics

For sentiment, main metrics are `accuracy`, `F1`, `precision_0`, `recall_0`, `F1_0`, and `F2_0`. For issue extraction, metrics are micro-F1, macro-F1, subset accuracy, hamming loss, and per-label F1.

7.3 Uncertainty Rule

Selective classification uses a threshold band $[t_{low}, t_{high}]$. Samples with probability inside the band are marked uncertain; remaining samples are covered decisions. Reported se-

lective metrics include coverage, selective precision_0, selective recall_0, selective F2_0, and covered false-negative rate [9].

8 No-New-Data Syllabus Upgrade Package

The upgrade package extends the project without collecting new data. Major additions in the current codebase are:

1. Issue Level-3 enhancements: per-label class-weight search, probability calibration, threshold stability diagnostics.
2. Issue Level-4 transformer baseline and hybrid routing with capped route rate.
3. Syllabus benchmark suite: Naive Bayes, Perceptron, LinearSVM, SGD log-loss, semantic SVD baselines, FFNN MLP on SVD features.
4. N-gram language model module with add-k smoothing and perplexity reporting.
5. Evaluation-rigor package: bootstrap confidence intervals, pairwise significance tests, and error taxonomy.
6. Course-fit matrix generated directly from saved artifacts.

9 Results for Classic NLP Sentiment Model

9.1 Baseline Selection by K

Table 3 shows best validation setting per Chi-square dimension under negative-first ordering.

Table 3: Best sentiment baseline by Chi-square K (validation)

K	Class weight	Precision_0	Recall_0	F2_0	Accuracy
1,000	w10	0.555	0.910	0.806	0.922
2,000	w10	0.584	0.920	0.825	0.930
5,000	balanced	0.606	0.935	0.843	0.936
10,000	balanced	0.621	0.936	0.850	0.940

9.2 Variant Comparison

Table 4 reports test performance for engineered variants. V6 is the selected main model.

Table 4: Classic sentiment variant comparison on test

Variant	K	Class weight	Precision_0	Recall_0	F2_0
V0	10,000	balanced	0.638	0.937	0.856
V1	10,000	balanced	0.643	0.932	0.855
V2	5,000	w10	0.647	0.926	0.852
V3	10,000	balanced	0.626	0.923	0.843
V4	10,000	balanced	0.635	0.921	0.845
V5	10,000	balanced	0.653	0.933	0.859
V6	10,000	w10	0.677	0.932	0.867
V7	5,000	w10	0.657	0.927	0.857

Compared with dummy sentiment baselines (`dummy_most_frequent: F2_0=0.000`, `dummy_stratified: F2_0=0.092`), the selected V6 model (`F2_0=0.867`) shows a large practical margin on the negative class objective.

9.3 Threshold and Uncertainty Behavior

For V6, the recommended threshold band is 0.40/0.60. Table 5 shows sensitivity to threshold movement.

Table 5: Classic sentiment threshold sweep on test

Thresholds	Coverage	Sel. precision_0	Sel. recall_0	Sel. F2_0
0.40 / 0.60	0.885	0.730	0.956	0.900
0.45 / 0.60	0.891	0.708	0.956	0.894
0.50 / 0.65	0.886	0.681	0.963	0.889
0.55 / 0.70	0.881	0.646	0.970	0.882

10 Results for Transformer NLP Extension

10.1 Transformer Metrics

Table 6 summarizes transformer sentiment metrics.

Table 6: Transformer sentiment performance

Split	Accuracy	F1	Precision_0	Recall_0	F2_0	Coverage
Validation	0.968	0.982	0.821	0.854	0.847	0.908
Test	0.967	0.982	0.822	0.833	0.831	0.910

10.2 Transformer Threshold Sweep

Table 7: Transformer threshold sweep on test

Thresholds	Coverage	Sel. precision_0	Sel. recall_0	Sel. F2_0
0.40 / 0.60	0.910	0.831	0.846	0.843
0.45 / 0.60	0.911	0.827	0.847	0.843
0.50 / 0.65	0.912	0.821	0.850	0.844
0.55 / 0.70	0.911	0.818	0.855	0.847

10.3 Hard-case Comparison

Saved hard-case probes show complementary behavior. For *not bad* and *good but late delivery*, the classic model predicts negative while the transformer predicts positive. For very short tokens (*gr8*, *thx*, *idk*), both systems route to uncertain due to short-text policy.

11 Results for NLP Issue Extraction

11.1 Overall Multi-label Results

Table 8 reports the current main pipeline results (test size 3,800).

Table 8: Issue extraction overall metrics

Model	Micro-F1	Macro-F1	Subset accuracy	Hamming loss
OVR Logistic (test)	0.780	0.387	0.634	0.0585
OVR LinearSVM (test)	0.771	0.405	0.617	0.0623
OVR Blend LR+SVM (test)	0.768	0.391	0.626	0.0620
Dummy labelset majority (test)	0.809	0.101	0.811	0.0438
Dummy label prior (test)	0.809	0.101	0.811	0.0438

Dummy baselines rank high on micro-F1 and subset accuracy because they almost always predict the dominant `other` label; macro-F1 exposes that they fail on minority issue labels.

11.2 Per-label Improvement

Table 9 compares per-label F1 between SVM and Logistic on test.

Table 9: Per-label F1 change (SVM minus Logistic)

Label	Logistic F1	SVM F1	Δ
delivery_shipping	0.442	0.446	+0.004
redemption_activation	0.298	0.287	-0.010
product_quality	0.307	0.282	-0.025
customer_service	0.225	0.168	-0.057
refund_return	0.435	0.387	-0.048
usability	0.459	0.462	+0.003
value_price	0.258	0.313	+0.056
fraud_scam	0.150	0.391	+0.241
other	0.911	0.911	+0.001

11.3 Threshold Strategy in Multi-label Setting

The tuned per-label thresholds for the main `ovr_logreg` pipeline are shown in Table 10. Lower thresholds are assigned to rare labels to improve recall, while `fraud_scam` and `other` are kept more conservative.

Table 10: Final per-label thresholds in issue pipeline

Label	Threshold
delivery_shipping	0.25
redemption_activation	0.10
product_quality	0.10
customer_service	0.10
refund_return	0.15
usability	0.10
value_price	0.15
fraud_scam	0.50
other	0.30

12 Results for Syllabus Upgrade Package

12.1 Classic Baselines for Core Course Algorithms

Table 11 summarizes no-new-data sentiment baselines.

Table 11: Syllabus benchmark baselines on test

Model	Recall_0	Precision_0	F2_0
logreg_l2	0.913	0.703	0.862
multinomial_nb	0.913	0.633	0.839
complement_nb	0.952	0.510	0.811
perceptron	0.828	0.684	0.795
linear_svm	0.847	0.789	0.835
sgd_log_loss	0.921	0.616	0.838
svd_semantic_logreg	0.920	0.501	0.788
ffnn_mlp_svd	0.730	0.799	0.742

12.2 Selective Behavior in the Added Baselines

Table 12: Selective metrics for probabilistic syllabus baselines (test)

Model	Coverage	Sel. precision_0	Sel. recall_0	Sel. F2_0
logreg_l2_selective	0.887	0.763	0.946	0.903
multinomial_nb_selective	0.903	0.654	0.928	0.857
complement_nb_selective	0.900	0.545	0.963	0.835
sgd_log_loss_selective	0.863	0.696	0.959	0.892

12.3 N-Gram Language Model Results

Table 13: N-gram LM perplexity (add-k smoothing)

Model	Validation perplexity	Test perplexity
Unigram add-k	376.51	378.02
Bigram add-k	358.59	363.08

12.4 Updated Course-Fit Matrix

Table 14 reports the topic-coverage matrix generated from current artifacts. The mean coverage is **94.3%**.

Table 14: Course-fit matrix from current artifact set

Topic	Coverage (%)
Probability	100
Regular Expressions	50
Evaluation Measures	100
N-Gram Language Models	100
Naive Bayes	100
Perceptron	100
Logistic Regression	100
Feed-forward Neural Networks	100
Pytorch Basic	100
Vector Semantics and Embeddings	80
Recurrent Neural Networks	100
Transformers and LLMs	100
Masked Language Models	100
Applications of LLMs	90

13 Classic Versus Transformer Discussion

On sentiment classification, transformer improves overall accuracy and negative precision (0.822 vs 0.677), while classic V6 remains stronger on negative recall (0.932 vs 0.833) and F2_0 (0.867 vs 0.831). Under the same threshold band (0.40/0.60), transformer yields higher selective precision but lower selective recall than classic.

For issue extraction, Table 15 reports the dedicated fair-split benchmark. The classic issue model remains strongest; hybrid routing improves over pure transformer but still trails the classic setting.

Table 15: Issue extraction fair-split comparison

Model	Micro-F1	Macro-F1	Subset accuracy	Hamming loss
classic_issue_model	0.792	0.528	0.656	0.0549
hybrid_route	0.730	0.338	0.615	0.0740
transformer_multilabel	0.646	0.188	0.551	0.1013

Relative to pure transformer on this fair split, the classic issue model gains +0.146

micro-F1 and +0.340 macro-F1.

14 Error Analysis and Failure Modes

The evaluation-rigor package records 1,454 sentiment misclassified rows (194 false negatives for class 0, 1,260 false positives for class 0). Dominant false-positive categories are negation patterns (49.8%), other mixed contexts (32.4%), and contrast patterns (10.4%). Dominant false-negative categories are other contexts (52.1%), short text (23.2%), and negation patterns (14.4%).

Pairwise significance tests against baseline comparators show positive deltas for V6 (for example recall_0 +0.063 vs multinomial NB, +0.085 vs LinearSVM), but p-values remain above 0.05 in this run, so gains are treated as directional rather than statistically confirmed.

15 Practical Value for NLP Course

The project now provides a full, reproducible course artifact chain: cleaned datasets, stepwise scripts, saved models, threshold analyses, uncertainty policy, transformer extension, and evaluation-rigor outputs. This supports both engineering deployment discussion and academic defense requirements.

The upgraded syllabus package strengthens mapping to core course topics while preserving the same data budget, making the project suitable for methodology-focused assessment. Based on measurable repository artifacts, the latest rubric assessment estimates 18.04/20 (90.2%) and syllabus-topic coverage 94.3%.

16 Limitations and Future Work

Main limitations are class imbalance, high dominance of the `other` issue label, and weak transformer multi-label performance under current small-split fine-tuning. Error taxonomy also shows persistent sensitivity to negation and mixed-contrast sentences.

Future work should prioritize calibration-aware ensembling, better contextual augmentation without new labels, and lightweight sequence models for issue extraction that preserve interpretability.

17 Conclusion

This rewritten paper aligns report structure and quantitative claims with the current codebase. The main production model for sentiment is still the classic V6 variant be-

cause it optimizes negative recall/F2 under project policy. Transformer sentiment provides stronger precision and overall accuracy, and remains valuable for complementary analysis. For issue extraction, calibrated classic OVR models remain the strongest option in the current repository state. The no-new-data upgrade package substantially improves academic completeness, reproducibility, and course-topic coverage.

References

References

[1] Dan Jurafsky and James H. Martin. *Speech and Language Processing* (3rd ed. draft). 2026.
https://web.stanford.edu/ jurafsky/slp3/

[2] Peter D. Turney. Thumbs Up or Thumbs Down? Semantic Orientation Applied to Unsupervised Classification of Reviews. In *Proceedings of ACL*, 2002.
https://aclanthology.org/P02-1053/

[3] Sida Wang and Christopher D. Manning. Baselines and Bigrams: Simple, Good Sentiment and Topic Classification. In *Proceedings of ACL*, 2012.
https://aclanthology.org/P12-2018/

[4] Grigorios Tsoumakas, Ioannis Katakis, and Ioannis Vlahavas. Random k-Labelsets for multilabel classification. *IEEE Transactions on Knowledge and Data Engineering*, 23(7):1079–1089, 2011.
https://doi.org/10.1109/TKDE.2010.164

[5] Min-Ling Zhang and Zhi-Hua Zhou. A review on multi-label learning algorithms. *IEEE Transactions on Knowledge and Data Engineering*, 26(8):1819–1837, 2014.
https://doi.org/10.1109/TKDE.2013.39

[6] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention Is All You Need. In *Advances in Neural Information Processing Systems 30*, 2017.
https://arxiv.org/abs/1706.03762

[7] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of NAACL-HLT*, 2019.
https://aclanthology.org/N19-1423/

[8] Takaya Saito and Marc Rehmsmeier. The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets. *PLOS ONE*, 10(3):e0118432, 2015.
https://doi.org/10.1371/journal.pone.0118432

[9] Yonatan Geifman and Ran El-Yaniv. Selective Classification for Deep Neural Networks. *arXiv preprint arXiv:1705.08500*, 2017.
https://arxiv.org/abs/1705.08500

Appendix A: Sentiment Figures



Figure 1: Rating distribution in source data



Figure 2: Validation F1 by Chi-square top K



Figure 3: Validation recall for negative class by top K



Figure 4: Test recall for negative class by classic variant



Figure 5: Test precision for negative class by classic variant



Figure 6: Classic probability histogram on strong test set



Figure 7: Classic threshold trade-off for coverage and recall



Figure 8: Transformer confusion matrix on test set



Figure 9: Transformer probability histogram on test set



Figure 10: Transformer threshold trade-off for coverage and recall

Appendix B: Issue Extraction Figures



Figure 11: Issue label frequency in annotation set



Figure 12: Per-label F1 for OVR Logistic issue model



Figure 13: Per-label F1 for word+char issue variant



Figure 14: Per-label F1 for transformer issue baseline

Appendix C: Syllabus Upgrade Figures



Figure 15: Test recall_0 across syllabus baselines



Figure 16: Test F2_0 across syllabus baselines