

SOC/L1 -12.4.Invite Only

Extract insight from a set of flagged artefacts, and distil the information into usable threat intelligence.

Invite Only room is part of the Threat Analysis Tools module and part of the SOC Level 1 path. In this room, we are investigating a suspicious hash and IP. A file hash is a fixed-length value which uniquely identifies a file, regardless of changes to the file name. The hash will remain the same provided the file contents are identical. Hashes are used to identify suspicious files across different devices and consolidate knowledge via threat intelligence platforms. An IP is like an address for a digital device. However, IPs used for each device routinely change, so any blocks put on suspicious or malicious IPs are generally temporary.

1. What is the name of the file identified with the flagged SHA256 hash?

To start investigating the suspicious hash, we need to copy the hash given in the TryHackMe room and paste it into TryDetectThis. The initial results show file details, including the name and file type, as seen below.




Figure 1: File name and type for suspicious hash.

2. What is the file type associated with the flagged SHA256 hash?

As shown in figure 1 above, we can see the file type in the initial file report screen for the suspicious hash. In this case, the answer requires 'Win32 EXE' as the file type, rather than just .exe.

3. What are the execution parents of the flagged hash? List the names chronologically, using a comma as a separator. Note down the hashes for later use.

To find the execution parents, we need to select the *relations* tab to view related information. Here, there is a section called *Execution Parents*. The results show the file type, then the file name, and the file hash underneath. We need the file names, so we take the second value and note down the file hashes for later.



Figure 2: Execution Parents.

4. What is the name of the file being dropped? Note down the hash value for later use.

Also in the relations tab is the *dropped files* section. We once again take the name as the answer and note down the hash.




Figure 3: Dropped file.

5. Research the second hash in question 3 and list the four malicious dropped files in the order they appear (from up to down), separated by commas.

The second hash from question 3 is, fa102d4e3cfbe85f5189da70a52c1d266925f3efd122091cdc8fe0fc39033942. We search for this in TryDetectThis and view the relations tab to find the dropped files. Here, we want the malicious dropped files. These are the ones with a caution symbol on the right. We can ignore the dropped files with a green tick on the right. This gives us exactly 4 malicious dropped files which we can take the names of.




Figure 4: First 3 malicious dropped files.




Figure 5: Last malicious dropped file.

6. Analyse the files related to the flagged IP. What is the malware family that links these files?

Now we move to analysing the flagged IP. Copy the defanged IP given in the THM room and paste it into the TryDetectThis search box then remove the square brackets. Defanged refers to these square brackets surrounding the .s which prevent it from being interpreted as an IP by a browser. It is best to copy the defanged form to avoid accidents which could result in you visiting a malicious IP.

Explore the information about the IP. Information about the malware family can be found in the *community* tab where people are providing enrichment. The malware family is named as AsyncRAT.




Figure 6: Community comments for the suspicious IP.

7. What is the title of the original report where these flagged indicators are mentioned? Use Google to find the report.

To find the original report for this malware, we can use a browser to search for some of the indicators. I used the defanged IP and the malware family but other combinations of indicators will also work. The first result is the report we're looking for. Open the article to find the whole title.




Figure 7: Malware report

8. Which tool did the attackers use to steal cookies from the Google Chrome browser?

Now, we view the key takeaways section at the beginning of the article. This provides a useful, minimally technical overview of the malware. This provides the answers to the next few questions.

FROM TRUST TO THREAT: HIJACKED DISCORD INVITES USED FOR MULTI-STAGE MALWARE DELIVERY

📅 June 12, 2025

Key Takeaways

- Check Point Research uncovered an active malware campaign exploiting expired and released Discord invite links. Attackers hijacked the links through vanity link registration, allowing them to silently redirect users from trusted sources to malicious servers.
- The attackers combined the ClickFix phishing technique, multi-stage loaders, and time-based evasions to stealthily deliver AsyncRAT, and a customized Skuld Stealer targeting crypto wallets.
- Payload delivery and data exfiltration occur exclusively via trusted cloud services such as GitHub, Bitbucket, Pastebin, and Discord, helping the operation blend into normal traffic and avoid raising alarms.
- The operation continues to evolve, and threat actors can now bypass Chrome's App Bound Encryption (ABE) by using adapted tools like ChromeKatz to steal cookies from new Chromium browser versions.

Figure 8: Report key takeaways

9. Which phishing technique did the attackers use? Use the report to answer the question.

We can refer to the above bullet points to learn about the phishing technique used.

10. What is the name of the platform that was used to redirect a user to malicious servers?

We can refer to the bullet points again to learn that Discord invite links were abused to redirect users to malicious servers.

Conclusion

We have now gathered threat intelligence and enriched the flagged artefacts. This is a fundamental part of daily work as a SOC analyst.