

SOC/L1 - 4.1. Pyramid of Pain

Task 1 - Introduction

The **Pyramid of Pain** is a cybersecurity concept used in **Threat Hunting, Incident Response (IR), and Cyber Threat Intelligence (CTI)** to improve detection capabilities. It explains that defenders should move beyond **IOC-based detection** (such as malware hashes, IP addresses, and domains) and focus on **behavior-based detection**, including attacker **Tactics, Techniques, and Procedures (TTPs)**.

- **IOCs (Hashes, IPs, Domains):** Easy for attackers to change and replace, causing minimal disruption.
- **TTP-based Detection:** Harder for attackers to modify because it represents their methods and behaviors.

The key principle is:

The harder something is for an attacker to change, the more pain they experience when defenders detect it.

By focusing on attacker behaviors rather than individual indicators, SOC analysts, threat hunters, and incident responders can build more resilient security detections and improve their ability to identify advanced threats.

Task 2 - Hash Values (Trivial)

A **hash value** is a fixed-length numeric or hexadecimal value generated by a **hashing algorithm** that uniquely identifies data, such as files or malware samples.

- **MD5 (Message Digest):** Produces a **128-bit hash value**. It is widely used but is **no longer secure** due to hash collision vulnerabilities.
- **SHA-1 (Secure Hash Algorithm 1):** Produces a **160-bit hash value** (40 hexadecimal characters). It has been **deprecated by NIST** due to collision and brute-force weaknesses.
- **The SHA-2 (Secure Hash Algorithm 2):** Developed as a replacement for SHA-1. **SHA-256** is the most common variant, producing a **256-bit hash value** (64 hexadecimal characters) and is considered secure.

Security professionals use hashes to:

- Identify and track **malware samples** and suspicious files.
- Perform **threat intelligence investigations**.
- Create **IOC-based detections** in security tools.
- Reference malicious artifacts in malware reports.

A hash is **not secure** if two different files can generate the same hash value (**hash collision**). Hashes are valuable **Indicators of Compromise (IOCs)** for identifying known malicious files, but attackers can easily modify malware to change its hash. Therefore, modern detection focuses increasingly on **behavior and TTPs** rather than only hashes.

Hash Lookup Tools: Security analysts commonly use online platforms to investigate file hashes, such as:

- VirusTotal
- OPSWAT MetaDefender Cloud

VirusTotal:

The screenshot shows the VirusTotal interface for a file with hash 3f33734b2d34cce83936ce99c3494cd845fd2c02d7f6da31d42dfc1ca15a171. The file is named 'm_croetian.wnry' and is an RTF file (38.15 KB, uploaded 28 days ago). A red circle indicates that 14 security vendors flagged this file as malicious. Below this, a table lists the detections from various vendors.

DETECTION	DETAILS	RELATIONS	BEHAVIOR	COMMUNITY
Antiy-AVL	ⓘ Trojan.Generic.ASSuf.19EC8	CAT-QuickHeal	ⓘ RTF.Trojan.Agent.40329	
Comodo	ⓘ Malware@#1t7uob1a9vm9d	ESET-NOD32	ⓘ Win32/Filecoder.WannaCryptor.D	
Gridinsoft	ⓘ Ransom.U.Ransom.oa	Ikarus	ⓘ Trojan.Win32.Filecoder	
Lionic	ⓘ Trojan.MSOffice.Generic.Alc	McAfee	ⓘ RTF/Wannacry.a	
McAfee-GW-Edition	ⓘ RTF/Wannacry.a	Microsoft	ⓘ Ransom.Win32/WannaCrypt.Alsrm	
Symantec	ⓘ Trojan.Gen.NPE.2	Tencent	ⓘ Win32.Trojan.Filecoder.Dvzt	
TrendMicro	ⓘ TROJ_RANSOMNOTE.RTF	TrendMicro-HouseCall	ⓘ TROJ_RANSOMNOTE.RTF	

Below the hash in the screenshot above, you can see the filename. In this case, it is "m_croetian.wnry"

MetaDefender Cloud - OPSWAT:

Overview

Static Analysis

Community

E325988F68D327743926EA317ABB9882F347...

↓ Sanitized version

Threat name: Trojan/WcrylyBhUK2kw

Cast your vote on this file: 0 0 0

Metascan

Threats detected

08 /34
ENGINES

Get full report

[Upgrade limits](#)

Sandbox Threat Score

No dynamic analysis performed

00 /10

View dynamic analysis

[Sandbox documentation](#)

Community Insight

User votes

%

View leaderboards

[Check out our community](#)

Analyse the report associated with the hash

"b8ef959a9176aef07fdca8705254a163b50b49a17217a4ff0107487f59d4a35d"
here. What is the filename of the sample?

Sales_Receipt 5606.xls

b8ef959a9176aef07fdca8705254a163b50b49a17217a4ff0107487f59d4a35d



37 security vendors and 2 sandboxes flagged this file as malicious

b8ef959a9176aef07fdca8705254a163b50b49a17217a4ff0107487f59d4a35d

Sales_Receipt 5606.xls

[xls](#) [spreader](#) [calls-vml](#) [attachment](#)

Task 3 - IP Address (Easy)

IP addresses are used to identify devices connected to a network and enable communication between systems. In the **Pyramid of Pain**, IP addresses are classified as a lower-level indicator because attackers can easily change them. From a defensive perspective, blocking malicious IP addresses using firewalls can help prevent attacks, but this method is not highly effective because attackers can quickly switch to new IP addresses. Attackers often use **Fast Flux**, a DNS technique that associates multiple changing IP addresses with a single domain. This helps hide phishing sites, malware delivery systems, and **Command and**

Task 4 - Domain Names (Simple)

Domain names map IP addresses to human-readable names (e.g., `evilcorp.com`). In the **Pyramid of Pain**, domain names are more difficult for attackers to change than IP addresses because they must register new domains and modify DNS records. However, attackers can still quickly change domains using flexible DNS providers and APIs.

Attackers use techniques like **Punycode attacks** to create malicious domains that look similar to legitimate websites. Punycode converts Unicode characters into ASCII format, allowing attackers to create lookalike domains for phishing campaigns.


Attackers also use **URL shorteners** to hide malicious links and make detection harder. Security analysts can investigate shortened URLs by checking their redirect destinations.

Tools like **Any.Run** help analysts analyze malware behavior by monitoring:

- **HTTP requests** – Shows web traffic and resources accessed by malware.
- **Network connections** – Reveals communication with external hosts, such as C2 servers.
- **DNS requests** – Shows domain lookups made by malware, often used for command-and-control communication or internet connectivity checks.

"Punycode is a way of converting words that cannot be written in ASCII, into a Unicode ASCII encoding."

HTTP Requests: This tab shows the recorded HTTP requests since the detonation of the sample. This can be useful to see what resources are being retrieved from a webserver, such as a dropper or a callback.



HTTP Requests		7	Connections	51	DNS Requests	20	Threats	0	Filter by PID, name or url		PCAP
Timeshift	Headers	Rep	PID	Process name	CN	URL	Content				
25853 ms	GET 204: No Content	✓	2572	chrome.exe	🇺🇸	http://www.gstatic.com/generate_204	—				
44576 ms	GET 200: OK	✓	2572	chrome.exe	🇺🇸	http://ctldl.windowsupdate.com/msdownload/update/v3/static/trustedr/en/authrootstl.cab...	62.3 Kb	↓	compressed		
76052 ms	HEAD 200: OK	✓	852	svchost.exe	🇺🇸	http://edgedl.me.gvt1.com/edgedl/release2/chrome_component/YGkwa4MXjfwSuRyWQY...	—				
81155 ms	GET 200: OK	✓	852	svchost.exe	🇺🇸	http://edgedl.me.gvt1.com/edgedl/release2/chrome_component/YGkwa4MXjfwSuRyWQY...	3.72 Kb	↓	binary		
10577 s	HEAD 200: OK	✓	852	svchost.exe	🇺🇸	http://edgedl.me.gvt1.com/edgedl/release2/chrome_component/eua6zlfhp3roq46nymxtbz...	3.72 Kb	↓	crx		
10577 s	GET 206: Partial Con...	✓	852	svchost.exe	🇺🇸	http://edgedl.me.gvt1.com/edgedl/release2/chrome_component/eua6zlfhp3roq46nymxtbz...	7.13 Kb	↓	binary		
11088 s	GET 206: Partial Con...	✓	852	svchost.exe	🇺🇸	http://edgedl.me.gvt1.com/edgedl/release2/chrome_component/eua6zlfhp3roq46nymxtbz...	3.11 Kb	↓	binary		

Connections: This tab shows any communications made since the detonation of the sample. This can be useful to see if a process communicates with another host. For example, this could be C2 traffic, uploading/downloading files over FTP, etc.

HTTP Requests7 Connections51 DNS Requests20 Threats0 Filter by PID, domain, name or ip PCAP										
NETWORK	Timeshift	Protocol	Rep	PID	Process name	CN	IP	Port	Domain	ASN
										Traffic
FILES	1309 ms	UDP	✓	4	System	?	192.168.100.255	138	-	-
	1312 ms	UDP	✓	1076	svchost.exe	?	224.0.0.252	5355	-	-
	1314 ms	UDP	✓	3740	svchost.exe	?	239.255.255.250	1900	-	-
	1315 ms	UDP	✓	4	System	?	192.168.100.255	137	-	-
	4397 ms	UDP	✓	1076	svchost.exe	?	224.0.0.252	5355	-	-
	4399 ms	UDP	✓	1076	svchost.exe	?	224.0.0.252	5355	-	-
	4405 ms	UDP	✓	2044	chrome.exe	?	239.255.255.250	1900	-	-
	4408 ms	UDP	✓	1076	svchost.exe	?	224.0.0.252	5355	-	-
	5412 ms	TCP	✓	2572	chrome.exe	🇺🇸	142.250.185.173	443	accounts.google.com	GOOGLE
	5573 ms	TCP	✓	2572	chrome.exe	🇺🇸	142.250.186.142	443	clients2.google.com	GOOGLE
DEBUG										No Data

DNS Requests: This tab shows the DNS requests made since the detonation of the sample. Malware often makes DNS requests to check for internet connectivity.

HTTP Requests7Connections51DNS Requests20Threats0

Filter by IP or domain

PCAP

	Timeshift	Status	Rep	Domain	IP
NETWORK	5371 ms	Responded	?	ice-eng.app.box.com	74.112.186.144
	5373 ms	Responded	✓	accounts.google.com	142.250.185.173
	5373 ms	Responded	✓	clients2.google.com	142.250.186.142
	5374 ms	Responded	✓	clients2.googleusercontent.com	142.250.186.97
FILES	11478 ms	Responded	✓	ssl.gstatic.com	142.250.184.227
	25794 ms	Responded	✓	www.gstatic.com	142.250.186.99
	27799 ms	Responded	✓	cdn01.boxcdn.net	104.16.74.20
					104.18.103.56
DEBUG					52.222.206.6
					52.222.206.178
	29500 ms	Responded	✓	cdn.amplitude.com	

Answer the questions below

Go to this report on app.any.run (opens in new tab) and provide the first suspicious domain request you are seeing, you will be using this report to answer the remaining questions of this task. craftingalegacy.com

What term refers to an address used to access websites? Domain Name

What type of attack uses Unicode characters in the domain name to imitate the a known domain? Punycode attack

Provide the redirected website for the shortened URL using a preview:

<https://tinyurl.com/bw7t8p4u><https://tryhackme.com/>

<https://tinyurl.com/bw7t8p4u> + (to see that put + aign at the end of url)

Task 5 - Host Artifacts (Annoying)

Artifacts : In cybersecurity, **artifacts** are **traces, evidence, or observable data left behind by users, attackers, malware, or system activities**. Security analysts examine these artifacts during **incident response, digital forensics, and threat hunting** to identify suspicious behavior and investigate attacks.

Host artifacts are the traces or observables that attackers leave on the system, such as registry values, suspicious process execution, attack patterns or IOCs (Indicators of Compromise), files dropped by malicious applications, or anything exclusive to the current threat.

Host artifacts are traces left by attackers on a compromised system, such as registry changes, suspicious processes, malicious files, attack patterns, or other **Indicators of Compromise (IOCs)**. In the **Pyramid of Pain**, detecting host artifacts causes more frustration for attackers because they must change their tools, techniques, and methods. This requires more time, effort, and resources to bypass detection. Host artifact detection provides stronger defense because attackers must modify their attack approach instead of simply changing IP addresses or domains.

Suspicious process execution from Word:

 WINWORD.EXE	0.01	51,500 K	134,300 K	3640 Microsoft Word	Microsoft Corporation
 api-ms-win-downlevel-user32-l1-...		4,632 K	11,192 K	3300 EffectDemo MFC Application	

Suspicious events followed by opening a malicious application:

Time o...	Process Name	PID	Operation	Path	Result
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS
3/24/26...	Powershell.exe	3540	WriteFile	C:\Users\RussianPanda\Jehhzda\Ben14f\G_jugk.exe	SUCCESS
3/24/26...	Powershell.exe	3540	TCP Receive	192.168.75.222:1047 -> 35.214.215.33:80	SUCCESS

The files modified/dropped by the malicious actor:

2728	WINWORD.EXE	C:\Users\admin\AppData\Local\Temp\VBEM\MSForms.exd	MD5: CC11BFD14D6ECC83477B69FF06C6C587	SHA256: A4E8F5821887AC26449C33D9B027CE31BE0E7203DD035C5DC7D34A9AEF01A6DA	tlb
2728	WINWORD.EXE	C:\Users\admin\AppData\Local\Temp\~\$O-100120 CDW-102220.doc	MD5: 2E7A3442236F2D50C669BC791888BD69	SHA256: BF007001BACF8F6ABF371B0B2797B7D13B741879E1E5B76FB616A934318418A9	pgc
3828	Powershell.exe	C:\Users\admin\Jehhzda\Ben14f\G_jugk.exe	MD5: 92F58C4E2F524EC53EBE10D914D96CCB	SHA256: 4A9E32BC5348265C43945ADAAAF140B98B64329BD05878BC13671FA916F423710	executable
1640	G_jugk.exe	C:\Users\admin\AppData\Local\photowiz\regidle.exe	MD5: 92F58C4E2F524EC53EBE10D914D96CCB	SHA256: 4A9E32BC5348265C43945ADAAAF140B98B64329BD05878BC13671FA916F423710	executable

Answer the questions below

A process named regidle.exe makes a POST request to an IP address based in the United States (US) on port 8080. What is the IP address? 96.126.101.6

Network activity

HTTP(S) requests	TCP/UDP connections	DNS requests	Threats
18	25	4	27

HTTP requests

PID	Process	Method	HTTP Code	IP	URL	CN	Type	Size	Reputation
3164	regidle.exe	POST	—	200.116.145.225:443	http://200.116.145.225:443/x4VtVzvRhVPEyfb/Xq02AK6oEVt/	CO	—	—	malicious
3164	regidle.exe	POST	—	96.126.101.6:8080	http://96.126.101.6:8080/VDpVH/UUmWd7VBxpU7L/VxWud uF/zT560LD/f6oH6uVWDWqAskvA/U3LgE/	US	—	—	malicious
3828	POWershell.exe	GET	404	69.65.3.162:80	http://eubanks7.com/administrator/ubdDbB/	US	html	315 b	suspicious
3828	POWershell.exe	GET	200	35.214.215.33:80	http://lidoraggiadisole.it/cgi-bin/zLG879/	US	executable	368 Kb	malicious
3164	regidle.exe	POST	404	5.196.108.185:8080	http://5.196.108.185:8080/VznUAWLq/pARcFNvv/EWIHCiK Kbvaf/zQVAdPyKoQYwu/GZAcsRRGqJEa3/QNV1u3DgLR5d n8G/	FR	html	564 b	malicious
3164	regidle.exe	POST	—	167.114.153.111:8080	http://167.114.153.111:8080/8zgZioGYStRl/Jk8OOBe/ HRAZSzsYY/9lpMzzRmtoHM/	CA	—	—	malicious
3164	regidle.exe	POST	—	194.187.133.160:443	http://194.187.133.160:443/Nqdlz/w2BG/	BG	—	—	malicious
3164	regidle.exe	POST	—	103.86.49.11:8080	http://103.86.49.11:8080/VCvOqXmJgEehauu/AyEp/O9Qn2/ R6Rj7Gw9eOvbyJ/FCsa36YtopGe/Q2AwYvSohZlYaEtbb0/	TH	—	—	malicious
3164	regidle.exe	POST	—	98.174.164.72:80	http://98.174.164.72/ghMuzyNCNWN/kMmYdVlthxvVyoZfe o8eu7Jyv/O2MSWlF9SpyCp/jLVEV96eosyd5URJ477/8wdGX dz9k9hhJ/Wp/	US	—	—	malicious

The actor drops a malicious executable (EXE). What is the name of this executable? (Host artifact) G_jugk.exe


Files activity

Executable files	Suspicious files	Text files	Unknown types
2	3	0	3

Dropped files

PID	Process	Filename	Type
2728	WINWORD.EXE	C:\Users\admin\AppData\Local\Temp\CVR442C.tmp.cvr MD5: — SHA256: —	—
3828	POWershell.exe	C:\Users\admin\AppData\Roaming\Microsoft\Windows\Recent\CustomDestinations\d93f411851d7c929.customDestinations.ms MD5: FF2E5687F6AEB2AD7D5766EF1959944F SHA256: B4985E762E7471F122FBD6A9B7FF91E810B644CB827469EA77736E5A6107ED01	binary
3828	POWershell.exe	C:\Users\admin\AppData\Roaming\Microsoft\Windows\Recent\CustomDestinations\FIT0N66RBH0VW9F6AR5X.tmp MD5: FF2E5687F6AEB2AD7D5766EF1959944F SHA256: B4985E762E7471F122FBD6A9B7FF91E810B644CB827469EA77736E5A6107ED01	binary
2728	WINWORD.EXE	C:\Users\admin\AppData\Roaming\Microsoft\Templates\~\$Normal.dotm MD5: 475553794AFCEFC9B9C775CB487A133 SHA256: EDA472127C813AD9BAE1D0D5575D8FAA2B95568639563D81408EDB4C71962BA5	pgc
3828	POWershell.exe	C:\Users\admin\AppData\Roaming\Microsoft\Windows\Recent\CustomDestinations\d93f411851d7c929.customDestinations-ms~RF2b495c.TMP MD5: FF2E5687F6AEB2AD7D5766EF1959944F SHA256: B4985E762E7471F122FBD6A9B7FF91E810B644CB827469EA77736E5A6107ED01	binary
2728	WINWORD.EXE	C:\Users\admin\AppData\Local\Temp\VBEM\MSForms.exe MD5: CC118FD14D6ECC83477B69FF06C6C587 SHA256: A4E8F5821887AC26449C33D9B027CE318E0E7203DD035C5DC7D34A9AEF01A6DA	tib
2728	WINWORD.EXE	C:\Users\admin\AppData\Local\Temp\~\$O-100120 CDW-102220.doc MD5: 2E7A3442236F2D50C669BC791888BD69 SHA256: BF007001BACF8F6ABF37180B2797B7D13B741879E1E5B76FB616A93418418A9	pgc
3828	POWershell.exe	C:\Users\admin\Jehhzda\Ben14fr\G_jugk.exe MD5: 92F58C4E2F524EC53EBE10D914D96CCB SHA256: 4A9E32BC5348265C43945ADAAAF140B98B64329BD05878BC13671FA916F423710	executable
1640	G_jugk.exe	C:\Users\admin\AppData\Local\photowiz\regidle.exe MD5: 92F58C4E2F524EC53EBE10D914D96CCB SHA256: 4A9E32BC5348265C43945ADAAAF140B98B64329BD05878BC13671FA916F423710	executable

Look at this report by VirusTotal. How many vendors determine this host to be malicious? 9



Task 6 - Network Artifacts (Annoying)

Network Artifacts also belong to the yellow zone in the Pyramid of Pain. This means if you can detect and respond to the threat, the attacker would need more time to go back and change his tactics or modify the tools, which gives you more time to respond and detect the upcoming threats or remediate the existing ones.

A network artifact can be a user-agent string, C2 information, or URI patterns followed by the HTTP POST requests. An attacker might use a User-Agent string that hasn't been observed in your environment before or seems out of the ordinary. The User-Agent is defined by [RFC2616](#) ([opens in new tab](#)) as the request-header field that contains the information about the user agent originating the request.

Network artifacts can be detected in PCAPs (file that contains the network packet dumps) by using a tool such as Wireshark or TShark, or exploring IDS (Intrusion Detection System) alerts from a tool such as [Snort](#) ([opens in new tab](#)). You will learn these tools in the following rooms, but in short, imagine a list of suspicious HTTP POST requests:

192.168.100.140	194.187.133.160	936 HTTP	POST /Nqd1z/wZBG/ HTTP/1.1
192.168.100.140	98.174.164.72	936 HTTP	POST /ghMuzyNCHNM/kMmYdVithxeVy/o2feo8eu73yv/02M8WIF99pyCp/yLVEV96eosyd5URJ477/8wdGxdz9k9hh3jWp/ HTTP/1.1
192.168.100.140	103.86.49.11	936 HTTP	POST /VCvOqXhJgEehau/AyEp/09Qn2/R6Rj7Gw9e0v6yJ/FC5a36YfopGe/Q2AwYvSohZiyaEtbbo/ HTTP/1.1
192.168.100.140	78.24.219.147	904 HTTP	POST /jC0c/oQQPMafJlpMi6n3/Pbao/K7oB22aAUKQ61A6r/Go0MY/ HTTP/1.1
192.168.100.140	50.245.107.73	888 HTTP	POST /ukXcIslj3svd7W/h2VQ1YqB/csuQkgUq1kakMvQRJ9/NCjJodG/ HTTP/1.1
192.168.100.140	110.145.77.103	888 HTTP	POST /QZvVQ6o1I/DYk9QgXU/HtoxmCRHbYCJhgamm/5NsCejn3/ HTTP/1.1

It's hard to attribute the requests to a specific malware from the first glance, but you can dig deeper and look for its network indicators, such as the **User-Agent**. In TShark, you could use the following command:


- `tshark --Y http.request -T fields -e http.host -e http.user_agent -r analysis_file.pcap`

[illegible]

These are the most common User-Agent strings found for the [Emotet](#) (opens in new tab) trojan. If you can detect the custom User-Agent strings that the attacker is using, you might be able to block them, creating more obstacles and making their attempt to compromise the network more annoying.

Answer the questions below

Which network indicator helped us identify the malware type (Emotet)? User-Agent (google the string)



How many POST requests are in the screenshot from the PCAP file? 6

192.168.100.140	194.187.133.160	936 HTTP	POST /Nqdlz/w2BG/ HTTP/1.1
192.168.100.140	98.174.164.72	936 HTTP	POST /ghMuzyNCNWN/kMmYdVithxeVy/o2feo8eu7Jyv/O2M8WIf9SpyCp/yLVEV9
192.168.100.140	103.86.49.11	936 HTTP	POST /VCv0qXMjgEehauu/AyEp/O9Qn2/R6Rj7Gw9e0v6yJ/FC5a36YfopGe/Q2Aw
192.168.100.140	78.24.219.147	904 HTTP	POST /jC0c/oQQPMaFJ1pMi6n3/Pbao/K7oB22aAUKQ61A6r/GoOMY/ HTTP/1.1
192.168.100.140	50.245.107.73	888 HTTP	POST /ukXcIsljsvd7W/h2VQlYqB/csuQkgUq1kakMvQRJ9/NCjJodG/ HTTP/1.1
192.168.100.140	110.145.77.103	888 HTTP	POST /QZvVQ6o1I/DYk9QgXU/HtoXMRHbYCJhganW/SNsCeJn3/ HTTP/1.1

Task 7 - Tools (Challenging)

At the **Tools** level of the Pyramid of Pain, defenders can detect and identify the specific tools attackers use. This creates more difficulty for attackers because they must develop new tools, find alternatives, or gain new skills to continue their operations.

Attackers commonly use tools to:


- Create malicious documents (**maldocs**) for spear-phishing.
- Build backdoors for **Command and Control (C2)** communication.
- Generate custom **EXE/DLL files**, payloads, and password-cracking tools.

Security teams can detect these tools using:

- **Antivirus signatures**
- **Detection rules**
- **YARA rules**
- Threat intelligence sources such as **MalwareBazaar** and **Malshare**

Threat hunters can also use **fuzzy hashing** (e.g., **SSDeep**) to perform similarity analysis and identify modified versions of malware even when small changes have been made.

A Trojan dropped the suspicious "Stealer.exe" in the Temp folder:



The execution of the suspicious binary:

payload.exe	1356	12.09 MB	WIN-31...	RussianPanda
Stealer.exe	2928	11.63 MB	WIN-31...	RussianPanda Galactus

Fuzzy hashing is to perform similarity analysis and identify modified versions of malware even when small changes have been made.

Example of SSDeep from VirusTotal:

DETECTION	DETAILS	RELATIONS	BEHAVIOR	COMMUNITY 13+
Basic Properties ⓘ				
MD5	9498ff82a64ff445398c8426ed63ea5b			
SHA-1	36f9ca40b3ce96fcee1cf1d4a7222935536fd25b			
SHA-256	8b2e701e91101955c73865589a4c72999aeabc11043f712e05fdb1c17c4ab19a			
Vhash	025056657d755510804011z9005b9z25z12z3afz			
Authentihash	ad56160b465f7bd1e7568640397f01fc4f8819ce6f0c1415690ecee646464cec			
Imphash	d7584447a5c5ca9b4a55946317137951			
Rich PE header hash	fa4dbca9180170710b3c245464efa483			
SSDEEP	6144:Gz90qLc1zR98hUb4UdjzEwG+vgAWiR4EXePbix67CNzjX:Gz90qLc1lWhUbhVqJPbiQ7CNzb			
TLSH	T1DB44CF267660D833D0DF94316C75C3F9673BFC2123215A6B6A4417699E307E0AE7839E			
File type	Win32 EXE			
Magic	PE32 executable for MS Windows (GUI) Intel 80386 32-bit			
TrID	Win32 Executable MS Visual C++ (generic) (48.8%)			
TrID	Win64 Executable (generic) (16.4%)			
TrID	Win32 Dynamic Link Library (generic) (10.2%)			
TrID	Win16 NE executable (generic) (7.8%)			
TrID	Win32 Executable (generic) (7%)			
File size	249.00 KB (254976 bytes)			

Answer the questions below

Provide the method used to determine similarity between the files. Fuzzy Hashing

Provide the alternative name for fuzzy hashes without the abbreviation context triggered piecwise hashes ssdeep - Fuzzy hashing program

Task 8 - TTPs (Tough)

TTPs stand for **Tactics, Techniques, and Procedures** and describe the complete methods attackers use to achieve their objectives. They include activities covered in the **MITRE ATT&CK Framework**, from initial access techniques like **phishing** to **persistence, lateral movement, and data exfiltration**. Detecting and responding to attacker **TTPs** is one of the strongest defense strategies because attackers must significantly change their behavior and methods to bypass detection.

A **Pass-the-Hash attack** allows attackers to use stolen password hashes as **authentication tokens**, enabling lateral movement without needing the actual password.

Answer the questions below

Navigate to ATT&CK Matrix webpage. How many techniques fall under the Exfiltration category? 9



The image shows a screenshot of the ATT&CK Matrix website for the 'Exfiltration' category. At the top, there is a grey header bar. Below it, the word 'Exfiltration' is displayed in a large, bold, blue font. Underneath, it says '9 techniques'. A list of nine techniques is shown in a table-like format with a light blue background and a dark blue border. Each technique has a small icon to its right. The techniques are: Automated Exfiltration (1), Data Transfer Size Limits, Exfiltration Over Alternative Protocol (3), Exfiltration Over C2 Channel, Exfiltration Over Other Network Medium (1), Exfiltration Over Physical Medium (1), Exfiltration Over Web Service (4), Scheduled Transfer, and Transfer Data to Cloud Account.

Exfiltration	
9 techniques	
Automated Exfiltration (1)	II
Data Transfer Size Limits	
Exfiltration Over Alternative Protocol (3)	II
Exfiltration Over C2 Channel	
Exfiltration Over Other Network Medium (1)	II
Exfiltration Over Physical Medium (1)	II
Exfiltration Over Web Service (4)	II
Scheduled Transfer	
Transfer Data to Cloud Account	

From left to right based on the **attacker's attack lifecycle** (tactics). Each column represents a **Tactic**, which describes the attacker's goal at that stage. **Under each tactic, Techniques** and **Sub-techniques** that describe *how* attackers achieve those goals.

A **Cobalt Strike attack** refers to the misuse of the **Cobalt Strike framework** by threat actors to control compromised systems, perform post-exploitation activities, and move deeper into a target network.

Rapid7 is a **cybersecurity company** that provides security solutions for **vulnerability management, SIEM, threat detection, and incident response**

Chimera is a China-based hacking group that has been active since 2018. What is the name of the commercial, remote access tool they use for C2 beacons and data exfiltration? Cobalt Strike

MITRE | ATT&CK®

GROUPS

Carbanak

Chimera

Cinnamon Tempest

Cleaver

Cobalt Group

Confucius

Contagious Interview

CopyKittens

CURIUM

CyberAv3ngers

Daggerfly

Dark Caracal

Darkhotel

			Pass the
Enterprise	T1078		Valid Ac
		.002	Domain
Enterprise	T1047		Window: Instrume

Software

ID	Name	References
S0521	BloodHound	[1]
S0154	Cobalt Strike	[1][2]

Task 9 - Practical: The Pyramid of Pain

Deploy the static site attached to this task

Answer the questions below

| Complete the static site. What is the flag? THM{PYRAMIDS_COMPLETE}

