REPORT HW2

- *When we enter one parameter in the console
- *When we enter more than two parameter in the console

```
thiscat@Thiscat: ~/Masaüstü

File Edit View Search Terminal Help

thiscat@Thiscat: ~/Masaüstü$ gcc taskQueue.c -o queue
thiscat@Thiscat: ~/Masaüstü$ ./queue
We only need 2 arguments
thiscat@Thiscat: ~/Masaüstü$ ./queue 5 7
We only need 2 arguments
thiscat@Thiscat: ~/Masaüstü$ ...
```

*When we keep our range of values small

Ex. ==> int rand_value = rand() % 5;

./queue 0

./queue 1

./ queue 10

```
thiscat@Thiscat: ~/Masaüstü
File Edit View Search Terminal Help
thiscat@Thiscat:~/Masaüstü$ gcc taskQueue.c -o queue
thiscat@Thiscat:~/Masaüstü$ ./queue 10
**********
  Generated 10 random list tasks...
*********
  Task 0 ~ Delete 2 ==> 2 cannot be deleted.
  Task 1 ~ Delete 4 ==> 4 cannot be deleted.
  Task 2 ~ Insert 2 ==> 2 inserted.
  Task 3 ~ Delete 4 ==> 4 cannot be deleted.
Task 4 ~ Insert 2 ==> 2 cannot be inserted.
  Task 5 ~ Insert 4 ==> 4 inserted.
  Task 6 ~ Insert 1 ==> 1 inserted.
Task 7 ~ Delete 4 ==> 4 deleted.
  Task 8 ~ Delete 4 ==> 4 cannot be deleted.
  Task 9 ~ Insert 1 ==> 1 cannot be inserted.
 ********* Final List ********
 thiscat@Thiscat:~/Masaüstü$
```

*When we keep our range of values large

Ex. ==> int rand_value = rand() % 50;

./ queue 10