

# 1. Two Sum [↗](#) (/problems/two-sum/)

March 5, 2016 | 1.5M views

Average Rating: 4.80 (1974 votes)

Given an array of integers, return **indices** of the two numbers such that they add up to a specific target.

You may assume that each input would have **exactly** one solution, and you may not use the *same* element twice.

## Example:

```
Given nums = [2, 7, 11, 15], target = 9,
```

```
Because nums[0] + nums[1] = 2 + 7 = 9,  
return [0, 1].
```

## Solution

### Approach 1: Brute Force

The brute force approach is simple. Loop through each element  $x$  and find if there is another value that equals to  $target - x$ .



Java

```
1 public int[] twoSum(int[] nums, int target) {
2     for (int i = 0; i < nums.length; i++) {
3         for (int j = i + 1; j < nums.length; j++) {
4             if (nums[j] == target - nums[i]) {
5                 return new int[] { i, j };
6             }
7         }
8     }
9     throw new IllegalArgumentException("No two sum solution");
10 }
```

## Complexity Analysis


- Time complexity :  $O(n^2)$ . For each element, we try to find its complement by looping through the rest of array which takes  $O(n)$  time. Therefore, the time complexity is  $O(n^2)$ .
- Space complexity :  $O(1)$ .

## Approach 2: Two-pass Hash Table

To improve our run time complexity, we need a more efficient way to check if the complement exists in the array. If the complement exists, we need to look up its index. What is the best way to maintain a mapping of each element in the array to its index? A hash table.

We reduce the look up time from  $O(n)$  to  $O(1)$  by trading space for speed. A hash table is built exactly for this purpose, it supports fast look up in *near* constant time. I say "near" because if a collision occurred, a look up could degenerate to  $O(n)$  time. But look up in hash table should be amortized  $O(1)$  time as long as the hash function was chosen carefully.

A simple implementation uses two iterations. In the first iteration, we add each element's value and its index to the table. Then, in the second iteration we check if each element's complement ( $target - nums[i]$ ) exists in the table. Beware that the complement must not be  $nums[i]$  itself!



Java


```
1 public int[] twoSum(int[] nums, int target) {
2     Map<Integer, Integer> map = new HashMap<>();
3     for (int i = 0; i < nums.length; i++) {
4         map.put(nums[i], i);
5     }
6     for (int i = 0; i < nums.length; i++) {
7         int complement = target - nums[i];
8         if (map.containsKey(complement) && map.get(complement) != i) {
9             return new int[] { i, map.get(complement) };
10        }
11    }
12    throw new IllegalArgumentException("No two sum solution");
13 }
```

### Complexity Analysis:

- Time complexity :  $O(n)$ . We traverse the list containing  $n$  elements exactly twice. Since the hash table reduces the look up time to  $O(1)$ , the time complexity is  $O(n)$ .
- Space complexity :  $O(n)$ . The extra space required depends on the number of items stored in the hash table, which stores exactly  $n$  elements.

### Approach 3: One-pass Hash Table

It turns out we can do it in one-pass. While we iterate and inserting elements into the table, we also look back to check if current element's complement already exists in the table. If it exists, we have found a solution and return immediately.



Java

```
1 public int[] twoSum(int[] nums, int target) {
2     Map<Integer, Integer> map = new HashMap<>();
3     for (int i = 0; i < nums.length; i++) {
4         int complement = target - nums[i];
5         if (map.containsKey(complement)) {
6             return new int[] { map.get(complement), i };
7         }
8         map.put(nums[i], i);
9     }
10    throw new IllegalArgumentException("No two sum solution");
11 }
```

### Complexity Analysis:

- Time complexity :  $O(n)$ . We traverse the list containing  $n$  elements only once. Each look up in the table costs only  $O(1)$  time.
- Space complexity :  $O(n)$ . The extra space required depends on the number of items stored in the hash table, which stores at most  $n$  elements.

Rate this article:

◀ Previous (/articles/reverse-linked-list/)

Next ▶ (/articles/first-bad-version/)

Comments: **911**

Sort By ▼

Type comment here... (Markdown is supported)

👁 Preview

Post

adarshnaidu2511 (adarshnaidu2511) ★ 357 🕒 October 20, 2018 4:59 PM



How to view the solution in c

356 ^ v | 📄 Share | ↩ Reply

SHOW 5 REPLIES

zk584807419 (zk584807419) ★ 188 🕒 June 8, 2018 11:54 AM



python3 version

python3的版本,原谅我太笨

```
class Solution:
```

Read More

181 ^ v | 📄 Share | ↩ Reply

SHOW 7 REPLIES

HankLiu5 (hankliu5) ★ 129 🕒 November 7, 2018 7:37 AM



python3

Read More

125 ^ v | Share | Reply

SHOW 4 REPLIES

jakesully (jakesully) ★ 94 ⌚ November 22, 2018 12:49 PM



[JAVASCRIPT] Took me several attempts...But this code says:

"Runtime: 52 ms, faster than 100.00% of JavaScript online submissions for Two Sum."

```
const twoSum = function(nums, target) {  
  const comp = {};
```

Read More

94 ^ v | Share | Reply

SHOW 13 REPLIES

panahi (panahi) ★ 107 ⌚ April 27, 2019 11:10 PM



Clean Python One-Pass solution:

```
def twoSum(self, nums, target):  
    seen = {}  
    for i, v in enumerate(nums):
```

Read More

74 ^ v | Share | Reply

SHOW 3 REPLIES

A\_xian\_ (a\_xian\_) ★ 69 ⌚ October 10, 2018 6:15 PM



It takes 208ms to run my code.Could it faster?

Here is my code:

```
public:  
    vector twoSum(vector& nums, int target) {
```

Read More

69 ^ v | Share | Reply

SHOW 1 REPLY

ketong (ketong) ★ 62 ⌚ February 28, 2019 10:23 AM



Python one-pass has table - faster than 100%

# 1. Two sum

Read More



62 ^ v | Share | Reply

kvnyang (kvnyang) ★ 70 ⓘ September 9, 2018 5:04 PM ⓘ

Fastest C solution in 0 ms, beats 100.00%:

```
/**
 * C solution in O(n) time, using open addressing hash table.
 */
```

Read More

47 ^ v |  Share |  Reply



SHOW 5 REPLIES

pradeepvrd (pradeepvrd) ★ 42 ⓘ September 5, 2018 12:20 AM ⓘ

My Python3 solution:

```
class Solution:
    def twoSum(self, nums, target):
        """
```



Read More

42 ^ v |  Share |  Reply

SHOW 3 REPLIES

shihab8983 (shihab8983) ★ 41 ⓘ October 11, 2018 11:19 PM ⓘ

What would the fastest way be in python?

41 ^ v |  Share |  Reply

SHOW 5 REPLIES

< 1 2 3 4 5 6 ... 91 92 >

Copyright © 2019 LeetCode

[Help Center \(/support/\)](/support/) | [Terms \(/terms/\)](/terms/) | [Privacy Policy \(/privacy/\)](/privacy/)

 [United States \(/region/\)](/region/)