Version	Change Discription	Author	Date	Comments
1.1.0	First releasd version based on "Geely_ZCUD_Outer Schematic_Quote" V1.0.5. 1. Update IO interface according to GEELY's input. 2. Add PIN num defintion.	Du Bo	2023/5/5	Aligh with customer PIN list verison: V2.4.7
1.1.1	1. Update the PIN size of "PrivateUnlockSwitch (reserved)" from 0.64 to 2.8, "DriverSidePositionLightRearSupply" from 2.8 to 0.64. 2. Move TempSensorGND from J6-27 to J6-24. 3. Update the maximum current of "HeadampHightControl" and "WirelessPowerChargeMute" to 100mA by GEELY. 4. Update the external relay connection way by GEELY. 5. Add way connection between "DriverDoorCrashUnlock/IceBreaker (reserved)" and "DriverDoorPowerReleaseReset (reserved)", "RearDriverDoorCrashUnlock/IceBreaker (reserved)" and "RearDriverDoorPowerReleaseReset (reserved)" by GEELY. 6. Add wakeup source: "DriverDoorPawlSwitch" and "RearDriverDoorPawlSwitch" by GEELY. 7. Update the pin definition of CAN/LIN bus to be same with network topology. 8. Update the pin num of "ZCU CANFD4_H" and "ZCU CANFD4_L".	Du Bo	2023/5/12	First review with Ou Jianping, Wang Hongtao and Bao Mingyang on site.

