
LIGHTING FIXTURE SCHEDULE (REFER TO FIXTURE DESCRIPTIONS FOR ADDITIONAL INFORMATION)

	DESCRIPTION	REFER TO FIXTURE DESCRIPTIONS FOR AD				DEMARK
TAG	DESCRIPTION	MANUFACTURER	WATTAGE /LAMPS /COLOR	VOLT	MOUNTING	REMARK
(A) 47.9	LUMINAIRE: LANDSCAPEFORMS FGP FIXTURE, CAST ALUMINUM ALLOY HOUSING, POWDER COATED BLACK, 30 CREE XP-G2 LEDS, 3000°K COLOR TEMPERATURE, 100V-277V, 0-10V DIMMABLE, 7 PIN TWIST LOCK RECEPTACLE WITH PHOTOCELL AND IP66. POLE: 14' HOT DIPPED GALVANIZED STEEL POLE WITH FACTORY BAKED POWDER COAT BLACK.	FIXTURE: LANDSCAPEFORMS FGP CAT#: AG500L3-046F-30K-UV1-14-TW1 POLE: PER SPECIFICATION 26 56 19 (2.2) PHOTOCELL: PER SPECIFICATION 26 56 19(2.5)	47.9W 30LED 3000°K	MULTI TAP VOLT 120- 277V	POLE	COLOR: BLACK FINISH: SEMI—GLOSS FACTORY BAKED POWDER COATED
	PHOTOCELL: MULTI-VOLTAGE; DUSK TO DAWN CONTROL, FAIL-ON, 1.5 ANSI STD.					
(A1) 47.9	SAME AS FIXTURE TYPE "A" EXCEPT WITH SPECIAL FOUNDATION. SUB-SIDEWALK FOUNDATION DETAIL REFER TO STRUCTURAL DRAWING.	FIXTURE: LANDSCAPEFORMS FGP CAT#: AG500L3-046F-30K-UV1-14-TW1 POLE: PER SPECIFICATION 26 56 19 (2.2)	47.9W 30LED 3000°K	MULTI TAP VOLT 120- 277V	POLE	COLOR: BLACK FINISH: SEMI-GLOSS FACTORY BAKED
(A2) (47.9)	SAME AS "A", EXCEPT 12 FEET POLE	PHOTOCELL: PER SPECIFICATION 26 56 19(2.5) FIXTURE: LANDSCAPEFORMS FGP CAT#: AG500L3-046F-30K-UV1-12-TW1 VALMONT POLE: PER SPECIFICATION 26 56 19 (2.2)	47.9W 30LED 3000°K	MULTI TAP VOLT 120– 277V	POLE	POWDER COATED COLOR: BLACK FINISH: SEMI-GLOSS FACTORY BAKED POWDER COATED
(B)	ROADFOCUS RFM ROADWAY LED FIXTURE WITH 108W 3000K 48LED LAMP, TYPE III DISTRIBUTION, HEAT SINK, 120-277V AUTO-ADJUSTING INPUT AND 0-10V DIMMING DRIVER, FIELD SELECTABLE OUTPUT, PHOTOCELL AND 7 PIN TWIST-LOOK RECEPTACLE FOR PHOTOCELL, +/- 5	PHOTOCELL: PER SPECIFICATION 26 56 19(2.5) FIXTURE: PHILIPS LUMEC ROADFOCUS CAT# RFM-108W48LED3K-T-R3S-UNIV-DMG-RCD7-SP1 -GALVANIZED- ARM: PER SPECIFICATION 26 56 19(2.2) 6' ARM FOR STANDARD SIMPLEX TWO -	108W LED 3000°K	MULTI TAP VOLT 120– 277V	POLE	COLOR: BLACK FINISH: SEMI-GLOSS NEW FIXTURE, ARM AND CONTROL
	DEGREE ADJUST TILT, DIE CAST ALUMINUM HOUSING, STANDARD SURGE PROTECTION, GALVANIZE WITH THE BASE METAL COLOR, UL LISTED FOR DAMP LOCATION, IP66 LIGHT ENGINE, BIRD GUARD. BLACK COLOR, SEMI-GLOSS FINISHED. ARM: 6' HORIZONTAL STANDARD SIMPLEX MOUNTED ARM.	BOLT MOUNT PHOTOCELL: PER SPECIFICATION 25 56 19(2.5)				
	PHOTOCELL: MULTI-VOLTAGE; DUSK TO DAWN CONTROL, FAIL-ON, 1.5 ANSI STD. FIXTURE TO WITHSTAND POLE VIBRATION REQUIREMENTS AT 100 MPH.					
(B1) 72)	SAME AS FIXTURE TYPE "B" EXCEPT WATTAGE, NEW POLE, ARM, CONTROL AND FOUNDATION.	FIXTURE: PHILIPS LUMEC ROADFOCUS CAT# RFM-72W32LED3K-T-R3S-UNIV-DMG-RCD7-SP1 -GALVANIZED-	72W LED 3000°K	MULTI TAP VOLT 120-	POLE	COLOR: BLACK FINISH: SEMI-GLOSS
	POLE: 28.5' HOT DIPPED GALVANIZED STEEL POLE WITH FACTORY BAKED POWDER COAT BLACK.	ARM: PER SPECIFICATION 26 56 19(2.2) 6' ARM FOR STANDARD SIMPLEX TWO — BOLT MOUNT		277V		NEW FIXTURE, CONTROL, POLE AND ARM
		POLE: PER SPECIFICATION 26 56 19 (2.2) PHOTOCELL: PER SPECIFICATION 25 56 19(2.5)				FACTORY BAKED POWDER COATED
B2 108	SAME AS FIXTURE TYPE "B" EXCEPT USING EXISTING FOUNDATION REFURBISH AND PAINT EXISTING ARM AND POLE TO MATCH LUMINAIRE.	FIXTURE: PHILIPS LUMEC ROADFOCUS CAT# RFM-108W48LED3K-T-R3S-UNIV-DMG-RCD7-SP1 -GALVANIZED- PHOTOCELL: PER SPECIFICATION 25 56 19(2.5)	108W LED 3000°K	MULTI TAP VOLT 120- 277V	POLE	COLOR:BLACK FIXTURE: SEMI-GLOSS REPLACE EXISTING FIXTURE WITH NEW FIXTURE AND CONTROL. REFURBISH AND PAINT POLE AND ARM

TAG	DESCRIPTION	MANUFACTURER	WATTAGE /LAMPS /COLOR	VOLT	MOUNTING	REMARK
/B3 72	SAME AS FIXTURE TYPE "B2" EXCEPT WATTAGE.	FIXTURE: PHILIPS LUMEC ROADFOCUS CAT# RFM-72W32LED3K-T-R3S-UNIV-DMG-RCD7-SP1 -GALVANIZED- PHOTOCELL: PER SPECIFICATION 26 56 19(2.5)	72W LED 3000°K	MULTI TAP VOLT 120– 277V	POLE	COLOR: BLACK FINISH: SEMI-GLOSS REPLACE EXISTING FIXTURE WITH NEW FIXTURE AND CONTROL. REFURBISH AND PAINT POLE AND ARM
B4 108	SAME AS FIXTURE TYPE "B1" EXCEPT WATTAGE	FIXTURE: PHILIPS LUMEC ROADFOCUS CAT# RFM-72W32LED3K-T-R3S-UNIV-DMG-RCD7-SP1 -GALVANIZED- PHOTOCELL: PER SPECIFICATION 25 56 19(2.5) ARM AND POLE: PER SPECIFICATION 25 56 19(2.5)	108W LED 3000°K	MULTI TAP VOLT 120– 277V	POLE	COLOR: BLACK FINISH: SEMI-GLOSS NEW FIXTURE, ARM, CONTROL AND POLE FACTORY BAKED POWDER COATED
A3 57	SAME AS FIXTURE TYPE "A" EXCEPT WITH TYPE IV PATTERN AND WATTAGE.	FIXTURE: LANDSCAPEFORMS FGP CAT#: AG500L5-056F-30K-UV1-14-TW1 POLE: PER SPECIFICATION 26 56 19 (2.2) PHOTOCELL: PER SPECIFICATION 26 56 19(2.5)	57W 30LED 3000°K	MULTI TAP VOLT 120– 277V	POLE	COLOR: BLACK FINISH: SEMI-GLOSS FACTORY BAKED POWDER COATED NEW NATOMA EXTENSION FOUNDATION DETAIL REFER TO STRUCTURAL DRAWING.

NOTE;
THIS AUTOCAD DRAWING HAS BEEN REVISED AND REPLOTTED SUBSEQUENT TO INTERNAL ENGINEERING APPROVAL AND SIGN—OFF. FOR THOSE SIGNATURES, SEE THE DRAWING PLOTTED AND ISSUED PREVIOUSLY DURING BIDDING. THE SIGNED DRAWING REMAINS VALID EXCEPT FOR THE CHANGES ONLY AS CLEARLY MARKED ON THIS DRAWING AND ISSUED UNDER THIS LATEST REVISION NUMBER AS SHOWN IN THE TABLE OF REVISIONS LOCATED AT THE LOWER LEFT CORNER OF THE DRAWING. ALL ISSUED REVISIONS SUBSEQUENT TO PREVIOUSLY PLOTTED DRAWING DURING BIDDING REMAIN VALID UNLESS SUPERSEDED BY LATER ISSUED REVISIONS. CHECK ALL ISSUED REVISIONS OF THIS DRAWING.

					REFERENCE INFORMATION & FILE NO. OF SURVEYS
(1)	9/17/18	PCO #6 Natoma Extension	ST	SL	
NO.	DATE	DESCRIPTION	BY	APP.	
	-	TABLE OF REVISIONS			





BUREAU OF DESIGN &
ENGINEERING
CITY & COUNTY OF SAN FRANCISCO
SAN FRANCISCO PUBLIC WORKS
30 VAN NESS AVENUE, 5TH FLOOR
SAN FRANCISCO, CA 94102 - 6028

		Date:	DESIGNED: DATE:
Section Mgr:	PHILIP THWIN		ST/ZH/LD 8/18
Deputy Bureau Mgr:	IQBALBHAI DHAPA		DRAWN: DATE: ST/ZH/LD 8/18
Bureau Mgr:	PATRICK RIVERA		CHECKED: DATE: SL 8/18
and the second of the second of			

8	PROFESSION T. LEGALET
8	NO. E15417
8	OF CALIFORNIA

NONE	2]
OF SHEETS	

2ND STREET STREETSCAPE
IMPROVEMENTS PROJECT

STREET LIGHT
LIGHTING FIXTURE SCHEDULE AND DETAILS

CONTRACT NO.
1064J

DRAWING NO.
E-0.2

FILE NO.
106,284

REV. NO.