The Pascaline: findings

West bay 3: the Pascaline · 19 October 2026

How the carry was made to work in the simulation, in the order the problems turned up. All the numbers live in `pascaline-geometry.lua`.

The tuning history

1. **The hand turned into the cam's drop.** The first build turned the digits the wrong way, so the follower met the cam's steep face and jammed. Fixed by turning clockwise as seen from the front (the cam rises under the follower). Note that bpp's `getHingeAngle` is clockwise-positive about the hinge's axis, so a digit's value is `angle / 36°`.
2. **The digits passed through everything.** They had been added with `collides` set after `v:add`; collision groups are fixed when a body is added, so it must be set before.
3. **A high pivot swung the pawl sideways.** With the sautoir pivoted above the axles, the follower and the pawl's tip moved along arcs that pushed sideways on the cam and the pins as much as up. Moving the pivot down to the axles' height (`PA` 6 cm, then 10 cm from the next axle) made both move nearly straight up and down.
4. **Neighbouring cams collided.** A cam of radius 4.5 to 5 cm needs room; the axles' spacing `D` went from 8 cm to 11 cm.
5. **The nose caught the cam's foot.** At rest the follower's nose overlapped the start of the snail. Raising the cam's base radius to `R0` 1.5 cm and starting the nose `NOSEGAP` 0.5 mm above it fixed it.
6. **The pawl swung out as the lever dropped.** A pawl that yields one way must also be held against its stop, or the jolt of the drop throws it open and it misses the pin. A tail weight of 8 g (`TAIL`) holds it.
7. **The kick fell short** (about 0.88 of a step) and the click pulled the tens back. Two changes: the pawl's tip lowered (`TIPY` -0.17 cm) so it pushes the pin for more of the drop, and the weight raised to 60 g.
8. **The ripple (99 + 1) failed.** The tens' sautoir dropped while the units' pawl was still on its way back, so the second carry came before the first had finished. Raising the cam's top (`R1` 4.5 to 5.0 cm) lifts the pawl clear of the pins sooner and gives it time to come back.
9. **Making it printable** changed nothing the simulation sees: gaps between the pawl's carrier and its arm were closed (the carrier's bar reaches 1 cm further forward, the tail block reaches back to the link), and a boss was added round the pawl's pivot, where nothing comes near it.

The checks

The tour (7, + 8 = 15, + 84 = 99, + 1 = 100) passes in all six runs of the sweep:

friction	turn rate (turns/s)	result
0.15	0.3	PASS
0.30	0.3	PASS
0.45	0.3	PASS
0.30	0.15	PASS
0.30	0.6	PASS

friction	turn rate (turns/s)	result
0.45	0.6	PASS

It also passes inside the hall (`HALL_START=pascaline`), in the exhibit's own sandboxed world.

Every STL checks as a single watertight solid (trimesh), and the simulated parts do not overlap at rest (manifold3d).

What a real build should watch

- **The weight** is what the carry runs on. With the lighter weight used before step 7 the kick fell short in the simulation; a real machine, with more friction, may want more than 60 g.
- **The pawl's tail** must hold the pawl against its stop firmly but let it yield easily over a pin. Adjust by adding or removing a nut.
- **The click** in the simulation is gentle. A real detent spring that is too strong will need a heavier weight to overcome.