

N/	lΔ.	TΕ	ΡI	ΔΙ	٠.
IV		' _	1 /1	$\overline{}$	∟.

INSULATOR: THERMOPLASTIC POLYESTER, UL94-0,

CHEMICAL RESISTANCE, BLACK, 230°C PROCESS TEMP.

SHELL: STEEL, NICKEL PLATED

CONTACT: BRASS; GOLD FLASH OR 30 MICRO-INCH


IN MATING AREA. TIN PLATED ON TAIL ENDS

ELECTRICAL:

CURRENT RATING: 3 AMPS

WITHSTANDING VOLTAGE: 250 VAC (RMS) MAX INSULATION RESISTANCE: 5,000 MOhms Min. CONTACT RESISTANCE: 25 mOhms Max. WORKING TEMPERATURE: -55° TO +85°C

DO NOT SCALE FROM DRAWING



NUMBER OF	"A"	"B"	"C"	
CONTACTS	Inch (mm)	Inch (mm)	Inch (mm)	
9	1.213(30.81)	.984 (24.99)	.666 (16.92)	
15	1.543 (39.19)	1.312 (33.32)	.994 (25.25)	
25	2.088(53.04)	1.852 (47.04)	1.534 (38.96)	
37	2.729(69.32)	2.500 (63.50)	2.182 (55.42)	

NorComp

THESE DRAWINGS AND SPECIFICATIONS ARE

THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

UNITS = INCHES [MM]

PAM JENKINS DATE:

PAM JENKINS 8-22-05

SCALE: SHEET OF REV


NTS 1 2 5

DWG NO. 191-YYY-113LYYY


ROHS COMPLIANT

DESCRIPTION: 191 SERIES HARDWARE OPTIONS


00 = .125 DIA. HOLE




55 = 4-40 INSERT




56 = 4-40 INSERT WITH BOARD LOCK



57 = 4-40 STANDOFF WITH BOARD LOCKS



59 = 4-40 STANDOFF



DO NOT SCALE FROM DRAWING

DWG NO.



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

PAM JENKINS DATE:

PAM JENKINS 8-22-05

SCALE: OF 2 REV 5

191-YYY-113LYYY

RoHS COMPLIANT

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

NorComp:

191-009-113L001 191-009-113L571 191-015-113L001 191-025-113L001 191-009-213-571