

Insert here your thesis' task.



**FACULTY
OF INFORMATION
TECHNOLOGY
CTU IN PRAGUE**

Master's thesis

Thesis title (SPECIFY)

Your Name & degrees

Department of ... (SPECIFY)

Supervisor: Your Supervisor's Name (SPECIFY)

February 28, 2023

Acknowledgements

THANKS (remove entirely in case you do not wish to thank anyone)

Declaration

I hereby declare that the presented thesis is my own work and that I have cited all sources of information in accordance with the Guideline for adhering to ethical principles when elaborating an academic final thesis.

I acknowledge that my thesis is subject to the rights and obligations stipulated by the Act No.121/2000 Coll., the Copyright Act, as amended, in particular that the Czech Technical University in Prague has the right to conclude a license agreement on the utilization of this thesis as a school work under the provisions of Article 60 (1) of the Act.

In Prague on February 28, 2023

.....

Czech Technical University in Prague

Faculty of Information Technology

© 2023 Your Given Name(s) (SPECIFY) Your Family Name (surname, SPECIFY). All rights reserved.

This thesis is school work as defined by Copyright Act of the Czech Republic. It has been submitted at Czech Technical University in Prague, Faculty of Information Technology. The thesis is protected by the Copyright Act and its usage without author's permission is prohibited (with exceptions defined by the Copyright Act).

Citation of this thesis

Your Family Name (surname, SPECIFY), Your Given Name(s) (SPECIFY). *Thesis title (SPECIFY)*. Master's thesis. Czech Technical University in Prague, Faculty of Information Technology, 2023.

Abstrakt

V několika větách shrňte obsah a přínos této práce v českém jazyce.

Klíčová slova Replace with comma-separated list of keywords in Czech.

Abstract

Summarize the contents and contribution of your work in a few sentences in English language.

Keywords Replace with comma-separated list of keywords in English.

Contents

Introduction	1
Methods	1
Orientation	1
Directed agents	1
Partner agents	2
Pair formation	2
Maneuvers	3
Static floor field	4
Leader	4
Todo:	5
1 State-of-the-art	7
2 Analysis and design	9
3 Realisation	11
Conclusion	13
Bibliography	15
A Acronyms	17
B Contents of enclosed CD	19

List of Figures

0.1	Simple maneuvers of paired agents.	3
0.2	Complex maneuvers of paired agents.	3

Introduction

Methods

Orientation

The grid in this model is a rectangular lattice of square cells where the agents can move from one cell to another in 8 directions of Moore neighbourhood. The agents have four orientations: North represents the top of the grid and South the bottom, East is the right-hand side of the grid and West is the left-hand side. The orientations are perpendicular one to each other. Even though the movement is possible in 8 directions the agent has only 4 orientations because of the nature of paired agents. Two agents in a pair have the same orientation and are located in adjacent cells.

Directed agents

Agents can move to cells in Moore neighbourhood in 8 directions or stay in the same cell. Directed agents take into consideration the direction of the movement. The agents move in a discretized rectangular grid. The agent has 4 possible orientations - North, East, South, West - which are global and not relative to the agent itself. This means that agent which has orientation East is directed to the right-hand side of the grid.

Moore neighbourhood allows movement in 4 non-diagonal and 4 diagonal directions. In case of the non-diagonal directions, the agent orientation after the move is the same as the direction e.g. agent with orientation North moving to adjacent cell on the right will change orientation to East. In case of diagonal directions there are 2 types of movements: the first is movement to diagonal cells where the steering angle is ± 45 degrees and the second is movement to diagonal cells where the steering angle is ± 135 degrees. In the case of the first movement the agents keeps his orientation unchanged, e.g. agent facing West moves to diagonal upper left cell will have West orientation after the movement. In the case of the second movement the agent changes the

orientation to the opposite orientation e.g. North to South and vice versa, East to West and vice versa.

Partner agents

Partner agents form a pair of two directed agents that are tightly bound so that they are in adjacent cells to each other. Two partner agents in the pair cannot be in cells diagonal one to each other. Their movement is synchronous, which means that if any of the agent is not able to move to the desired cell (conflict, bound agent did not move), the partner agent will abort its movement. The algorithm which checks whether both agents will successfully move is described below. In this model, the two agents in the pair are in a hierarchy of one agent being the leader while the second agent is not. The leader is responsible for calculating the probabilities of movement to cells for itself and it's partner according to maneuvers. The leader is the agent which has it's partner on the right. The partner agents are directed agents and both have the same orientation. Note that some maneuvers change the leadership in the pair.

Pair formation

The children in pre-school age are being taught to form a pair and hold hands when walking through corridor or crossing a road as these situations pose risks such as getting lost or encountering traffic. The model in this thesis simulates the coordinated evacuation with supervisor where a risk element is present.

The pupils are located in a classroom in a cluster where some pupils are close to each other and others are more isolated. The model does not consider any friendship preferences between children and assumes that pupils close to each other are more likely to form a pairs. It also assumes that pupils form pairs in group of even number of pupils so that there are no solitary children. If a pupil can't form pair immediately it will do so when other solitary pupil is nearby.

The Algorithm 1 below finds a way to form pairs of pupils which are not yet in pair.

Algorithm 1 Finding pairs

```

1:  $G = (V, E)$ 
2: while  $\exists v \in V : d(v) > 1$  do
3:   Let  $v^* \in V : d(v^*) = \max_{u \in V} d(u)$ .
4:   Let  $w \in V : d(w) = \max_{(v^*, w) \in E} d(w)$ .
5:   Remove  $(v^*, w)$ .
6: end while
7: for  $(v, w) \in E$  do
8:   formPair(v,w)
9: end for

```

Locations of pupils (directed agents) not in pair are transformed to a graph. The vertices of the graph correspond to the pupils' locations, and an edge is formed between two vertices in adjacent cells. The vertices in the graph may have different degrees, and cycles may be present. The algorithm iteratively selects the vertex with the highest degree and removes the edge connecting it to the vertex with the highest degree until all vertices have at most one edge. The vertices connected by an edge represent a pair.

Maneuvers

Each agent in a pair has the potential to move to 8 cells in the Moore neighbourhood, allowing for a vast number of possible maneuvers. However, most of these maneuvers do not maintain the structure of the pair and are therefore prohibited. Specifically, only 18 viable maneuvers are allowed for each orientation of the paired agents.




Figure 0.1: Simple maneuvers of paired agents.

Some maneuvers can alter the leadership of the pair or the orientation of the agents. Additionally, in some cases, the agents may have different movement speeds. During the synchronous atomic movement of a maneuver, both agents may move to diagonal cells, or one agent may move to a diagonal cell while the other remains in its current cell. Alternatively, one agent may even move outside its Moore neighbourhood in order to preserve the structure of the pair. In the Figure 0.2 can be seen the notable maneuvers.




Figure 0.2: Complex maneuvers of paired agents.

conflicts stochasticity strategy virtual leader topology

Static floor field

Each cell in the grid in the static floor field *SFF* holds the value of shortest distance to the goal. The value is computed using BFS algorithm which allows diagonal movement. Alternatively the distance can be computed by novel approximate algorithm described in [1]. The leader has full information about the topology of the map and he moves towards the closest goal. The follower agents, solitary or in pairs, follow the leader and they do not attempt to find their own way to the exit. The leader has computes SFF for the follower agents where the goal is the leaders position.

Leader

The solitary agent responsible for navigation is the leader agent, which has complete information about the map topology and goals.

The leader agent is not directed and can move to cells in the Moore neighborhood based on the SFF of the current goal. The virtual leader is a leader agent, which does not occupy a cell and is used to set SFF for follower agents. The SFF for the leader agent differs from the SFF of follower agents. The SFF for follower agents is calculated in every step based on the virtual leader's position. The virtual agent navigates the followers when the leader moves to the end of the crowd.

Agent's proximity to the leader (not virtual leader) proportionally increases the static potential value:

$$d = \text{distance}(\text{leader}, \text{follower})$$

$$S = S * (1 + \frac{1}{d})$$

With a higher static potential value, the agent is less likely to deviate from the optimal trajectory set by the SFF of the virtual leader. The leader has simple rules for navigating towards the closest goal and checking if all follower agents reached the goal. One rule is the leader's ability to command the follower agents to continue to the goal while the leader moves to the most distant agent. Additionally, the (virtual) leader agent waits near the goal area and attracts the follower agents until they all reach it. The solitary agent responsible for navigation is the leader agent. In every step, the SFF for follower agents is calculated based on the leader's or the virtual leader's position. The leader has simple rules for navigating towards the closest goal and checking if all follower agents reached the goal. One rule is the leader's ability to move to the distant end of the cluster to speed up follower agents left behind. Additionally, the leader agent waits near the goal area and attracts the follower agents with its SFF until they all reach this area.

crossing the corner numerical exponents with offset ability to pass tight space

Todo:

Todo:

proximity to leader increases discipline of the agents (lower probability of error step) lonely agents try to pair?? ability to pass tight space - decouple pairs?

State-of-the-art

Analysis and design

Realisation

Conclusion

Bibliography

- [1] Huang, R.; Zhao, X.; et al. Static floor field construction and fine discrete cellular automaton model: Algorithms, simulations and insights. *Physica A: Statistical Mechanics and its Applications*, volume 606, 2022: p. 128150, ISSN 0378-4371, doi:<https://doi.org/10.1016/j.physa.2022.128150>. Available from: <https://www.sciencedirect.com/science/article/pii/S0378437122007099>

Acronyms

GUI Graphical user interface

XML Extensible markup language

Contents of enclosed CD

	readme.txt	the file with CD contents description
	exe	the directory with executables
	src	the directory of source codes
	wbdcm	implementation sources
	thesis	the directory of \LaTeX source codes of the thesis
	text	the thesis text directory
	thesis.pdf	the thesis text in PDF format
	thesis.ps	the thesis text in PS format