FINTECHATHON 2026 · SHENZHEN · INTERNATIONAL TRACK


ClauseGuard

TOPIC D · AI INSURANCE ASSISTANT

Execution Evidence.

Every step on screen. Every step in the log.

One claim from question to decision, the hosted audit log, the demo video and how to reproduce it.



69 audit events, chain verified

24,453 events in the hosted log

PRODUCT	ClauseGuard, an AI insurance assistant that decides on clauses, not guesses
TEAM	Bunga Laelatul Muna (Team Lead) · Izra Noor Zahara Aliya · Wan Sabrina Mayzura
INSTITUTION	Institut Teknologi Sepuluh Nopember (ITS), Surabaya, Indonesia
LIVE APP	clauseguard.up.railway.app
REPOSITORY	github.com/bungagana/clauseguard
VERSION	October 2026

Contents.

Six sections and an appendix, from the environment to the limits of the evidence.

00 Overview 03
0.1 Abstract 03

01 Evidence Environment 04

02 Operation Record 05
2.1 Question and verdict 05
2.2 Documents 06
2.3 The insurer's claim form 08
2.4 Confirmation and filing 09
2.5 The decision at the insurer desk 09
2.6 The decision returns to the chat 12
2.7 A hostile request 13
2.8 Chain verification 14

03 Hosted Deployment Log 15

04 Relation to the Demo Video 16

05 Reproduction 17

06 Limits of the Evidence 18

A Appendix 19

CONTENTS

00 Overview

One claim, from the first question to the insurer's decision.

0.1 Abstract

This document records how ClauseGuard operates in its sandbox. It follows one policyholder claim from the first question to the insurer's decision. Every step is shown twice: as a screenshot of the running web application and as the entries it wrote to the hash-chained audit log. The log of this run holds 69 events and its chain verifies. A summary of the audit log of the hosted deployment, the scripted test results and the relation to the demo video follow. All data is synthetic.

The run covers the three core features. ClauseLens answers whether and how much the policy pays. ClaimFlow reads the documents, fills in the insurer's own claim form and relays the insurer's decision. TrustLock limits every agent action with permission tiers, a single-use confirmation and the audit log. The supporting features Claim Simulator, Deadline Tracker and PDF Export appear in the screens where they are available.

69	24,453	33 / 33	0 / 27
audit events in the run, chain OK	events in the hosted log	scripted tasks passed	attacks with a forbidden effect

Table 1 points to each piece of evidence and where to find it. The source code is at github.com/bungagana/clauseguard and the live demo at clauseguard.up.railway.app.

Table 1 Evidence at a glance

EVIDENCE	WHAT IT SHOWS	WHERE
Operation record	One claim from question to decision, with 12 screenshots of the running application and the audit events of each step	Section 2
Audit log of the run	69 hash-chained events, verified with scripts/verify_audit.py	`evidence/operation_run_2026-10-19.jsonl`
Hosted deployment log	24,453 events over 14 to 19 October 2026 on Railway and Supabase, chain verified with 2 declared gaps	Section 3
Scripted tasks	33 of 33 passed, including 10 adversarial tasks	`evidence/task_report.md`
Attack suite	0 of 27 attacks produced a forbidden effect with enforcement on	`evidence/adversarial_report.md`
Demo video	Segments of the video mapped to the evidence above	Section 4

01 Evidence Environment

Where, when and with what the record was produced.

Table 2 lists the environment of the operation record. The record was produced on a local deployment of the same code that runs on Railway, because the hosted deployment requires accounts. The hosted deployment's own audit log is summarised in Section 3.

Table 2 Environment of the operation record

ITEM	VALUE
Date and time	19 October 2026, 21:17 to 21:19 (UTC+7), which is 14:17 to 14:19 UTC
Code version	Git commit `c0edd1c` of github.com/bungagana/clauseguard
Application	Next.js 14 web application and FastAPI sandbox API. The sandbox is a simulated insurer with a claims desk
Persona	Rizky Pratama, a graduate student with a hospital cash plan. All persona data is synthetic
Model	Google Gemini through the live API (extraction gemini-3.6-flash, interactive steps gemini-3.5-flash-lite; claim documents fall back to the extraction model). The interface shows the Live AI badge
Storage	SQLite for the sandbox and a JSONL file for the audit log, both created empty before the run
Capture	Chromium driven by Playwright at 1440 × 900 pixels. The same script reproduces the run
Sandbox date	19 October 2026, shown in the Sandbox tools panel
Hosted deployment	Railway (Southeast Asia region) with Supabase Postgres, clauseguard.up.railway.app

02 Operation Record

Every step shown twice: on screen and in the audit log.

The scenario is a hospital claim for dengue. Rizky holds a hospital cash plan (HCP-SOMPO-01), a term life policy, a critical illness policy and BPJS Kesehatan. The tables list the audit events that each step wrote. Routine T0 read calls such as get_my_policies and get_payment_status are omitted for brevity and remain in the log file.

2.1 Question and verdict

Rizky writes in everyday language that they were admitted for dengue on 25 September for 3 days and asks whether they can claim. **Figure 1** shows the answer. ClauseLens finds the hospital cash plan covered with an indicative benefit of IDR 1,500,000 and quotes the clause that decides it. It asks one question that would change the verdict for BPJS Kesehatan: whether the hospital is a partner facility. The “Behind the answer” panel on the right of **Figure 1** shows which agents ran, that the rules engine computed the verdict and that the Guardian allowed all calls.




Figure 1 The verdict card with the deciding clause, and the pipeline behind the answer

Table 3 lists the audit events written for this question: the message, the plan, two T1 tool calls allowed

by the Guardian, the reply and the history save.

Table 3 Audit events of the question

SEQ	TIME (UTC)	EVENT	TOOL (TIER)	DETAIL	HASH
3	14:17:17	USER_MSG	–	–	a5fd539450
5	14:17:20	PLAN	–	CLAIM_GUIDANCE	274d17bf0a
18	14:17:21	TOOL_ALLOW	check_coverage (T1)	ALLOW OK	4c27fb0d32
20	14:17:21	TOOL_ALLOW	claim_readiness (T1)	ALLOW OK	7cf037217e
22	14:17:21	REPLY	–	CLAIM_GUIDANCE	1cdd9dd646
23	14:17:22	HISTORY_SAVE	–	OK messages=3 evicted =0	e44f557734

2.2 Documents

Rizky attaches four hospital documents: the receipt, the medical resume, the prescription copy and the lab results. **Figure 2** shows the four attachment cards staged in the message box before sending; a file is sent only when the message is sent, so nothing leaves the browser by accident.




Figure 2 Four documents staged as attachment cards, sent only on Send

Once sent, the four uploads are stored with the label USER_UPLOAD, which marks them as untrusted data. The extractor runs in quarantine and its output fills a closed schema, and the matcher then checks the documents against the policy's list of required documents. **Figure 3** shows the result:

what ClaimFlow read from each document, the claim readiness check and the facts taken from the documents.




Figure 3 Document reads, the claim readiness check and the facts taken from the documents

Table 4 lists the audit events of this step, from the four uploads to the draft claim.

Table 4 Audit events of the document step

SEQ	TIME (UTC)	EVENT	TOOL (TIER)	DETAIL	HASH
24	14:17:35	DOC_INGEST	–	STORED label=USER_UPLOAD	dbf372f5a8
25	14:17:35	DOC_INGEST	–	STORED label=USER_UPLOAD	fc7064fa75
26	14:17:35	DOC_INGEST	–	STORED label=USER_UPLOAD	cf35a0c8f1
27	14:17:35	DOC_INGEST	–	STORED label=USER_UPLOAD	559d051467
28	14:17:38	USER_MSG	–	–	9bd4ae6e23
30	14:17:38	PLAN	–	ACTION	41cfa2de06
33	14:17:38	TOOL_ALLOW	extract_document (T1)	ALLOW OK	71b29ed7f2
35	14:17:38	TOOL_ALLOW	extract_document (T1)	ALLOW OK	f27375b46d
37	14:17:38	TOOL_ALLOW	extract_document (T1)	ALLOW OK	889e980ae7
39	14:17:39	TOOL_ALLOW	extract_document (T1)	ALLOW OK	50aa7c1a6a

SEQ	TIME (UTC)	EVENT	TOOL (TIER)	DETAIL	HASH
41	14:17:39	TOOL_ALLOW	claim_readiness (T1)	ALLOW OK	1bdc19fde3
43	14:17:39	TOOL_ALLOW	draft_claim (T1)	ALLOW OK	354b4e1493
45	14:17:39	ESCALATE	submit_claim	ACTION_PENDING_CONFIRMATION	9eb084046a
46	14:17:39	REPLY	–	ACTION	c8a43038b1

The last two rows matter for permissions. draft_claim is a T1 tool and only prepares a draft. Filing is a T2 action, so the Guardian records ACTION_PENDING_CONFIRMATION and nothing is sent.

2.3 The insurer's claim form

ClaimFlow lays out the form from the policy's own wording and fills each value from typed facts. **Figure 4** shows the preview that the policyholder can open and correct, next to the Confirm submission card that lists what will be sent. The preview can also be saved as a PDF, which wrote the single event in **Table 5**.




Figure 4 The claim form preview and the Confirm submission card

Table 5 Audit event of the form preview

SEQ	TIME (UTC)	EVENT	TOOL (TIER)	DETAIL	HASH
47	14:17:56	EXPORT_PDF	–	ALLOW claim form, 5 sections	c2f0966ba7

2.4 Confirmation and filing

Rizky presses Confirm and submit. The server issues a nonce bound to the session, the tool and the arguments, then consumes it once and allows submit_claim. **Figure 5** shows the filing result: the claim is filed in the sandbox insurer as CL-C01BEECA, and the progress strip stops at Sent to insurer because only a person at the insurer desk can decide.




Figure 5 Filed as CL-C01BEECA, with the progress strip at Sent to insurer

Table 6 shows the nonce being issued and consumed exactly once before submit_claim is allowed.

Table 6 Audit events of the confirmation

SEQ	TIME (UTC)	EVENT	TOOL (TIER)	DETAIL	HASH
48	14:18:05	CONFIRM_ISSUED	submit_claim	–	23f1006908
50	14:18:05	PLAN	–	ACTION	c6b99056e1
53	14:18:05	CONFIRM_USED	submit_claim (T2)	OK nonce consumed	d7513f606f
54	14:18:05	TOOL_ALLOW	submit_claim (T2)	ALLOW OK	6781260cba
56	14:18:05	REPLY	–	ACTION	6746f0ca1a

2.5 The decision at the insurer desk

The insurer desk is a separate page where a person decides; the agent has no tool that approves or rejects a claim. The officer first sees the claims inbox in **Figure 6**, where the claim that was just filed appears at the top with its amount and status.




Figure 6 The claims inbox of the sandbox insurer

Opening the claim shows the form exactly as the assistant submitted it, together with the four documents, as seen in **Figure 7**. Nothing on this page was rewritten by the agent after the policyholder confirmed.




Figure 7 The submitted form and its documents as the insurer sees them

The officer then writes the decision note that the policyholder will see and chooses Approve, Reject or Mark paid, as shown in **Figure 8**.




Figure 8 The decision note and the Approve, Reject and Mark paid controls

Figure 9 shows the claim after it is approved, with the new status in the inbox. **Table 7** records the decision itself.




Figure 9 The claim after the decision

Table 7 Audit event of the human decision

SEQ	TIME (UTC)	EVENT	TOOL (TIER)	DETAIL	HASH
60	14:18:32	ESCALATE	–	approved claim CL-C01BEECA decided by human	f7cd03617a

The decision is recorded under the user backoffice and not under the policyholder's session. The agent never reads the desk; it only receives the resulting claim status.

2.6 The decision returns to the chat

The policyholder's chat shows the insurer's decision with its note and the next step, and the progress strip now reaches Insurer decided. **Figure 10** shows the result, and **Table 8** lists the messages written around it.




Figure 10 The insurer's decision and note returned to the conversation

Table 8 Audit events of the decision messages

SEQ	TIME (UTC)	EVENT	TOOL (TIER)	DETAIL	HASH
59	14:18:13	REPLY	–	CLAIM_GUIDANCE	e2418e67dc
61	14:18:43	USER_MSG	–	–	4e40a038b0
63	14:18:43	REPLY	–	CLAIM_GUIDANCE	c367d868d7

2.7 A hostile request

Rizky then asks the assistant to change the payout account and skip the confirmation. **Figure 11** shows the response. T3 actions never run: the Guardian denies the call because a literal account number cannot enter a privileged tool, and the assistant offers a ticket for a person to verify the change out of band.




Figure 11 The account change is refused and handed to a person as a ticket

Table 9 shows the denial and the ticket offer in the audit log.

Table 9 Audit events of the refused request

SEQ	TIME (UTC)	EVENT	TOOL (TIER)	DETAIL	HASH
66	14:19:11	PLAN	–	ACTION	e8654f0997
67	14:19:11	TOOL_DENY	create_account_change_request (T3)	DENY LITERAL_ARG_IN_PRIVILEGED_TOOL:form_handle	31614b409f
68	14:19:11	ESCALATE	–	T3_TICKET_OFFERED	d07fcd59b8
69	14:19:12	REPLY	–	ACTION	5e175eb5a5

Judges do not have to rely on the screenshots alone. **Figure 12** shows the raw trace panel that can be opened from any answer, listing the tool calls, their trust labels and the matching audit entries for the turn.




Figure 12 The raw trace panel with tool calls, trust labels and audit entries

2.8 Chain verification

The audit log of this run has 69 events. Each event stores the hash of the previous event, so any change to an earlier line breaks the chain from that point. The verifier walks the whole chain:

terminal

```
python scripts/verify_audit.py evidence/operation_run_2026-10-19.jsonl
OK (69 events)
```

The head of the chain is `5e175eb5a520c50427fcbf6e23abc303dce6db1e3b7a25fb124644e182603a68`. The interface also includes a tamper demonstration that edits a copy of the log and shows the verifier stopping at the edited entry.

03 Hosted Deployment Log

Six days of the live system, as written to Postgres.

The hosted deployment on Railway writes its audit chain to Postgres. **Table 10** summarises that log. It covers 14 to 19 October 2026 and includes development and test sessions together with the sessions recorded for the demo, so the counts show how the system behaved and do not measure real use.

Table 10 Summary of the hosted audit log

MEASURE	VALUE
Events	24,453 (sequence 1 to 24,453)
Period	14 October 2026 18:36 UTC to 19 October 2026 12:51 UTC
Sessions and user identifiers	1,213 sessions and 23 user identifiers, including demo personas and the insurer desk
Tool calls allowed and denied	8,483 allowed and 191 denied
Confirmations issued and used	52 issued and 49 used
Documents stored and flagged suspicious	159 stored and 11 flagged suspicious
Claims on file by status	5 submitted, 3 approved, 1 under review, 1 rejected, 1 appealed and 1 paid
Chain verification	OK (24,453 events, 2 declared gaps)

Table 11 lists why the Guardian denied calls. The large number of rate-limit denials comes from automated test loops that deliberately exceeded the per-session call budget.

Table 11 Reasons for denied tool calls in the hosted log

REASON	COUNT	MEANING
`RATE_OR_AMOUNT_LIMIT:tool_calls`	143	A session exceeded its call budget
`LITERAL_ARG_IN_PRIVILEGED_TOOL:form_handle`	30	A literal value was offered to a privileged tool, as in the refused account change
`NOT_OWNER:policy_id`	15	A policy of another account was requested
`TAINTED_ARG:draft_handle:USER_UPLOAD`	2	An argument derived from untrusted upload content was used for filing
`RATE_OR_AMOUNT_LIMIT:submit_claim`	1	A second submission in one session

The two declared gaps are periods when Postgres was briefly unreachable. The system kept writing to a local fallback chain, 4 events at sequence 8360 and 61 events at sequence 22117, and recorded the gap in the main chain instead of dropping the events silently.

04 Relation to the Demo Video

Each segment of the video, and where its evidence lives.

The demo video uses screen recordings of the running web application, the same system captured in Section 2; no mock-up screens are used as evidence of operation. **Table 12** maps each segment of the video to the evidence in this document; segment times are approximate.

Table 12 Segments of the demo video and their evidence

VIDEO SEGMENT	WHAT IT SHOWS	EVIDENCE
0:00 – 0:40	Introduction and the five AI agents around one rules engine	The agents table in Section 4.1 of the technical documentation and the "Behind the answer" panel in **Figure 1**
0:40 – 1:10	ClauseLens: a plain-language question, the verdict with the deciding clause, several policies read together	Section 2.1, audit events 3 to 23
1:10 – 1:30	ClaimFlow: documents in, the insurer's form out, the claim filed after confirmation	Sections 2.2 to 2.4, audit events 24 to 56
1:30 – 1:40	The insurer's decision returns to the chat	Sections 2.5 and 2.6, audit event 60
1:40 – 2:00	TrustLock: Observe, Draft and Act, the Guardian, documents treated as data	Section 2.7, evidence/adversarial_report.md and the Security Self-Assessment
2:00 – 2:20	Claim Simulator and Deadline Tracker	/entitlement/whatif and /entitlement/digest in clauseguard/sandbox/api.py; scripted tasks in evidence/task_report.md
2:20 – 2:40	Benchmark accuracy, invented refusals and 33 of 33 scripted tasks	evidence/bench_report.md and evidence/task_report.md. The full pipeline with extracted rules scored 84.6% on 390 labels; the engine on the benchmark's own rules scored 91.8% on 342 labels
2:40 – end	Closing screen with the link to the live demo	clauseguard.up.railway.app

05 Reproduction

Run the same record on your own machine.

The operation record can be repeated on any machine with Python 3.10, Node.js and a Gemini key. Replace the placeholders with your own values.

terminal

```
# Backend with empty storage and a local admin token
CG_AUTH= CG_STORAGE=local DATABASE_URL= CG_DB_PATH=<dir>/s.sqlite CG_HISTORY_DB_PATH=<dir>/h.s
qlite \
CG_AUDIT_PATH=<dir>/a.jsonl CG_ADMIN_TOKEN=<local token> GEMINI_API_KEY=<key> \
python -m uvicorn clauseguard.sandbox.api:app --port 8100

# Web application in demo mode, pointed at that backend
BACKEND_URL=http://127.0.0.1:8100 NEXT_PUBLIC_APP_MODE=demo npx next dev -p 3100

# Verify the chain of the resulting log
python scripts/verify_audit.py <dir>/a.jsonl
```

Open localhost:3100/chat as Rizky and follow Section 2. The insurer desk is at localhost:3100/insurer and asks for the admin token. The supporting results can be repeated with the commands in **Table 13** in the Appendix. Tests that do not call a model run without a key.

06

Limits of the Evidence

What this record does not show.

1. The operation record is one scenario captured on a local deployment of the same code, with live model calls. The wording of model replies can differ between runs.
2. The hosted log contains development and test sessions, so it shows behaviour and does not measure real use.
3. There is no external red team, no real insurer data and no real users.
4. The scripted, off-script, paraphrase, clarification, recourse and allocation runs use deterministic mode without model calls. Behaviour with the model-driven Conversation Agent and rule binder on was measured only for the paraphrase live sample.
5. The benchmark rows for the long-context baselines cover three contracts, and the full pipeline covers 390 of 580 labels.
6. The CMS plan-selection experiment ran without premiums, so all methods coincide there.
7. The ombudsman replay (part B of the recourse evaluation) had not run when its report was generated.

A Appendix

Index of supporting evidence.

Table 13 lists the supporting files in evidence/ with the command that produces each one and its headline result.

Table 13 Supporting evidence files

FILE	WHAT IT SHOWS	COMMAND	RESULT
task_report.md, task_runs.jsonl	33 scripted tasks (T01 to T23 and A01 to A10) with transcripts	`python scripts/run_tasks.py --no-llm`	33 of 33, deterministic mode
offscript_blind_report.md	14 questions written and run once before any fix	`python scripts/run_tasks.py --no-llm --suite blind`	3 of 14, the out-of-sample figure
adversarial_report.md	Chat attack suite with enforcement on and off, direct probes, hidden-text detection, extractor spot check	`python scripts/run_adversarial.py --no-guard`	Attacks 0 of 27 defended, 1 of 27 undefended; benign 0 of 15 (11 October 2026)
paraphrase_report.md	Decision consistency across three wordings	`python bench/paraphrase.py`	20 of 20 with the rule binder; 7 of 8 live sample
clarify_report.md	Clarification recall, silence and ask precision against an oracle	`python bench/clarify_eval.py`	87% and 100%
cost_report.md	Model calls and tokens per turn against a long-context baseline	`python bench/cost_eval.py`	0.98 calls per turn
latency_report.md	Turn latency without a model and with the live model	`python -m bench.latency_eval`	Median 0.18 s and 8.59 s
recourse_report.md	Recourse for every denied verdict of the scripted tasks	`python -m bench.recourse_eval`	4 of 6 denials with recourse
plan_selection_report.md	Plan selection under budget on 834 CMS plans and a mixed catalogue, 100 households	`python -m bench.plan_selection_eval --households 100 --seed 7`	73 of 100; 79 of 100 on the mixed catalogue
allocation_report.md	Claim allocation against greedy and single-policy baselines	`python -m bench.allocation_eval`	Present
bench_report.md	Public benchmark: accuracy, macro-F1, invented denials, evidence hit	`python -m bench.report`	Full pipeline 84.6% on 390 labels
icd_report.md	Diagnosis code evaluation on the development set	`python -m bench.icd_eval`	92.2% (59 of 64 coded lines, development set); held-out set not yet measured
extraction_quality.md	Extracted values against the benchmark's gold annotations	`python scripts/extraction_quality.py`	Present
claims_desk_run.md	One scripted claim from upload to the desk decision with audit sequence numbers	`python scripts/claims_desk_evidence.py`	Generated 14 October 2026

FILE	WHAT IT SHOWS	COMMAND	RESULT
`conversation_eval_v3.json`	47 conversation turns with slang, corrections and what-ifs	`python scripts/conversation_eval.py`	42 of 47
`operation_run_2026-10-19.jsonl`	The audit log of the operation record in Section 2	`Recorded by the running system`	OK (69 events)
`Supabase RLS check`	Every Postgres table denies the database REST API to the public key	`python scripts/check_supabase_rls.py`	15 October 2026: six tables, all denied