LAB ASSIGNMENT 1 — UNDERSTANDING LINEAR AND LOGISTIC REGRESSION

Experimental report | Biomedical System Design Capsule-S1

Burak Bekir Çakırer | Student ID: 2211011008

21 October 2026

Abstract

This lab studies two supervised machine-learning tasks on real biomedical datasets. Linear regression predicts a continuous one-year diabetes disease-progression score from body mass index (BMI) and average blood pressure (442 observations). Logistic regression distinguishes malignant from benign breast-tumor samples using worst radius and worst concave points (569 observations). Both datasets were split into 80% training and 20% held-out testing data with a fixed random seed of 42. The linear model obtained a test MAE of **50.04** and R^2 of **0.294**. The two-feature logistic model obtained **95.61% accuracy** and **0.938 F1** at threshold 0.5. Additional controlled experiments examine standardization, learning-rate convergence, decision thresholds, and feature inclusion. The goal is to interpret model behavior, rather than to claim clinical readiness.

Keywords: linear regression; logistic regression; feature scaling; gradient descent; decision threshold; biomedical data.

1. Study Design and Reproducibility

The experiments follow the assignment's Parts A–D. Only two prespecified features per dataset are used to keep the fitted models and visualizations interpretable. The datasets are publicly distributed with scikit-learn and are loaded locally; no external download or fabricated records are required. Both are observational biomedical datasets used here solely as teaching benchmarks. Dataset origin and feature definitions are documented in References [1–5].

Setting	Linear regression	Logistic regression
Dataset	Diabetes (442 samples)	Wisconsin Diagnostic Breast Cancer (569 samples)
Features	BMI, average blood pressure	Worst radius, worst concave points
Label	Continuous progression score	Malignant = 1; benign = 0
Train / test	353 / 89	455 / 114
Partition	80/20, random seed 42	80/20, seed 42, stratified
Baseline estimator	Ordinary least squares (OLS)	L2-regularized logistic regression
Preprocessing	Unscaled raw features for B1; train-only z-scaling for B2–B3	Train-only z-scaling

Software and configuration. Python 3.13.5; NumPy 2.3.5; pandas 2.2.3; scikit-learn 1.8.0; Matplotlib 3.10.8 [6]. For logistic regression, the `lbfgs` solver, C = 1, and maximum 2000 iterations were used. All coefficients below correspond to models fitted on the training split only. In B3, batch gradient descent uses 150 iterations for all learning rates. Test observations do not contribute to fitting the scalers, model coefficients, or gradient-descent settings.

Reproducibility note: the project ZIP contains the analysis program, dependency specification, saved train/test assignments, figures, and machine-readable result tables. **No implementation code is included in this report.** For a different environment, numerical differences may occur from library versions.

2. Part A — Dataset Selection and Exploration

2.1 Dataset 1: Diabetes progression (linear regression)

Problem. Estimate a continuous one-year disease-progression score using two baseline measurements. The scikit-learn diabetes dataset is documented in Efron et al. (2004) and the official dataset description [1, 2]. There are 442 observations, with measurements at baseline and a disease-progression outcome recorded one year later. The target is a numeric progression measure, **not** a diabetes diagnosis, probability, or measured glucose concentration.

Inputs and suitability. BMI represents body mass index; BP represents average blood pressure. The continuous target makes regression appropriate. Only these two variables are selected from the ten available, deliberately trading explanatory power for interpretability. The scikit-learn loader was configured to return the original (not library-standardized) feature values, making coefficient units interpretable. No missing-value imputation was necessary; the model uses the numeric feature values as provided.




Figure 1: Exploratory relationships of BMI and average blood pressure with the continuous disease-progression target. Wide scatter indicates that two predictors cannot explain all variation.

Observation. Higher BMI and higher blood pressure tend to accompany higher progression scores, but both scatter plots show substantial spread. This is an early indication that the two-feature linear fit may have limited predictive accuracy.

2.2 Dataset 2: Breast cancer diagnostic features (logistic regression)

Problem. Classify pre-existing diagnostic feature records as malignant or benign. The Wisconsin Diagnostic Breast Cancer dataset is documented in the UCI Machine Learning Repository, in Street et al. (1993), and in the scikit-learn dataset guide [3–5]. It contains 569 observations, including 212 malignant and 357 benign samples. It contains 30 candidate features; this lab selects just two: worst radius and worst concave points. These describe properties derived from cell-nucleus images rather than clinical symptoms.

Dataset provenance and interpretation. The UCI repository identifies these as measurements derived from digitized fine-needle aspirate images of breast masses [3, 4]. Records in this experiment are pre-extracted feature measurements, not raw images.

Inputs and preprocessing. The binary outcome is encoded **1 = malignant**, **0 = benign**. This reverses the dataset's original numeric label mapping to make sensitivity to malignancy explicit. The split is stratified to preserve relative class proportions. StandardScaler means and standard deviations are estimated on training

samples only. This dataset is suitable for logistic regression because the outcome is binary and both selected predictors are numerical.




Figure 2: Distribution of the 569 diagnostic records across the two input features. The partially overlapping regions motivate probabilistic classification.

Observation. Malignant observations tend to have larger values of both features. The classes overlap, implying that no simple boundary can eliminate every mistake without changing the balance between false positives and false negatives.

3. Part B — Linear Regression Experiments

B1. Model parameters and predictions

Ordinary least squares was fitted on the raw BMI and blood-pressure values. The resulting linear model is an intercept plus one coefficient for each input.

Fitted parameter	Estimate	Meaning with other feature fixed
Intercept	-215.053	Prediction when BMI and BP are both zero (outside the observed population)
BMI coefficient	+9.048	+9.05 progression points per BMI unit
Blood pressure coefficient	+1.355	+1.35 points per BP unit

Held-out test metric	Result
Mean absolute error (MAE)	50.044
Mean squared error (MSE)	3740.507
Root mean squared error (RMSE; additional context)	61.160

Held-out test metric	Result
Coefficient of determination (R^2)	0.294

Interpretation. Holding blood pressure constant, one higher BMI unit is associated with about 9.05 higher predicted progression points, whereas one higher BP unit is associated with about 1.35 higher points, all else equal in this simple model. Because the feature units differ, coefficient magnitudes should not be interpreted as direct rankings of importance. The negative intercept is an extrapolation, not a physically meaningful patient's score. Test MAE approximately 50.0 progression points and R^2 approximately 0.294 show moderate-to-weak explanatory ability; predictions cluster toward the mean and miss extreme cases. Association does not establish causation.

B2. Feature scaling

A second OLS model was trained after fitting StandardScaler **only to the training set**. It subtracts training means and divides by training standard deviations. For unregularized OLS with an intercept, this affine transformation changes the numerical coefficients, but not the set of fitted predictions.

Comparison	Raw features	Standardized features
BMI coefficient	9.048	39.632
Blood pressure coefficient	1.355	19.043
Intercept	-215.053	153.737
Test MAE	50.044	50.044
Test R^2	0.294	0.294

Interpretation. The largest absolute difference between the two models' test predictions was only 5.68e-14, attributable to floating-point precision. After standardization, the BMI coefficient represents one **training-set standard deviation** of BMI rather than one BMI unit; the intercept becomes the predicted score at the training feature means. Standardization matters especially to gradient-based optimization, distance-based methods, and regularized models, even though it leaves this OLS model's predictive accuracy unchanged.

B3. Learning rate and convergence

To make learning behavior observable, batch gradient descent minimized half the **training** mean squared error using the same standardized diabetes features and centered training target. All runs started with zero coefficients, used 150 iterations, and differed **only** in learning rate (η). The exact OLS minimum of this same objective was 1773.929 training-loss units. "Within 1%" means the first iteration at which the loss is no greater than 1.01 times that minimum.

Learning rate (η)	Loss at iteration 10	Loss at iteration 150	First within 1% of optimum
0.01	2737.0	1802.1	Not reached
0.10	1851.9	1773.9	17
0.80	1773.9	1773.9	2
1.50	8682.6	3.03e+14	Diverges

Interpretation. Among tested values, $\eta = 0.80$ was the fastest stable choice, reaching the 1% band after **2 iterations**. $\eta = 0.10$ needed **17 iterations**, whereas $\eta = 0.01$ remained outside the band after 150 iterations. At $\eta = 1.50$, the step size overshot repeatedly and training loss grew to about 3.03e+14. More iterations can help a stable small step, but cannot fix a divergent step. These findings apply to this standardized two-feature quadratic objective, not to every dataset.




Figure 3: Actual versus predicted progression scores on the 89 held-out diabetes observations. The dashed diagonal denotes perfect predictions.




Figure 4: Baseline versus standardized OLS: identical test MAE, despite changed coefficient scales. Coefficient groups use different units and must not be compared directly.




Figure 5: Training loss versus iteration for four learning rates, shown on a log scale. $\eta = 0.80$ converges rapidly; $\eta = 1.50$ diverges.

4. Part C — Logistic Regression Experiments

C1. Model parameters and binary classification

The classifier uses a linear function of the two **standardized** inputs, transformed by a sigmoid function into a probability of malignancy. At threshold 0.5, probabilities at least 0.5 are labeled malignant. An L2 penalty is applied by scikit-learn with C = 1.

Parameter (standardized model)	Coefficient	Interpretation
Worst radius	+3.269	Higher standardized radius increases predicted malignant log-odds
Worst concave points	+2.311	Higher standardized concavity increases predicted malignant log-odds
Intercept	-0.835	Baseline log-odds at training mean feature values

Test metric at threshold 0.5	Result
Accuracy	0.956 (95.61%)
Precision (malignant positive)	0.974
Recall / sensitivity	0.905
F1-score	0.938
True negative / false positive	71 / 1
False negative / true positive	4 / 38




Figure 6: Confusion matrix on the 114 held-out diagnostic observations at threshold 0.5. Rows indicate actual diagnoses and columns indicate predicted classes.

Interpretation. The raw linear score is a log-odds value; the sigmoid produces a probability between 0 and 1 **before** thresholding. A one-training-standard-deviation increase in worst radius, with the other feature fixed, multiplies modeled odds by approximately 26.27; the analogous factor for worst concave points is 10.09. These are model associations, not causal effects. The confusion matrix shows **1 false positive** (benign labeled malignant) and **4 false negatives** (malignant labeled benign). Missing malignant cases is consequential in a hypothetical screening workflow, though this dataset and model must **not** be interpreted as a validated clinical tool.

C2. Decision-threshold experiment

The logistic model was trained **once**. Exactly the same held-out predicted probabilities were converted to labels using thresholds 0.3, 0.5, and 0.7; no refitting or new probability estimates were performed.

Threshold	Accuracy	Precision	Recall	F1	FP	FN
0.3	0.974	0.933	1.000	0.966	3	0
0.5	0.956	0.974	0.905	0.938	1	4
0.7	0.930	1.000	0.810	0.895	0	8

Interpretation. Lowering the threshold to 0.3 classified all 42 test malignant cases correctly (zero observed false negatives), at the cost of 3 false positives. Raising it to 0.7 eliminated false positives but increased false negatives to 8. For an illustrative high-sensitivity triage setting, **0.3 is the preferred illustrative threshold** among these options, because missing a positive is treated as more costly than triggering follow-up review. This is **not a clinically validated choice** and must not be selected for deployment from test-set results: any genuine operating threshold should be fixed on a separate validation set using explicit error costs, calibration, and prospective evaluation.





Figure 7: Precision and recall evaluated on identical test probabilities for three thresholds. A lower threshold emphasizes sensitivity; a higher threshold emphasizes precision.

C3. One input feature versus two input features

Two logistic models used the **same** training/test indices and threshold 0.5: one used worst radius alone; the other included worst radius and worst concave points. A fresh train-only scaler was fitted within each model pipeline.

Test metric	One feature	Two features
Accuracy	0.904	0.956
Precision	0.943	0.974
Recall	0.786	0.905
F1-score	0.857	0.938
False negatives	9	4






Figure 9: Classification accuracy and malignant recall using one feature versus both features on the identical held-out partition.

2. What is a parameter versus a hyperparameter? Parameters are learned from training data: the BMI coefficient 9.048, the unscaled regression intercept -215.053, and the standardized logistic coefficient 3.269 are examples. Hyperparameters are settings specified before fitting, such as logistic C = 1, gradient-descent learning rate η, the iteration count (150 in B3), and the classification cutoff. The cutoff changes decisions, but not the fitted logistic coefficients.

3. How does learning rate affect fitting? A low rate moves slowly ($\eta = 0.01$ did not reach the 1% training-loss band in 150 iterations), $\eta = 0.80$ reached it in two, and $\eta = 1.50$ diverged. Iteration count and rate jointly control convergence; the largest step is not always fastest in a stable sense.

4. Why use different metrics? Regression errors have a magnitude in target units, so MAE, MSE, and R^2 communicate numeric performance. Classification errors are discrete and often have unequal consequences. Accuracy alone hides the direction of errors; precision, recall, F1, and the confusion matrix identify the trade-off. For example, moving from threshold 0.5 to 0.7 raises malignant precision from 0.974 to 1.000 but lowers recall from 0.905 to 0.810.

5. What was unexpected? Standardizing the OLS inputs dramatically altered the numerical coefficients, while changing held-out predictions by only 5.68e-14. This is explained by OLS being invariant to invertible affine rescaling when an intercept is fitted. A second informative result is that threshold 0.3 achieved zero false negatives **on this particular test partition**; that result is not proof of perfect sensitivity in unseen populations.

6. Limitations and Conclusion

Limitations. The diabetes fit uses only two of ten available predictors, yielding a modest R^2; omitted predictors, nonlinearity, and measurement noise may account for residual errors. The cancer comparison also uses just two of 30 features, evaluated on one stratified holdout split (114 cases). A single split provides uncertain performance estimates and the class frequencies may not reflect screening populations. The threshold comparison is explanatory, not a valid procedure for optimizing an operational cutoff on the test set. Neither exercise performs patient-level external validation, fairness assessment, probability calibration, or clinical risk analysis. No medical decision should be based on these models.

Conclusion. The experiments demonstrate that model output determines the appropriate learning objective and evaluation metrics. OLS input standardization changes parameter units but not predictions, whereas gradient descent shows strong sensitivity to step size. Logistic classifications depend on both the learned probability surface and the operating threshold. Adding a second diagnostic feature improved held-out malignant recall in this study, yet careful validation is more important than a single attractive test score.

References

[1] Efron, B., Hastie, T., Johnstone, I., and Tibshirani, R. (2004). "Least Angle Regression." *The Annals of Statistics*, 32(2), 407–499. https://doi.org/10.1214/009053604000000067. (Original research reference for the Diabetes data.)

[2] scikit-learn developers. (2026). "Diabetes dataset — load_diabetes." Official documentation. https://scikit-learn.org/stable/modules/generated/sklearn.datasets.load_diabetes.html (accessed 21 October 2026). (Sample count, feature names, target definition, and loader settings.)

[3] Wolberg, W., Mangasarian, O., Street, N., and Street, W. (1993). *Breast Cancer Wisconsin (Diagnostic)* [Data set]. UCI Machine Learning Repository. https://doi.org/10.24432/C5DW2B. (Original dataset citation, as provided by UCI.)

[4] Street, W. N., Wolberg, W. H., and Mangasarian, O. L. (1993). "Nuclear feature extraction for breast tumor diagnosis." In *Biomedical Image Processing and Biomedical Visualization*, SPIE Vol. 1905, 861–870. https://doi.org/10.1117/12.148698. (Study describing source-image feature extraction.)

[5] scikit-learn developers. (2026). "Breast cancer Wisconsin dataset — load_breast_cancer." Official documentation. https://scikit-learn.org/stable/modules/generated/sklearn.datasets.load_breast_cancer.html (accessed 21 October 2026). (Original class encoding, counts, and input-feature dimensions.)

[6] Pedregosa, F., et al. (2011). "Scikit-learn: Machine Learning in Python." *Journal of Machine Learning Research*, 12, 2825–2830. https://jmlr.org/papers/v12/pedregosa11a.html. (Software citation.)