

4.11 Exercise: Advanced scatterplots for deeper analysis – R version

This exercise will enable you to explore more complicated relationships between variables and the effects of a third and fourth variable, enabling you to view changes over time.

The skills addressed are:






1. Create a scatterplot of two numeric variables, subset by a 3rd variable.
2. Explore the effect of a third and fourth variable using colour and size.

We will use the **gapminder** dataset (but **not** *gapminder_2008*).

Create a scatterplot of two numeric variables, subset by a 3rd variable


We are going to explore the relationship between the variables **Infantmortality** and **ChildrenPerWoman** of countries in the **Gapminder** dataset over time.

#R Code	Output and/or Commentary
<pre># Setup library(iNZightPlots) library(FutureLearnData) data(gapminder)</pre>	

<p># Scatterplot of <i>Infantmortality</i> against <i>ChildrenPerWoman</i></p> <pre>iNZightPlot(ChildrenPerWoman,Infantmortality , data=gapminder)</pre>	 <p>Infantmortality versus ChildrenPerWoman</p> <p>Infantmortality</p> <p>ChildrenPerWoman</p> <p>1265 missing values (606 in ChildrenPerWoman, 1109 in Infantmortality)</p>
<p># Subset by <i>Year_cat</i></p> <pre>iNZightPlot(ChildrenPerWoman,Infantmortality, g1=Year_cat, data=gapminder)</pre>	 <p>Infantmortality versus ChildrenPerWoman subset by Year_cat</p> <p>Infantmortality</p> <p>ChildrenPerWoman</p> <p>1265 missing values (606 in ChildrenPerWoman, 1109 in Infantmortality)</p>
<p># Change size and colour of points</p> <pre>iNZightPlot(ChildrenPerWoman,Infantmortality,g1=Year_cat, data=gapminder, colby=Region, sizeby=Populationtotal)</pre>	 <p>Infantmortality versus ChildrenPerWoman subset by Year_cat (size proportional to Populationtotal)</p> <p>Infantmortality</p> <p>ChildrenPerWoman</p> <p>1265 missing values (606 in ChildrenPerWoman, 1109 in Infantmortality)</p> <p>Region</p> <ul style="list-style-type: none"> America East Asia & Pacific Europe & Central Asia Middle East & North Africa South Asia Sub-Saharan Africa
<p># Show results for 1972 only</p> <pre>iNZightPlot(ChildrenPerWoman,Infantmortality,g1=Year_cat, g1.level="[1972]",data=gapminder, colby=Region, sizeby=Populationtotal)</pre>	 <p>Infantmortality versus ChildrenPerWoman subset by Year_cat (size proportional to Populationtotal)</p> <p>[1972]</p> <p>Infantmortality</p> <p>ChildrenPerWoman</p> <p>91 missing values (38 in ChildrenPerWoman, 85 in Infantmortality)</p> <p>Region</p> <ul style="list-style-type: none"> America East Asia & Pacific Europe & Central Asia Middle East & North Africa South Asia Sub-Saharan Africa
<p># Darker background (often easier to see some of the lighter dots)</p> <pre>iNZightPlot(ChildrenPerWoman,Infantmortality, g1=Year_cat, g1.level="[1972]",data=gapminder, colby=Region, sizeby=Populationtotal, bg="darkgray")</pre>	 <p>Infantmortality versus ChildrenPerWoman subset by Year_cat (size proportional to Populationtotal)</p> <p>[1972]</p> <p>Infantmortality</p> <p>ChildrenPerWoman</p> <p>91 missing values (38 in ChildrenPerWoman, 85 in Infantmortality)</p> <p>Region</p> <ul style="list-style-type: none"> America East Asia & Pacific Europe & Central Asia Middle East & North Africa South Asia Sub-Saharan Africa

Try transparency and smaller points (removed garkgray)


```
iNZightPlot(ChildrenPerWoman,Infantmortality,g1=Year_cat,
  g1.level="[1972]",data=gapminder,colby=Region,
  sizeby=Populationtotal,alpha=.45,cex.dotpt=.5)
```



Try subsetting by different years, e.g. g1.level="[1976]",

Label some of the extreme points (ask for 4)


```
iNZightPlot(ChildrenPerWoman,Infantmortality,g1=Year_cat,
  g1.level="[1972]",data=gapminder,colby=Region,
  sizeby=Populationtotal,alpha=.45,cex.dotpt=.5,
  locate.extreme=4,locate=Country)
```



Label some specific countries


```
ids = (1:nrow(gapminder))[gapminder$Country %in%
  c("United States of America","China","Brazil", "India")]
```

```
iNZightPlot(ChildrenPerWoman,Infantmortality,g1=Year_cat,
  g1.level="[1972]",data=gapminder,colby=Region,
  sizeby=Populationtotal,alpha=.45,cex.dotpt=.5,
  locate.id=ids,locate=Country)
```




Allow a little more room on left to accommodate label

```
iNZightPlot(ChildrenPerWoman, Infantmortality, g1=Year_cat,
             g1.level="[1972]", data=gapminder, colby=Region,
             sizeby=Populationtotal, alpha=.45, cex.dotpt=.5,
             locate.id=ids, locate=Country, xlim=c(0,9))
```



Subset by a fourth variable (Region)

```
iNZightPlot(ChildrenPerWoman, Infantmortality, g1=Year_cat,
             g2=Region, g2.level="America", data=gapminder, colby=Region)
```



Play through the years

```
for (k in levels(gapminder$Year_cat)) {
  iNZightPlot(ChildrenPerWoman, Infantmortality, g1=Year_cat,
              g1.level=k, data=gapminder, colby=Region,
              sizeby=Populationtotal, alpha=.45, cex.dotpt=.5,
              locate.id=ids, locate=Country)
  Sys.sleep(1)
}
```

- Play some more with these settings and try other variables
- For even more settings, type `?inzpar` into R to get help on the `inzpar`, or type `inzpar` to just get a complete list (last time I looked the help file wasn't entirely complete)

To discuss issues related to this Exercise,

go to <https://gitter.im/iNZightVIT/d2i-R-discussion>

To be able to post to the list you will have to set up a (free) account on **Github**

<https://github.com/login>

If your question relates to an Exercise, say which one you are talking about!