基于大语言模型微调的公司产品 FAQ 聊天机器人

项目背景:

通过该机器人可以回复用户关于具体产品的问题，解决用户在使用过程中遇到的各种问题。

基于模型:

Qwen-14B-Chat

微调数据集:

1. 公司产品信息。
2. 公司售后人员常见问题总结列表。

使用样例:

```
from modelscope import AutoModelForCausalLM, AutoTokenizer from modelscope
import GenerationConfig
# Note: The default behavior now has injection attack prevention off.
tokenizer = AutoTokenizer.from_pretrained("qwen/Qwen-14B-Chat",
trust_remote_code=True)
# use bf16 # model = AutoModelForCausalLM.from_pretrained("qwen/Qwen-14B-
Chat", device_map="auto", trust_remote_code=True, bf16=True).eval() # use
fp16 # model = AutoModelForCausalLM.from_pretrained("qwen/Qwen-14B-Chat",
```

```
device_map="auto", trust_remote_code=True, fp16=True).eval() # use cpu only
# model = AutoModelForCausalLM.from_pretrained("qwen/Qwen-14B-Chat",
device_map="cpu", trust_remote_code=True).eval() # use auto mode,
automatically select precision based on the device. model =
AutoModelForCausalLM.from_pretrained("qwen/Qwen-14B-Chat",
device_map="auto", trust_remote_code=True).eval()
# Specify hyperparameters for generation. But if you use
transformers>=4.32.0, there is no need to do this. #
model.generation_config = GenerationConfig.from_pretrained("Qwen/Qwen-14B-
Chat", trust_remote_code=True) # 可指定不同的生成长度、top_p 等相关超参

# 第一轮对话 1st dialogue turn response, history = model.chat(tokenizer, "你
好", history=None) print(response) # 你好！很高兴为你提供帮助。

# 第二轮对话 2nd dialogue turn response, history = model.chat(tokenizer, "给
我讲一下虹膜产品的特点。", history=history) print(response) # xxxx

# 第三轮对话 3rd dialogue turn response, history = model.chat(tokenizer, "虹
膜摄像头不能连接是什么原因？", history=history) print(response) # xxxxxx
```