SOC L1 LAB · INC-002

Attack Setup Guide — INC-002

Creating a rogue sudo account, phase by phase, inside the lab

INCIDENT	INC-002 — Rogue local account added to sudo
REPORT DATE	2026-10-31
CLASSIFICATION	Lab exercise — sanitized for publication
ENVIRONMENT	Wazuh 4.14.7 · Debian 12 · QEMU/KVM
SEVERITY	High

Independent portfolio lab. No production systems, client data, or real credentials.

Contents

1. Authorization and safety
2. Topology and assumptions
3. Phase 0 — Clean state
4. Phase 1 — Start legitimate noise
5. Phase 2 — Create the account
6. Phase 3 — Set a password
7. Phase 4 — Grant sudo
8. Phase 5 — Verify
9. Phase 6 — Capture evidence
10. Expected detections
11. Phase 7 — Clean up
12. Variations for detection testing
13. Why this is realistic
14. Legal and ethical notes

A step-by-step script for reproducing INC-002 **inside the isolated lab**. It is for testing detection, not for use against systems you do not own.

---

1. Authorization and safety

Rule	Detail
Scope	Only the `soc-victim` VM on `10.0.2.0/24`
Never	Touch any other host, network, or account
Never	Use real credentials or employer systems
Authorization	You own the host and the VM
Reversibility	Snapshot before the run; revert or clean up after
Data	Synthetic accounts and passwords only

The scenario models an insider or a compromised administrator session. It is deliberately an authorised admin action, because that is the case logs cannot distinguish from abuse without change-control evidence.

---

2. Topology and assumptions

```
Host 10.0.2.2
  ├── Wazuh manager / indexer / dashboard
  ├── analyst SSH session (key) → 127.0.0.1:2222
  └── QEMU user network
        └── soc-victim 10.0.2.15
              sshd, auditd, FIM, wazuh-agent
              actor: analyst (uid 1000) via sudo
```

Assumptions:

- The base lab from `writeups/INC-001/02-reproduction-guide.md` is running.
- The agent is `Active`, auditd keys are loaded, `/etc` has realtime FIM.
- Rule 100121 is deployed and validated (see the INC-002 reproduction guide).
- `analyst` has passwordless sudo.
- No `svc-ops` account exists.

```
export LAB="$HOME/Documents/Eterna/soc-l1-lab"
export VMKEY="$LAB/lab/vm/keys/id_ed25519"
export VM="analyst@127.0.0.1"
export VMPORT=2222
```

---

3. Phase 0 — Clean state

```
cd "$LAB/lab/vm"
./snapshot.sh save pre-inc002
sleep 5

ssh -i "$VMKEY" -p "$VMPORT" -o StrictHostKeyChecking=no "$VM" '
getent passwd svc-ops || echo "svc-ops absent"
getent group sudo'
```

Expected:

```
svc-ops absent
sudo:x:27:analyst,debian
```

If a validation account (`svc-test`) remains, remove it now:

```
ssh -i "$VMKEY" -p "$VMPORT" "$VM" '
sudo gpasswd -d svc-test sudo 2>/dev/null || true
sudo userdel -r svc-test 2>/dev/null || true'
```

---

4. Phase 1 — Start legitimate noise

```
END=$(( $(date +%s) + 180 ))
setsid /tmp/noise.sh "$END" >/dev/null 2>&1 &
sleep 40
date -u +%FT%TZ > /tmp/inc002_start
```

If `/tmp/noise.sh` is missing, recreate it:

```
cat > /tmp/noise.sh <<EOF
#!/usr/bin/env bash
KEY=$VMKEY
END=\$1
while [ "\$(date +%s)" -lt "\$END" ]; do
  ssh -i "\$KEY" -p $VMPORT -o StrictHostKeyChecking=no \
      -o UserKnownHostsFile=/dev/null -o BatchMode=yes "$VM" \
      'uptime -p; systemctl is-active nginx' >/dev/null 2>&1
  ssh -i "\$KEY" -p $VMPORT -o StrictHostKeyChecking=no \
      -o UserKnownHostsFile=/dev/null -o BatchMode=yes "$VM" \
      'sudo -n systemctl is-active nginx' >/dev/null 2>&1
  sleep 30
done
```

```
EOF
chmod +x /tmp/noise.sh
```

---

5. Phase 2 — Create the account

```
ssh -i "$VMKEY" -p "$VMPORT" -o StrictHostKeyChecking=no "$VM" '
sudo useradd -m -s /bin/bash svc-ops
getent passwd svc-ops'
```

Expected:

```
svc-ops:x:1003:1003::/home/svc-ops:/bin/bash
```

Why these flags:

Flag	Effect
`-m`	Creates `/home/svc-ops`
`-s /bin/bash`	Interactive shell, which a service account should not have

---

6. Phase 3 — Set a password

```
ssh -i "$VMKEY" -p "$VMPORT" "$VM" '
echo "svc-ops:Summer2026!" | sudo chpasswd
sudo passwd -S svc-ops'
```

Expected: the account has a usable password (`P` in the second field).

This is part of the misconfiguration. Service accounts should use keys only, or no credentials at all if they are not interactive.

---

7. Phase 4 — Grant sudo

```
ssh -i "$VMKEY" -p "$VMPORT" "$VM" '
sudo usermod -aG sudo svc-ops
id svc-ops
getent group sudo'
```

Expected:

```
uid=1003(svc-ops) gid=1003(svc-ops) groups=1003(svc-ops),27(sudo)
sudo:x:27:analyst,debian,svc-ops
```

This is the action the custom rule is designed to catch.

---

8. Phase 5 — Verify

```
ssh -i "$VMKEY" -p "$VMPORT" "$VM" '
sudo -l -U svc-ops 2>&1 | tail -5'
```

If `sudo -l -U` requires a TTY, run it interactively or skip it; the group line from `getent` is sufficient evidence.

Record the time:

```
date -u +%FT%TZ > /tmp/inc002_action
echo "action: $(cat /tmp/inc002_action)"
```

Wait 60–90 seconds before extracting alerts.

---

9. Phase 6 — Capture evidence

```
docker exec single-node-wazuh.manager-1 cat /var/ossec/logs/alerts/alerts.json \
  > /tmp/alerts_all.json

python3 - <<'PY'
import json, datetime
start = datetime.datetime.fromisoformat("2026-10-31T04:30:40+00:00")
end   = datetime.datetime.fromisoformat("2026-10-31T04:32:00+00:00")
rows=[]
for line in open('/tmp/alerts_all.json'):
    try: a=json.loads(line)
    except: continue
    if a.get('agent',{}).get('name')=='soc-victim' and \
       start <= datetime.datetime.fromisoformat(a['timestamp']) <= end:
        rows.append(a)
json.dump(rows, open('docs/evidence/INC-002-alerts.json','w'), indent=1)
print(len(rows), "alerts")
PY
```

Export the account records:

```
ssh -i "$VMKEY" -p "$VMPORT" "$VM" \
  'sudo journalctl --since "2026-10-31 04:30:40" --until "2026-10-31 04:31:20" --no-pager \
   | grep -Ei "useradd|usermod|chpasswd|new user|new group|sudo:"' \
```

```
  > docs/evidence/INC-002-account.log

ssh -i "$VMKEY" -p "$VMPORT" "$VM" \
  'getent group sudo; getent passwd svc-ops' \
  > docs/evidence/INC-002-membership.txt
```

---

10. Expected detections

Phase	Rule	Expected
`useradd`	80792	`Audit: Command: /usr/sbin/useradd`
`useradd`	5901 / 5902	New group and new user, level 8
`chpasswd`	80792	`Audit: Command: /usr/sbin/chpasswd`
`usermod -aG sudo`	**100121**	Privilege assignment, level 12, names `svc-ops`
File writes	550	`/etc/passwd`, `/etc/group`, `/etc/shadow`, `/etc/gshadow`
File writes	80781	Write access to `/etc/passwd` and `/etc/group`
Noise	5715 / 5402 / 80792	Routine logins, sudo, commands

Expected window volume: roughly 200–250 alerts, most of them audit command events.

---

11. Phase 7 — Clean up

```
ssh -i "$VMKEY" -p "$VMPORT" "$VM" '
sudo gpasswd -d svc-ops sudo
sudo userdel -r svc-ops
getent group sudo
getent passwd svc-ops || echo "svc-ops removed"'
```

Expected:

```
sudo:x:27:analyst,debian
svc-ops removed
```

Or revert the snapshot:

```
cd "$LAB/lab/vm"
./snapshot.sh load pre-inc002
```

---

12. Variations for detection testing

12.1 `-G` instead of `-aG`

```
sudo usermod -G sudo svc-ops
```

This replaces the account's supplementary groups. Rule 100121 still matches, because `a2` is still `sudo`. Verify it fires, then restore the account's groups if needed.

12.2 A custom privileged group

On a RHEL-family host, the group is often `wheel`. Rule 100121 will not match until the group name is added or a CDB list is used. This is the most important variant to test; it is the difference between a portable rule and a Debian-only rule.

```
sudo groupadd -r ops-admin
sudo usermod -aG ops-admin svc-ops
# expected: 100121 does NOT fire until the rule or list is updated
```

12.3 Direct `/etc/group` edit

This simulates an attacker who can write the file without `usermod`:

```
sudo cp /etc/group /etc/group.bak
sudo sed -i 's/^\(sudo:x:27:.*\)$/\1,svc-ops/' /etc/group
```

Expected: FIM **550** on `/etc/group`, **no 100121**. This is the documented gap. A membership baseline or a FIM-diff rule is required to catch it. Restore the file afterwards:

```
sudo mv /etc/group.bak /etc/group
```

12.4 Account without a shell

```
sudo useradd -m -s /usr/sbin/nologin svc-svc
sudo usermod -aG sudo svc-svc
```

Rule 100121 still fires, correctly: the account is non-interactive but still privileged. This variant tests the policy "service accounts are never in sudo."

12.5 Add an SSH key

```
sudo -u svc-ops bash -c \
  'mkdir -p ~/.ssh; echo "ssh-ed25519 AAAATEST" >> ~/.ssh/authorized_keys'
```

Expected: rule **100120** from INC-001 fires on the key file, in addition to 100121. The combination is a strong signal: a new privileged account with a persistence mechanism.

---

13. Why this is realistic

- **The actor is an authenticated administrator.** That is how most rogue local accounts are created, and why source IP alone cannot decide the case.
- **The name looks legitimate.** `svc-ops` follows a service-account pattern.
- **The change is small.** Two commands, under two seconds, in a queue of 237 alerts.
- **The privilege is implicit.** Nothing in 5902 says "root"; the analyst has to read the group membership.
- **The evidence is split.** FIM shows the file change, audit shows the command, and the rule connects them.

---

14. Legal and ethical notes

- Run this only on the VM you created.
- The account, password, and UID are synthetic.
- Do not use these commands on an employer's system without written authorisation and a scoped engagement.
- Publishing the detection logic is fine; publishing a real credential or a real hostname is not.