

Using HTTP Methods for RESTful Services

[Quick-Tips](#)[Resource Naming](#)

The HTTP verbs comprise a major portion of our “uniform interface” constraint and provide us the action counterpart to the noun-based resource. The primary or most-commonly-used HTTP verbs (or methods, as they are properly called) are POST, GET, PUT, PATCH, and DELETE. These correspond to create, read, update, and delete (or CRUD) operations, respectively. There are a number of other verbs, too, but are utilized less frequently. Of those less-frequent methods, OPTIONS and HEAD are used more often than others.

Below is a table summarizing recommended return values of the primary HTTP methods in combination with the resource URIs:

| HTTP Verb | CRUD | Entire Collection (e.g. /customers) | Specific Item (e.g. /customers/{id}) |
|-----------|----------------|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|
| POST | Create | 201 (Created), 'Location' header with link to /customers/{id} containing new ID. | 404 (Not Found), 409 (Conflict) if resource already exists.. |
| GET | Read | 200 (OK), list of customers. Use pagination, sorting and filtering to navigate big lists. | 200 (OK), single customer. 404 (Not Found), if ID not found or invalid. |
| PUT | Update/Replace | 405 (Method Not Allowed), unless you want to update/replace every resource in the entire collection. | 200 (OK) or 204 (No Content). 404 (Not Found), if ID not found or invalid. |
| PATCH | Update/Modify | 405 (Method Not Allowed), unless you want to modify the collection itself. | 200 (OK) or 204 (No Content). 404 (Not Found), if ID not found or invalid. |
| DELETE | Delete | 405 (Method Not Allowed), unless you want to delete the whole collection—not often desirable. | 200 (OK). 404 (Not Found), if ID not found or invalid. |

Below is a more-detailed discussion of the main HTTP methods. Click on a tab for more information about the desired HTTP method.

[POST](#)[GET](#)[PUT](#)[PATCH](#)[DELETE](#)

The HTTP GET method is used to ****read**** (or retrieve) a representation of a resource. In the “happy” (or non-error) path, GET returns a representation in XML or JSON and an HTTP response code of 200 (OK). In an error case, it most often returns a 404 (NOT FOUND) or 400 (BAD REQUEST).

According to the design of the HTTP specification, GET (along with HEAD) requests are used only to read data and not change it. Therefore, when used this way, they are considered safe. That is, they can be called without risk of data modification or corruption—calling it once has the same effect as calling it 10 times, or none at all. Additionally, GET (and HEAD) is idempotent, which means that making multiple identical requests ends up having the same result as a single request.

Do not expose unsafe operations via GET—it should never modify any resources on the server.

Examples:

- GET `http://www.example.com/customers/12345`