

# List of HTTP status codes

---

This is a list of [Hypertext Transfer Protocol](#) (HTTP) response status codes. Status codes are issued by a server in response to a client's request made to the server. It includes codes from IETF [Request for Comments](#) (RFCs), other specifications, and some additional codes used in some common applications of the [Hypertext Transfer Protocol](#) (HTTP). The first digit of the status code specifies one of five standard classes of responses. The message phrases shown are typical, but any human-readable alternative may be provided. Unless otherwise stated, the status code is part of the HTTP/1.1 standard ([RFC 7231](#)).<sup>[1]</sup>

The [Internet Assigned Numbers Authority](#) (IANA) maintains the official registry of HTTP status codes.<sup>[2]</sup>

Microsoft [Internet Information Services](#) (IIS) sometimes uses additional decimal sub-codes for more specific information,<sup>[3]</sup> however these sub-codes only appear in the response payload and in documentation, not in the place of an actual HTTP status code.

## Contents

---

### 1xx Informational responses

### 2xx Success

### 3xx Redirection

### 4xx Client errors

### 5xx Server errors

### Unofficial codes

- Internet Information Services

- nginx

- Cloudflare

### See also

### Notes

### References

### External links

## 1xx Informational responses

---

An informational response indicates that the request was received and understood. It is issued on a provisional basis while request processing continues. It alerts the client to wait for a final response. The message consists only of the status line and optional header fields, and is terminated by an empty line. As the HTTP/1.0 standard did not define any 1xx status codes, servers *must not*<sup>[note 1]</sup> send a 1xx response to an HTTP/1.0 compliant client except under experimental conditions.<sup>[4]</sup>

### 100 Continue

The server has received the request headers and the client should proceed to send the request body (in the case of a request for which a body needs to be sent; for example, a [POST](#) request). Sending a large request body to a server after a request has been rejected for inappropriate headers would be inefficient. To have a server check the request's headers, a client must send `Expect: 100-continue` as a header in its initial request and receive a 100 Continue status code in response before sending the body. If the client receives an error code such as 403 (Forbidden) or 405 (Method Not Allowed) then it shouldn't send the request's body. The response 417 Expectation Failed indicates that the request should be

repeated without the Expect header as it indicates that the server doesn't support expectations (this is the case, for example, of HTTP/1.0 servers).<sup>[5]</sup>

### **101 Switching Protocols**

The requester has asked the server to switch protocols and the server has agreed to do so.<sup>[6]</sup>

### **102 Processing (WebDAV; RFC 2518)**

A WebDAV request may contain many sub-requests involving file operations, requiring a long time to complete the request. This code indicates that the server has received and is processing the request, but no response is available yet.<sup>[7]</sup> This prevents the client from timing out and assuming the request was lost.

### **103 Early Hints (RFC 8297)**

Used to return some response headers before final HTTP message.<sup>[8]</sup>

## **2xx Success**

---

This class of status codes indicates the action requested by the client was received, understood and accepted.<sup>[2]</sup>

### **200 OK**

Standard response for successful HTTP requests. The actual response will depend on the request method used. In a GET request, the response will contain an entity corresponding to the requested resource. In a POST request, the response will contain an entity describing or containing the result of the action.<sup>[9]</sup>

### **201 Created**

The request has been fulfilled, resulting in the creation of a new resource.<sup>[10]</sup>

### **202 Accepted**

The request has been accepted for processing, but the processing has not been completed. The request might or might not be eventually acted upon, and may be disallowed when processing occurs.<sup>[11]</sup>

### **203 Non-Authoritative Information (since HTTP/1.1)**

The server is a transforming proxy (e.g. a *Web accelerator*) that received a 200 OK from its origin, but is returning a modified version of the origin's response.<sup>[12][13]</sup>

### **204 No Content**

The server successfully processed the request and is not returning any content.<sup>[14]</sup>

### **205 Reset Content**

The server successfully processed the request, but is not returning any content. Unlike a 204 response, this response requires that the requester reset the document view.<sup>[15]</sup>

### **206 Partial Content (RFC 7233)**

The server is delivering only part of the resource (*byte serving*) due to a range header sent by the client. The range header is used by HTTP clients to enable resuming of interrupted downloads, or split a download into multiple simultaneous streams.<sup>[16]</sup>

### **207 Multi-Status (WebDAV; RFC 4918)**

The message body that follows is by default an *XML* message and can contain a number of separate response codes, depending on how many sub-requests were made.<sup>[17]</sup>

### **208 Already Reported (WebDAV; RFC 5842)**

The members of a DAV binding have already been enumerated in a preceding part of the (multistatus) response, and are not being included again.

### **226 IM Used (RFC 3229)**

The server has fulfilled a request for the resource, and the response is a representation of the result of one or more instance-manipulations applied to the current instance.<sup>[18]</sup>

## **3xx Redirection**

---

This class of status code indicates the client must take additional action to complete the request. Many of these status codes are used in *URL redirection*.<sup>[2]</sup>

A user agent may carry out the additional action with no user interaction only if the method used in the second request is GET or HEAD. A user agent may automatically redirect a request. A user agent should detect and intervene to prevent cyclical redirects.<sup>[19]</sup>

### 300 Multiple Choices

Indicates multiple options for the resource from which the client may choose (via agent-driven content negotiation). For example, this code could be used to present multiple video format options, to list files with different filename extensions, or to suggest word-sense disambiguation.<sup>[20]</sup>

### 301 Moved Permanently

This and all future requests should be directed to the given URI.<sup>[21]</sup>

### 302 Found (Previously "Moved temporarily")

Tells the client to look at (browse to) another url. 302 has been superseded by 303 and 307. This is an example of industry practice contradicting the standard. The HTTP/1.0 specification (RFC 1945) required the client to perform a temporary redirect (the original describing phrase was "Moved Temporarily"),<sup>[22]</sup> but popular browsers implemented 302 with the functionality of a 303 See Other. Therefore, HTTP/1.1 added status codes 303 and 307 to distinguish between the two behaviours.<sup>[23]</sup> However, some Web applications and frameworks use the 302 status code as if it were the 303.<sup>[24]</sup>

### 303 See Other (since HTTP/1.1)

The response to the request can be found under another URI using the GET method. When received in response to a POST (or PUT/DELETE), the client should presume that the server has received the data and should issue a new GET request to the given URI.<sup>[25]</sup>

### 304 Not Modified (RFC 7232)

Indicates that the resource has not been modified since the version specified by the request headers If-Modified-Since or If-None-Match. In such case, there is no need to retransmit the resource since the client still has a previously-downloaded copy.<sup>[26]</sup>

### 305 Use Proxy (since HTTP/1.1)

The requested resource is available only through a proxy, the address for which is provided in the response. Many HTTP clients (such as Mozilla<sup>[27]</sup> and Internet Explorer) do not correctly handle responses with this status code, primarily for security reasons.<sup>[28]</sup>

### 306 Switch Proxy

No longer used. Originally meant "Subsequent requests should use the specified proxy."<sup>[29]</sup>

### 307 Temporary Redirect (since HTTP/1.1)

In this case, the request should be repeated with another URI; however, future requests should still use the original URI. In contrast to how 302 was historically implemented, the request method is not allowed to be changed when reissuing the original request. For example, a POST request should be repeated using another POST request.<sup>[30]</sup>

### 308 Permanent Redirect (RFC 7538)

The request and all future requests should be repeated using another URI. 307 and 308 parallel the behaviors of 302 and 301, but *do not allow the HTTP method to change*. So, for example, submitting a form to a permanently redirected resource may continue smoothly.<sup>[31]</sup>

## 4xx Client errors

---

This class of status code is intended for situations in which the error seems to have been caused by the client. Except when responding to a HEAD request, the server *should* include an entity containing an explanation of the error situation, and whether it is a temporary or permanent condition. These status codes are applicable to any request method. User agents *should* display any included entity to the user.<sup>[32]</sup>

### 400 Bad Request

The server cannot or will not process the request due to an apparent client error (e.g., malformed request syntax, size too large, invalid request message framing, or deceptive request routing).<sup>[33]</sup>

### 401 Unauthorized (RFC 7235)

Similar to *403 Forbidden*, but specifically for use when authentication is required and has failed or has not yet been provided. The response must include a WWW-Authenticate header field containing a challenge applicable to the requested resource. See [Basic access authentication](#) and [Digest access authentication](#).<sup>[34]</sup> 401 semantically means "unauthenticated",<sup>[35]</sup> i.e. the user does not have the necessary credentials.

Note: Some sites issue HTTP 401 when an IP address is banned from the website (usually the website domain) and that specific address is refused permission to access a website.



404 error on Wikipedia

#### **402 Payment Required**

Reserved for future use. The original intention was that this code might be used as part of some form of [digital cash](#) or [micropayment](#) scheme, as proposed for example by GNU Taler<sup>[36]</sup>, but that has not yet happened, and this code is not usually used. [Google Developers API](#) uses this status if a particular developer has exceeded the daily limit on requests.<sup>[37]</sup> Sipgate uses this code if an account does not have sufficient funds to start a call.<sup>[38]</sup>

#### **403 Forbidden**

The request was valid, but the server is refusing action. The user might not have the necessary permissions for a resource, or may need an account of some sort.

#### **404 Not Found**

The requested resource could not be found but may be available in the future. Subsequent requests by the client are permissible.

#### **405 Method Not Allowed**

A request method is not supported for the requested resource; for example, a GET request on a form that requires data to be presented via [POST](#), or a PUT request on a read-only resource.

#### **406 Not Acceptable**

The requested resource is capable of generating only content not acceptable according to the Accept headers sent in the request.<sup>[39]</sup> See [Content negotiation](#).

#### **407 Proxy Authentication Required (RFC 7235)**

The client must first authenticate itself with the [proxy](#).<sup>[40]</sup>

#### **408 Request Timeout**

The server timed out waiting for the request. According to HTTP specifications: "The client did not produce a request within the time that the server was prepared to wait. The client MAY repeat the request without modifications at any later time."<sup>[41]</sup>

#### **409 Conflict**

Indicates that the request could not be processed because of conflict in the current state of the resource, such as an [edit conflict](#) between multiple simultaneous updates.

#### **410 Gone**

Indicates that the resource requested is no longer available and will not be available again. This should be used when a resource has been intentionally removed and the resource should be purged. Upon receiving a 410 status code, the client should not request the resource in the future. Clients such as search engines should remove the resource from their indices.<sup>[42]</sup> Most use cases do not require clients and search engines to purge the resource, and a "404 Not Found" may be used instead.

#### **411 Length Required**

The request did not specify the length of its content, which is required by the requested resource.<sup>[43]</sup>

#### **412 Precondition Failed (RFC 7232)**

The server does not meet one of the preconditions that the requester put on the request.<sup>[44]</sup>

#### **413 Payload Too Large (RFC 7231)**

The request is larger than the server is willing or able to process. Previously called "Request Entity Too Large".<sup>[45]</sup>

#### **414 URI Too Long (RFC 7231)**

The URI provided was too long for the server to process. Often the result of too much data being encoded as a query-string of a GET request, in which case it should be converted to a POST request.<sup>[46]</sup> Called "Request-URI Too Long" previously.<sup>[47]</sup>

#### **415 Unsupported Media Type**

The request entity has a media type which the server or resource does not support. For example, the client uploads an image as image/svg+xml, but the server requires that images use a different format.

#### **416 Range Not Satisfiable (RFC 7233)**

The client has asked for a portion of the file (byte serving), but the server cannot supply that portion. For example, if the client asked for a part of the file that lies beyond the end of the file.<sup>[48]</sup> Called "Requested Range Not Satisfiable" previously.<sup>[49]</sup>

#### **417 Expectation Failed**

The server cannot meet the requirements of the Expect request-header field.<sup>[50]</sup>

#### **418 I'm a teapot (RFC 2324, RFC 7168)**

This code was defined in 1998 as one of the traditional IETF April Fools' jokes, in RFC 2324, Hyper Text Coffee Pot Control Protocol, and is not expected to be implemented by actual HTTP servers. The RFC specifies this code should be returned by teapots requested to brew coffee.<sup>[51]</sup> This HTTP status is used as an Easter egg in some websites, including Google.com.<sup>[52][53]</sup>

#### **421 Misdirected Request (RFC 7540)**

The request was directed at a server that is not able to produce a response<sup>[54]</sup> (for example because of connection reuse).<sup>[55]</sup>

#### **422 Unprocessable Entity (WebDAV; RFC 4918)**

The request was well-formed but was unable to be followed due to semantic errors.<sup>[17]</sup>

#### **423 Locked (WebDAV; RFC 4918)**

The resource that is being accessed is locked.<sup>[17]</sup>

#### **424 Failed Dependency (WebDAV; RFC 4918)**

The request failed because it depended on another request and that request failed (e.g., a PROPPATCH).<sup>[17]</sup>

#### **426 Upgrade Required**

The client should switch to a different protocol such as TLS/1.0, given in the Upgrade header field.<sup>[56]</sup>

#### **428 Precondition Required (RFC 6585)**

The origin server requires the request to be conditional. Intended to prevent the 'lost update' problem, where a client GETs a resource's state, modifies it, and PUTs it back to the server, when meanwhile a third party has modified the state on the server, leading to a conflict."<sup>[57]</sup>

#### **429 Too Many Requests (RFC 6585)**

The user has sent too many requests in a given amount of time. Intended for use with rate-limiting schemes.<sup>[57]</sup>

#### **431 Request Header Fields Too Large (RFC 6585)**

The server is unwilling to process the request because either an individual header field, or all the header fields collectively, are too large.<sup>[57]</sup>

#### **451 Unavailable For Legal Reasons (RFC 7725)**

A server operator has received a legal demand to deny access to a resource or to a set of resources that includes the requested resource.<sup>[58]</sup> The code 451 was chosen as a reference to the novel Fahrenheit 451 (see the Acknowledgements in the RFC).

## **5xx Server errors**

---

The server failed to fulfil a request.<sup>[59]</sup>

Response status codes beginning with the digit "5" indicate cases in which the server is aware that it has encountered an error or is otherwise incapable of performing the request. Except when responding to a HEAD request, the server *should* include an entity containing an explanation of the error situation, and indicate whether it is a temporary or permanent condition. Likewise, user

agents *should* display any included entity to the user. These response codes are applicable to any request method.<sup>[60]</sup>

### **500 Internal Server Error**

A generic error message, given when an unexpected condition was encountered and no more specific message is suitable.<sup>[61]</sup>

### **501 Not Implemented**

The server either does not recognize the request method, or it lacks the ability to fulfil the request. Usually this implies future availability (e.g., a new feature of a web-service API).<sup>[62]</sup>

### **502 Bad Gateway**

The server was acting as a gateway or proxy and received an invalid response from the upstream server.<sup>[63]</sup>

### **503 Service Unavailable**

The server is currently unavailable (because it is overloaded or down for maintenance). Generally, this is a temporary state.<sup>[64]</sup>

### **504 Gateway Timeout**

The server was acting as a gateway or proxy and did not receive a timely response from the upstream server.<sup>[65]</sup>

### **505 HTTP Version Not Supported**

The server does not support the HTTP protocol version used in the request.<sup>[66]</sup>

### **506 Variant Also Negotiates (RFC 2295)**

Transparent content negotiation for the request results in a circular reference.<sup>[67]</sup>

### **507 Insufficient Storage (WebDAV; RFC 4918)**

The server is unable to store the representation needed to complete the request.<sup>[17]</sup>

### **508 Loop Detected (WebDAV; RFC 5842)**

The server detected an infinite loop while processing the request (sent in lieu of 208 Already Reported).

### **510 Not Extended (RFC 2774)**

Further extensions to the request are required for the server to fulfil it.<sup>[68]</sup>

### **511 Network Authentication Required (RFC 6585)**

The client needs to authenticate to gain network access. Intended for use by intercepting proxies used to control access to the network (e.g., "captive portals" used to require agreement to Terms of Service before granting full Internet access via a Wi-Fi hotspot).<sup>[57]</sup>

## **Unofficial codes**

---

The following codes are not specified by any standard.

### **103 Checkpoint**

Used in the resumable requests proposal to resume aborted PUT or POST requests.<sup>[69]</sup>

### **218 This is fine (Apache Web Server)**

Used as a catch-all error condition for allowing response bodies to flow through Apache when ProxyErrorOverride is enabled. When ProxyErrorOverride is enabled in Apache, response bodies that contain a status code of 4xx or 5xx are automatically discarded by Apache in favor of a generic response or a custom response specified by the ErrorDocument directive.<sup>[70]</sup>

### **420 Method Failure (Spring Framework)**

A deprecated response used by the Spring Framework when a method has failed.<sup>[71]</sup>

### **420 Enhance Your Calm (Twitter)**

Returned by version 1 of the Twitter Search and Trends API when the client is being rate limited; versions 1.1 and later use the 429 Too Many Requests response code instead.<sup>[72]</sup>

### **450 Blocked by Windows Parental Controls (Microsoft)**

The Microsoft extension code indicated when Windows Parental Controls are turned on and are blocking access to the requested webpage.<sup>[73]</sup>

### **498 Invalid Token (Esri)**

Returned by ArcGIS for Server. Code 498 indicates an expired or otherwise invalid token.<sup>[74]</sup>

#### **499 Token Required (Esri)**

Returned by ArcGIS for Server. Code 499 indicates that a token is required but was not submitted.<sup>[74]</sup>

#### **509 Bandwidth Limit Exceeded (Apache Web Server/cPanel)**

The server has exceeded the bandwidth specified by the server administrator; this is often used by shared hosting providers to limit the bandwidth of customers.<sup>[75]</sup>

#### **530 Site is frozen**

Used by the Pantheon web platform to indicate a site that has been frozen due to inactivity.<sup>[76]</sup>

#### **598 (Informal convention) Network read timeout error**

Used by some HTTP proxies to signal a network read timeout behind the proxy to a client in front of the proxy.<sup>[77]</sup>

### **Internet Information Services**

Microsoft's Internet Information Services web server expands the 4xx error space to signal errors with the client's request.

#### **440 Login Time-out**

The client's session has expired and must log in again.<sup>[78]</sup>

#### **449 Retry With**

The server cannot honour the request because the user has not provided the required information.<sup>[79]</sup>

#### **451 Redirect**

Used in Exchange ActiveSync when either a more efficient server is available or the server cannot access the users' mailbox.<sup>[80]</sup> The client is expected to re-run the HTTP AutoDiscover operation to find a more appropriate server.<sup>[81]</sup>

### **nginx**

The nginx web server software expands the 4xx error space to signal issues with the client's request.<sup>[82][83]</sup>

#### **444 No Response**

Used internally<sup>[84]</sup> to instruct the server to return no information to the client and close the connection immediately.

#### **494 Request header too large**

Client sent too large request or too long header line.

#### **495 SSL Certificate Error**

An expansion of the 400 Bad Request response code, used when the client has provided an invalid client certificate.

#### **496 SSL Certificate Required**

An expansion of the 400 Bad Request response code, used when a client certificate is required but not provided.

#### **497 HTTP Request Sent to HTTPS Port**

An expansion of the 400 Bad Request response code, used when the client has made a HTTP request to a port listening for HTTPS requests.

#### **499 Client Closed Request**

Used when the client has closed the request before the server could send a response.

### **Cloudflare**

Cloudflare's reverse proxy service expands the 5xx series of errors space to signal issues with the origin server.<sup>[85]</sup>

#### **520 Unknown Error**

The 520 error is used as a "catch-all response for when the origin server returns something unexpected", listing connection resets, large headers, and empty or invalid responses as

common triggers.

#### 521 Web Server Is Down

The origin server has refused the connection from Cloudflare.

#### 522 Connection Timed Out

Cloudflare could not negotiate a TCP handshake with the origin server.

#### 523 Origin Is Unreachable

Cloudflare could not reach the origin server; for example, if the DNS records for the origin server are incorrect.

#### 524 A Timeout Occurred

Cloudflare was able to complete a TCP connection to the origin server, but did not receive a timely HTTP response.

#### 525 SSL Handshake Failed

Cloudflare could not negotiate a SSL/TLS handshake with the origin server.

#### 526 Invalid SSL Certificate

Cloudflare could not validate the SSL/TLS certificate that the origin server presented.

#### 527 Railgun Error

Error 527 indicates that the request timed out or failed after the WAN connection had been established.<sup>[86]</sup>

#### 530 Origin DNS Error

Error 530 indicates that the requested host name could not be resolved on the Cloudflare network to an origin server.<sup>[87]</sup>

## See also

---

- Custom error pages
- List of FTP server return codes
- List of HTTP header fields
- Common Log Format

## Notes

---

1. Italicised words and phrases such as *must* and *should* represent interpretation guidelines as given by RFC 2119

## References

---

1. "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content" (<https://tools.ietf.org/html/rfc7231>). *IETF*. Retrieved 16 December 2017.
2. "Hypertext Transfer Protocol (HTTP) Status Code Registry" (<http://www.iana.org/assignments/http-status-codes/>). *iana.org*. Retrieved January 8, 2015.
3. "The HTTP status codes in IIS 7.0" (<http://support.microsoft.com/kb/943891/>). *Microsoft*. July 14, 2009. Retrieved April 1, 2009.
4. "10 Status Code Definitions" (<http://www.w3.org/Protocols/rfc2616/rfc2616-sec10.html>). *W3*. Retrieved 16 October 2015.
5. "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content - 5.1.1. Expect" (<https://tools.ietf.org/html/rfc7231#section-5.1.1>). Retrieved 27 September 2017.
6. "101" (<http://httpstatus.es/101>). *httpstatus*. Retrieved 16 October 2015.
7. Goland, Yaronn; Whitehead, Jim; Faizi, Asad; Carter, Steve R.; Jensen, Del (February 1999). *HTTP Extensions for Distributed Authoring – WEBDAV* (<https://tools.ietf.org/html/rfc2518>). *IETF*. doi:10.17487/RFC2518 (<http://dx.doi.org/10.17487%2FRFC2518>). RFC 2518. <https://tools.ietf.org/html/rfc2518>. Retrieved October 24, 2009.
8. Oku, Kazuho (December 2017). *An HTTP Status Code for Indicating Hints* (<https://tools.ietf.org/html/rfc8297>). *IETF*. doi:10.17487/RFC8297 (<http://dx.doi.org/10.17487%2FRFC8297>). RFC 8297. <https://tools.ietf.org/html/rfc8297>. Retrieved December 20, 2017.



9. "200 OK" (<https://tools.ietf.org/html/rfc2616#section-10.2.1>). *Hypertext Transfer Protocol -- HTTP/1.1* (<https://tools.ietf.org/html/rfc2616>). IETF. June 1999. sec. 10.2.1. doi:10.17487/RFC2616 (<http://dx.doi.org/10.17487%2FRFC2616>). RFC 2616. <https://tools.ietf.org/html/rfc2616#section-10.2.1>. Retrieved August 30, 2016.
10. Stewart, Mark; djna. "Create request with POST, which response codes 200 or 201 and content" (<https://stackoverflow.com/questions/1860645/create-request-with-post-which-response-codes-200-or-201-and-content>). *Stack Overflow*. Retrieved 16 October 2015.
11. "202" (<http://httpstatus.es/202>). *httpstatus*. Retrieved 16 October 2015.
12. "RFC 7231, Section 6.3.4" (<https://tools.ietf.org/html/rfc7231#section-6.3.4>).
13. "RFC 7230, Section 5.7.2" (<https://tools.ietf.org/html/rfc7230#section-5.7.2>).
14. Simmance, Chris. "Server Response Codes And What They Mean" (<http://www.koozai.com/blog/analytics/server-response-codes-and-what-they-mean/>). *koozai*. Retrieved 16 October 2015.
15. ikitommi; Deraen. "metosin/ring-http-response" (<https://github.com/metosin/ring-http-response/blob/master/dev/user.clj>). *GitHub*. Retrieved 16 October 2015.
16. "diff --git a/linkchecker.module b/linkchecker.module" (<https://www.drupal.org/files/issues/linkchecker-report-descriptions-2403161-1.patch>). *Drupal*. Retrieved 16 October 2015.
17. Dusseault, Lisa, ed. (June 2007). *HTTP Extensions for Web Distributed Authoring and Versioning (WebDAV)* (<https://tools.ietf.org/html/rfc4918>). IETF. doi:10.17487/RFC4918 (<http://dx.doi.org/10.17487%2FRFC4918>). RFC 4918. <https://tools.ietf.org/html/rfc4918>. Retrieved October 24, 2009.
18. *Delta encoding in HTTP* (<https://tools.ietf.org/html/rfc3229>). IETF. January 2002. doi:10.17487/RFC3229 (<http://dx.doi.org/10.17487%2FRFC3229>). RFC 3229. <https://tools.ietf.org/html/rfc3229>. Retrieved February 25, 2011.
19. "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content" (<http://tools.ietf.org/html/rfc7231#section-6.4>). *IETF*. Retrieved 13 February 2016.
20. "300" (<http://httpstatus.es/300>). *httpstatus*. Retrieved 16 October 2015.
21. "301" (<http://httpstatus.es/301>). *httpstatus*. Retrieved 16 October 2015.
22. Berners-Lee, Tim; Fielding, Roy T.; Nielsen, Henrik Frystyk (May 1996). *Hypertext Transfer Protocol – HTTP/1.0* (<https://tools.ietf.org/html/rfc1945>). IETF. doi:10.17487/RFC1945 (<http://dx.doi.org/10.17487%2FRFC1945>). RFC 1945. <https://tools.ietf.org/html/rfc1945>. Retrieved October 24, 2009.
23. "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content, Section 6.4" (<http://tools.ietf.org/html/rfc7231#section-6.4>). *IETF*. Retrieved June 12, 2014.
24. "Reference of method redirect\_to in Ruby Web Framework "Ruby on Rails". It states: The redirection happens as a "302 Moved" header unless otherwise specified" ([http://api.rubyonrails.org/classes/ActionController/Redirecting.html#method-i-redirect\\_to](http://api.rubyonrails.org/classes/ActionController/Redirecting.html#method-i-redirect_to)). Retrieved June 30, 2012.
25. "303" (<http://httpstatus.es/303>). *httpstatus*. Retrieved 16 October 2015.
26. "304 Not Modified" (<https://developer.mozilla.org/en-US/docs/Web/HTTP/Status/304>). *Mozilla Developer Network*. Retrieved 2017-07-06.
27. "Mozilla Bugzilla Bug 187996: Strange behavior on 305 redirect" ([https://bugzilla.mozilla.org/show\\_bug.cgi?id=187996](https://bugzilla.mozilla.org/show_bug.cgi?id=187996)). March 3, 2003. Retrieved May 21, 2009.
28. "Mozilla Bugzilla Bug 187996: Strange behavior on 305 redirect, comment 13" ([https://bugzilla.mozilla.org/show\\_bug.cgi?id=187996#c13](https://bugzilla.mozilla.org/show_bug.cgi?id=187996#c13)). March 3, 2003. Retrieved May 21, 2009.
29. Cohen, Josh. "HTTP/1.1 305 and 306 Response Codes" (<https://tools.ietf.org/html/draft-cohen-http-305-306-responses-00>). HTTP Working Group.
30. "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content, Section 6.4.7 307 Temporary Redirect" (<https://tools.ietf.org/html/rfc7231#section-6.4.7>). IETF. 2014. Retrieved September 20, 2014.
31. "The Hypertext Transfer Protocol Status Code 308 (Permanent Redirect)" (<https://tools.ietf.org/html/rfc7538>). Internet Engineering Task Force. April 2015. Retrieved 2015-04-06.
32. "E Explanation of Failure Codes" ([https://docs.oracle.com/cd/E14269\\_01/doc.451/e14266/result\\_codes.htm](https://docs.oracle.com/cd/E14269_01/doc.451/e14266/result_codes.htm)). *Oracle*. Retrieved 16 October 2015.
33. "RFC7231 on code 400" (<https://tools.ietf.org/html/rfc7231#section-6.5.1>). *Tools.ietf.org*. Retrieved January 8, 2015.
34. "401" (<http://httpstatus.es/401>). *httpstatus*. Retrieved 16 October 2015.
35. "RFC7235 on code 401" (<https://tools.ietf.org/html/rfc7235#section-3.1>). *Tools.ietf.org*. Retrieved February 8, 2015.

36. "The GNU Taler tutorial for PHP Web shop developers 0.4.0" (<https://docs.taler.net/merchant/frontend/php/html/tutorial.html#Headers-for-HTTP-402>). *docs.taler.net*. Retrieved 2017-10-29.
37. "Google API Standard Error Responses" ([https://developers.google.com/doubleclick-search/v2/standard-error-responses#PAYMENT\\_REQUIRED](https://developers.google.com/doubleclick-search/v2/standard-error-responses#PAYMENT_REQUIRED)). *Google*. 2016. Retrieved June 21, 2017.
38. "Sipgate API Documentation" (<https://api.sipgate.com/v2/doc#operations-sessions-newCall>). Retrieved July 10, 2018.
39. Singh, Prabhat; user1740567. "Spring 3.x JSON status 406 "characteristics not acceptable according to the request "accept" headers ()"" (<https://stackoverflow.com/questions/12865093/spring-3-x-json-status-406-characteristics-not-acceptable-according-to-the-requ>). *Stack Overflow*. Retrieved 16 October 2015.
40. "407" (<http://httpstatus.es/407>). *httpstatus*. Retrieved 16 October 2015.
41. "408" (<http://httpstatus.es/408>). *httpstatus*. Retrieved 16 October 2015.
42. "Does Google treat 404 and 410 status codes differently? (Youtube)" (<https://www.youtube.com/watch?v=xp5Nf8ANfOw>). *Google*. 2014. Retrieved February 4, 2015.
43. "List of HTTP status codes" ([https://books.google.co.uk/books?id=J1gb2eb-NuEC&pg=PA197&lpg=PA197&dq=The+request+did+not+specify+the+length+of+its+content,+which+is+required+by+the+requested+resource.&source=bl&ots=o4rBopF2G4&sig=f\\_IFpmPcMqrSBLxhhf0yVVPedYU&hl=en&sa=X&ved=0CDEQ6AEwA2oVChMIo6KixN3HyAIVRhkeCh3xAw04#v=onepage&q=The%20request%20did%20not%20specify%20the%20length%20of%20its%20content%2C%20which%20is%20required%20by%20the%20requested%20resource.&f=false](https://books.google.co.uk/books?id=J1gb2eb-NuEC&pg=PA197&lpg=PA197&dq=The+request+did+not+specify+the+length+of+its+content,+which+is+required+by+the+requested+resource.&source=bl&ots=o4rBopF2G4&sig=f_IFpmPcMqrSBLxhhf0yVVPedYU&hl=en&sa=X&ved=0CDEQ6AEwA2oVChMIo6KixN3HyAIVRhkeCh3xAw04#v=onepage&q=The%20request%20did%20not%20specify%20the%20length%20of%20its%20content%2C%20which%20is%20required%20by%20the%20requested%20resource.&f=false)). *Google Books*. Retrieved 16 October 2015.
44. Kowser; Patel, Amit. "REST response code for invalid data" (<https://stackoverflow.com/questions/6123425/rest-response-code-for-invalid-data>). *Stack Overflow*. Retrieved 16 October 2015.
45. "RFC2616 on status 413" (<https://tools.ietf.org/html/rfc2616#section-10.4.14>). *Tools.ietf.org*. Retrieved November 11, 2015.
46. user27828. "GET Request - Why is my URI so long?" (<https://stackoverflow.com/questions/20157706/get-request-why-is-my-uri-so-long>). *Stack Overflow*. Retrieved 16 October 2015.
47. "RFC2616 on status 414" (<https://tools.ietf.org/html/rfc2616#section-10.4.15>). *Tools.ietf.org*. Retrieved November 11, 2015.
48. Sigler, Chris. "416 Requested Range Not Satisfiable" (<https://web.archive.org/web/20151022220744/http://getstatuscode.com/416>). *GetStatusCode*. Archived from the original (<http://getstatuscode.com/416>) on October 22, 2015. Retrieved October 16, 2015.
49. "RFC2616 on status 416" (<https://tools.ietf.org/html/rfc2616#section-10.4.17>). *Tools.ietf.org*. Retrieved November 11, 2015.
50. TheDeadLike. "HTTP/1.1 Status Codes 400 and 417, cannot choose which" (<http://serverfault.com/questions/433470/http-1-1-status-codes-400-and-417-cannot-choose-which>). *serverFault*. Retrieved 16 October 2015.
51. Larry Masinter (1 April 1998). *Hyper Text Coffee Pot Control Protocol (HTCPCP/1.0)* (<https://tools.ietf.org/html/rfc2324>). doi:10.17487/RFC2324 (<http://dx.doi.org/10.17487%2FRFC2324>). RFC 2324. <https://tools.ietf.org/html/rfc2324>.
52. Barry Schwartz (26 August 2014). "New Google Easter Egg For SEO Geeks: Server Status 418, I'm A Teapot" (<http://searchengineland.com/new-google-easter-egg-seo-geeks-server-status-418-im-teapot-201739>). *Search Engine Land*.
53. *Google's Teapot* (<https://www.google.com/teapot>)
54. "Hypertext Transfer Protocol version 2" (<https://http2.github.io/http2-spec/#MisdirectedRequest>). March 2015. Retrieved April 25, 2015.
55. "9.1.1. Connection Reuse" (<https://tools.ietf.org/html/rfc7540#section-9.1.1>). *RFC7540*. May 2015.
56. Khare, R; Lawrence, S. "Upgrading to TLS Within HTTP/1.1" (<https://tools.ietf.org/html/rfc2817>). *IETF. Network Working Group*. Retrieved 16 October 2015.
57. Nottingham, M.; Fielding, R. (April 2012). "RFC 6585 – Additional HTTP Status Codes" (<http://tools.ietf.org/html/rfc6585>). *Request for Comments. Internet Engineering Task Force*. Retrieved May 1, 2012.
58. Bray, T. (February 2016). "An HTTP Status Code to Report Legal Obstacles" (<https://tools.ietf.org/html/rfc7725>). *ietf.org*. Retrieved 7 March 2015.
59. "Server Error Codes" (<http://www.csgnetwork.com/servererrors.html>). *CSGNetwork.com*. Retrieved 16 October 2015.

60. mrGott. "HTTP Status Codes To Handle Errors In Your API" (<https://web.archive.org/web/20150930030217/http://blog.mrgott.com/misc/5-http-status-codes-to-handle-errors-in-your-api>). *mrGott*. Archived from the original (<http://blog.mrgott.com/misc/5-http-status-codes-to-handle-errors-in-your-api>) on September 30, 2015. Retrieved October 16, 2015.
61. Fisher, Tim. "500 Internal Server Error" (<https://www.lifewire.com/500-internal-server-error-explained-2622938>). *Lifewire*. Retrieved 22 February 2017.
62. "HTTP Error 501 Not implemented" (<http://www.checkupdown.com/status/E501.html>). *Check Up Down*. Retrieved 22 February 2017.
63. Fisher, Tim. "502 Bad Gateway" (<https://www.lifewire.com/502-bad-gateway-error-explained-2622939>). *Lifewire*. Retrieved 22 February 2017.
64. alex. "What is the correct HTTP status code to send when a site is down for maintenance?" (<https://stackoverflow.com/questions/2786595/what-is-the-correct-http-status-code-to-send-when-a-site-is-down-for-maintenance>). *Stack Overflow*. Retrieved 16 October 2015.
65. "HTTP Error 504 Gateway timeout" (<http://www.checkupdown.com/status/E504.html>). *Check Up Down*. Retrieved 16 October 2015.
66. "HTTP Error 505 - HTTP version not supported" (<http://www.checkupdown.com/status/E505.html>). *Check Up Down*. Retrieved 16 October 2015.
67. Holtman, Koen; Mutz, Andrew H. (March 1998). *Transparent Content Negotiation in HTTP* (<https://tools.ietf.org/html/rfc2295>). IETF. doi:10.17487/RFC2295 (<http://dx.doi.org/10.17487%2FRFC2295>). RFC 2295. <https://tools.ietf.org/html/rfc2295>. Retrieved October 24, 2009.
68. Nielsen, Henrik Frystyk; Leach, Paul; Lawrence, Scott (February 2000). *An HTTP Extension Framework* (<https://tools.ietf.org/html/rfc2774>). IETF. doi:10.17487/RFC2774 (<http://dx.doi.org/10.17487%2FRFC2774>). RFC 2774. <https://tools.ietf.org/html/rfc2774>. Retrieved October 24, 2009.
69. "ResumableHttpRequestsProposal" (<https://web.archive.org/web/20151013212135/http://code.google.com/p/gears/wiki/ResumableHttpRequestsProposal>). Archived from the original (<http://code.google.com/p/gears/wiki/ResumableHttpRequestsProposal>) on October 13, 2015. Retrieved 2017-03-08.
70. "Apache ProxyErrorOverride" ([https://httpd.apache.org/docs/2.4/mod/mod\\_proxy.html#ProxyErrorOverride](https://httpd.apache.org/docs/2.4/mod/mod_proxy.html#ProxyErrorOverride)). Retrieved 7 June 2018.
71. "Enum HttpStatus" (<https://docs.spring.io/spring/docs/current/javadoc-api/org/springframework/http/HttpStatus.html>). *Spring Framework*. org.springframework.http. Retrieved 16 October 2015.
72. "Twitter Error Codes & Responses" (<https://developer.twitter.com/en/docs/basics/response-codes>). *Twitter*. 2014. Retrieved January 20, 2014.
73. "Screenshot of error page" ([https://public.bn1.livefilestore.com/y1pJXeg\\_sNOONKwMraE-xmZFWafZF6COAKnyfgc-2ykUof743pV4XuRqm14pj-b\\_yK8Km4sfSR6mU5OhLrupZ8dFg](https://public.bn1.livefilestore.com/y1pJXeg_sNOONKwMraE-xmZFWafZF6COAKnyfgc-2ykUof743pV4XuRqm14pj-b_yK8Km4sfSR6mU5OhLrupZ8dFg)) (bmp). Retrieved October 11, 2009.
74. "Using token-based authentication" ([http://help.arcgis.com/en/arcgisserver/10.0/apis/soap/index.htm#Using\\_token\\_authentication.htm](http://help.arcgis.com/en/arcgisserver/10.0/apis/soap/index.htm#Using_token_authentication.htm)). *ArcGIS Server SOAP SDK*.
75. "HTTP Error Codes and Quick Fixes" (<https://documentation.cpanel.net/display/CKB/HTTP+Error+Codes+and+Quick+Fixes#HTTPErrorCodesandQuickFixes-509BandwidthLimitExceeded>). Docs.cpanel.net. Retrieved October 15, 2015.
76. "Platform Considerations | Pantheon Docs" (<https://pantheon.io/docs/platform-considerations/>). *pantheon.io*.
77. <http://www.injosoftware.se>, Injosoftware AB., "HTTP status codes - ascii-code.com" (<http://www.ascii-code.com/http-status-codes.php>). *www.ascii-code.com*. Retrieved 2016-12-23.
78. "Error message when you try to log on to Exchange 2007 by using Outlook Web Access: "440 Login Time-out"" (<https://support.microsoft.com/en-us/help/941201/>). Microsoft. 2010. Retrieved November 13, 2013.
79. "2.2.6 449 Retry With Status Code" ([http://msdn.microsoft.com/en-us/library/dd891478\(PROT.10\).aspx](http://msdn.microsoft.com/en-us/library/dd891478(PROT.10).aspx)). Microsoft. 2009. Retrieved October 26, 2009.
80. "MS-ASCMD, Section 3.1.5.2.2" (<http://msdn.microsoft.com/en-us/library/gg651019>). Msdn.microsoft.com. Retrieved January 8, 2015.
81. "Ms-oxdisco" (<http://msdn.microsoft.com/en-us/library/cc433481>). Msdn.microsoft.com. Retrieved January 8, 2015.
82. "ngx\_http\_request.h" ([http://lxr.nginx.org/source/src/http/ngx\\_http\\_request.h](http://lxr.nginx.org/source/src/http/ngx_http_request.h)). *nginx 1.9.5 source code*. nginx inc. Retrieved 2016-01-09.

83. ["ngx\\_http\\_special\\_response.c"](http://lxr.nginx.org/source/src/http/nginx_http_special_response.c) ([http://lxr.nginx.org/source/src/http/nginx\\_http\\_special\\_response.c](http://lxr.nginx.org/source/src/http/nginx_http_special_response.c)). *nginx 1.9.5 source code*. nginx inc. Retrieved 2016-01-09.
84. ["return" directive](http://nginx.org/en/docs/http/nginx_http_rewrite_module.html#return) ([http://nginx.org/en/docs/http/nginx\\_http\\_rewrite\\_module.html#return](http://nginx.org/en/docs/http/nginx_http_rewrite_module.html#return)) ([http\\_rewrite module](#)) documentation.
85. ["Troubleshooting: Error Pages"](https://support.cloudflare.com/hc/en-us/sections/200820298-Error-Pages) (<https://support.cloudflare.com/hc/en-us/sections/200820298-Error-Pages>). [Cloudflare](#). Retrieved 2016-01-09.
86. ["Railgun Listener to Origin Error"](https://support.cloudflare.com/hc/en-us/articles/217891268-527-Railgun-Listener-to-Origin-Error) (<https://support.cloudflare.com/hc/en-us/articles/217891268-527-Railgun-Listener-to-Origin-Error>). [Cloudflare](#). Retrieved 2016-10-12.
87. ["Error 1016 - Origin DNS error"](https://support.cloudflare.com/hc/en-us/articles/234979888-Error-1016-Origin-DNS-error) (<https://support.cloudflare.com/hc/en-us/articles/234979888-Error-1016-Origin-DNS-error>). [Cloudflare](#).

## External links

---

- [Hypertext Transfer Protocol \(HTTP\) Status Code Registry](http://www.iana.org/assignments/http-status-codes/http-status-codes.xhtml) (<http://www.iana.org/assignments/http-status-codes/http-status-codes.xhtml>)
  - [Microsoft Knowledge Base: MSKB943891: The HTTP status codes in IIS 7.0](http://support.microsoft.com/kb/943891/) (<http://support.microsoft.com/kb/943891/>)
- 

Retrieved from "[https://en.wikipedia.org/w/index.php?title=List\\_of\\_HTTP\\_status\\_codes&oldid=849770321](https://en.wikipedia.org/w/index.php?title=List_of_HTTP_status_codes&oldid=849770321)"

---

**This page was last edited on 11 July 2018, at 06:50 (UTC).**

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.