

AutoML FraudShield – V3 (Revised): SRS + TDD + Deployment Manifest

0. Project Overview

- **Project Name:** AutoML FraudShield V3 (The "Real-Time Velocity" Upgrade)
- **Role:** Principal AI Architect / Streaming Data Engineer
- **V2 Recap:** Delivered a production-grade batch system with Explainability (SHAP), Drift Monitoring, and Auto-Retraining using supervised XGBoost.
- **V3 Goal:** Transition from "Reactive Batch" to "Proactive Real-Time" detection. We will implement the streaming infrastructure to catch velocity attacks and unsupervised anomalies in real-time, while establishing the data structures for future multi-tenancy.
- **Philosophy:** "Velocity First." We prioritize the correctness of the streaming data path and hybrid scoring before adding complex network intelligence (GNNs) in V4.

Primary Architecture Changes (V2 to V3)

1. **Ingestion:** Batch CSV to **Streaming Pub/Sub + Dataflow**.
 2. **Features:** Daily Aggregates to **Sliding Window Aggregates (10m)**.
 3. **Model:** Single XGBoost to **Hybrid Ensemble (XGBoost + Isolation Forest)**.
 4. **Tenancy:** Single Tenant to **Schema-Level Multi-Tenancy**.
-

1. Scope & Requirements (SRS)

1.1 In-Scope (V3)

1. **Streaming Infrastructure:** Deploy a Dataflow (Apache Beam) pipeline to ingest raw events and compute windowed features.
2. **Real-Time Feature Store:** Materialize sliding window aggregates (e.g., `txn_count_10m`) to Vertex AI Feature Store (Online) with strict time semantics.
3. **Hybrid Model Serving:** Implement a Custom Prediction Routine (CPR) container that runs XGBoost (Supervised) and Isolation Forest (Unsupervised) sequentially.
4. **Schema-Level Multi-Tenancy:** Add `tenant_id` to all APIs, logs, storage, and feature lookups to prepare for SaaS scale.

1.2 Out-of-Scope (Deferred to V4)

- **Graph Neural Networks (GNN):** No graph embeddings or neighbor aggregations in this phase.
- **Active Feedback Loop:** No "Confirm Fraud" dashboard write-backs; retraining remains batch-based on historical data.
- **Hard Infrastructure Isolation:** No separate GCP projects or IAM namespaces per tenant.

1.3 Functional Requirements

1.3.1 Real-Time Data (FR-S)

- **FR-S1 – Ingestion:** The system **MUST** accept JSON transaction events via `fraudshield-raw-events` Pub/Sub topic.
- **FR-S2 – Windowing:** A Dataflow job **MUST** compute **Sliding Windows** (Size: 10m, Period: 1m) for velocity features.
- **FR-S3 – Time Semantics:** The pipeline **MUST** handle late data with an **Allowed Lateness of 5 minutes**. Data arriving after this threshold is dropped.

1.3.2 Hybrid Intelligence (FR-I)

- **FR-I1 – Unsupervised Detection:** The training pipeline **MUST** train an Isolation Forest on non-fraud data to learn "normality."
- **FR-I2 – Ensemble Logic:** The Scoring API **MUST** return a weighted score:
$$FinalScore = (w_1 \times P_{XGB}) + (w_2 \times S_{IsoForest})$$

(Default weights: $w_1=0.8$, $w_2=0.2$, normalized to 0-1).

1.3.3 Operations (FR-O)

- **FR-O1 – Schema Isolation:** Every API request and database row **MUST** contain a `tenant_id`. Feature Store entity IDs **MUST** be constructed as `tenant_id#entity_id`.
- **FR-O2 – Multi-Model Drift:** The monitoring system **MUST** track:
 - **PSI** for XGBoost input features.
 - **Mean Anomaly Score** for Isolation Forest (to detect global behavior shifts).

1.4 Non-Functional Requirements (NFR)

- **NFR-1 – Latency Budget (P95):** Total API response time \leq **300ms**.
 - Network: 20ms
 - Feature Fetch: 50ms
 - Ensemble Inference: 80ms
 - Overhead/Buffer: 150ms
 - **NFR-2 – Data Freshness:** Streaming features **MUST** be available in the Online Store \leq **60 seconds** after the event is published to Pub/Sub.
-

2. High-Level Architecture (System View)

2.1 Component Diagram

2.2 Data Flow (The "Fast Path")

1. **Event:** Client publishes transaction JSON (inc. `tenant_id`) to Pub/Sub.
2. **Process:** Dataflow job:
 - Reads stream.
 - Assigns Event Time timestamps.
 - Groups by `tenant_id` + `card_id`.

- Calculates **count**, **sum** over 10m sliding window.
 - 3. **Materialize**: Writes result to Vertex AI Feature Store (Online).
 - 4. **Score**: Client calls API `/v1/score`.
 - 5. **Fetch**: API fetches fresh **txn_count_10m** + static features.
 - 6. **Predict**: Vertex Endpoint runs CPR (XGB + IsoForest).
 - 7. **Respond**: Returns Score + Risk Band.
-

3. Detailed Design (TDD)

3.1 Streaming Pipeline (Dataflow / Apache Beam)

- **Input**: **fraudshield-raw-sub**
- **Window Configuration**:
 - Type: **SlidingWindows(size=600s, period=60s)**
 - Trigger: **AfterWatermark(early=AfterProcessingTime(delay=10s), late=AfterCount(1))**
 - Allowed Lateness: **300s** (5 minutes)
- **Deduplication**:
 - Key: **transaction_id**
 - State: Bloom filter or StateId within the window to prevent double-counting retries.
- **Output Sink**: Vertex AI Feature Store (**write_feature_values**).

3.2 Hybrid Model Container (CPR)

We replace the standard XGBoost container with a **Custom Prediction Routine**.

- **Artifacts**:
 - **model.bst** (XGBoost)
 - **isolation_forest.joblib** (Sklearn)
- **Predictor Logic (**predictor.py**)**:


```
Python
def predict(self, instances):
```

 - `# 1. Preprocess`
 - `# 2. Thread A: XGBoost Probability`
 - `prob_xgb = self.xgb_model.predict_proba(instances)[: , 1]`
 - `# 3. Thread B: Isolation Forest Score (Normalized)`
 - `# IsoForest returns -1 (anomaly) to 1 (normal). We invert and normalize to 0-1.`
 - `raw_iso = self.iso_model.decision_function(instances)`
 - `prob_iso = self.normalize_anomaly_score(raw_iso)`
 - `# 4. Weighted Ensemble`
 - `final_score = (0.8 * prob_xgb) + (0.2 * prob_iso)`

- return final_score.tolist()
-

3.3 Training Pipeline Updates

The training pipeline now produces *two* artifacts.

- **Step 1:** Load Data (Filter by `tenant_id` if specific model, or global).
- **Step 2:** Split Data.
 - *Supervised Set:* Labeled transactions.
 - *Unsupervised Set:* All transactions (ignoring labels) for IsoForest training.
- **Step 3:** Train XGBoost (Optimize for AUC).
- **Step 4:** Train Isolation Forest (Optimize for outlaw density).
- **Step 5:** Upload both to Vertex Model Registry as a single `Model` resource (using the Custom Container).

3.4 API Schema Updates

- **Request Header:** `X-Tenant-ID` (Required).
 - **Feature Lookup:**
 - Key Construction: `entity_id = f"{tenant_id}#{customer_id}"`
 - This ensures Tenant A cannot access Tenant B's feature history.
-

4. Deployment Manifest (DM)

4.1 Infrastructure Resources (Terraform)

- **Pub/Sub:**
 - `fraudshield-raw-events` (Topic)
 - `fraudshield-raw-sub` (Subscription, Ack Deadline: 60s)
- **Dataflow:**
 - Service Account: `fraudshield-dataflow-sa`
 - IAM: `roles/dataflow.worker`, `roles/aiplatform.user` (for Feature Store write)
 - Bucket: `gs://fraudshield-dataflow-temp-{env}`
- **Vertex AI:**
 - Feature Store: Add `txn_count_10m` (INT64), `txn_sum_10m` (FLOAT).
 - Endpoint: `fraudshield-hybrid-endpoint`

4.2 Repository Structure (V3)

Plaintext

- `fraudshield-v3/`
- | — `streaming/` # [NEW]
- | | — `pipeline.py` # Beam Logic
- | | — `setup.py` # Worker dependencies

- | └─ run.sh # Submission script
- | ── models/
- | └─ ensemble_cpr/ # [NEW]
- | └─ predictor.py # Hybrid Logic
- | └─ requirements.txt
- | └─ Dockerfile
- | ── api/ # Updated for Tenant ID
- | ── infra/ # Updated Terraform
- | ── pipelines/ # Training (produces 2 artifacts)

4.3 Deployment Strategy

1. **Infrastructure:** [terraform apply](#) to create Pub/Sub and Feature Store updates.
 2. **Streaming:** Submit Dataflow job. Verify watermark progression and Feature Store writes.
 3. **Training:** Run pipeline to generate initial XGB+IsoForest artifacts.
 4. **Serving:** Deploy CPR container to Vertex Endpoint.
 5. **Cutover:** Update API to point to new Endpoint and require [tenant_id](#).
-

5. Roadmap Check

- **V3 (Current):** Streaming Velocity, Hybrid Model, Schema Multi-tenancy.
- **V4 (Next):** Graph Neural Networks, Active Feedback Loop, Hard Isolation.