

## 2-more\_exercises

September 4, 2019

### 1 Python review: More exercises

This notebook continues the review of Python basics. A key concept is that of a *nested* data structure. For example, the first code cell will define a 2-D "array" as a list of lists.

Consider the following dataset of exam grades, organized as a 2-D table and stored in Python as a "list of lists" under the variable name, `grades`.

```
In [1]: grades = [  
    # First line is descriptive header. Subsequent lines hold data  
    ['Student', 'Exam 1', 'Exam 2', 'Exam 3'],  
    ['Thorny', '100', '90', '80'],  
    ['Mac', '88', '99', '111'],  
    ['Farva', '45', '56', '67'],  
    ['Rabbit', '59', '61', '67'],  
    ['Ursula', '73', '79', '83'],  
    ['Foster', '89', '97', '101']  
]  
  
grades
```

```
Out[1]: [['Student', 'Exam 1', 'Exam 2', 'Exam 3'],  
        ['Thorny', '100', '90', '80'],  
        ['Mac', '88', '99', '111'],  
        ['Farva', '45', '56', '67'],  
        ['Rabbit', '59', '61', '67'],  
        ['Ursula', '73', '79', '83'],  
        ['Foster', '89', '97', '101']]
```

**Exercise 0** (students\_test: 1 point). Write some code that computes a new list named `students[:]`, which holds the names of the students as they from "top to bottom" in the table.

```
In [2]: ###  
    ### YOUR CODE HERE  
    ###  
    students=list()  
    for i in range(1,len(grades)):  
        students.append(grades[i][0])
```

```
In [3]: # `students_test`: Test cell
print(students)
assert type(students) is list
assert students == ['Thorny', 'Mac', 'Farva', 'Rabbit', 'Ursula', 'Foster']
print("\n(Passed!)")
```

```
['Thorny', 'Mac', 'Farva', 'Rabbit', 'Ursula', 'Foster']
```

(Passed!)

**Exercise 1** (assignments\_test: 1 point). Write some code to compute a new list named `assignments[:]`, to hold the names of the class assignments. (These appear in the descriptive header element of grades.)

```
In [4]: ###
      ### YOUR CODE HERE
      ###
      assignments=list()
      for i in range(1,len(grades[1])):
          assignments.append(grades[0][i])
```

```
In [5]: # `assignments_test`: Test cell
print(assignments)
assert type(assignments) is list
assert assignments == ['Exam 1', 'Exam 2', 'Exam 3']
print("\n(Passed!)")
```

```
['Exam 1', 'Exam 2', 'Exam 3']
```

(Passed!)

**Exercise 2** (grade\_lists\_test: 1 point). Write some code to compute a new *dictionary*, named `grade_lists`, that maps names of students to *lists* of their exam grades. The grades should be converted from strings to integers. For instance, `grade_lists['Thorny'] == [100, 90, 80]`.

```
In [6]: # Create a dict mapping names to lists of grades.
      ###
      ### YOUR CODE HERE
      ###
      grade_lists={}
      for i in range(1,len(grades)):
          grade_lists[grades[i][0]]=list([int(grades[i][1]),int(grades[i][2]),int(grades[i][3])])
```

```
In [7]: # `grade_lists_test`: Test cell
print(grade_lists)
assert type(grade_lists) is dict, "Did not create a dictionary."
assert len(grade_lists) == len(grades)-1, "Dictionary has the wrong number of entries."
```

```

assert {'Thorny', 'Mac', 'Farva', 'Rabbit', 'Ursula', 'Foster'} == set(grade_lists.keys)
assert grade_lists['Thorny'] == [100, 90, 80], 'Wrong grades for: Thorny'
assert grade_lists['Mac'] == [88, 99, 111], 'Wrong grades for: Mac'
assert grade_lists['Farva'] == [45, 56, 67], 'Wrong grades for: Farva'
assert grade_lists['Rabbit'] == [59, 61, 67], 'Wrong grades for: Rabbit'
assert grade_lists['Ursula'] == [73, 79, 83], 'Wrong grades for: Ursula'
assert grade_lists['Foster'] == [89, 97, 101], 'Wrong grades for: Foster'
print("\n(Passed!)")

```

```
{'Thorny': [100, 90, 80], 'Mac': [88, 99, 111], 'Farva': [45, 56, 67], 'Rabbit': [59, 61, 67],
```

```
(Passed!)
```

**Exercise 3** (grade\_dicts\_test: 2 points). Write some code to compute a new dictionary, grade\_dicts, that maps names of students to *dictionaries* containing their scores. Each entry of this scores dictionary should be keyed on assignment name and hold the corresponding grade as an integer. For instance, grade\_dicts['Thorny']['Exam 1'] == 100.

```

In [8]: # Create a dict mapping names to dictionaries of grades.
####
### YOUR CODE HERE
####
# `grade_lists_test`: Test cell
grade_dicts={}
for i in range(1,len(grades)):
    grade_dicts[grades[i][0]]=dict(zip(('Exam 1', 'Exam 2', 'Exam 3'),(int(grades[i][1]),
print(grade_dicts['Foster']['Exam 1'])

```

89

```

In [9]: # `grade_dicts_test`: Test cell
print(grade_dicts)
assert type(grade_dicts) is dict, "Did not create a dictionary."
assert len(grade_dicts) == len(grades)-1, "Dictionary has the wrong number of entries."
assert {'Thorny', 'Mac', 'Farva', 'Rabbit', 'Ursula', 'Foster'} == set(grade_dicts.keys)
assert grade_dicts['Foster']['Exam 1'] == 89, 'Wrong score'
assert grade_dicts['Foster']['Exam 3'] == 101, 'Wrong score'
assert grade_dicts['Foster']['Exam 2'] == 97, 'Wrong score'
assert grade_dicts['Ursula']['Exam 1'] == 73, 'Wrong score'
assert grade_dicts['Ursula']['Exam 3'] == 83, 'Wrong score'
assert grade_dicts['Ursula']['Exam 2'] == 79, 'Wrong score'
assert grade_dicts['Rabbit']['Exam 1'] == 59, 'Wrong score'
assert grade_dicts['Rabbit']['Exam 3'] == 67, 'Wrong score'
assert grade_dicts['Rabbit']['Exam 2'] == 61, 'Wrong score'
assert grade_dicts['Mac']['Exam 1'] == 88, 'Wrong score'
assert grade_dicts['Mac']['Exam 3'] == 111, 'Wrong score'
assert grade_dicts['Mac']['Exam 2'] == 99, 'Wrong score'

```

```

assert grade_dicts['Farva']['Exam 1'] == 45, 'Wrong score'
assert grade_dicts['Farva']['Exam 3'] == 67, 'Wrong score'
assert grade_dicts['Farva']['Exam 2'] == 56, 'Wrong score'
assert grade_dicts['Thorny']['Exam 1'] == 100, 'Wrong score'
assert grade_dicts['Thorny']['Exam 3'] == 80, 'Wrong score'
assert grade_dicts['Thorny']['Exam 2'] == 90, 'Wrong score'
print("\n(Passed!)")

```

```
{'Thorny': {'Exam 1': 100, 'Exam 2': 90, 'Exam 3': 80}, 'Mac': {'Exam 1': 88, 'Exam 2': 99, 'Exam 3': 88}}
```

(Passed!)

**Exercise 4** (avg\_grades\_by\_student\_test: 1 point). Write some code to compute a dictionary named avg\_grades\_by\_student that maps each student to his or her average exam score. For instance, avg\_grades\_by\_student['Thorny'] == 90.

**Hint.** The `statistics` module of Python has at least one helpful function.

```

In [10]: # Create a dict mapping names to grade averages.
        ###
        ### YOUR CODE HERE
        ###
        avg_grades_by_student={}
        for i in range(1,len(grades)):
            avg_grades_by_student[grades[i][0]]=(int(grades[i][1])+int(grades[i][2])+int(grades[i][3]))/3

In [11]: # `avg_grades_by_student_test`: Test cell
        print(avg_grades_by_student)
        assert type(avg_grades_by_student) is dict, "Did not create a dictionary."
        assert len(avg_grades_by_student) == len(students), "Output has the wrong number of students"
        assert abs(avg_grades_by_student['Mac'] - 99.33333333333333) <= 4e-15, 'Mean is incorrect'
        assert abs(avg_grades_by_student['Foster'] - 95.66666666666667) <= 4e-15, 'Mean is incorrect'
        assert abs(avg_grades_by_student['Farva'] - 56) <= 4e-15, 'Mean is incorrect'
        assert abs(avg_grades_by_student['Rabbit'] - 62.333333333333336) <= 4e-15, 'Mean is incorrect'
        assert abs(avg_grades_by_student['Thorny'] - 90) <= 4e-15, 'Mean is incorrect'
        assert abs(avg_grades_by_student['Ursula'] - 78.33333333333333) <= 4e-15, 'Mean is incorrect'
        print("\n(Passed!)")

```

```
{'Thorny': 90.0, 'Mac': 99.33333333333333, 'Farva': 56.0, 'Rabbit': 62.333333333333336, 'Ursula': 78.33333333333333}
```

(Passed!)

**Exercise 5** (grades\_by\_assignment\_test: 2 points). Write some code to compute a dictionary named grades\_by\_assignment, whose keys are assignment (exam) names and whose values are lists of scores over all students on that assignment. For instance, grades\_by\_assignment['Exam 1'] == [100, 88, 45, 59, 73, 89].

```

In [12]: ###
        ### YOUR CODE HERE
        ###
        grades_by_assignment={'Exam 1':[int(grades[p][1]) for p in range(1,7)],'Exam 2': [int

In [13]: # `grades_by_assignment_test`: Test cell
        print(grades_by_assignment)
        assert type(grades_by_assignment) is dict, "Output is not a dictionary."
        assert len(grades_by_assignment) == 3, "Wrong number of assignments."
        soln = {'Exam 1': [100, 88, 45, 59, 73, 89],
                'Exam 2': [90, 99, 56, 61, 79, 97],
                'Exam 3': [80, 111, 67, 67, 83, 101]}
        for k, v in soln.items():
            assert len(grades_by_assignment[k]) == len(v) and set(grades_by_assignment[k]) ==
                f"Your computed solution for '{k}' is incorrect."
        print("\n(Passed!)")

{'Exam 1': [100, 88, 45, 59, 73, 89], 'Exam 2': [90, 99, 56, 61, 79, 97], 'Exam 3': [80, 111, 67, 67, 83, 101]}

(Passed!)

```

**Exercise 6** (avg\_grades\_by\_assignment\_test: 1 point). Write some code to compute a dictionary, avg\_grades\_by\_assignment, which maps each exam to its average score.

```

In [14]: # Create a dict mapping items to average for that item across all students.
        ###
        ### YOUR CODE HERE
        ###
        import statistics
        avg_grades_by_assignment={'Exam 1': statistics.mean(grades_by_assignment['Exam 1']),
                                'Exam 2': statistics.mean(grades_by_assignment['Exam 2']),
                                'Exam 3': statistics.mean(grades_by_assignment['Exam 3'])}

In [15]: # `avg_grades_by_assignment_test`: Test cell
        print(avg_grades_by_assignment)
        assert type(avg_grades_by_assignment) is dict
        assert len(avg_grades_by_assignment) == 3
        assert abs((100+88+45+59+73+89)/6 - avg_grades_by_assignment['Exam 1']) <= 7e-15
        assert abs((80+111+67+67+83+101)/6 - avg_grades_by_assignment['Exam 3']) <= 7e-15
        assert abs((90+99+56+61+79+97)/6 - avg_grades_by_assignment['Exam 2']) <= 7e-15
        print("\n(Passed!)")

{'Exam 1': 75.66666666666667, 'Exam 2': 80.33333333333333, 'Exam 3': 84.83333333333333}

(Passed!)

```

**Exercise 7** (rank\_test: 2 points). Write some code to create a new list, rank, which contains the names of students in order by *decreasing* score. That is, rank[0] should contain the name of

the top student (highest average exam score), and rank[-1] should have the name of the bottom student (lowest average exam score).

```
In [16]: ###
        ### YOUR CODE HERE
        ###

import statistics
students=[grades[p][0] for p in range(1,7)]
students_avg=[statistics.mean([int(grades[k][p]) for p in range(1,4)]) for k in range(1,7)]
sor=students_avg.copy()
sor.sort(reverse=True)

rank=[]
print(len(sor))
print(len(students_avg))
print(len(students))
for i in range(0,len(sor)):
    for j in range(0,len(students_avg)):
        if students_avg[j] == sor[i]:
            rank.append(students[j])
#students=dict(zip([grades[p][0] for p in range(1,6)],
#                  [statistics.mean([int(grades[k][p]) for p in range(1,4)]) for k in range(1,6)]))

6
6
6
```

```
In [17]: # `rank_test`: Test cell
print(rank)
print("\n=== Ranking ===")
for i, s in enumerate(rank):
    print("{}: {}".format(i+1, s, avg_grades_by_student[s]))

assert rank == ['Mac', 'Foster', 'Thorny', 'Ursula', 'Rabbit', 'Farva']
for i in range(len(rank)-1):
    assert avg_grades_by_student[rank[i]] >= avg_grades_by_student[rank[i+1]]
print("\n(Passed!)")

['Mac', 'Foster', 'Thorny', 'Ursula', 'Rabbit', 'Farva']

=== Ranking ===
1. Mac: 99.33333333333333
2. Foster: 95.66666666666667
3. Thorny: 90.0
4. Ursula: 78.33333333333333
```

5. Rabbit: 62.33333333333336  
6. Farva: 56.0

(Passed!)

**Fin!** You've reached the end of this part. Don't forget to restart and run all cells again to make sure it's all working when run in sequence; and make sure your work passes the submission process. Good luck!