

Creating a Relative file from a Sequential file.

Example program

Click to view.

When viewing the program left click (or press the Page Up key) to see next comment and right click (or press Page Down) to see the previous comment.

```
$ SET SOURCEFORMAT"FREE"  
IDENTIFICATION DIVISION.  
PROGRAM-ID. CreateRelativeFromSeq.  
ENVIRONMENT DIVISION.  
INPUT-OUTPUT SECTION.  
FILE-CONTROL.
```

```
SELECT SupplierFile ASSIGN TO "SUPPLIERFILE"  
ORGANIZATION IS RELATIVE  
ACCESS MODE IS RANDOM  
RELATIVE KEY IS SupplierKey  
FILE STATUS IS SupplierStatus.  
SELECT SupplierFileSeq ASSIGN TO "INSUPPSEQ"
```

DATA DIVISION.

FILE SECTION.

FD SupplierFile.

01 SupplierRecord.

02 SupplierCode	PIC 99.
02 SupplierName	PIC X(20).
02 SupplierAddress	PIC X(60).

FD SupplierFileSeq.

01 SupplierRecordSeq.

88 EndOfFile	VALUE HIGH-VALUES.
02 SupplierCodeSeq	PIC 99.
02 SupplierNameSeq	PIC X(20).
02 SupplierAddressSeq	PIC X(60).

WORKING-STORAGE SECTION.

01 SupplierStatus	PIC X(2).
01 SupplierKey	PIC 99.

Let's look
we ne
R

The FILE STATUS clause specifies a two character area of storage that will hold a code indicating the success or failure of each I-O operation. If an I-O operation fails, the code will indicate what went wrong.

PROCEDURE DIVISION.

Begin.

OPEN OUTPUT SupplierFile

OPEN INPUT SupplierFileSeq

~~READ SupplierFileSeq~~

~~AT END SET EndOfFile TO TRUE~~

~~END-READ~~

~~PERFORM UNTIL EndOfFile~~

~~MOVE SupplierCodeSeq TO SupplierKey~~

~~MOVE SupplierRecordSeq TO SupplierRecord~~

~~WRITE SupplierRecord~~

~~INVALID KEY~~

~~DISPLAY "SUPP STATUS :-", SupplierStatus~~

~~END-WRITE~~

~~READ SupplierFileSeq~~

~~AT END SET EndOfFile TO TRUE~~

~~END-READ~~

~~END-PERFORM~~

~~CLOSE SupplierFile, SupplierFileSeq~~

~~STOP RUN.~~

Let's look at
Division

The INVALID KEY clause will activate if anything goes wrong with the attempt to WRITE the record. For instance, a record with this Relative Record Number might already exist in the file.