

Condition Names

Click to view.

When viewing , left click (or press the Page Up key) to see the next frame and right click (or press Page Down) to see the previous frame.

```
01 CityCode          PIC 9 VALUE 8.  
   88 Dublin         VALUE 1.  
   88 Limerick        VALUE 2.  
   88 Cork            VALUE 3.  
   88 Galway          VALUE 4.  
   88 Sligo           VALUE 5.  
   88 Waterford       VALUE 6.  
   88 UniversityCity VALUE 1 THRU 4.
```

A Condition Name monitors the contents of its associated data-item and when it contains any of the condition values, the Condition Name is set to True

```
MOVE 2 TO CityCode.  
IF Limerick  
    DISPLAY "Hey, we're home."  
END-IF.  
IF UniversityCity  
    PERFORM CalcRentSurcharge  
END-IF.  
MOVE 6 TO CityCode.  
SET Cork TO TRUE.
```

CityCode

8

Dublin
FALSE
Limerick
FALSE
Cork
FALSE
Galway
FALSE

```
01 CityCode          PIC 9 VALUE 5.
   88 Dublin          VALUE 1.
   88 Limerick         VALUE 2.
   88 Cork             VALUE 3.
   88 Galway           VALUE 4.
   88 Sligo            VALUE 5.
   88 Waterford        VALUE 6.
   88 UniversityCity  VALUE 1 THRU 4.
```

Note that more than one
Condition Name can be True at
the same time.

UniversityCity is set to True
when CityCode has a value in
the range 1-4.



```
MOVE 2 TO CityCode.
IF Limerick
  DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
  PERFORM CalcRentSurcharge
END-IF.
MOVE 6 TO CityCode.
SET Cork TO TRUE.
```

CityCode

2

Dublin

FALSE

Limerick

TRUE

Cork

FALSE

Galway

FALSE

Sligo

```
01 CityCode          PIC 9 VALUE 5.
   88 Dublin          VALUE 1.
   88 Limerick         VALUE 2.
   88 Cork             VALUE 3.
   88 Galway           VALUE 4.
   88 Sligo            VALUE 5.
   88 Waterford        VALUE 6.
   88 UniversityCity  VALUE 1 THRU 4.
```

```
MOVE 2 TO CityCode.
IF Limerick
    DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
    PERFORM CalcRentSurcharge
END-IF.
MOVE 6 TO CityCode.
SET Cork TO TRUE.
```

CityCode

2

Dublin

FALSE

Limerick

TRUE

Cork

FALSE

Galway

FALSE

Sligo

```
01 CityCode          PIC 9 VALUE 5.  
   88 Dublin         VALUE 1.  
   88 Limerick        VALUE 2.  
   88 Cork            VALUE 3.  
   88 Galway          VALUE 4.  
   88 Sligo           VALUE 5.  
   88 Waterford       VALUE 6.  
   88 UniversityCity VALUE 1 THRU 4.
```

```
MOVE 2 TO CityCode.  
IF Limerick  
  DISPLAY "Hey, we're home."  
END-IF.  
IF UniversityCity  
  PERFORM CalcRentSurcharge  
END-IF.  
MOVE 6 TO CityCode.  
SET Cork TO TRUE.
```

CityCode

2

Dublin

FALSE

Limerick

TRUE

Cork

FALSE

Galway

FALSE

Sligo

```
01 CityCode          PIC 9 VALUE 5.  
   88 Dublin         VALUE 1.  
   88 Limerick       VALUE 2.  
   88 Cork           VALUE 3.  
   88 Galway         VALUE 4.  
   88 Sligo          VALUE 5.  
   88 Waterford      VALUE 6.  
   88 UniversityCity VALUE 1 THRU 4.
```

```
MOVE 2 TO CityCode.  
IF Limerick  
  DISPLAY "Hey, we're home."  
END-IF.  
IF UniversityCity  
  PERFORM CalcRentSurcharge  
END-IF.  
MOVE 6 TO CityCode.  
 SET Cork TO TRUE.
```

CityCode

6

Dublin

FALSE

Limerick

FALSE

Cork

FALSE

Galway

FALSE

```
01 CityCode          PIC 9 VALUE 5.
   88 Dublin          VALUE 1.
   88 Limerick         VALUE 2.
   88 Cork             VALUE 3.
   88 Galway           VALUE 4.
   88 Sligo            VALUE 5.
   88 Waterford        VALUE 6.
   88 UniversityCity  VALUE 1 THRU 4.
```

```
MOVE 2 TO CityCode.
IF Limerick
  DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
  PERFORM CalcRentSurcharge
END-IF.
MOVE 6 TO CityCode.
SET Cork TO TRUE.
```



CityCode

3

Dublin

FALSE

Limerick

FALSE

Cork

Galway

FALSE

Sligo

TRUE

If one of its condition values is
But this can work the other way
around as well.

If the SET verb is used to set a
Condition Name to TRUE, one of
the condition values will be
moved into the data-item (as has
happened here).

```
01 InputChar PIC X VALUE SPACES.
```

```
88 Vowel      VALUE "A","E","I","O","U".
```

```
88 Consonant  VALUE "B" THRU "D", "F","G","H"  
                "J" THRU "N", "P" THRU "T"  
                "V" THRU "Z".
```

```
88 Digit      VALUE "0" THRU "9".
```

```
88 LowerCase  VALUE "a" THRU "z".
```

```
88 ValidChar  VALUE "A" THRU "Z", "0" THRU "9".
```

You can specify individual values, a range of values, or a mixture of these.

```
PERFORM 3 TIMES
```

```
ACCEPT InputChar
```

```
EVALUATE TRUE
```

```
    WHEN Vowel      DISPLAY "Vowel."
```

```
    WHEN Consonant  DISPLAY "Consonant".
```

```
    WHEN Digit      DISPLAY "Digit."
```

```
    WHEN LowerCase  DISPLAY "lower".
```

```
END-EVALUATE
```

```
END-PERFORM
```

InputChar



Vowel

FALSE

Consonant

FALSE

Digit

FALSE

LowerCase

FALSE


```

01 InputChar PIC X VALUE SPACES.
   88 Vowel      VALUE "A","E","I","O","U".
   88 Consonant  VALUE "B" THRU "D", "F","G","H"
                        "J" THRU "N", "P" THRU "T"
                        "V" THRU "Z".
   88 Digit      VALUE "0" THRU "9".
   88 LowerCase  VALUE "a" THRU "z".
   88 ValidChar  VALUE "A" THRU "Z", "0" THRU "9".

```

```

PERFORM 3 TIMES
→ ACCEPT InputChar
EVALUATE TRUE
   WHEN Vowel      DISPLAY "Vowel."
   WHEN Consonant  DISPLAY "Consonant".
   WHEN Digit      DISPLAY "Digit."
   WHEN LowerCase  DISPLAY "lower".
END-EVALUATE
END-PERFORM

```

InputChar

E

Vowel
 Consonant
 FALSE
 Digit
 FALSE
 LowerCase
 FALSE
 ValidChar

TRUE

TRUE

```

01 InputChar PIC X VALUE SPACES.
   88 Vowel      VALUE "A","E","I","O","U".
   88 Consonant  VALUE "B" THRU "D", "F","G","H"
                   "J" THRU "N", "P" THRU "T"
                   "V" THRU "Z".
   88 Digit      VALUE "0" THRU "9".
   88 LowerCase  VALUE "a" THRU "z".
   88 ValidChar  VALUE "A" THRU "Z", "0" THRU "9".

```

```

PERFORM 3 TIMES
ACCEPT InputChar
EVALUATE TRUE
  WHEN Vowel      DISPLAY "Vowel."
  WHEN Consonant  DISPLAY "Consonant".
  WHEN Digit      DISPLAY "Digit."
  WHEN LowerCase  DISPLAY "lower".
END-EVALUATE
END-PERFORM

```

InputChar

E

Vowel
 Consonant
 FALSE
 Digit
 FALSE
 LowerCase
 FALSE
 ValidChar

TRUE

TRUE

```

01 InputChar PIC X VALUE SPACES.
   88 Vowel      VALUE "A","E","I","O","U".
   88 Consonant  VALUE "B" THRU "D", "F","G","H"
                   "J" THRU "N", "P" THRU "T"
                   "V" THRU "Z".
   88 Digit      VALUE "0" THRU "9".
   88 LowerCase  VALUE "a" THRU "z".
   88 ValidChar  VALUE "A" THRU "Z", "0" THRU "9".

```

```

PERFORM 3 TIMES
ACCEPT InputChar
EVALUATE TRUE
    WHEN Vowel      DISPLAY "Vowel."
    WHEN Consonant  DISPLAY "Consonant".
    WHEN Digit      DISPLAY "Digit."
    WHEN LowerCase  DISPLAY "lower".
END-EVALUATE
END-PERFORM

```

InputChar

4

Vowel
 FALSE
 Consonant
 FALSE
 Digit TRUE
 LowerCase
 FALSE
 ValidChar TRUE

```

01 InputChar PIC X VALUE SPACES.
88 Vowel      VALUE "A","E","I","O","U".
88 Consonant  VALUE "B" THRU "D", "F","G","H"
               "J" THRU "N", "P" THRU "T"
               "V" THRU "Z".
88 Digit      VALUE "0" THRU "9".
88 LowerCase  VALUE "a" THRU "z".
88 ValidChar  VALUE "A" THRU "Z", "0" THRU "9".

```

```

PERFORM 3 TIMES
ACCEPT InputChar
EVALUATE TRUE
    WHEN Vowel      DISPLAY "Vowel."
    WHEN Consonant  DISPLAY "Consonant".
    WHEN Digit      DISPLAY "Digit."
    WHEN LowerCase  DISPLAY "lower".
END-EVALUATE
END-PERFORM

```

InputChar

4

Vowel

FALSE

Consonant

FALSE

Digit

TRUE

LowerCase

FALSE

ValidChar

TRUE

```

01 InputChar PIC X VALUE SPACES.
   88 Vowel      VALUE "A","E","I","O","U".
   88 Consonant  VALUE "B" THRU "D", "F","G","H"
                   "J" THRU "N", "P" THRU "T"
                   "V" THRU "Z".
   88 Digit      VALUE "0" THRU "9".
   88 LowerCase  VALUE "a" THRU "z".
   88 ValidChar  VALUE "A" THRU "Z", "0" THRU "9".

```

```

PERFORM 3 TIMES
ACCEPT InputChar
EVALUATE TRUE
    WHEN Vowel      DISPLAY "Vowel."
    WHEN Consonant  DISPLAY "Consonant".
    WHEN Digit      DISPLAY "Digit."
    WHEN LowerCase  DISPLAY "lower".
END-EVALUATE
END-PERFORM

```

InputChar

d

Vowel

FALSE

Consonant

FALSE

Digit

FALSE

LowerCase

TRUE

ValidChar

```

01 InputChar PIC X.
88 Vowel      VALUE "A","E","I","O","U".
88 Consonant  VALUE "B" THRU "D", "F","G","H"
               "J" THRU "N", "P" THRU "T"
               "V" THRU "Z".
88 Digit      VALUE "0" THRU "9".
88 LowerCase  VALUE "a" THRU "z".
88 ValidChar  VALUE "A" THRU "Z", "0" THRU "9".

```

```

PERFORM 3 TIMES
ACCEPT InputChar
EVALUATE TRUE
    WHEN Vowel      DISPLAY "Vowel."
    WHEN Consonant  DISPLAY "Consonant".
    WHEN Digit      DISPLAY "Digit."
    WHEN LowerCase  DISPLAY "lower".
END-EVALUATE
END-PERFORM

```

InputChar

d

Vowel

FALSE

Consonant

FALSE

Digit

FALSE

LowerCase

TRUE

ValidChar