

Creating a Relative file from a Sequential file.

Example program

Click to view.

When viewing the program left click (or press the Page Up key) to see next comment and right click (or press Page Down) to see the previous comment.

```
$ SET SOURCEFORMAT"FREE"
IDENTIFICATION DIVISION.
PROGRAM-ID. CreateRelativeFromSeq.
ENVIRONMENT DIVISION.
INPUT-OUTPUT SECTION.
FILE-CONTROL.
```

```
SELECT SupplierFile ASSIGN TO "SUPP.DAT"
    ORGANIZATION IS RELATIVE
    ACCESS MODE IS RANDOM
    RELATIVE KEY IS SupplierKey
    FILE STATUS IS SupplierStatus.
SELECT SupplierFileSeq ASSIGN TO "INSURP
```

DATA DIVISION.

FILE SECTION.

FD SupplierFile.

01 SupplierRecord.

02 SupplierCode

PIC 99.

02 SupplierName

PIC X(20).

02 SupplierAddress

PIC X(60).

FD SupplierFileSeq.

01 SupplierRecordSeq.

88 EndOfFile VALUE HIGH-VALUES.

02 SupplierCodeSeq

PIC 99.

02 SupplierNameSeq

PIC X(20).

02 SupplierAddressSeq

PIC X(60).

WORKING-STORAGE SECTION.

01 SupplierStatus

PIC X(2).

01 SupplierKey

PIC 99.

Let's
entries
the

The FILE STATUS
clause specifies a
two character area of
storage that will hold
a code indicating the
success or failure of
each I-O operation.
If an I-O operation
fails, the code will
indicate what went
wrong.

DYNAMIC

PROCEDURE DIVISION.

Begin.

OPEN OUTPUT SupplierFile

OPEN INPUT SupplierFileSeq

READ SupplierFileSeq

AT END SET EndOfFile TO TRUE

END-READ

PERFORM UNTIL EndOfFile

MOVE SupplierCodeSeq TO SupplierKey

MOVE SupplierRecordSeq TO SupplierRecord

WRITE SupplierRecord

INVALID KEY

DISPLAY "SUPP STATUS :-", SupplierStatus

END-WRITE

READ SupplierFileSeq

AT END SET EndOfFile TO TRUE

END-READ

END-PERFORM

CLOSE SupplierFile, SupplierFileSeq

STOP RUN.

Let's look at this
Division

The INVALID KEY clause will activate if anything goes wrong with the attempt to WRITE the record. For instance, a record with this Relative Record Number might already exist in the file.