

Condition Names

Click to view.

When viewing , left click (or press the Page Up key)
to see the next frame and right click (or press Page
Down) to see the previous frame.

```
01 CityCode          PIC 9 VALUE 8.
   88 Dublin          VALUE 1.
   88 Limerick         VALUE 2.
   88 Cork             VALUE 3.
   88 Galway           VALUE 4.
   88 Sligo            VALUE 5.
   88 Waterford        VALUE 6.
   88 UniversityCity  VALUE 1 THRU 4.
```

A Condition Name monitors the contents of its associated data-item and when it contains any of the condition values, the Condition Name is set to True

```
MOVE 2 TO CityCode.
IF Limerick
    DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
    PERFORM CalcRentSurcharge
END-IF.
MOVE 6 TO CityCode.
SET Cork TO TRUE.
```

CityCode

8

Dublin	FALSE
Limerick	FALSE
Cork	FALSE
Galway	FALSE
Sligo	FALSE
Waterford	FALSE
UniversityCity	FALSE

```
01 CityCode          PIC 9 VALUE 5.
   88 Dublin         VALUE 1.
   88 Limerick        VALUE 2.
   88 Cork            VALUE 3.
   88 Galway          VALUE 4.
   88 Sligo           VALUE 5.
   88 Waterford       VALUE 6.
   88 UniversityCity VALUE 1 THRU 4.
```

Note that more than one
Condition Name can be
True at the same time.

UniversityCity is set to
True when CityCode has
a value in the range 1-4.

→ **MOVE 2 TO CityCode.**
IF Limerick
 DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
 PERFORM CalcRentSurcharge
END-IF.
MOVE 6 TO CityCode.
SET Cork TO TRUE.

CityCode

2

Dublin	FALSE
Limerick	TRUE
Cork	FALSE
Galway	FALSE
Sligo	FALSE
Waterford	FALSE
UniversityCity	TRUE

```
01 CityCode          PIC 9 VALUE 5.
   88 Dublin          VALUE 1.
   88 Limerick         VALUE 2.
   88 Cork             VALUE 3.
   88 Galway           VALUE 4.
   88 Sligo            VALUE 5.
   88 Waterford        VALUE 6.
   88 UniversityCity  VALUE 1 THRU 4.
```



```
MOVE 2 TO CityCode.
IF Limerick
  DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
  PERFORM CalcRentSurcharge
END-IF.
MOVE 6 TO CityCode.
SET Cork TO TRUE.
```

CityCode

2

Dublin	FALSE
Limerick	TRUE
Cork	FALSE
Galway	FALSE
Sligo	FALSE
Waterford	FALSE
UniversityCity	TRUE

```
01 CityCode          PIC 9 VALUE 5.
   88 Dublin         VALUE 1.
   88 Limerick        VALUE 2.
   88 Cork            VALUE 3.
   88 Galway          VALUE 4.
   88 Sligo           VALUE 5.
   88 Waterford       VALUE 6.
   88 UniversityCity VALUE 1 THRU 4.
```

```
MOVE 2 TO CityCode.
IF Limerick
    DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
    PERFORM CalcRentSurcharge
END-IF.
MOVE 6 TO CityCode.
SET Cork TO TRUE.
```

CityCode

2

Dublin	FALSE
Limerick	TRUE
Cork	FALSE
Galway	FALSE
Sligo	FALSE
Waterford	FALSE
UniversityCity	TRUE

```
01 CityCode          PIC 9 VALUE 5.
   88 Dublin          VALUE 1.
   88 Limerick         VALUE 2.
   88 Cork             VALUE 3.
   88 Galway           VALUE 4.
   88 Sligo            VALUE 5.
   88 Waterford        VALUE 6.
   88 UniversityCity  VALUE 1 THRU 4.
```

```
MOVE 2 TO CityCode.
IF Limerick
    DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
    PERFORM CalcRentSurcharge
END-IF.
→ MOVE 6 TO CityCode.
SET Cork TO TRUE.
```

CityCode

6

Dublin	FALSE
Limerick	FALSE
Cork	FALSE
Galway	FALSE
Sligo	FALSE
Waterford	TRUE
UniversityCity	FALSE

```
01 CityCode          PIC 9 VALUE 5.
   88 Dublin          VALUE 1.
   88 Limerick         VALUE 2.
   88 Cork             VALUE 3.
   88 Galway           VALUE 4.
   88 Sligo            VALUE 5.
   88 Waterford        VALUE 6.
   88 UniversityCity  VALUE 1 THRU 4.
```

But this can work the other way around as well.

If the SET verb is used to set a Condition Name to TRUE, one of the condition values will be moved into the data-item (as has happened here).

```
MOVE 2 TO CityCode.
IF Limerick
    DISPLAY "Hey, we're home."
END-IF.
IF UniversityCity
    PERFORM CalcRentSurcharge
END-IF.
MOVE 6 TO CityCode.
→ SET Cork TO TRUE.
```

CityCode

3

Dublin	FALSE
Limerick	FALSE
Cork	TRUE
Galway	FALSE
Sligo	FALSE
Waterford	FALSE
UniversityCity	TRUE

```
01 InputChar PIC X VALUE SPACES.  
88 Vowel      VALUE "A","E","I","O","U".  
88 Consonant  VALUE "B" THRU "D", "F","G","H"  
              "J" THRU "N", "P" THRU "T"  
              "V" THRU "Z".  
88 Digit      VALUE "0" THRU "9".  
88 LowerCase  VALUE "a" THRU "z".  
88 ValidChar  VALUE "A" THRU "Z","0" THRU "9".
```

You can specify individual values, a range of values, or a mixture of these.

```
PERFORM 3 TIMES  
  ACCEPT InputChar  
  EVALUATE TRUE  
    WHEN Vowel      DISPLAY "Vowel."  
    WHEN Consonant  DISPLAY "Consonant".  
    WHEN Digit      DISPLAY "Digit."  
    WHEN LowerCase  DISPLAY "lower".  
  END-EVALUATE  
END-PERFORM
```

InputChar

Vowel	FALSE
Consonant	FALSE
Digit	FALSE
LowerCase	FALSE
ValidChar	FALSE

```
01 InputChar PIC X VALUE SPACES.  
88 Vowel      VALUE "A","E","I","O","U".  
88 Consonant  VALUE "B" THRU "D", "F","G","H"  
              "J" THRU "N", "P" THRU "T"  
              "V" THRU "Z".  
88 Digit      VALUE "0" THRU "9".  
88 LowerCase  VALUE "a" THRU "z".  
88 ValidChar  VALUE "A" THRU "Z","0" THRU "9".
```

```
PERFORM 3 TIMES  
→ ACCEPT InputChar  
EVALUATE TRUE  
  WHEN Vowel      DISPLAY "Vowel."  
  WHEN Consonant  DISPLAY "Consonant".  
  WHEN Digit      DISPLAY "Digit."  
  WHEN LowerCase  DISPLAY "lower".  
END-EVALUATE  
END-PERFORM
```

InputChar

E

Vowel	TRUE
Consonant	FALSE
Digit	FALSE
LowerCase	FALSE
ValidChar	TRUE

```
01 InputChar PIC X VALUE SPACES.  
88 Vowel      VALUE "A","E","I","O","U".  
88 Consonant  VALUE "B" THRU "D", "F","G","H"  
              "J" THRU "N", "P" THRU "T"  
              "V" THRU "Z".  
88 Digit      VALUE "0" THRU "9".  
88 LowerCase  VALUE "a" THRU "z".  
88 ValidChar  VALUE "A" THRU "Z","0" THRU "9".
```

```
PERFORM 3 TIMES  
  ACCEPT InputChar  
  EVALUATE TRUE  
  WHEN Vowel      DISPLAY "Vowel."  
  WHEN Consonant  DISPLAY "Consonant".  
  WHEN Digit      DISPLAY "Digit."  
  WHEN LowerCase  DISPLAY "lower".  
END-EVALUATE  
END-PERFORM
```

InputChar

E

Vowel	TRUE
Consonant	FALSE
Digit	FALSE
LowerCase	FALSE
ValidChar	TRUE

```
01 InputChar PIC X VALUE SPACES.  
88 Vowel      VALUE "A","E","I","O","U".  
88 Consonant  VALUE "B" THRU "D", "F","G","H"  
              "J" THRU "N", "P" THRU "T"  
              "V" THRU "Z".  
88 Digit      VALUE "0" THRU "9".  
88 LowerCase  VALUE "a" THRU "z".  
88 ValidChar  VALUE "A" THRU "Z","0" THRU "9".
```

PERFORM 3 TIMES

→ **ACCEPT** InputChar

EVALUATE TRUE

WHEN Vowel DISPLAY "Vowel."

WHEN Consonant DISPLAY "Consonant".

WHEN Digit DISPLAY "Digit."

WHEN LowerCase DISPLAY "lower".

END-EVALUATE

END-PERFORM

InputChar

4

Vowel

FALSE

Consonant

FALSE

Digit

TRUE

LowerCase

FALSE

ValidChar

TRUE

```
01 InputChar PIC X VALUE SPACES.  
88 Vowel      VALUE "A","E","I","O","U".  
88 Consonant  VALUE "B" THRU "D", "F","G","H"  
              "J" THRU "N", "P" THRU "T"  
              "V" THRU "Z".  
88 Digit      VALUE "0" THRU "9".  
88 LowerCase  VALUE "a" THRU "z".  
88 ValidChar  VALUE "A" THRU "Z","0" THRU "9".
```

```
PERFORM 3 TIMES  
  ACCEPT InputChar  
  EVALUATE TRUE  
    WHEN Vowel      DISPLAY "Vowel."  
    WHEN Consonant  DISPLAY "Consonant".  
    WHEN Digit      DISPLAY "Digit."  
    WHEN LowerCase  DISPLAY "lower".  
  END-EVALUATE  
END-PERFORM
```

InputChar

4

Vowel	FALSE
Consonant	FALSE
Digit	TRUE
LowerCase	FALSE
ValidChar	TRUE

```
01 InputChar PIC X VALUE SPACES.  
   88 Vowel      VALUE "A","E","I","O","U".  
   88 Consonant  VALUE "B" THRU "D", "F","G","H"  
                        "J" THRU "N", "P" THRU "T"  
                        "V" THRU "Z".  
   88 Digit      VALUE "0" THRU "9".  
   88 LowerCase  VALUE "a" THRU "z".  
   88 ValidChar  VALUE "A" THRU "Z","0" THRU "9".
```

PERFORM 3 TIMES

→ **ACCEPT** InputChar

EVALUATE TRUE

WHEN Vowel DISPLAY "Vowel."

WHEN Consonant DISPLAY "Consonant".

WHEN Digit DISPLAY "Digit."

WHEN LowerCase DISPLAY "lower".

END-EVALUATE

END-PERFORM

InputChar

d

Vowel

FALSE

Consonant

FALSE

Digit

FALSE

LowerCase

TRUE

ValidChar

FALSE

```
01 InputChar PIC X.  
   88 Vowel      VALUE "A", "E", "I", "O", "U".  
   88 Consonant  VALUE "B" THRU "D", "F", "G", "H"  
                        "J" THRU "N", "P" THRU "T"  
                        "V" THRU "Z".  
   88 Digit      VALUE "0" THRU "9".  
   88 LowerCase  VALUE "a" THRU "z".  
   88 ValidChar  VALUE "A" THRU "Z", "0" THRU "9".
```

```
PERFORM 3 TIMES  
  ACCEPT InputChar  
  EVALUATE TRUE  
    WHEN Vowel      DISPLAY "Vowel."  
    WHEN Consonant  DISPLAY "Consonant".  
    WHEN Digit      DISPLAY "Digit."  
    WHEN LowerCase  DISPLAY "lower".  
  END-EVALUATE  
END-PERFORM
```

InputChar

d

Vowel	FALSE
Consonant	FALSE
Digit	FALSE
LowerCase	TRUE
ValidChar	FALSE