

Py-Bussilab Documentation

Contents

Module <code>bussilab</code>	3
Install	3
Checking the installation	4
Setting autocompletion	5
Getting started	5
Python	5
Examples	5
Command line	5
Advanced stuff	5
Install with no dependencies	5
Building documentation	5
Implementing your modifications	6
Testing the code	6
Running and rendering jupyter examples from the command line	6
Sub-modules	7
Functions	7
Function <code>describe_submodule</code>	7
Function <code>import_submodules</code>	7
Function <code>list_submodules</code>	8
Function <code>required_conda</code>	8
Function <code>required_macports</code>	8
Function <code>required_pip</code>	8
Module <code>bussilab.ann</code>	8
Classes	8
Class <code>ANN</code>	8
Methods	8
Module <code>bussilab.cli</code>	10
Tools to implement the command line interface	10
Functions	10
Function <code>arg</code>	10
Function <code>cli</code>	11
Function <code>command</code>	11
Function <code>endgroup</code>	12
Function <code>group</code>	12
Module <code>bussilab.cli_documentation</code>	12
Documentation for command line tools	12
list	12
check	13
wham	13

jrun	13
notify	15
required	17
Module bussilab.clustering	17
Functions	17
Function daura	17
Function max_clique	17
Function qt	18
Classes	19
Class ClusteringResult	19
Ancestors (in MRO)	19
Instance variables	19
Module bussilab.coretools	19
Functions	19
Function cd	19
Function config	20
Function config_path	20
Function ensure_np_array	20
Function file_or_path	20
Function import_numba_jit	20
Classes	20
Class Result	20
Examples	20
Ancestors (in MRO)	21
Descendants	21
Class TestCase	21
Ancestors (in MRO)	21
Methods	21
Module bussilab.cron	22
Functions	22
Function cron	22
Module bussilab.installers	22
Functions	22
Function build_viennarna	22
Function install_viennarna	23
Module bussilab.jremote	23
Functions	23
Function find_free_port	23
Function remote	23
Function run_server	24
Module bussilab.lohman	24
Functions	24
Function lohman	24
Module bussilab.maxent	24
Functions	25
Function maxent	25
Classes	26
Class MaxentResult	26
Ancestors (in MRO)	26
Instance variables	26
Module bussilab.notify	26

Functions	28
Function <code>notify</code>	28
Module <code>bussilab.pip</code>	29
Functions	29
Function <code>install</code>	29
Function <code>upgrade_all</code>	29
Function <code>upgrade_self</code>	30
Module <code>bussilab.potts</code>	30
Classes	30
Class <code>InferResult</code>	30
Ancestors (in MRO)	30
Instance variables	30
Class <code>Model</code>	31
Methods	31
Module <code>bussilab.reports</code>	32
Functions	32
Function <code>workstations</code>	32
Module <code>bussilab.rna2d</code>	32
Functions	32
Function <code>reset_default_parameters</code>	32
Function <code>sample_to_numpy</code>	32
Function <code>set_default_parameters</code>	33
Function <code>suboptimal_to_numpy</code>	33
Classes	34
Class <code>Molecule</code>	34
Parameters	34
Notes	35
Methods	35
Module <code>bussilab.wham</code>	38
Functions	38
Function <code>wham</code>	38
Classes	41
Class <code>WhamResult</code>	41
Ancestors (in MRO)	41
Instance variables	41

Module `bussilab`

A package collecting a heterogeneous set of tools.

This package collects a number of tools that are useful enough to be distributed but too small to deserve being published as separate packages. Source code is on [GitHub](https://github.com/bussilab/py-bussilab)¹. Submodules are listed at the end of the current page. Command-line tools are described at this page². A test pdf manual is available here³. This is the documentation for version 0.0.51.

Install

This package is only compatible with Python ≥ 3.8 (no compatibility with Python 2!). The recommended way to install this package depends on how you prefer to manage your python dependencies.

pip. If you manage your dependencies with pip and install packages in your home, use:

¹<https://github.com/bussilab/py-bussilab>

²[cli_documentation.html](#)

³[../bussilab.pdf](#)

```

pip install --user bussilab
# make sure the user installed packages can be imported, or add this to your python path
export PYTHONPATH="$(python -c 'import site; print(site.USER_SITE)'):$PYTHONPATH"
# make sure the bussilab script is in your execution the path, or add this to your shell path
export PATH="$(python -c 'import site; print(site.USER_BASE + "/bin")'):$PATH"

```

Required packages will be downloaded and installed automatically in your home.

pip + venv. If you manage your dependencies with pip and work in a virtual environment⁴, use:

```
pip install bussilab
```

Required packages will be downloaded and installed automatically in the virtual environment.

conda. If you manage your dependencies with conda, use:

```
conda install -c conda-forge -c bussilab py-bussilab
```

Required packages will be downloaded and installed automatically in the active conda environment.

macports. If you manage your dependencies with macports you might prefer to install required packages first. Since the list of requirements might change, it is recommended to use the bussilab package itself to obtain the list of requirements. You can do it as follows: ⁵

```

# install pip and setuptools first
sudo port install py39-pip py39-setuptools
# install a bare version of the package, without dependencies
pip-3.9 install --user --no-deps bussilab
# make sure the user installed packages can be imported, or add this to your python path
export PYTHONPATH="$(python3.9 -c 'import site; print(site.USER_SITE)'):$PYTHONPATH"
# make sure the bussilab script is your execution the path, or add this to your shell path
export PATH="$(python3.9 -c 'import site; print(site.USER_BASE + "/bin")'):$PATH"
# install the dependencies
sudo port install $(bussilab required --macports --pyver 39)

```

Notice that the list of required packages might change. It is thus recommended to run the commands above every time you update the bussilab package.

Checking the installation

Once the package is installed you should be able to import the module from the python interpreter:⁶

```

import bussilab
# this command can be used to check if all dependencies are in place:
bussilab.import_submodules()

```

You should also have access to an executable script that can be used from the command line:⁷

```

bussilab -h
# this command can be used to check if all dependencies are in place:
bussilab check --import

```

⁴<https://docs.python.org/3/library/venv.html>

⁵Notice that on macports the name of the python executable is python3.9 and the name of the pip installer is pip-3.9. A different python version should work as well.

⁶If you installed the package using the --user option, in order to be able to import the package you will have to make sure that the directory returned by the command `python -c 'import site; print(site.USER_SITE)'` is included in your python search path. If not, you can add it to the environment variable PYTHONPATH.

⁷If you installed the package using the --user option, in order to be able to execute the script you will have to make sure that the directory returned by the command `python -c 'import site; print(site.USER_BASE + "/bin")'` is included in your PATH environment variable. Alternatively, if the `bussilab` script is not in your PATH you can run it as `python -m bussilab -h`.

Setting autocompletion

In order to benefit from autocompletion for the executable script you should install the `argcomplete`⁸ package (with `pip`, `conda`, or `macports`) and add the following command to your `.bashrc` file:⁹

```
eval "$(register-python-argcomplete bussilab)"
```

Getting started

Python

The `bussilab` module itself only contains some basic infrastructure. Most of the features are implemented in the submodules listed at the end of this page. Submodules should be explicitly imported using, e.g.:

```
from bussilab import wham
```

Check their documentation to see how to use them.

You can directly use the submodules without importing them explicitly:

```
import bussilab as bl
bl.wham.wham()
```

Examples

In the examples¹⁰ directory you can find a number of notebooks that can be used as a source of inspiration.

Command line

In addition, the `bussilab` script allows to access some functionality directly from the command line, without entering python. For instance, you can execute the `wham` subcommand typing

```
bussilab wham
```

Check their documentation in the `cli_documentation`¹¹ submodule.

Advanced stuff

Notice that instructions below assume you are using `pip`. If you use `conda` or `macports` you might have to adjust the commands.

Install with no dependencies

You might want to ignore dependencies completely:

```
pip install --no-deps bussilab
```

If you proceed this way, you will still be able to import `bussilab` module and to execute the `bussilab` script, but some of the submodules might not be importable. The following command will report which submodules can be used then:

```
bussilab check --import
```

The result will depend on which of the required packages are already installed on your system.

Building documentation

You can build the documentation using `pdoc3`:

```
pip install pdoc3
pdoc3 -f --html -o doc/ bussilab
```

⁸<https://github.com/kislyuk/argcomplete>

⁹If you are using `macports`, the command would be `eval "$(register-python-argcomplete-3.9 bussilab)"`.

¹⁰[../examples](#)

¹¹[cli_documentation.html](#)

Documentation will be visible at `doc/bussilab/index.html`. This is normally not necessary, since the pre-built documentation of the latest version can be found at this link¹², but can be useful to test changes to the documentation before pushing them to GitHub.

Implementing your modifications

If you want to modify the Python source code you should download it from GitHub:

```
git clone https://github.com/bussilab/py-bussilab.git
cd py-bussilab
```

Since the module is written in pure python,¹³ it can be used by just adding its path to `PYTHONPATH` and the bin directory to `PATH`:

```
export PATH="/path/to/py-bussilab/bin:$PATH"
export PYTHONPATH="/path/to/py-bussilab:$PYTHONPATH"
```

Testing the code

If you modified the code, it is recommended to test that your changes did not break existing features.

You can run the tests using `pytest`:

```
pip install pytest
pytest
```

All tests should succeed. Notice that the tests will import the `bussilab` module. Thus, if you want the version modified by you to be tested (and not another version that you might have installed with `pip` already) you should properly set the `PYTHONPATH` variable as explained above.

Static types can be checked using `mypy`:

```
pip install mypy
mypy bussilab
```

This check should succeed.

Other static checks can be done with `pyflakes`:

```
pip install pyflakes
pyflakes bussilab
```

This check should succeed.

Correct code formatting can be checked using `pylint`:

```
pip install pylint
pylint -E bussilab
```

This check should succeed.

Running and rendering jupyter examples from the command line

The GitHub repository also contains jupyter examples. You can rerun all the jupyter examples from the command line:

```
cd examples
pip install jupyter jupyter_contrib_nbextensions matplotlib
./rerun.sh
```

You can render all the jupyter examples as html from the command line:

```
cd examples
pip install jupyter nbconvert
./render.sh
```

¹²<https://bussilab.github.io/doc-py-bussilab>

¹³This might change in the future.

Sub-modules

- [bussilab.ann](#)
- [bussilab.cli](#)
- [bussilab.cli_documentation](#)
- [bussilab.clustering](#)
- [bussilab.coretools](#)
- [bussilab.cron](#)
- [bussilab.installers](#)
- [bussilab.jremote](#)
- [bussilab.lohman](#)
- [bussilab.maxent](#)
- [bussilab.notify](#)
- [bussilab.pip](#)
- [bussilab.potts](#)
- [bussilab.reports](#)
- [bussilab.rna2d](#)
- [bussilab.wham](#)

Functions

Function `describe_submodule`

```
def describe_submodule(  
    module: str  
    ) -> str
```

Return a short description of a submodule without importing it.

Parameters

module : str Name of the module.

Returns

str The docstring of the module. If the docstring is not present, returns an empty string. If an empty string is passed as module, the docstring of the main package is returned.

Raises

ModuleNotFoundError If the module does not exist.

Examples

```
from bussilab import describe_submodule  
print(describe_submodule("lohman"))
```

Function `import_submodules`

```
def import_submodules() -> None
```

Import all the available submodules.

The main [bussilab](#) module does not explicitly import the available submodules so as not to slow down the behavior of the command line interface and to allow importing individual modules even if not all the dependencies of the other modules are installed. Use this function to import all the submodules (might take a few seconds).

Mostly for testing that the packages required by the available submodules are installed, but it can also be used to preload all the submodules (and required packages) making them load faster later.

Raises

If one or more submodules cannot be imported it will raise an Exception.

Function `list_submodules`

```
def list_submodules() -> List[str]
```

Return a list of all the available submodules.

It can be used to quickly show which submodules are available for importing.

Returns

list A list of names of available submodules.

Examples

Print the available submodules and a short description for each of them.

```
from bussilab import list_submodules, describe_submodule
for m in list_submodules():
    print(m, describe_submodule(m))
```

Function `required_conda`

```
def required_conda() -> List[str]
```

Function `required_macports`

```
def required_macports(
    pyver=''
) -> str
```

Function `required_pip`

```
def required_pip() -> str
```

Module `bussilab.ann`

Module with artificial neural networks.

ANN can be constructed with `cuda=True`, in which case it will use cudamat.

Classes

Class `ANN`

```
class ANN(
    layers,
    random_weights=False,
    init_b=0.0,
    activation='softplus',
    cuda=False
)
```

Methods

Method `apply`

```
def apply(
    self,
    x
)
```


Method applyVec

```
def applyVec(  
    self,  
    x  
)
```

Method backward

```
def backward(  
    self,  
    deriv,  
    hidden  
)
```

Method backward_par

```
def backward_par(  
    self,  
    deriv,  
    hidden  
)
```

Method cuda_setup

```
def cuda_setup(  
    self  
)
```

Method deriv

```
def deriv(  
    self,  
    x  
)
```

Method derivVec

```
def derivVec(  
    self,  
    x  
)
```

Method derpar

```
def derpar(  
    self,  
    x  
)
```

Method derparVec

```
def derparVec(  
    self,  
    x  
)
```

Method dumpPlumed

```
def dumpPlumed(
    self,
    path,
    style='ann',
    prefix=None,
    arguments=None
)
```

Method forward

```
def forward(
    self,
    x
)
```

Method getpar

```
def getpar(
    self
)
```

Method setpar

```
def setpar(
    self,
    par
)
```

Module bussilab.cli

Tools to implement the command line interface

This module is used internally to implement the command line interface. In addition, it can be used to run the commands that are available in the command line interface without the need to leave python:

```
from bussilab.cli import cli
cli("-h")
cli("wham -b bias") # provide the command line as a string
cli(["wham", "-b", "bias"]) # alternatively use a list
```

The documentation of all the commands can be found in the `cli_documentation`¹⁴ submodule.

Notice however that these commands typically have alternative python implementations that allow you to work directly on data structures and are thus more flexible. For instance, `wham()(bias)`, where `bias` is a numpy array, is often more convenient than `bussilab.cli.cli("wham -b bias")`, where `bias` is a file.

Functions

Function arg

```
def arg(
    *name,
    **kwargs
)
```

¹⁴[cli_documentation.html](#)

Decorator that adds an argument to a command line tool.

Parameters are passed to the `parser.add_argument()` function. It should be written **after** the `command()` decorator.

Function cli

```
def cli(
    arguments: str | List[str] = '',
    *,
    prog: str | None = '',
    use_argcomplete: bool = False,
    throws_on_parser_errors: bool = True
) -> int | None
```

Executes a command line tool from python.

This is the main function of this module and allows to launch all the subcommands available in the command line interface directly from python.

Parameters

arguments : str or list Command line arguments. If a string is passed, it is first split using `shlex.split()`
prog : str Name of the calling program. It is used to build help texts. **Mostly for internal use.**
use_argcomplete : bool If True, the `argcomplete` function of `argcomplete` module is called on the parser, so as to allow autocompletion in the command line tool. If `argcomplete` module is not installed, nothing is done and no failure is reported. **Mostly for internal use.**
throws_on_parser_errors : bool If True, in case of command line error it throws a `TypeError` exception. **Mostly for internal use.**

Returns

None or int If an error happens while parsing, it throws a `TypeError` exception, unless `throws_on_parser_errors` is set to false, in which case it returns the corresponding error code. If an error happens while executing the requested command, an exception is thrown. If everything goes well, it returns `None`.

Function command

```
def command(
    name: str,
    help: str | None = None,
    description: str | None = None,
    **kwargs
)
```

Decorator that registers a function as a subcommand.

This decorator should be written **before** the other decorators `arg()`, `group()`, and `endgroup()`.

Parameters

name : str Name of the subcommand (will be used on the command line)
help : str Short help message for the subcommand (one line).
description : str, optional Longer description. If not provided, it is set to a copy of help.
kwargs Other parameters are passed as is to the `add_parser` function of `argparse`.

Examples

Simple command line tool that accepts a single `--out` argument followed by a string and call the function `do_something` with that string as an argument.

```
from bussilab.cli import command, arg
```

```
@command("subcommand")
@arg("--out")
```

```
def myfunc(out):
    do_something(out)
```

Function `endgroup`

```
def endgroup(
    f: Callable | None = None
)
```

Decorator that ends a group of arguments for a command line tool.

See `group()`.

Function `group`

```
def group(
    title: str | Callable | None = None,
    description: str | None = None,
    exclusive: bool | None = None,
    required: bool | None = None
)
```

Decorator that adds a group of arguments for a command line tool.

It should be written **after** the `command()` decorator. It should be followed by a number of `arg()` decorators and by a closing `endgroup()` decorator.

Parameters

title : str The name of the group. Can only be used for non exclusive groups.

description : str A description of the group. Can only be used for non exclusive groups.

exclusive : bool If True, the arguments belonging to this group are mutually exclusive

required : bool If True, one of the arguments at least should be passed. Can only be used for exclusive groups.

Examples

This is a simple command line tool that accepts three arguments (`-a`, `-b`, or `-c`), mutually exclusive. When ran, it will just print booleans showing if these arguments were passed.

```
from bussilab.cli import command, group, arg, endgroup

@command("doit")
@group(exclusive=True)
@arg("-a", action='store_true')
@arg("-b", action='store_true')
@arg("-c", action='store_true')
@endgroup
def check(a, b, c):
    print(a, b, c)
```

Module `bussilab.cli_documentation`

Documentation for command line tools

This module only contains the documentation of the subcommands used in the command line interface. For all the subcommands, a short help identical to that generated by the `-h` option is shown. In addition, if present, the docstring of the function is also shown here.

`list`

usage: `bussilab list [-h]`

List available python modules.

options:

-h, --help show this help message and exit

check

usage: bussilab check [-h] [--import]

Check installed features

options:

-h, --help show this help message and exit
--import check if all the submodules can be imported

wham

usage: bussilab wham [-h] -b BIAS [-o OUT] [--use-frame-weight]
[--traj-weight [TRAJ_WEIGHT ...]] [-T T] [-m MAXITER]
[-t THRESHOLD] [-v]

Perform binless WHAM

options:

-h, --help show this help message and exit
-b BIAS, --bias BIAS File containing bias potential (default: None)
-o OUT, --out OUT Output file with weights (default: None)
--use-frame-weight
--traj-weight [TRAJ_WEIGHT ...]
-T T, --temperature T
system temperature in energy units (default: 1.0)
-m MAXITER, --maxiter MAXITER
maximum number of iterations (default: 1000)
-t THRESHOLD, --threshold THRESHOLD
threshold for convergence (default: 1e-40)
-v, --verbose

jrun

usage: bussilab jrun [-h] [-d] [--lab] [--port PORT] [--screen-cmd SCREEN_CMD]
[--screen-log SCREEN_LOG] [--python-exec PYTHON_EXEC]
[-S SOCKNAME] [--no-screen] [--keep-ld-library-path]
[--detach]

Run jupyter server

options:

-h, --help show this help message and exit
-d, --dry-run show command instead of executing it (default: False)
--lab use jupyterlab (default: False)
--port PORT set port (default: 0)
--screen-cmd SCREEN_CMD
screen command (default: screen)
--screen-log SCREEN_LOG
screen logfile (no logfile by default) (default:)
--python-exec PYTHON_EXEC
python executable (default:)
-S SOCKNAME, --sockname SOCKNAME
screen sockname (default: (path):(port):jupyter)

```

--no-screen          do not run screen (default: False)
--keep-ld-library-path
                    (ignored, this is the default now) (default: False)
--detach            detach screen (default: False)

```

This is a tool to run a jupyter server within a screen command. The typical usage would be

```

cd /path/to/your/notebook/dir
bussilab jrun

```

A free port is identified first (can be overridden with the `--port` option) and a jupyter server is then run inside a screen instance. You will thus have to type `CTRL+aCTRL+d` in order to detach the screen letting it run in the background.

Alternatively, you can immediately detach the screen with

```

cd /path/to/your/notebook/dir
bussilab jrun --detach

```

Notice that, since the server is run inside a screen instance, in order to visualize python outputs that has been sent directly to the terminal you should connect to the screen instance later. By default, a socket name containing the path where the server is running is used, with `/` replaced by `..`. It should thus be easy to use `screen -ls` to find the proper screen instance. `## jremote`

```

usage: bussilab jremote [-h] [-d] [-l] [--port PORT] [-i INDEX]
                        [--python-exec PYTHON_EXEC] [--server-url SERVER_URL]
                        [--open-cmd OPEN_CMD]
                        server

```

Run jupyter client

positional arguments:

```

server              server URL (e.g. giorgione.phys.sissa.it)

```

options:

```

-h, --help          show this help message and exit
-d, --dry-run       show command instead of executing it (default: False)
-l, --list-only     only report a list or servers (default: False)
--port PORT        set port (default: 0)
-i INDEX, --index INDEX
                  choose server, by default interactive choice (default:
                  0)
--python-exec PYTHON_EXEC
                  remote python executable (e.g. module load python3
                  python-home; python) (default: python)
--server-url SERVER_URL
                  URL on server (default: choose interactively)
                  (default: )
--open-cmd OPEN_CMD
                  open command (detected automatically by default)
                  (default: )

```

This is a tool to connect to a remote running jupyter server. The typical usage would be

```

bussilab jremote server.url

```

A list of jupyter servers running on the selected machines will be shown, and one of them can be picked typing its progressive number. In case there is a single server running, it will be opened by default.

Notice that if the name of the python executable on the server is different from plain python you can override it with `--python-exec`. You can also run other scripts before, for instance loading relevant modules:

```

bussilab jremote giorgione.phys.sissa.it          --python-exec "module load python3 python-home;

```

If you recurrently connect to the same workstation, it is convenient to write a small script like this one, call it jremote and put it in your path:

```
export PYTHONPATH=/path/to/bussilab/source
python -m bussilab jremote giorgione.phys.sissa.it --python-exec "module load python3 python-home ;
```

Here replace python with the name of your python interpreter (might be python3.7). ##
pip_upgrade_all

usage: bussilab pip_upgrade_all [-h] [--user]

Upgrade all packages with pip

options:

-h, --help show this help message and exit
--user install/upgrade in user location (default: False)

This is a tool to upgrade all your packages with pip. It is a convenient way to upgrade all the packages without the need to list them explicitly.

Warning: this uses pip, so it might not work as expected if you are working in conda.

The typical usage would be

bussilab pip_upgrade_all

If you installed packages in your home you should use

bussilab pip_upgrade_all --user

notify

usage: bussilab notify [-h] [-m MESSAGE] [--markdown-file MARKDOWN_FILE]
[-c CHANNEL | -u UPDATE | -d DELETE | -r REPLY | -R REPLY_BROADCAST | -X REACT]
[-f FILE [FILE ...]] [-t TITLE] [--no-footer]
[--no-unfurl] [--screenlog SCREENLOG]
[--screenlog-maxlines SCREENLOG_MAXLINES] [--type TYPE]
[--token TOKEN] [-q]

Send a notification to Slack

options:

-h, --help show this help message and exit
-m MESSAGE, --message MESSAGE message (default: None)
--markdown-file MARKDOWN_FILE path to a standard Markdown message (default: None)
-c CHANNEL, --channel CHANNEL channel (check ~/.bussilabrc by default) (default: None)
-u UPDATE, --update UPDATE url of the message to be updated (default: None)
-d DELETE, --delete DELETE url of the message to be deleted (default: None)
-r REPLY, --reply REPLY url of the message to be replied (default: None)
-R REPLY_BROADCAST, --reply-broadcast REPLY_BROADCAST url of the message to be broadcast-replied (default: None)
-X REACT, --react REACT react to a message (default: None)
-f FILE [FILE ...], --file FILE [FILE ...] path(s) to files to be uploaded (incompatible with -u

```

                                and -d) (default: None)
-t TITLE, --title TITLE
                                title of the message (default: None)
--no-footer                    ignore footer (default: False)
--no-unfurl                    disable link and media previews (default: False)
--screenlog SCREENLOG
                                screenlog file (default: None)
--screenlog-maxlines SCREENLOG_MAXLINES
                                maximum number of lines in screenlog (0 means all)
                                (default: 0)
--type TYPE
                                'plain_text' or 'mrkdwn' (use --markdown-file for
                                standard Markdown) (default: mrkdwn)
--token TOKEN
                                token (check ~/.bussilabrc by default) (default: None)
-q, --quiet
                                quiet (do not write output) (default: False)

```

This is a tool to send a notification to Slack. See the documentation of [bussilab.notify](#). ## cron

```

usage: bussilab cron [-h] [--quick-start]
                    [--quick-start-skip-steps QUICK_START_SKIP_STEPS]
                    [--quick-start-event QUICK_START_EVENT]
                    [--cron-file CRON_FILE] [--screen-cmd SCREEN_CMD]
                    [--screen-log SCREEN_LOG] [--no-screen]
                    [--keep-ld-library-path] [-S SOCKNAME]
                    [--python-exec PYTHON_EXEC] [--detach] [--unique]
                    [--window] [--period PERIOD] [--max-times MAX_TIMES]

```

Run cron

options:

```

-h, --help
                                show this help message and exit
--quick-start
                                run immediately (default: False)
--quick-start-skip-steps QUICK_START_SKIP_STEPS
                                skip steps on quick start (default: None)
--quick-start-event QUICK_START_EVENT
                                event number for quick start (default: None)
--cron-file CRON_FILE
                                path to cron file (default: None)
--screen-cmd SCREEN_CMD
                                screen command (default: screen)
--screen-log SCREEN_LOG
                                screen logfile (no logfile by default) (default: )
--no-screen
                                do not run screen (default: False)
--keep-ld-library-path
                                (ignored, this is the default now) (default: False)
-S SOCKNAME, --sockname SOCKNAME
                                screen sockname (default: (path):cron)
--python-exec PYTHON_EXEC
                                python executable (default: )
--detach
                                detach screen (default: False)
--unique
                                allow only one screen with this socket (default:
                                False)
--window
                                run a new window within the same screen (default:
                                False)
--period PERIOD
                                period (seconds) default read from cron file or set to
                                3600 (default: None)
--max-times MAX_TIMES
                                maximum number of calls (default: None)

```


required

usage: bussilab required [-h] [--macports | --conda] [--pyver PYVER]

print requirements

options:

-h, --help show this help message and exit
--macports macports syntax (default: False)
--conda conda syntax (default: False)
--pyver PYVER pyversion (e.g. 38), for macports only (default:)

Module `bussilab.clustering`

Module with some clustering tools

Functions

Function `daura`

```
def daura(  
    adj,  
    weights=None,  
    *,  
    min_size=0,  
    max_clusters=None  
)
```

Clustering algorithm introduced in Daura et al, Angew. Chemie (1999).

WARNING: important fix in v0.0.39 for version with weights

Parameters

adj : **array_like**, **square matrix** `adj[i,j]` contains 1 (or True) if frames `i` and `j` are adjacent, 0 (or False) otherwise.

weights : **array_like**, **optional** `weights[i]` contains the weight of the `i`-th frame.

min_size : **number** Minimum cluster size. Clusters smaller than this size are not reported. When using weights, the cluster size is defined as the sum of the weights of the members of the cluster.

max_clusters : **int** Maximum number of clusters.

Example

```
import scipy.spatial.distance as distance  
dist=distance.squareform(distance.pdist(trajjectory))  
clustering.daura(dist<0.7)
```

Function `max_clique`

```
def max_clique(  
    adj,  
    weights=None,  
    *,  
    min_size=0,  
    max_clusters=None,  
    use_networkit=False  
)
```

Clustering algorithm used in Reisser et al, NAR (2020)¹⁵.

Parameters

¹⁵<https://doi.org/10.1093/nar/gkz1184>

adj : array_like, square matrix adj[i,j] contains 1 (or True) if frames i and j are adjacent, 0 (or False) otherwise.

weights : array_like, optional weights[i] contains the weight of the i-th frame.

min_size : number Minimum cluster size. Clusters smaller than this size are not reported. When using weights, the cluster size is defined as the sum of the weights of the members of the cluster.

max_clusters : int Maximum number of clusters.

use_networkit : bool, optional if True, use a networkit implementation that seems to be faster. It requires python package networkit to be installed in advance!

Example

```
import scipy.spatial.distance as distance
dist=distance.squareform(distance.pdist(trajjectory))
clustering.max_clique(dist<0.7)
```

Function qt

```
def qt(
    distances,
    cutoff,
    weights=None,
    *,
    min_size=0,
    max_clusters=None
)
```

Quality threshold clustering.

The method is explained in the original paper¹⁶. The implementation has been adapted from this one¹⁷, which is also released under a GPL licence. Thus, if you use this algorithm please cite this article¹⁸, which also discusses the important differences between this algorithm and the Daura et al algorithm in the context of analysing molecular dynamics simulations. Additionally, mention which exact version of the bussilab package you used.

The implementation included here, at variance with the original one, allows passing weights and can be used with arbitrary metrics. In addition, it also reports clusters of size 1 (unless one passes max_clusters>1). The code is optimized when compared with the original one, and speed can be further increased by passing `np.array(distances, dtype='float32')` to distances.

WARNING: important fix in v0.0.39 for version with weights

As of version v0.0.40, clusters with the same number of members are prioritized based on their diameter (smaller diameter gets the priority). This is expected to make non-weighted calculations more reproducible, but might change some results when compared with previous versions. In addition, when growing a single candidate cluster, if two points are at the same distance from the growing cluster the one with higher weight is chosen. With these priorities, any choice where either (a) weights are float or (b) distances are float should lead to determinising clustering irrespective of roundoff errors, assuming floats are never identical.

Parameters

distances : array_like, square matrix distances[i,j] contains the distance between i and j frame.

cutoff : number maximum distance for two frames to be included in the same cluster

weights : array_like, optional weights[i] contains the weight of the i-th frame.

min_size : number Minimum cluster size. Clusters smaller than this size are not reported. When using weights, the cluster size is defined as the sum of the weights of the members of the cluster.

max_clusters : int Maximum number of clusters.

Example

¹⁶<https://doi.org/10.1101/gr.9.11.1106>

¹⁷<https://github.com/rglez/QT>

¹⁸<https://doi.org/10.1021/acs.jcim.9b00558>

```
import scipy.spatial.distance as distance
dist=distance.squareform(distance.pdist(trajjectory))
clustering.qc(dist,0.7)

clustering.qc(np.array(dist,dtype='float32')) # should be slightly faster
```

Classes

Class ClusteringResult

```
class ClusteringResult(
    *,
    method: str,
    clusters: list,
    weights: list | None
)
```

Result of a [bussilab.clustering](#) calculation.

Ancestors (in MRO)

- [bussilab.coretools.Result](#)
- [builtins.dict](#)

Instance variables

Variable clusters list of lists containing the members of each cluster.

Variable method str containing the name of the method used.

Variable weights list containing the weights of the clusters.

Module `bussilab.coretools`

General purpose tools.

Functions

Function `cd`

```
def cd(
    newdir: os.PathLike,
    *,
    create: bool = False
)
```

Context manager to temporarily change working directory.

Can be used to change working directory temporarily making sure that at the end of the context the working directory is restored. Notably, it also works if an exception is raised within the context.

Parameters

newdir : path Path to the desired directory.

create : bool (default False) Create directory first. If the directory exists already, no error is reported

Examples

```
from bussilab.coretools import cd
with cd("/path/to/dir"):
```

```

do_something() # this is executed in the /path/to/dir directory
do_something_else() # this is executed in the original directory

```

Function config

```

def config(
    path: os.PathLike | None = None
)

```

Function config_path

```

def config_path(
    path: os.PathLike | None = None
)

```

Function ensure_np_array

```

def ensure_np_array(
    arg
) -> numpy.ndarray | None

```

Convert arg to np.array if necessary.

Function file_or_path

```

def file_or_path(
    arg,
    mode: str
)

```

Convert a path to an open file object if necessary.

Function import_numba_jit

```

def import_numba_jit()

```

Return a numba.njit object. If import fails, return a fake jit object and emits a warning.

Currently, the returned object can only be used as @njit (no option). It might be extended to allow more jit options.

Classes

Class Result

```

class Result(
    *args,
    **kwargs
)

```

Base class for objects returning results.

It allows one to create a return type that is similar to those created by `scipy.optimize.minimize`. The string representation of such an object contains a list of attributes and values and is easy to visualize on notebooks.

Examples The simplest usage is this one:

```

from bussilab import coretools

class MytoolResult(coretools.Result):
    """Result of a mytool calculation."""
    pass

```

```
def mytool():
    a = 3
    b = "ciao"
    return MytoolResult(a=a, b=b)
```

```
m=mytool()
print(m)
```

Notice that the class variables are dynamic: any keyword argument provided in the class constructor will be processed. If you want to enforce the class attributes you should add an explicit constructor. This will also allow you to add pdoc docstrings. The recommended usage is thus:

```
from bussilab import coretools

class MytoolResult(coretools.Result):
    """Result of a mytool calculation."""
    def __init__(a, b):
        super().__init__()
        self.a = a
        """Documentation for attribute a."""
        self.b = b
        """Documentation for attribute b."""

def mytool():
    a = 3
    b = "ciao"
    return MytoolResult(a=a, b=b)

m = mytool()
print(m)
```

Ancestors (in MRO)

- [builtins.dict](#)

Descendants

- [bussilab.clustering.ClusteringResult](#)
- [bussilab.maxent.MaxentResult](#)
- [bussilab.potts.InferResult](#)
- [bussilab.wham.WhamResult](#)

Class TestCase

```
class TestCase(
    methodName='runTest'
)
```

Improved base class for test cases.

Extends the unittest.TestCase class with some additional assertion.

Create an instance of the class that will use the named test method when executed. Raises a ValueError if the instance does not have a method with the specified name.

Ancestors (in MRO)

- [unittest.case.TestCase](#)

Methods

Method `assertEqualFile`

```
def assertEqualFile(
    self,
    file1: os.PathLike,
    file2: os.PathLike | None = None
)
```

Check if two files are equal.

Parameters

file1 : **path** Path to the first file

file2 : **path**, **optional** Path to the second file. If not provided, defaults to `file1+".ref"`.

Module `bussilab.cron`

Functions

Function `cron`

```
def cron(
    *,
    quick_start: bool = False,
    quick_start_skip_steps: int = 0,
    quick_start_event: int = 0,
    cron_file: str = '',
    screen_cmd: str = 'screen',
    screen_log: str = '',
    no_screen: bool = True,
    keep_ld_library_path: bool = True,
    sockname: str = '(path):cron',
    python_exec: str = '',
    detach: bool = False,
    period: int | None = None,
    max_times: int | None = None,
    unique: bool = False,
    window: bool = False
)
```

Module `bussilab.installers`

Install and build selected external scientific packages.

At present, the functions in this module support Google Colab only.

Functions

Function `build_viennarna`

```
def build_viennarna(
    version: str = '2.7.2-patch2',
    output_directory: str | os.PathLike | None = None,
    jobs: int | None = None,
    verbose: bool = True
) -> Tuple[pathlib.Path, pathlib.Path]
```

Build a patched ViennaRNA archive in Google Colab.

The archive and its complete build log receive the same basename.

Parameters

version Patched release identifier, for example "2.7.2-patch2".
output_directory Destination for the .tgz and .log files. The default is the current working directory.
jobs Number of parallel make jobs. The default is at most two, to avoid excessive memory use while compiling the SWIG wrapper.
verbose Print progress information and the final elapsed time.

Returns

archive, log Paths of the generated archive and build log.

Function `install_viennarna`

```
def install_viennarna(
    version: str = '2.7.2-patch2',
    prefix: str | os.PathLike | None = None,
    force: bool = False,
    verbose: bool = True
)
```

Install a precompiled patched ViennaRNA distribution in Google Colab.

Parameters

version Patched release identifier, for example "2.7.2-patch2".
prefix Installation directory. The default is ViennaRNA below the current working directory.
force Download and extract the archive again if the installation directory already exists.
verbose Print progress information.

Returns

module The imported `:mod:RNA` module.

Raises

RuntimeError If the function is not running in Google Colab, the archive is malformed, or the installed module cannot be imported.

Module `bussilab.jremote`

Module implementing tools for remote jupyter connections.

This module contains some utilities that are mostly designed to be used as command line tools. The interface of the functions defined in this module is subject to changes. One should instead use the subcommands `jrun` and `jremote` in the `cli_documentation`¹⁹ submodule.

Functions

Function `find_free_port`

```
def find_free_port()
```

Returns the number of a free port.

Function `remote`

```
def remote(
    server: str,
    python_exec: str = 'python',
    dry_run: bool = False,
    list_only: bool = False,
    server_url: str = '',
    port: int = 0,
    index: int = 0,
```

¹⁹[cli_documentation.html](#)

```

        open_cmd: str = ''
    )

```

Function `run_server`

```

def run_server(
    dry_run: bool = False,
    port: int = 0,
    screen_cmd: str = 'screen',
    screen_log: str = '',
    no_screen: bool = False,
    keep_ld_library_path: bool = True,
    python_exec: str = '',
    sockname: str = '(path):(port):jupyter',
    lab: bool = False,
    detach: bool = False
)

```

Runs a jupyter server inside a screen command.

This function is only designed to be used as a command line tool.

Module `bussilab.lohman`

Module implementing Lohman model for helicases.

Functions

Function `lohman`

```

def lohman(
    t,
    ku: float,
    kd: float,
    n: int = 1,
    boundaries: Tuple[float, float] = (0.0, 1.0)
) -> float | numpy.ndarray

```

Lohman model for helicases.

Compute the fraction of unwound helices as a function of time. See Lucius et al, Biophys J 2003²⁰.

Parameters

t : float or sequence or np.ndarray Time. If a sequence or np.ndarray is provided, the function is computed for all values and an array is returned.

ku : float Unwinding rate.

kd : float Dissociation rate.

n : int, optional Step size

boundaries : tuple with 2 elements Result is mapped to this range.

Returns

float or np.ndarray The fraction of unfolded helices at a given time t. If an array is provided for t, an array is returned containing the fractions at all the times. If boundaries is provided, the fraction is linearly mapped into the boundaries[0], boundaries[1] range.

Module `bussilab.maxent`

Tools to perform reweighting using MaxEnt.

²⁰<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC1303449/>

Functions

Function maxent

```
def maxent(
    traj,
    reference,
    *,
    logW=None,
    maxiter: int = 1000,
    verbose: bool = False,
    lambdas=None,
    l2=None,
    l1=None,
    method: str = 'L-BFGS-B',
    regularization: Callable | None = None,
    tol: float | None = None,
    options=None,
    cuda=False
)
```

Tool that computes new weights to enforce reference values.

This tool processes an array containing the observables computed along a trajectory and returns new weights that satisfy the maximum entropy principle and so that weighted averages agree with reference values.

Parameters

traj : **array_like** A 2D array (lists or tuples are internally converted to numpy arrays). `traj[i,j]` is `j`-th observable computed in the `i`-th frame. If `traj` is a `CUDAMatrix` object, then `cudamat` is used irrespectively of the `bool` parameter `cuda`.

reference : **array_like** A 1D array (lists or tuples are internally converted to numpy arrays) containing the reference values to be enforced. If the `i`-th element is a tuple or an array with 2 elements, they are interpreted as boundaries. For instance, `reference=[1.0, (2.0,3.0)]` will make sure the first observable has value 1 and the second observable is within the range (2,3). Boundaries equal to `+np.inf` or `-np.inf` can be used to imply no boundary. Notice that boundaries in the form (A,B) where both A and B are finite are implemented by adding fictitious variables in a way that is transparent to the user. Boundaries in the form (A,B) where one of A or B is finite and the other is infinite are implemented as boundaries on `lambdas`. Boundaries in the form (A,A) are interpreted as constraints.

logW : **array_like** A 1D array (lists or tuples are internally converted to numpy arrays) containing the logarithm of the a priori weight of the provided frames.

lambdas : **array_like** A 1D array with initial values of `lambda`. A good guess will minimize faster. A typical case would be recycling the `lambdas` obtained with slightly different regularization parameters.

l2 : **None, float, or array_like** Prefactor for L2 regularization. If `None`, no regularization is applied. If `float`, the same factor is used on all the `lambdas`. If it is an array, it should have length equal to `len(reference)`.

l1 : **None, float, or array_like** Prefactor for L1 regularization. If `None`, no regularization is applied. If `float`, the same factor is used on all the `lambdas`. If it is an array, it should have length equal to `len(reference)`.

regularization : **callable or None** A function that takes as argument the current `lambdas` and return an tuple containing the regularization function and its derivatives. For instance, passing a function defined as `def reg(x): return (0.0001*0.5*np.sum(x**2),0.0001*x)` is equivalent to passing `l2=0.0001`.

verbose : **bool** If `True`, progress informations are written on `stdout`.

method : **str** Minimization method. See documentation of `scipy.optimize.minimize`.

maxiter : **int** Maximum number of iterations

tol : **float or None** Tolerance for minimization. See documentation of `scipy.optimize.minimize`.

options : **dict** Arbitrary options passed to `scipy.optimize.minimize`.

cuda : **bool or None (default False)** Use cuda. If None, chosen based on the availability of the cudamat library.

Notes On Using Cuda

Note that for normal datasets the cost of transferring the traj object to the GPU dominates. It is however possible to transfer the traj object first to the GPU with `cu_traj=cm.CUDAMatrix(traj)` and then reuse it for multiple calls (e.g. for a hyper parameter scan).

Classes

Class MaxentResult

```
class MaxentResult(
    *,
    logW_ME: numpy.ndarray,
    lambdas: numpy.ndarray,
    averages: numpy.ndarray,
    gamma: float,
    success: bool,
    message: str,
    nfev: int,
    nit: int
)
```

Result of a `maxent()` calculation.

Ancestors (in MRO)

- [bussilab.coretools.Result](#)
- [builtins.dict](#)

Instance variables

Variable averages np.ndarray with len(reference) elements, resulting averages.

Variable gamma float containing the resulting likelihood Gamma.

Variable lambdas np.ndarray with len(reference) elements, optimized Lagrangian multipliers.

Variable logW_ME np.ndarray with traj.shape[0] elements, logarithms of the optimized weights.

Variable message str reporting the possible reason of failure of the minimizer.

Variable nfev int reporting the number of function evaluations.

Variable nit int reporting the number of iterations in the minimization procedure.

Variable success bool reporting the success of the minimizer.

Module `bussilab.notify`

Module implementing Slack notifications.

This module sends notification through an App installed in the Slack workspace. Some settings are needed first for authentication. It is recommended to add a file named `.bussilabrc` to your home directory with the following content:

```
notify:
  token: xoxb-00000
  channel: U00000
```

The token here should be provided by the administrator of your workspace. The channel should be the Slack ID associated to your user. It can be found looking in your Slack profile. With these settings, the tool will send notifications to you by default.

Notifications can then be sent using either the command line:

```
bussilab notify --message "text here"
```

or from python:

```
from bussilab.notify import notify
notify("text here")
```

Notice that the message is optional. Even with an empty message, the footer will allow you to reconstruct from which machine and directory the message was sent from. This might be sufficient for your goal.

Link and media previews can be disabled using the unfurl option:

```
bussilab notify --message "https://example.com" --no-unfurl
```

or from python:

```
notify("https://example.com", unfurl=False)
```

A file written in standard Markdown can be sent without adding a title or footer:

```
bussilab notify --markdown-file report.md
```

or from python:

```
notify(markdown_file="report.md")
```

You can also indicate a specific channel for the notification using the channel option:

```
bussilab notify --message "text here" --channel "project-myproject"
```

or from python:

```
from bussilab.notify import notify
notify("text here", channel="project-myproject")
```

This will only work if the App has been added to the specified channel.

The following syntax can be used to upload one or more files:

```
bussilab notify --message "text here" --file /path/to/file
bussilab notify --message "text here" --file first.dat second.dat
```

or from python:

```
from bussilab.notify import notify
notify("text here", file="/path/to/file")
notify("text here", file=["first.dat", "second.dat"])
```

The commands above will return the URL of the message. This URL can be used later to update or delete them or to post reactions:

```
url=$(bussilab notify --message "text here")
bussilab notify --update $url --message "revised message"
bussilab notify --react $url:heart
```

this will remove only the reaction:

```
bussilab notify --delete $url:heart
```

this will remove the entire message:

```
bussilab notify --delete $url
```

```
url=$(bussilab notify --message "text here")
```

or from python:

```
from bussilab.notify import notify
url=notify("text here")
notify("revised message", update=url)
notify(react=url+":heart")
notify(delete=url+":heart")
notify(delete=url)
```

In these cases, the channel is not needed and should not be provided. Notice that you will only be able to update or delete messages sent through the App.

Functions

Function notify

```
def notify(
    message: str = '',
    channel: str = None,
    *,
    markdown_file: str = '',
    react: str = None,
    update: str = None,
    delete: str = None,
    reply: str = None,
    reply_broadcast: str = None,
    title: str = '',
    screenlog: str = '',
    screenlog_maxlines: int = 0,
    footer: bool = True,
    unfurl: bool = True,
    type: str = 'mrkdwn',
    file: str | Sequence[str] = '',
    token: str = None
)
```

Tool to send notifications to Slack.

Parameters

message : str A string that will form the body of the message.

channel : None or str The channel. By default, taken from your ~/.bussilabrc configuration file.

markdown_file : str Read a standard Markdown message from this UTF-8 text file. This implies type="markdown" and cannot be combined with a non-empty message argument.

update : None or str The URL of a message to be updated.

delete : None or str The URL of a message to be deleted. By passing a URL concatenated with the string ":name_of_reaction" you can delete a reaction. By passing comma-separated URLs you can delete a message and all the files shared with it.

reply : None or str The URL of a message to be replied

reply_broadcast : None or str The URL of a message to be broadcast-replied

react : None or str The URL of a message to which you want to add a reaction, followed by the string :name_of_the_reaction

file : str or sequence of str The path of a file to be uploaded, or paths of multiple files.

title : str The title of the notification.

screenlog : str The path of a GNU Screen log file. Its contents are displayed in a fenced native Markdown block.

screenlog_maxlines : int If positive, include only this many lines from the end of the Screen log.

footer : bool If True, a footer is added with current user, machine, and directory.

unfurl : **bool** If False, link and media previews are disabled when posting a message or a reply. The option does not affect file-upload comments or message updates.
type : **str** The type of message. Can be “mrkdwn”, “plain_text”, or “markdown”. Standard Markdown uses a native Markdown block; title, screenlog, file uploads, and footers are not supported.
token : **None or str** The token. By default, taken from your ~/.bussilabrc configuration file.

Returns

str
A string with the URL of the sent message.
In case the `<code>delete</code>` keyword is used, it returns an empty string.
When files are uploaded, it returns comma-separated URLs for the message followed by every file.

Example

```
from bussilab.notify import notify
notify("send this message")
```

See [bussilab.notify](#) for more examples.

Module `bussilab.pip`

Module implementing a small tool for installing and updating packages with pip.

Functions

Function `install`

```
def install(
    packages: str | List[str],
    *,
    upgrade: bool = False,
    user: bool = False,
    timeout: int | None = None
)
```

Install one or more packages with pip.

Install packages making sure they get installed with the currently used python interpreter.

Parameters

packages : **str or list** Package to be installed/upgraded. If a list is passed, multiple packages are installed/upgraded.

upgrade : **bool, optional** if True, run pip with `--upgrade`.

user : **bool, optional** if True, run pip with `--user`.

Function `upgrade_all`

```
def upgrade_all(
    user: bool = False,
    *,
    timeout: int | None = None
)
```

Upgrade all installed packages using pip.

Warning: it assumes all available packages are installed with pip.

Parameters

user : **bool, optional** if True, install/upgrade packages in with `--user` option.

Function `upgrade_self`

```
def upgrade_self(
    *,
    user: bool = False,
    timeout: int | None = None
)
```

Module `bussilab.potts`

Module containing a tool to solve Potts models by enumeration

See [Model](#).

Classes

Class `InferResult`

```
class InferResult(
    *,
    h: numpy.ndarray,
    J: numpy.ndarray,
    averages: numpy.ndarray,
    loglike: float,
    success: bool,
    message: str,
    nfev: int,
    nit: int
)
```

Result of a [Model.infer\(\)](#) calculation.

Ancestors (in MRO)

- [bussilab.coretools.Result](#)
- [builtins.dict](#)

Instance variables

Variable `J` `np.ndarray`, optimized `h`.

Variable `averages` `np.ndarray`, resulting averages.

Variable `h` `np.ndarray`, optimized `h`.

Variable `loglike` `float` containing the resulting likelihood `Gamma`.

Variable `message` `str` reporting the possible reason of failuer of the minimizer.

Variable `nfev` `int` reporting the number of function evaluations.

Variable `nit` `int` reporting the number of iterations in the minimization procedure.

Variable `success` `bool` reporting the success of the minimizer.

Class Model

```
class Model(  
    size: int,  
    colors: int = 1,  
    shifted: bool = False,  
    fullmatrix: bool = True  
)
```

Init model. size: number of spins colors: number of colors fullmatrix: set to False to use less memory (slower)

Methods

Method compute

```
def compute(  
    self,  
    h: numpy.ndarray,  
    J: numpy.ndarray  
)
```

Compute averages $\langle \sigma_i, \sigma_j \rangle$ for a coupling matrix J. Returns (a,b) with a=free energy and b=averages

Method draw

```
def draw(  
    self,  
    h: numpy.ndarray,  
    J: numpy.ndarray,  
    n: int  
)
```

Compute averages for a coupling matrix J sampling n states.

Method fixJ

```
def fixJ(  
    self,  
    J: numpy.ndarray  
)
```

Method infer

```
def infer(  
    self,  
    averages: numpy.ndarray,  
    nseq: int = 1,  
    reg: Callable | None = None  
)
```

Method loglike

```
def loglike(  
    self,  
    h: numpy.ndarray,  
    J: numpy.ndarray,  
    ave: numpy.ndarray  
)
```

Compute -log likelihood for a coupling matrix J with averages ave. Returns (a,b) with a=-log likelihood and b=derivatives

Method `random_couplings`

```
def random_couplings(
    self,
    seed: int | None = None
)
```

Module `bussilab.reports`

Functions

Function `workstations`

```
def workstations(
    wks: List | None = None,
    short: bool = True
)
```

Module `bussilab.rna2d`

RNA secondary-structure ensembles built on ViennaRNA.

The module wraps `RNA.fold_compound` with a higher-level model that is useful when the energy depends on whether particular nucleotides are paired. Compared with using ViennaRNA directly, `:class:Molecule` provides continuous per-nucleotide pairing penalties without losing sub-centikcal precision, arbitrary coupled biases on selected paired/unpaired states, and transparent combination of the resulting conditioned ensembles. The same interface then provides MFE structures, structure evaluation, partition functions, base-pair probabilities, ensemble diversity, exact free-energy derivatives, Boltzmann sampling, suboptimal ensembles, and joint pairing probabilities.

The wrapper also manages thermodynamic parameter sets, caches calculations, recovers from partition-function scaling failures, and defaults to disabling ViennaRNA's partition-function energy smoothing so that partition functions, sampling, MFE, evaluation, and suboptimal structures share one energy model. The `:func:sample_to_numpy()` and `:func:suboptimal_to_numpy()` helpers convert structure collections to NumPy pair tables and normalized log weights.

ViennaRNA's Python package is an optional dependency of `bussilab` but is required when constructing a `:class:Molecule`.

Functions

Function `reset_default_parameters`

```
def reset_default_parameters()
```

Restore the original thermodynamic defaults for new molecules.

Function `sample_to_numpy`

```
def sample_to_numpy(
    samples,
    *,
    deduplicate=True
)
```

Convert sampled dot-bracket structures to NumPy arrays.

The input may be either a sequence of structure strings, as returned by `Molecule.sample(weights=False)`, or a sequence of `(structure, log_weight)` pairs, as returned by `Molecule.sample(weights=True)`. Mixed inputs are rejected.

Structures are represented by zero-based pair tables: `states[k, i]` is the index paired with nucleotide `i` in structure `k`, or `-1` when it is unpaired. This is a NumPy-oriented adaptation of ViennaRNA's pair table format. A row table can be converted to ViennaRNA's convention with `np.concatenate((len(table), table + 1))`: ViennaRNA prepends the sequence length, uses one-based partner indices, and uses zero for an unpaired nucleotide.

Parameters

samples : sequence of str or sequence of (str, float) Unweighted structures or structures with unnormalized log weights.

deduplicate : bool, default=True If True, merge identical structures. Unweighted occurrences are combined through their counts; supplied log weights are combined using logarithmic addition. If False, retain every occurrence.

Returns

states : ndarray of int16, shape (n_structures, sequence_length) Zero-based pair tables, with `-1` denoting an unpaired nucleotide.

logweights : ndarray of float, shape (n_structures,) Normalized log weights, satisfying `sum(exp(logweights)) == 1` up to floating-point precision.

Function `set_default_parameters`

```
def set_default_parameters(
    *,
    temperature=None,
    no_lonely_pair=None,
    pf_smooth=None,
    NaCl=None,
    parameters=None
)
```

Update the default thermodynamic parameters for new molecules.

Parameters set to None are left unchanged. Existing molecules are not affected. Use `:func:reset_default_parameters()` to restore all original defaults, including ViennaRNA's default salt concentration.

Function `suboptimal_to_numpy`

```
def suboptimal_to_numpy(
    suboptimal,
    temperature
)
```

Convert suboptimal dot-bracket structures and energies to NumPy arrays.

Structures use the same zero-based pair-table representation documented by `:func:sample_to_numpy()`. Energies are converted to Boltzmann log weights at the explicitly supplied temperature.

Parameters

suboptimal : sequence of (str, float) Structure and energy pairs, in kcal/mol, as returned by `Molecule.suboptimal_structures()`.

temperature : float Temperature in kelvin.

Returns

states : ndarray of int16, shape (n_structures, sequence_length) Zero-based pair tables, with `-1` denoting an unpaired nucleotide.

logweights : ndarray of float, shape (n_structures,) Normalized Boltzmann log weights, satisfying `sum(exp(logweights)) == 1` up to floating-point precision.

Classes

Class Molecule

```
class Molecule(
    seq: str,
    *,
    lambdas1d=None,
    temperature=None,
    force_paired=None,
    force_unpaired=None,
    state_positions=None,
    state_biases=None,
    reduce_state_space=True,
    no_lonely_pair=None,
    pf_smooth=None,
    NaCl=None,
    parameters=None
)
```

Model an RNA secondary-structure ensemble with pairing-dependent energies.

Molecule retains ViennaRNA's nearest-neighbor secondary-structure energy and augments it with continuous one-body pairing penalties and, optionally, arbitrary many-body biases on selected paired/unpaired states. For a structure s , the modeled energy is

$$E(s) = E_{\text{ViennaRNA}}(s) + \sum_i \lambda_i \text{paired}_i(s) + \text{state_bias}(s),$$

where paired_i is one when nucleotide i is paired and zero otherwise. Positive λ_i values disfavor pairing and negative values favor it. A state-bias tensor can express cooperative or non-additive interactions between any chosen nucleotides; multiple tensors contribute additively.

Internally, pairing penalties are mapped to ViennaRNA soft constraints. State biases are represented exactly as a mixture of dynamic-programming ensembles hard-conditioned on selected nucleotides. Public results are combined across those components, so callers use the same API for an ordinary ensemble and for a biased state mixture.

Calculations are performed lazily and cached. The class supports MFE prediction, evaluation of a supplied dot-bracket structure, ensemble free energies, base-pair probabilities and diversity, derivatives with respect to penalties and state biases, Boltzmann sampling, suboptimal enumeration and coverage, and joint nucleotide-pairing probabilities. Structure energies and state biases are expressed in kcal/mol; temperatures are supplied in kelvin.

Parameters

seq : **str** RNA sequence.

lambdas1d : **array-like, optional** Per-nucleotide pairing penalties (kcal/mol). Positive values penalize pairing, whereas negative values favor pairing. If omitted, all penalties are zero.

force_paired : **array-like of int, optional** Zero-based indices of nucleotides that are required to be paired, without specifying their pairing partners.

force_unpaired : **array-like of int, optional** Zero-based indices of nucleotides that are required to be unpaired.

state_positions : **array-like of int or sequence of array-like, optional** Zero-based indices defining binary paired/unpaired states. A flat sequence defines one state set. A sequence of sequences defines multiple disjoint state sets whose energy biases are additive. If **state_biases** is omitted, every state is assigned zero bias.

state_biases : **array-like or sequence of array-like, optional** Energy biases (kcal/mol) for the states defined by **state_positions**. For one state set, its shape must be $(2,) * \text{len}(\text{state_positions})$. For multiple sets, provide one tensor per set, with shape $(2,) * \text{len}(\text{positions})$. Index zero denotes an unpaired nucleotide and index one a paired nucleotide. It cannot be provided without **state_positions**.

reduce_state_space : bool, default=True If True, represent the final selected state position as an equivalent 1D pairing penalty, reducing the number of dynamic-programming ensembles from 2^N to $2(N-1)$. If False, use one hard-conditioned ensemble for every state.

no_lonely_pair : bool or None, default=None If True, exclude structures containing isolated base pairs using ViennaRNA's noLP model option. If None, use the current module default.

pf_smooth : bool or None, default=None Whether ViennaRNA should smooth energies in partition-function Boltzmann factors. If None, use the current module default, which is initially False. If True, partition functions and sampling use ViennaRNA's smoothed model, while MFE, evaluation, and suboptimal structures continue to use its unsmoothed energy model.

temperature : float or None, default=None Temperature in kelvin. If None, use the current module default, which is initially 310.15 K.

NaCl : float or None, default=None Sodium concentration (M). If None, use the current module default, which initially selects ViennaRNA's default value.

parameters : {"turner1999", "turner2004", "andronesescu2007", "langdon2018"} or None Thermodynamic parameter set. If None, use the current module default.

Notes A state set containing N positions normally requires 2^N conditioned dynamic-programming ensembles. By default, the final position of each set is represented by an equivalent constant shift and one-body penalty, reducing the total from $2^{\sum(N_k)}$ to $2^{(\sum(N_k) - K)}$ for K non-empty state sets. Consequently, large numbers of state positions can still be expensive even with `reduce_state_space=True`.

Standard ViennaRNA builds round soft-constraint energies to the nearest 0.01 kcal/mol. This class corrects that rounding: partition functions use a residual callback, sampling uses rejection or importance reweighting, and MFE and suboptimal candidates are widened and rescored. Therefore the requested continuous penalties are retained even without a patched ViennaRNA build that supports them natively.

With the default `pf_smooth=False`, partition-function and discrete structure calculations use compatible ViennaRNA energies. Setting `pf_smooth=True` reproduces ViennaRNA's default smoothed Boltzmann factors, but ViennaRNA's MFE, structure-evaluation, and suboptimal routines remain unsmoothed. In that mode, `suboptimal_coverage` mixes the two energy conventions and should be interpreted accordingly.

Hard constraints specify only whether a nucleotide is paired; they do not specify its partner. Structures are pseudoknot-free, as in ViennaRNA's standard single-strand folding grammar.

Methods

Method `base_pairing_probability`

```
def base_pairing_probability(
    self
)
```

Return the base-pairing probability matrix.

Returns

ndarray Symmetric $N \times N$ matrix whose element (i,j) is the equilibrium probability that nucleotides i and j form a base pair.

Method `d_free_energy_d_lambdas1d`

```
def d_free_energy_d_lambdas1d(
    self
)
```

Return the derivatives of the free energy with respect to `lambdas1d`.

The derivative for nucleotide i is its equilibrium pairing probability,

$dF / d \lambda_{i,i} = \langle s_i \rangle$.

Returns

ndarray One-dimensional array containing one derivative per nucleotide.

Method `d_free_energy_d_state_biases`

```
def d_free_energy_d_state_biases(  
    self  
)
```

Return the derivatives of the free energy with respect to state biases.

The derivative with respect to a state's energy bias is the equilibrium probability of that state.

Returns

ndarray or list of ndarray With the flat, single-set `state_positions` syntax, an array with the same shape as `state_biases`. With the list-of-sets syntax, one array per set, including when the list contains only one set.

Raises

ValueError If this molecule was not initialized with state biases.

Method `evaluate`

```
def evaluate(  
    self,  
    structure  
)
```

Return the exact free energy of a secondary structure.

Parameters

structure : str Dot-bracket representation of a secondary structure.

Returns

float Exact free energy (kcal/mol), including continuous pairing penalties and state biases.

Method `mean_bp_distance`

```
def mean_bp_distance(  
    self  
)
```

Return the mean base-pair distance between two ensemble structures.

The diversity is $\sum_{ij} p_{ij} * (1 - p_{ij})$, using the symmetric base-pairing probability matrix. For a state mixture, p_{ij} is the probability in the combined ensemble.

Returns

float Expected base-pair distance between two independent structures.

Method `mfe`

```
def mfe(  
    self  
)
```

Return the minimum-free-energy structure.

The returned energy always corresponds to the exact continuous pairing penalties, even when ViennaRNA internally rounds soft constraints.

Returns

structure : str Dot-bracket representation of the MFE structure.

energy : float Exact free energy (kcal/mol).

Method `pairing_correlation_matrix`

```
def pairing_correlation_matrix(
    self
)
```

Return the joint pairing-probability matrix.

Element (i, j) is the probability that nucleotides i and j are simultaneously paired, irrespective of their pairing partners.

The matrix is computed exactly using constrained partition-function calculations.

Returns

ndarray Symmetric NxN matrix whose diagonal contains the pairing probabilities.

Method `sample`

```
def sample(
    self,
    number,
    weights=False
)
```

Generate Boltzmann-distributed secondary structures.

By default, rejection sampling corrects ViennaRNA's rounded soft constraints and returns unweighted structures from the exact continuous model. Weighted samples from the rounded model can be requested instead.

Parameters

number : int Number of structures to sample.

weights : bool, default=False If False, return unweighted structures sampled from the exact model. If True, return rounded-model samples and their log-weight corrections. The weighted path is faster when rounding corrections are present.

Returns

list of str or list of (str, float) With **weights=False**, a list of dot-bracket structures. With **weights=True**, each element contains a structure and its unnormalized log-weight correction

$$\log(w) = -(E_{\text{exact}} - E_{\text{rounded}}) / (k_B T).$$

For state mixtures, the log-weight also includes the component-specific exact/rounded normalization correction. This correction is caused only by lambda rounding, not by the state bias.

When all lambdas are multiples of 0.01 kcal/mol, every returned log-weight is zero.

Method `suboptimal_coverage`

```
def suboptimal_coverage(
    self,
    delta
)
```

Return the fraction of the partition function represented by the suboptimal ensemble.

The suboptimal ensemble contains all structures whose exact energy is within delta kcal/mol of the minimum-free-energy structure.

Parameters

delta : float Maximum energy difference (kcal/mol) above the exact MFE.

Returns

float Fraction of the total partition function represented by the enumerated structures. The result lies between zero and one, apart from possible small numerical errors.

Method `suboptimal_structures`

```
def suboptimal_structures(  
    self,  
    delta  
)
```

Enumerate suboptimal secondary structures.

Candidate structures are generated using ViennaRNA's rounded soft constraints, rescored with the exact continuous penalties, and returned sorted by exact energy.

For state mixtures, the MFE of every feasible state is calculated first. Each component is then enumerated with the local energy window required by the common, globally biased cutoff.

Parameters

delta : float Maximum energy difference (kcal/mol) above the exact MFE.

Returns

list of (str, float) List of (structure, energy) pairs sorted by increasing exact energy.

Method `total_free_energy`

```
def total_free_energy(  
    self  
)
```

Return the ensemble free energy.

Returns

float Ensemble free energy (kcal/mol) corresponding to the exact continuous pairing penalties.

Module `bussilab.wham`

Module containing a WHAM implementation.

See [wham\(\)](#).

Functions

Function `wham`

```
def wham(  
    bias,  
    *,  
    frame_weight=None,  
    traj_weight=None,  
    T: float = 1.0,  
    maxiter: int = 1000,  
    threshold: float = 1e-20,  
    verbose: bool = False,  
    logZ: numpy.ndarray | None = None,  
    logW: numpy.ndarray | None = None,  
    normalize: bool | str = 'log',  
    method: str = 'minimize',  
    minimize_opt: dict | None = None  
)
```

Compute weights according to binless WHAM.

The main input for this calculation is in the 2D array `bias`. Element `bias[i, j]` should contain the energy of the *i*-th frame computed according to the *j*-th Hamiltonian. Trajectories should be concatenated first, so that the total number of frames should be equal to the number of frames of each trajectory multiplied by the number of trajectories. However, it is also possible to concatenate simulations of different lengths. It is crucial however to compute the potential according to each of the employed Hamiltonian on **all the frames**, not only on those simulated using that Hamiltonian.

Notice that by default weights are normalized. It is possible to override this behavior with `normalize=False`. However, starting with v0.0.40, this should not be necessary. The new implementation of normalization should be numerically stable in all cases.

Bugs

Up to version 0.042, `method="minimize"` does not work correctly when setting `traj_weights`. As a consequence, results produced with v0.0.41, where this method is the default, might be incorrect. In v0.0.42 this is temporarily fixed by reverting to `method="substitute"` when using `traj_weights`. In v0.0.43 this should be finally fixed: both methods should equally work in all cases, and the default "minimize" method should require less iterations.

Combining Trajectories Of Different Length

Let's imagine three frames obtained from three Hamiltonians. Let's assume that the energy of frame *i* in Hamiltonian *j* is given by `bias[i, j]` defined as

```
import numpy as np
bias = np.array([[1, 10, 7],
                 [2, 9, 6],
                 [3, 8, 5]])
```

We can compute the weights with the following command:

```
np.exp(wham.wham(bias).logW)

array([0.41728571, 0.39684866, 0.18586563])
```

We now notice that the second and third columns of this matrix are equal except for a rigid shift. They thus correspond to Hamiltonians that are equivalent. We should have been able to obtain the same result saying that these frames were coming from two simulations. If we only pass the first two columns however we obtain different weights

```
np.exp(wham.wham(bias[:, 0:2]).logW)

array([0.28224026, 0.43551948, 0.28224026])
```

In order to correctly analyze these frames we should pass the information that the second Hamiltonian was used for twice the time:

```
np.exp(wham.wham(bias[:, 0:2], traj_weight=(1, 2)).logW)

array([0.41728571, 0.39684866, 0.18586563])
```

Notice that now the weights are identical to those computed in the first example.

Trusting More A Trajectory Than Another

When you concatenate trajectories, you might explicitly want to trust more a trajectory than another. For instance, two trajectories might have been accumulated with a different stride, and the reliability of each frame of the one with smaller stride should be lower. We thus would like to assign a weight to each frame that accounts for its reliability.

Consider the following command:

```
import numpy as np
np.exp(wham.wham([[3, 5],
                  [4, 4],
```

```

[4, 4],
[4, 4],
[4, 4],
[4, 4],
[4, 4],
[4, 4],
[4, 4],
[4, 4],
[4, 4]]).logW)

```

that results in the following weights

```

array([0.06421006, 0.09357899, 0.09357899, 0.09357899, 0.09357899,
       0.09357899, 0.09357899, 0.09357899, 0.09357899, 0.09357899,
       0.09357899])

```

Notice that all the frames except for the first one are identical. An equivalent result would have been obtained using

```

import numpy as np
np.exp(wHAM.wham([[3, 5],
                  [4, 4]], frame_weight=(1, 10)).logW)

```

```

array([0.06421006, 0.93578994])

```

Clearly, the weight of the second frame in this example is equal to ten times the weights of the ten corresponding frames in the previous example.

Parameters

bias : **np.ndarray** An array with shape (nframes, ntraj) containing the bias potential applied to each frame according to each of the Hamiltonians.

frame_weight : **np.ndarray, optional** An array with nframes elements. These elements should contain the reliability weight of the frames. By default, these weights are set to one.

traj_weight : **np.ndarray, optional** An array with ntraj elements. These elements should contain the total weight of each of the Hamiltonians. Should be used when combining trajectories of different lengths.

T : **float, optional** The temperature of the system. This number is just used to divide the bias array in order to make it adimensional. In case replicas are simulated at different temperatures, it is possible to pass an array here, with ntraj elements.

maxiter : **int, optional** Maximum number of iterations in the minimization procedure.

threshold : **float, optional** Threshold for the minimization procedure.

verbose : **bool, optional** If True, print information as the minimization proceeds.

logZ : **np.ndarray, optional** Array with ntraj elements. Initial value for the logarithm of the partition functions. If not provided, it is computed from the bias. Providing an initial guess that is close to the converged value (e.g. as obtained from a calculation with a limited number of frames) can speed up significantly the convergence.

logW : **np.ndarray, optional** Array with nframes elements. Initial value for the logarithm of the weights. If not provided, they are computed from the bias. Providing an initial guess that is close to the converged value can speed up significantly the convergence. *If logW is provided, logZ is ignored.*

normalize : **bool or str, optional** By default, “log”, which properly normalizes weights in all cases. `normalize=True` or `False` is enabled for backward compatibility.

method : **str, optional** If “substitute”, solve self-consistent equations by substitution. If “minimize”, use a minimization as in J Chem Phys 136, 144102 (2012). Prior to version 0.0.40, the default was “substitute”. Starting with version 0.0.41, the default is “minimize”.

minimize_opt : **dict, optional** If `method==“minimize”`, this dict can be used to pass options to `scipy.minimize`. Notice that by default the minimization is performed using ‘L-BFGS-B’.

Classes

Class WhamResult

```
class WhamResult(
    *,
    logW: numpy.ndarray,
    logZ: numpy.ndarray,
    nit: int,
    nfev: int,
    eps: float
)
```

Result of a `wham()` calculation.

Ancestors (in MRO)

- [bussilab.coretools.Result](#)
- [builtins.dict](#)

Instance variables

Variable `eps` The final error in the iterative solution.

Variable `logW` `numpy.ndarray` containing the logarithm of the weight of the frames.

Variable `logZ` `numpy.ndarray` containing the logarithm of the partition function of each state.

Variable `nfev` The number of function evaluations (might differ from `nit` when using `method='minimize'`).

Variable `nit` The number of performed iterations.

Generated by *pdoc* 0.11.6 (<https://pdoc3.github.io>).