

Package gitissue

```
import "github.com/butlerx/AgileGit/gitissue"
```

[Overview](#)

[Index](#)

Index ▼

[Variables](#)

[func AddLabel\(repo, labelName string, issueNum int\) \(\[\]github.Label, error\)](#)
[func AddMilestone\(\)](#)
[func ChangeKey\(oldKey, newKey string\) error](#)
[func ChangeLogin\(user, oauth, key string\) error](#)
[func CloseIssue\(repo string, issue *github.Issue\) \(*github.Issue, error\)](#)
[func Comment\(repo, body string, issueNum int\) \(github.IssueComment, error\)](#)
[func CreateLabel\(repo, labelName string\) \(github.Label, error\)](#)
[func CreateMilestone\(repo, milestone string\) \(github.Milestone, error\)](#)
[func DeleteComment\(repo string, commentId int\) error](#)
[func DeleteLabel\(repo, labelName string\) error](#)
[func DeleteMilestone\(repo string, mileNum int\) error](#)
[func EditComment\(repo, body string, commentId int\) \(github.IssueComment, error\)](#)
[func EditIssue\(repo string, oldIssue *github.Issue\) \(*github.Issue, error\)](#)
[func EditLabel\(repo, labelName, newName string\) \(github.Label, error\)](#)
[func EditMilestone\(repo, newTitle string, mileNum int\) \(github.Milestone, error\)](#)
[func IsSetUp\(\) \(bool, error\)](#)
[func Issues\(repo string\) \(\[\]github.Issue, error\)](#)
[func IssuesFilter\(repo, state, milestone, assignee, creator, sort, order string, labels \[\]string\) \(\[\]github.Issue, error\)](#)
[func ListComments\(repo string, issueNum int\) \(\[\]github.IssueComment, error\)](#)
[func ListLabels\(repo string\) \(\[\]github.Label, error\)](#)
[func ListMilestones\(repo string\) \(\[\]github.Milestone, error\)](#)
[func LockIssue\(repo string, issueNum int\) error](#)
[func Login\(userkey string\) error](#)
[func MakeIssue\(repo, title, body, assignee string, milestone int, labels \[\]string\) \(*github.Issue, error\)](#)
[func OpenIssue\(repo string, issue *github.Issue\) \(*github.Issue, error\)](#)
[func PossibleAssignees\(repo string\) \(\[\]github.User, error\)](#)
[func RemoveLabel\(repo, labelName string, issueNum int\) error](#)
[func RemoveMilestone\(\)](#)
[func SetUp\(user, oauth, key string\) error](#)
[func UnlockIssue\(repo string, issueNum int\) error](#)
[func WatchRepo\(repo string\) \(string, string, bool\)](#)
[type Comments](#)
[type Config](#)
[Bugs](#)

Package files

[gitissue.go](#)

Variables

```
var (  
    Conf *Config  
  
    Path    = &folder  
    GitLog *log.Logger  
)
```

func [AddLabel](#)

```
func AddLabel(repo, labelName string, issueNum int) ([]github.Label, error)
```

Add a label to a issue.

func [AddMilestone](#)

```
func AddMilestone()
```

Add Milestone to an issue. BUG(butlerx) Currently adding a milestone is not supported as milestones in the api are a mix of strings and ints. Bug is noted in library docs.

func [ChangeKey](#)

```
func ChangeKey(oldKey, newKey string) error
```

Change user encryption key

func [ChangeLogin](#)

```
func ChangeLogin(user, oauth, key string) error
```

Change user name and Auth token and relogin.

func [CloseIssue](#)

```
func CloseIssue(repo string, issue *github.Issue) (*github.Issue, error)
```

Marks issue as closed.

func [Comment](#)

```
func Comment(repo, body string, issueNum int) (github.IssueComment, error)
```

Comment on a issue on github.

func [CreateLabel](#)

```
func CreateLabel(repo, labelName string) (github.Label, error)
```

Create a label for a repo.

func [CreateMilestone](#)

```
func CreateMilestone(repo, milestone string) (github.Milestone, error)
```

Create a Milestone for a repo.

func [DeleteComment](#)

```
func DeleteComment(repo string, commentId int) error
```

Remove a comment from an issue.

func [DeleteLabel](#)

```
func DeleteLabel(repo, labelName string) error
```

Delete a label from a repo.

func [DeleteMilestone](#)

```
func DeleteMilestone(repo string, mileNum int) error
```

Delet a Milestone from a repo.

func [EditComment](#)

```
func EditComment(repo, body string, commentId int) (github.IssueComment, error)
```

Edit a comment already on github.

func [EditIssue](#)

```
func EditIssue(repo string, oldIssue *github.Issue) (*github.Issue, error)
```

Edit a github issue. Edit the issue object before passing it to this method.

func [EditLabel](#)

```
func EditLabel(repo, labelName, newName string) (github.Label, error)
```

Change the name of a label.

func [EditMilestone](#)

```
func EditMilestone(repo, newTitle string, mileNum int) (github.Milestone, error)
```

Change the title of a milestone in a repo.

func [IsSetUp](#)

```
func IsSetUp() (bool, error)
```

Check if users config is set up and if being run in git repo.

func [Issues](#)

```
func Issues(repo string) ([]github.Issue, error)
```

Pull all issues and write them to .issue/issues.json. Pulls both open and closed issues. Used to update issues.json. Method for accessing issue.json. Returns last pull if cant connect to server. Repo should be structured as "user/repo"

func [IssuesFilter](#)

```
func IssuesFilter(repo, state, milestone, assignee, creator, sort, order string, labels []string) ([]github.Issue, error)
```

Filters issues based on mileston, assignee, creatoror, labels or state. Pass empty strings for things that arnt to be filtered. Returns array of issues in order asked for. TODO(butlerx) filter offline issues if query of repo fails.

func [ListComments](#)

```
func ListComments(repo string, issueNum int) ([]github.IssueComment, error)
```

Lists all the comments for a given issue.

func [ListLabels](#)

```
func ListLabels(repo string) ([]github.Label, error)
```

list all possible labels in a repo.

func [ListMilestones](#)

```
func ListMilestones(repo string) ([]github.Milestone, error)
```

List all Milestones in a repo.

func [LockIssue](#)

```
func LockIssue(repo string, issueNum int) error
```

Locks issue so it cant be changed.

func [Login](#)

```
func Login(userkey string) error
```

Logs in to github using oauth. Returns error if login fails.

func [MakeIssue](#)

```
func MakeIssue(repo, title, body, assignee string, milestone int, labels []string) (*github.Issue, error)
```

Create an issue on github. Requires repo and title args, rest are optinal arg and can be passed empty. Make issue put milestone at 0 for no milestone. BUG(butlerx) Issue Creation doesnt work in offile mode.

func [OpenIssue](#)

```
func OpenIssue(repo string, issue *github.Issue) (*github.Issue, error)
```

Mark issue as open.

func [PossibleAssignees](#)

```
func PossibleAssignees(repo string) ([]github.User, error)
```

Get a list of all possible assignees

func [RemoveLabel](#)

```
func RemoveLabel(repo, labelName string, issueNum int) error
```

Remove a label from an issue.

func [RemoveMilestone](#)

```
func RemoveMilestone()
```

Remove Milestone to an issue. BUG(butlerx) currently Removing milestones is not supported as milestones in the api are a mix of strings and ints. Bug is noted in library docs.

func [SetUp](#)

```
func SetUp(user, oauth, key string) error
```

Set up .issue folder, issues, comments & config file and begin logfile. Appends to to gitignore to ignore the config file. Checks if the files exist and if they dont creates them.

func [UnlockIssue](#)

```
func UnlockIssue(repo string, issueNum int) error
```

Unlocks issue to allow changes.

func [WatchRepo](#)

```
func WatchRepo(repo string) (string, string, bool)
```

Monitor for change in repo. Rings terminal bell and returns true and the reason if something happened in repo. returns false if nothing changed

type [Comments](#)

```
type Comments struct {  
    Issue []github.IssueComment  
    Num   int  
}
```

Structure for comments to file used for storing comments offline array of comments and issue number they relate to

type [Config](#)

```
type Config struct {  
    Username string  
    Token    string  
    Secure   bool  
}
```

Structure of User config file Username and oauth token stored check if user wants the token secured

Bugs

[🐞](#) Issue Creation doesnt work in offline mode.

[🐞](#) Currently adding a milestone is not supported as milestones in the api are a mix of strings and ints. Bug is noted in library docs.

[🐞](#) currently Removing milestones is not supported as milestones in the api are a mix of strings and ints. Bug is noted in library docs.