```
2:
                                                   %3 = alloca i32, align 4
                                                    %4 = alloca i32, align 4
                                                    %5 = alloca ptr, align 8
                                                    store i32 0, ptr %3, align 4
                                                    store i32 %0, ptr %4, align 4
                                                    store ptr %1, ptr %5, align 8
                                                    %6 = call noundef nonnull align 8 dereferenceable(8) ptr
                                                   ... @_ZStlsISt11char_traitsIcEERSt13basic_ostreamIcT_ES5_PKc(ptr noundef nonnull
                                                   ... align 8 dereferenceable(8) @_ZSt4cout, ptr noundef @.str)
                                                    %7 = load i32, ptr %4, align 4
                                                    %8 = icmp sqt i32 %7, 2
                                                    br i1 %8, label %9, label %11
9:
                                                                                                      11:
                                                                                                      %12 = call noundef nonnull align 8 dereferenceable(8) ptr
%10 = call noundef nonnull align 8 dereferenceable(8) ptr
... @_ZStlsIStl1char_traitsIcEERStl3basic_ostreamIcT_ES5_PKc(ptr noundef nonnull ... align 8 dereferenceable(8) @_ZSt4cout, ptr noundef @.str.1)
                                                                                                      ... @_ZStlsIStl1char_traitsIcEERStl3basic_ostreamIcT_ES5_PKc(ptr noundef nonnull ... align 8 dereferenceable(8) @_ZSt4cout, ptr noundef @.str.2)
                                                                                                       br label %13
br label %13
                                                  13:
                                                  %14 = call noundef nonnull align 8 dereferenceable(8) ptr
                                                   ... @_ZStlsIStl1char_traitsIcEERStl3basic_ostreamIcT_ES5_PKc(ptr noundef nonnull ... align 8 dereferenceable(8) @_ZSt4cout, ptr noundef @.str.3)
                                                    ret i32 0
```

CFG for 'main' function