

Designing an Index for ZooDB

Jonas Nick & Bogdan Vancea

May 30, 2014

Outline

- 1 Introduction
- 2 Goals & Challenges
- 3 The new Index Implementation
- 4 Benchmarks

ZooDB

- an open source object database written in Java
- JDO standard compliant
- 4 times faster than competitor db4o
- zoodb.org

Database Index

Key-Value data structure for fast retrieval and ordered iteration of entries stored in a file.

Database Index

Key-Value data structure for fast retrieval and ordered iteration of entries stored in a file.

Example:

```
ZooJdoHelper.createIndex(pm, Person.class, "name",  
false);
```

Database Index

Key-Value data structure for fast retrieval and ordered iteration of entries stored in a file.

Example:

```
ZooJdoHelper.createIndex(pm, Person.class, "name",  
false);
```


Attribute Index
Value \rightarrow Object-ID

Database Index

Key-Value data structure for fast retrieval and ordered iteration of entries stored in a file.


Example:

```
ZooJdoHelper.createIndex(pm, Person.class, "name",  
false);
```




B+ Tree

B+ Tree




- Inner node contains keys and children pointer, leaf contain keys and values.

B+ Tree




- Inner node contains keys and children pointer, leaf contain keys and values.
- **Node fills one disk page.**

B+ Tree




- Inner node contains keys and children pointer, leaf contain keys and values.
- **Node fills one disk page.**
- Node has maximum and minimum number of entries.


Example: insert (8, v)




Example: insert (8, v)




Example: insert (8, v)



Example: insert (8, v)




B+ Tree




- Inner node contains keys and children pointer, leaf contain keys and values.
- **Node fills one disk page.**
- Node has maximum and minimum number of entries.

B+ Tree



- Inner node contains keys and children pointer, leaf contain keys and values.
- **Node fills one disk page.**
- Node has maximum and minimum number of entries.
- Rebalancing on insert: split, on delete: redistribute or merge

B+ Tree



- Inner node contains keys and children pointer, leaf contain keys and values.
- **Node fills one disk page.**
- Node has maximum and minimum number of entries.
- Rebalancing on insert: split, on delete: redistribute or merge
- Insert, remove, search are logarithmic.

Goals

- faster B+ tree index

Goals

- faster B+ tree index
- key unique and key-value unique
 - Ex. insert (1,1), (1,2)

Goals

- faster B+ tree index
- key unique and key-value unique
 - Ex. insert (1,1), (1,2)
- range query iterators

Goals

- faster B+ tree index
- key unique and key-value unique
 - Ex. insert (1,1), (1,2)
- range query iterators
- buffer manager to allow caching
 - fetches pages

Goals

- faster B+ tree index
- key unique and key-value unique
 - Ex. insert (1,1), (1,2)
- range query iterators
- buffer manager to allow caching
 - fetches pages
- prefix sharing


Prefix Sharing

Exploit common prefix

00010000
00010100
00010110


Prefix Sharing

Exploit common prefix




Prefix Sharing

Exploit common prefix



Prefix Sharing


Exploit common prefix



- variable number of key-value entries per node

Prefix Sharing


Exploit common prefix



- variable number of key-value entries per node
- prefix determines
 - if two nodes can be split without underflow

Prefix Sharing


Exploit common prefix



- variable number of key-value entries per node
- prefix determines
 - if two nodes can be split without underflow
 - if two nodes can be merged without overflow

Prefix Sharing

Exploit common prefix



- variable number of key-value entries per node
- prefix determines
 - if two nodes can be split without underflow
 - if two nodes can be merged without overflow
 - the number of entries that can be redistributed from one node to the other

Challenges

- runtime dominated by disk access

Challenges

- runtime dominated by disk access
 - prefer fewer nodes

Challenges

- runtime dominated by disk access
 - prefer fewer nodes
 - rarely modify nodes

Challenges

- runtime dominated by disk access
 - prefer fewer nodes
 - rarely modify nodes
- New features are costly.

Challenges

- runtime dominated by disk access
 - prefer fewer nodes
 - rarely modify nodes
- New features are costly.
- Textbook algorithms need to be adapted.

Challenges

- runtime dominated by disk access
 - prefer fewer nodes
 - rarely modify nodes
- New features are costly.
- Textbook algorithms need to be adapted.
 1. not optimized for practical scenarios


Challenges

- runtime dominated by disk access
 - prefer fewer nodes
 - rarely modify nodes
- New features are costly.
- Textbook algorithms need to be adapted.
 1. not optimized for practical scenarios
 2. do not cover duplicates nor prefix sharing

Challenges

- runtime dominated by disk access
 - prefer fewer nodes
 - rarely modify nodes
- New features are costly.
- Textbook algorithms need to be adapted.
 1. not optimized for practical scenarios
 2. do not cover duplicates nor prefix sharing
- low-level implementation optimizations


Index Implementation





Operations

- Search - Similar to normal B+ Tree
- Insert overflow
 - attempt to redistribute values to left sibling before creating a new node
- Delete underflow
 - check if possible to merge with left or right neighbour
 - check if possible to split current node between left and right
 - redistribute from left or right
- Write
 - only write dirty nodes
 - prefix encoding



Microbenchmarks



Microbenchmarks




Microbenchmarks




- in every microbenchmark the new index is significantly slower
- in most microbenchmarks there s a significantly lower number of nodes



Microbenchmarks



StackOverflow Import



StackOverflow Import



Summary

- ...

Outlook

- ...