✅ Task 1 Examples (Client → Server → Client)

These examples cover **every possible case**: success, not found, invalid format, stock updates, etc.

🔵 Example 1 — VIEW (existing item)

Client sends:

```
VIEW|PIZZ|0
```

Server response:

```
Margherita Pizza:1200:10
```

Explanation:

- Item PIZZ exists
- Stock is 10
- Server returns: `name:price:stock`

🔵 Example 2 — VIEW (non-existing item)

Client sends:

```
VIEW|SOUP|0
```

Server response:

```
NOT_FOUND
```

Explanation:
No item with ID SOUP exists.

🟢 Example 3 — ORDER (success)

Assume PIZZ stock = 10.

Client sends:

```
ORDER|PIZZ|3
```

Server response:

```
SUCCESS:3600
```

Explanation:

- price = 1200
- quantity = 3

- total = 3600
- stock becomes **7**

🟡 Example 4 — ORDER (insufficient stock)

Assume PIZZ stock = 7 after previous order.

Client sends:

```
ORDER|PIZZ|8
```

Server response:

```
NO_STOCK
```

Explanation:
User requested 8 but only 7 left.

🔵 Example 5 — ORDER (item not found)

Client sends:

```
ORDER|XXXX|2
```

Server response:

```
NOT_FOUND
```

🔴 Example 6 — Invalid format (too few fields)

Client sends:

```
VIEW|PIZZ
```

Server response:

```
ERROR
```

🔴 Example 7 — Invalid format (too many fields)

Client sends:

```
ORDER|PIZZ|3|extra
```

Server response:

```
ERROR
```

🔴 Example 8 — Invalid action

Client sends:

```
DELETE|PIZZ|0
```

Server response:

```
ERROR
```

🔴 Example 9 — Quantity must be an integer

Client sends:

```
ORDER|PIZZ|two
```

Server response:

```
ERROR
```

🟣 Example 10 — VIEW must always send quantity 0

Client sends:

```
VIEW|PIZZ|5
```

Server response:

```
ERROR
```

🟢 Example 11 — Multiple operations in one session

```
Client: VIEW|BURG|0
Server: Cheeseburger:800:15

Client: ORDER|BURG|2
Server: SUCCESS:1600

Client: VIEW|BURG|0
Server: Cheeseburger:800:13

Client: QUIT
(Client disconnects)
```

🟩 Example 12 — Server stock update demonstration

Starting menu:

```
PIZZ: stock = 10
```

Sequence:

1. Client:

   ```
   ORDER|PIZZ|4
   ```

   Server:

   ```
   SUCCESS:4800
   ```

   New stock = 6
2. Client:

   ```
   VIEW|PIZZ|0
   ```

   Server:

   ```
   Margherita Pizza:1200:6
   ```