

# MP-3 Write-Up

Blake VERMEER

Kris HALL

Rohit ZAMBRE

October 26, 2014

Date Due: October 31, 2014

Instructors: Joseph Zambreno

## 1 Overview

In this lab we learned about the LEON processor on how to create and integrate a co-process with the LEON processor.

## 2 Software Grayscale Conversion

After getting acquainted with the build environment for the LEON processor, we dived into the *frameloop.c* code to see how it works. First we started by examining the main function and dissecting how it works. The main function of *frameloop.c* first sets up the environment by enabling the coprocessor, and configuring and enabling the SVGA controller. It primarily copies all (= NFRAMES) of the image frames from memory to the SVGA controller; it can do so via two modes: mode 1 and mode 2. After the completion of the transfer of all (= NFRAMES) image frames, it computes the Frame Per Second measure for the buffering process.

Next we looked at the two different modes that were present in *frameloop.c* to determine what they did. Mode 1 merely copies the current image from memory to the controller without applying any filters. Mode 2 is much more involved than mode 1. In mode 2, a filter is applied to each frame being transferred from memory to the buffer in the controller. Currently, two RGB values are being computed for each image frame and an OR is performed between the two RGB values to obtain the final the image frame that will be sent to the controller.

## 3 Conclusion