

Lecture 6: Quantum oracles & Recent experiments with quantum computers

Quantum Algorithms

Benoît Vermersch

October 19, 2021

LPMMC Grenoble & IQOQI Innsbruck

Information about the exam

Implementing a quantum oracle

Recent experimental breakthroughs with quantum computers

Presentation of a superconducting qubit quantum computer

The quantum supremacy experiment (Arute et al, 2019)

The toric code experiment (Satzinger et al, 2021)

Information about the exam

- Room D420 Jan 17th — 1:30 pm - 3:30 pm (2 hours).
- Two problems.
- Only the documents accessible on the Moodle (slides, exercices), and hand-written notes allowed.
- You can bring your laptop, but only to visualize the slides, not to use Internet.
- Use of smartphones/ipads, etc during the exam forbidden.

Information about the exam

Implementing a quantum oracle

Recent experimental breakthroughs with quantum computers

- Presentation of a superconducting qubit quantum computer

- The quantum supremacy experiment (Arute et al, 2019)

- The toric code experiment (Satzinger et al, 2021)

Grover's oracle: Reminder

- Problem given a n -bit Boolean function $f(x)$. Find the solution $x = w$ such that $f(w) = 1$
- The quantum algorithm is given by

$$U = (U_{\text{diffuser}} U_{\text{oracle}})^t H^{\otimes n} \quad (1)$$

Grover's oracle: Reminder

- Grover's algorithm converges to the solution for $t \propto \sqrt{N} = 2^n$.
- The diffuser $U_{\text{diffuser}} = 2|\psi\rangle\langle\psi| - 1$ can be implemented with the Toffoli gate
- How can we implement an oracle $U_{\text{oracle}}|x\rangle = (-1)^{f(x)}|x\rangle$? (without knowing the solution $w \dots$)?
- Let us show that this possible using elementary bitstring operations and the technique of 'uncomputation'.

Case study: 3-SAT Problem

- 3-SAT: Given n bits, we are looking for the bit strings $x = (x_1, \dots, x_n)$ that satisfy the Boolean function

$$f(x) = C_1(x) \wedge \dots \wedge C_M(x), \quad (2)$$

where \wedge is a conjunction (AND).

- Each clause $C_m(x)$ is made of a disjunction (OR: \vee) of at most three literals.
- Example with $M = 3, n = 2$

$$f(x) = (x_1 \vee x_2) \wedge (x_1 \vee \neg x_2) \wedge (\neg x_1 \vee x_2) \quad (3)$$

- 3-SAT is NP-Complete.

Implementing a Grover's oracle for 3-SAT


- Oracle $U_{\text{oracle}} |x\rangle = (-1)^{f(x)} |x\rangle$ with $f(x) = (x_1 \vee x_2) \wedge (x_1 \vee \neg x_2) \wedge (\neg x_1 \vee x_2)$
- Step 1: Convert each clause to conjunctions (de Morgan's law)

$$f(x) = \neg(\neg x_1 \wedge \neg x_2) \wedge \neg(\neg x_1 \wedge x_2) \wedge \neg(x_1 \wedge \neg x_2) \quad (4)$$

Implementing a Grover's oracle for 3-SAT

- Step 2: Add one ancilla qubit and Tofolli gates to test each clause


$$|x\rangle \otimes |00\rangle \rightarrow |x\rangle \otimes |C_1(x)\rangle |C_2(x)\rangle \quad (5)$$



Implementing a Grover's oracle for 3-SAT

- Step 3: Add an extra ancilla bit for performing the conjunctions between clauses and 'uncompute' the first ancilla qubits

$$|x\rangle |1\rangle^{\otimes M} |y\rangle \rightarrow |x\rangle |1\rangle^{\otimes M} |y \oplus f(x)\rangle \quad (6)$$



- If the last ancilla is flipped, $f(x) = 1$, i.e., we can mark the solution!

Implementing a Grover's oracle for 3-SAT

- All ancilla qubits except one have been uncomputed, we have effectively realized a *XOR* oracle


$$|x\rangle \otimes |y\rangle \rightarrow |x\rangle \otimes |y \oplus f(x)\rangle \quad (7)$$

- How to realize a *phase* oracle, as required for Grover's oracle, from a XOR oracle?

$$|x\rangle \rightarrow (-1)^{f(x)} |x\rangle \quad (8)$$

Implementing a Grover's oracle for 3-SAT

- XOR to phase oracle conversion: Simply initialize the last ancilla using the H gate



Implementing a Grover's oracle for 3-SAT

- We obtain

$$\begin{aligned} |x\rangle |1\rangle^{\otimes M} (H|1\rangle) &\rightarrow |x\rangle |1\rangle^{\otimes M} (|0 \oplus f(x)\rangle - |1 \oplus f(x)\rangle) \\ &\rightarrow |x\rangle |1\rangle^{\otimes M} (-1)^{f(x)} (|0\rangle - |1\rangle) \\ &\rightarrow (-1)^{f(x)} |x\rangle |1\rangle^{\otimes M} (H|1\rangle) \end{aligned} \tag{9}$$

- which effectively realizes our oracle (and uncomputes the last ancilla)!


$$|x\rangle \rightarrow (-1)^{f(x)} |x\rangle \tag{10}$$

The full circuit

- Problem function:

$$f(x) = (x_1 \vee x_2) \wedge (x_1 \vee \neg x_2) \wedge (\neg x_1 \vee x_2) \quad (11)$$

- Circuit



- Qiskit output: bistring 11 with probability 1.0: I coded the problem without knowing the solution, then the algorithm gives me the solution.

Information about the exam

Implementing a quantum oracle

Recent experimental breakthroughs with quantum computers

- Presentation of a superconducting qubit quantum computer

- The quantum supremacy experiment (Arute et al, 2019)


- The toric code experiment (Satzinger et al, 2021)

How does it work?

- Superconducting material+Josephson junctions
 - 53 ‘anharmonic oscillators’ $h_i = \omega_0 a_i^\dagger a_i + U a_i^\dagger a_i (a_i^\dagger a_i - 1) + \dots$
 - Reviews by Devoret, Girvin, etc
- Cool to 20 mK temperature via a dilution fridge
- We can control the qubit $|0\rangle_i, |1\rangle_i = a_i^\dagger |0\rangle_i$ with ‘single qubit gates’.
- iSwap gates between qubits $U_{i,j} = e^{i(\pi/4)(\sigma_i^x \sigma_j^x + \sigma_i^y \sigma_j^y)}$
- Each qubit can be measured.
- We have a universal quantum computer: Every N -qubit state ($\dim 2^N$) can be created and measured (Deutsch 1989).

$$|\psi\rangle = \sum_{s_1, \dots, s_N} c_{s_1, \dots, s_N} |s_1\rangle \otimes \dots \otimes |s_N\rangle \quad (12)$$

Programming a quantum computer



The quantum computing roadmap

- Long-term goals: Quantum algorithms to solve hard problems
 - Data search (Grover's 1996)
 - Factorization (Shor's 1995)
 - Large-scale optimization problems (on-going debate)
- Outstanding conceptual/technological challenges
 - Error propagation is typically exponential in problem size
 - Sophisticated algorithms for 'quantum error correction' required to achieve fault tolerance.
- Massive investments (USA, China, Europe, etc) are helpful, but should not hide conceptual challenges ('quantum hype').
- We need verification methods to validate technological progress


What is this about?

- It will probably take years before we can run a quantum algorithm solving an open problem in computer science.
- An important milestone is to check that a quantum computer is able to perform a computation that is not achievable via a classical computer with reasonable resources (Preskill 2012).
- Two important conceptual questions
 - How can I check something that I cannot compute?
 - How can I explore an gigantic Hilbert space of dimension $2^{53} \sim 10^{15}$ with a finite number of measurements?

The supremacy test

Idea

- Use random circuits that are difficult to simulate classically for $N > 50$
- Make use of random matrix theory to create a faithful figure of merit, based on measuring the system in terms of 'bitstrings' (ex $s = 01001\dots$).



The supremacy test

Algorithm

1. Consider a reduced or 'shallow' circuit U that I can compute classically.
 - 1.1 Implement $|\psi\rangle = U|0\rangle^{\otimes N}$
 - 1.2 Measure $M \ll 2^N$ bitstrings $\{s_m\}$ (sampled ideally according to $P(s) = |\langle s|\psi\rangle|^2$).
 - 1.3 Evaluate the fidelity based on computing

$$\mathcal{F}_{\text{XEB}} = \frac{2^N}{M} \sum_{m=1}^M P(s_m) - 1 \quad (13)$$

2. Consider a non-simulatable 'supremacy' circuit U
 - 2.1 Measure the bitstrings $\{s_m\}$ as above
 - 2.2 Archive the results, waiting for the classical computer to 'catch up' and allow for the evaluation of the fidelity.

The test is meaningful

- For sufficiently large M ,

$$\mathcal{F}_{\text{XEB}} = \frac{2^N}{M} \sum_{m=1}^M P(s_m) - 1 = 2^N \sum_{s=0}^{2^N-1} \sum_{m=1}^M \frac{\delta_{s,s_m}}{M} P(s) - 1 \approx 2^N \sum_{s=0}^{2^N-1} P(s)^2 - 1 \quad (14)$$

- For a random circuit this sum can be calculated analytically.

The test is meaningful


For sufficiently large N ,

$$\mathcal{F}_{\text{XEB}} \approx 2^N \sum_{s=0}^{2^N-1} P(s)^2 - 1 \approx 2^{2N} \langle P(s)^2 \rangle - 1 \quad (15)$$

$$\text{Prob}(P(s) \in [p, p + dp]) = 2^N \exp(-2^N p) dp \quad (16)$$

- In average, $\langle P(s) \rangle = 2^{-N}$, as for a uniform distribution $P_{\text{uni}}(s) = 2^{-N}$.
- However $\langle P(s)^2 \rangle = 2 \times 2^{-2N}$, *twice* compared to $P_{\text{uni}}(s)^2 = 2^{-2N}$!
- Therefore, $\mathcal{F}_{\text{XEB}} = 1$. For uniform distribution, we get instead $\mathcal{F}_{\text{XEB}} = 0$.
- Fast convergence of the estimation of \mathcal{F}_{XEB} with $\sim 10^6$ measurements.


Results



- A remarkable technological achievement.
- Exponential propagation of errors. This was expected
- The power of classical simulations was underestimated (see eg X. Waintal et al, PRX 2020).


Sycamore was made for quantum error correction

- Each qubit is subject to errors. This can be a spin flip error (σ_x on the state), phase error (σ_z), or both.
- In quantum error correction, we fix errors by encoding the quantum information using several physical qubits.



The toric code

- The toric code $|G\rangle$ is the ground state of the Hamiltonian $H = -\sum_s A_s - \sum_p B_p$ (Kitaev 1997)





B



- Blue plaquettes $A_s = \sigma_{s_1}^z \sigma_{s_2}^z \sigma_{s_3}^z \sigma_{s_4}^z$
- Purple plaquettes $B_p = \sigma_{p_1}^x \sigma_{p_2}^x \sigma_{p_3}^x \sigma_{p_4}^x$

- $|0\rangle_L = |G\rangle$ can be created easily with Sycamore. $|1\rangle_L = X_L |G\rangle$.
- $A_s |G\rangle = |G\rangle$, $B_p |G\rangle = |G\rangle$. If it is not the case, an error occurred!
- According to the quantum threshold theorem (Aharonov Ben-Or 1999), scaling up the toric code leads to fault-tolerant quantum computing

Experimental results



Experimental results




The toric code

- The toric code is also the simplest example of a quantum phase with ‘intrinsic’ topological order.
 - Non-local order parameter
 - Stability versus local perturbations
 - The excitations (i.e the errors) on top of $|G\rangle$ have anyonic statistics.
- The non-local order parameter: the topological entanglement entropy (Kitaev, Wen, Levin, Preskill 2006)

$$S_{\text{top}} = S_A + S_B + S_C - S_{AB} - S_{AC} - S_{BC} + S_{ABC} = -1 \quad (17)$$

with the entanglement entropy of subsystem X , $S_X = -\log(\text{Tr}[\rho_X^2])$.

Results



- First demonstration of intrinsic topological order
- Braiding of anyonic excitations (errors) have been also analyzed.
- Next step: non-abelian anyons in string nets models...