

Machine Learning System Design

LATEST SUBMISSION GRADE

100%

1. You are working on a spam classification system using regularized logistic regression. "Spam" is a positive class ($y = 1$) and "not spam" is the negative class ($y = 0$). You have trained your classifier and there are $m = 1000$ examples in the cross-validation set. The chart of predicted class vs. actual class is:

1 / 1 point

	Actual Class: 1	Actual Class: 0
Predicted Class: 1	85	890
Predicted Class: 0	15	10

For reference:

- Accuracy = (true positives + true negatives) / (total examples)
- Precision = (true positives) / (true positives + false positives)
- Recall = (true positives) / (true positives + false negatives)
- F_1 score = $(2 * \text{precision} * \text{recall}) / (\text{precision} + \text{recall})$

What is the classifier's recall (as a value from 0 to 1)?

Enter your answer in the box below. If necessary, provide at least two values after the decimal point.

.85



Correct

There are 85 true positives and 15 false negatives, so recall is $85 / (85 + 15) = 0.85$.

2. Suppose a massive dataset is available for training a learning algorithm. Training on a lot of data is likely to give good performance when two of the following conditions hold true. **1 / 1 point**

Which are the two?

- ☒ The features x contain sufficient information to predict y accurately. (For example, one way to verify this is if a human expert on the domain can confidently predict y when given only x).



Correct

It is important that the features contain sufficient information, as otherwise no amount of data can solve a learning problem in which the features do not contain enough information to make an accurate prediction.

- ☐ We train a learning algorithm with a small number of parameters (that is thus unlikely to overfit).

- ☒ We train a learning algorithm with a large number of parameters (that is able to learn/represent fairly complex functions).



Correct

You should use a "low bias" algorithm with many parameters, as it will be able to make use of the large dataset provided. If the model has too few parameters, it will underfit the large training set.

- ☐ We train a model that does not use regularization.

3. Suppose you have trained a logistic regression classifier which is outputting $h_{\theta}(x)$. **1 / 1 point**

Currently, you predict 1 if $h_{\theta}(x) \geq \text{threshold}$, and predict 0 if $h_{\theta}(x) < \text{threshold}$, where currently the threshold is set to 0.5.

Suppose you **decrease** the threshold to 0.3. Which of the following are true? Check all that apply.

- ☐ The classifier is likely to have unchanged precision and recall, but higher accuracy.
- ☐ The classifier is likely to now have higher precision.
- ☐ The classifier is likely to have unchanged precision and recall, but lower accuracy.
- ☒ The classifier is likely to now have higher recall.



Correct

Lowering the threshold means more $y = 1$ predictions. This will increase the number of true positives and decrease the number of false negatives, so recall will increase.

4. Suppose you are working on a spam classifier, where spam emails are positive examples ($y = 1$) and non-spam emails are negative examples ($y = 0$). You have a training set of emails in which 99% of the emails are non-spam and the other 1% is spam. Which of the following statements are true? Check all that apply.

1 / 1 point

- ☐ If you always predict non-spam (output $y = 0$), your classifier will have 99% accuracy on the training set, but it will do much worse on the cross validation set because it has overfit the training

data.

- ☒ If you always predict non-spam (output $y = 0$), your classifier will have an accuracy of 99%.



Correct

Since 99% of the examples are $y = 0$, always predicting 0 gives an accuracy of 99%. Note, however, that this is not a good spam system, as you will never catch any spam.

- ☒ A good classifier should have both a high precision and high recall on the cross validation set.



Correct

For data with skewed classes like these spam data, we want to achieve a high F_1 score, which requires high precision and high recall.

- ☒ If you always predict non-spam (output $y = 0$), your classifier will have 99% accuracy on the training set, and it will likely perform similarly on the cross validation set.



Correct

The classifier achieves 99% accuracy on the training set because of how skewed the classes are. We can expect that the cross-validation set will be skewed in the same fashion, so the classifier will have approximately the same accuracy.

5. Which of the following statements are true? Check all that apply.

☐ It is a good idea to spend a lot of time collecting a **large** amount of data before building your first version of a learning algorithm.

☒ Using a **very large** training set makes it unlikely for model to overfit the training data.



Correct

A sufficiently large training set will not be overfit, as the model cannot overfit some of the examples without doing poorly on the others.

☒ The "error analysis" process of manually examining the examples which your algorithm got wrong can help suggest what are good steps to take (e.g., developing new features) to improve your algorithm's performance.



Correct

This process of error analysis is crucial in developing high performance learning systems, as the space of possible improvements to your system is very large, and it gives you direction about what to work on next.

☐ After training a logistic regression classifier, you **must** use 0.5 as your threshold for predicting whether an example is positive or negative.

- ☐ If your model is underfitting the training set, then obtaining more data is likely to help.