

1. You are working on a spam classification system using regularized logistic regression. "Spam" is a positive class ($y = 1$) and "not spam" is the negative class ($y = 0$). You have trained your classifier and there are $m = 1000$ examples in the cross-validation set. The chart of predicted class vs. actual class is:

0 / 1 point

| | Actual Class: 1 | Actual Class: 0 |
|--------------------|-----------------|-----------------|
| Predicted Class: 1 | 85 | 890 |
| Predicted Class: 0 | 15 | 10 |

For reference:

- Accuracy = (true positives + true negatives) / (total examples)
- Precision = (true positives) / (true positives + false positives)
- Recall = (true positives) / (true positives + false negatives)
- F_1 score = $(2 * \text{precision} * \text{recall}) / (\text{precision} + \text{recall})$

What is the classifier's precision (as a value from 0 to 1)?

Enter your answer in the box below. If necessary, provide at least two values after the decimal point.

0.9

! Incorrect

2. Suppose a massive dataset is available for training a learning algorithm. Training on a lot of data is likely to give good performance when two of the following conditions hold true.

1 / 1 point

Which are the two?

- ☒ We train a learning algorithm with a large number of parameters (that is able to learn/represent fairly complex functions).



Correct

You should use a "low bias" algorithm with many parameters, as it will be able to make use of the large dataset provided. If the model has too few parameters, it will underfit the large training set.

- ☒ The features x contain sufficient information to predict y accurately. (For example, one way to verify this is if a human expert on the domain can confidently predict y when given only x).



Correct

It is important that the features contain sufficient information, as otherwise no amount of data can solve a learning problem in which the features do not contain enough information to make an accurate prediction.

- ☐ We train a learning algorithm with a small number of parameters (that is thus unlikely to overfit).
- ☐ We train a model that does not use regularization.

3. Suppose you have trained a logistic regression classifier which is outputting $h_{\theta}(x)$.

1 / 1 point

Currently, you predict 1 if $h_{\theta}(x) \geq \text{threshold}$, and predict 0 if $h_{\theta}(x) < \text{threshold}$, where currently the threshold is set to 0.5.

Suppose you **increase** the threshold to 0.7. Which of the following are true? Check all that apply.

- ☐ The classifier is likely to have unchanged precision and recall, but higher accuracy.
- ☐ The classifier is likely to have unchanged precision and recall, but lower accuracy.
- ☐ The classifier is likely to now have lower precision.
- ☒ The classifier is likely to now have lower recall.



Correct

Increasing the threshold means more $y = 0$ predictions. This will increase the decrease of true positives and increase the number of false negatives, so recall will decrease.

4. Suppose you are working on a spam classifier, where spam emails are positive examples ($y = 1$) and non-spam emails are negative examples ($y = 0$). You have a training set of emails in which 99% of the emails are non-spam and the other 1% is spam. Which of the following statements are true? Check all that apply.

0 / 1 point

- ☒ A good classifier should have both a high precision and high recall on the cross validation set.



Correct

For data with skewed classes like these spam data, we want to achieve a high F_1 score, which requires high precision and high recall.

F_1 score, which requires high precision and high recall.

☒ If you always predict non-spam (output $y = 0$), your classifier will have 99% accuracy on the training set, but it will do much worse on the cross validation set because it has overfit the training data.



This should not be selected

The classifier achieves 99% accuracy because of the skewed classes in the data, not because it is overfitting the training set. Thus, it is likely to perform just as well on the cross validation set.

☒ If you always predict non-spam (output $y = 0$), your classifier will have 99% accuracy on the training set, and it will likely perform similarly on the cross validation set.



Correct

The classifier achieves 99% accuracy on the training set because of how skewed the classes are. We can expect that the cross-validation set will be skewed in the same fashion, so the classifier will have approximately the same accuracy.

☐ If you always predict non-spam (output $y = 0$), your classifier will have an accuracy of 99%.

5. Which of the following statements are true? Check all that apply.

☒ Using a **very large** training set makes it unlikely for model to overfit the training

data.

✓ **Correct**

A sufficiently large training set will not be overfit, as the model cannot overfit some of the examples without doing poorly on the others.

✓ The "error analysis" process of manually

examining the examples which your algorithm got wrong

can help suggest what are good steps to take (e.g.,

developing new features) to improve your algorithm's

performance.

✓ **Correct**

This process of error analysis is crucial in developing high performance learning systems, as the space of possible improvements to your system is very large, and it gives you direction about what to work on next.

☐ If your model is underfitting the

training set, then obtaining more data is likely to

help.

☐ It is a good idea to spend a lot of time

collecting a **large** amount of data before building

your first version of a learning algorithm.

☐ After training a logistic regression

classifier, you **must** use 0.5 as your threshold

for predicting whether an example is positive or

negative.