

This is the svm workbook for ECE 239AS Assignment #2

Please follow the notebook linearly to implement a linear support vector machine.

Please print out the workbook entirely when completed.

We thank Serena Yeung & Justin Johnson for permission to use code written for the CS 231n class (cs231n.stanford.edu).

These are the functions in the cs231n folders and includes code to preprocess and show the images. The classifiers used are based off of code prepared for CS 231n as well.

The goal of this workbook is to give you experience with training an SVM classifier via gradient descent.

Importing libraries and data setup

```
In [1]: import numpy as np # for doing most of our calculations
import matplotlib.pyplot as plt # for plotting
from cs231n.data_utils import load_CIFAR10 # function to load the CIFAR-10
dataset.
import pdb

# Load matplotlib images inline
%matplotlib inline

# These are important for reloading any code you write in external .py file
s.
# see http://stackoverflow.com/questions/1907993/autoreload-of-modules-in-i
python
%load_ext autoreload
%autoreload 2
```

```
In [2]: # Set the path to the CIFAR-10 data
cifar10_dir = 'cifar-10-batches-py'
X_train, y_train, X_test, y_test = load_CIFAR10(cifar10_dir)

# As a sanity check, we print out the size of the training and test data.
print('Training data shape: ', X_train.shape)
print('Training labels shape: ', y_train.shape)
print('Test data shape: ', X_test.shape)
print('Test labels shape: ', y_test.shape)

('Training data shape: ', (50000, 32, 32, 3))
('Training labels shape: ', (50000,))
('Test data shape: ', (10000, 32, 32, 3))
('Test labels shape: ', (10000,))
```

```
In [3]: # Visualize some examples from the dataset.
# We show a few examples of training images from each class.
classes = ['plane', 'car', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship', 'truck']
num_classes = len(classes)
samples_per_class = 7
for y, cls in enumerate(classes):
    idxs = np.flatnonzero(y_train == y)
    idxs = np.random.choice(idxs, samples_per_class, replace=False)
    for i, idx in enumerate(idxs):
        plt_idx = i * num_classes + y + 1
        plt.subplot(samples_per_class, num_classes, plt_idx)
        plt.imshow(X_train[idx].astype('uint8'))
        plt.axis('off')
        if i == 0:
            plt.title(cls)
plt.show()
```



```
In [4]: # Split the data into train, val, and test sets. In addition we will
# create a small development set as a subset of the training data;
# we can use this for development so our code runs faster.
num_training = 49000
num_validation = 1000
num_test = 1000
num_dev = 500

# Our validation set will be num_validation points from the original
# training set.
mask = range(num_training, num_training + num_validation)
X_val = X_train[mask]
y_val = y_train[mask]

# Our training set will be the first num_train points from the original
# training set.
mask = range(num_training)
X_train = X_train[mask]
y_train = y_train[mask]

# We will also make a development set, which is a small subset of
# the training set.
mask = np.random.choice(num_training, num_dev, replace=False)
X_dev = X_train[mask]
y_dev = y_train[mask]

# We use the first num_test points of the original test set as our
# test set.
mask = range(num_test)
X_test = X_test[mask]
y_test = y_test[mask]

print('Train data shape: ', X_train.shape)
print('Train labels shape: ', y_train.shape)
print('Validation data shape: ', X_val.shape)
print('Validation labels shape: ', y_val.shape)
print('Test data shape: ', X_test.shape)
print('Test labels shape: ', y_test.shape)
print('Dev data shape: ', X_dev.shape)
print('Dev labels shape: ', y_dev.shape)

('Train data shape: ', (49000, 32, 32, 3))
('Train labels shape: ', (49000,))
('Validation data shape: ', (1000, 32, 32, 3))
('Validation labels shape: ', (1000,))
('Test data shape: ', (1000, 32, 32, 3))
('Test labels shape: ', (1000,))
('Dev data shape: ', (500, 32, 32, 3))
('Dev labels shape: ', (500,))
```


```
In [5]: # Preprocessing: reshape the image data into rows
X_train = np.reshape(X_train, (X_train.shape[0], -1))
X_val = np.reshape(X_val, (X_val.shape[0], -1))
X_test = np.reshape(X_test, (X_test.shape[0], -1))
X_dev = np.reshape(X_dev, (X_dev.shape[0], -1))

# As a sanity check, print out the shapes of the data
print('Training data shape: ', X_train.shape)
print('Validation data shape: ', X_val.shape)
print('Test data shape: ', X_test.shape)
print('dev data shape: ', X_dev.shape)

('Training data shape: ', (49000, 3072))
('Validation data shape: ', (1000, 3072))
('Test data shape: ', (1000, 3072))
('dev data shape: ', (500, 3072))
```

```
In [6]: # Preprocessing: subtract the mean image
# first: compute the image mean based on the training data
mean_image = np.mean(X_train, axis=0)
print(mean_image[:10]) # print a few of the elements
plt.figure(figsize=(4,4))
plt.imshow(mean_image.reshape((32,32,3)).astype('uint8')) # visualize the m
ean image
plt.show()

[130.64189796 135.98173469 132.47391837 130.05569388 135.34804082
 131.75402041 130.96055102 136.14328571 132.47636735 131.48467347]
```



```
In [7]: # second: subtract the mean image from train and test data
X_train -= mean_image
X_val -= mean_image
X_test -= mean_image
X_dev -= mean_image
```

```
In [8]: # third: append the bias dimension of ones (i.e. bias trick) so that our SVM
# only has to worry about optimizing a single weight matrix W.
X_train = np.hstack([X_train, np.ones((X_train.shape[0], 1))])
X_val = np.hstack([X_val, np.ones((X_val.shape[0], 1))])
X_test = np.hstack([X_test, np.ones((X_test.shape[0], 1))])
X_dev = np.hstack([X_dev, np.ones((X_dev.shape[0], 1))])

print(X_train.shape, X_val.shape, X_test.shape, X_dev.shape)

((49000, 3073), (1000, 3073), (1000, 3073), (500, 3073))
```

Question:

(1) For the SVM, we perform mean-subtraction on the data. However, for the KNN notebook, we did not. Why?

Answer:

(1) Mean subtracting on KNN would shift all of the points an equal amount, changing nothing about the neighbors. In the SVM we need to mean subtract so that the data is zero centered and the gradients behave well in multiple directions.

Training an SVM

The following cells will take you through building an SVM. You will implement its loss function, then subsequently train it with gradient descent. Finally, you will choose the learning rate of gradient descent to optimize its classification performance.

```
In [9]: from nndl.svm import SVM
```

```
In [10]: # Declare an instance of the SVM class.
# Weights are initialized to a random value.
# Note, to keep people's initial solutions consistent, we are going to use
# a random seed.

np.random.seed(1)

num_classes = len(np.unique(y_train))
num_features = X_train.shape[1]

svm = SVM(dims=[num_classes, num_features])
```

SVM loss

```
In [11]: ## Implement the loss function for in the SVM class(nndl/svm.py), svm.loss(
)

loss = svm.loss(X_train, y_train)
print('The training set loss is {}'.format(loss))

# If you implemented the loss correctly, it should be 15569.98

The training set loss is 15569.9779154.
```

SVM gradient

```
In [12]: ## Calculate the gradient of the SVM class.  
# For convenience, we'll write one function that computes the loss  
# and gradient together. Please modify svm.loss_and_grad(X, y).  
# You may copy and paste your loss code from svm.loss() here, and then  
# use the appropriate intermediate values to calculate the gradient.  
  
loss, grad = svm.loss_and_grad(X_dev, y_dev)  
  
# Compare your gradient to a numerical gradient check.  
# You should see relative gradient errors on the order of 1e-07 or less if  
you implemented the gradient correctly.  
svm.grad_check_sparse(X_dev, y_dev, grad)  
  
numerical: -1.206368 analytic: -1.206368, relative error: 2.021268e-08  
numerical: -3.718714 analytic: -3.718714, relative error: 4.861115e-08  
numerical: -15.580961 analytic: -15.580962, relative error: 8.377393e-09  
numerical: 7.447614 analytic: 7.447614, relative error: 9.620118e-09  
numerical: 1.463854 analytic: 1.463854, relative error: 2.810277e-08  
numerical: -1.582701 analytic: -1.582700, relative error: 5.687247e-08  
numerical: 10.859661 analytic: 10.859661, relative error: 2.932411e-08  
numerical: -10.477690 analytic: -10.477689, relative error: 8.514592e-09  
numerical: 3.381478 analytic: 3.381478, relative error: 1.827548e-09  
numerical: -17.365182 analytic: -17.365182, relative error: 2.538693e-09
```

A vectorized version of SVM

To speed things up, we will vectorize the loss and gradient calculations. This will be helpful for stochastic gradient descent.

```
In [13]: import time
```

```
In [14]: ## Implement svm.fast_loss_and_grad which calculates the loss and gradient
# WITHOUT using any for loops.

# Standard loss and gradient
tic = time.time()
loss, grad = svm.loss_and_grad(X_dev, y_dev)
toc = time.time()
print('Normal loss / grad_norm: {} / {} computed in {}'.format(loss, np.linalg.norm(grad, 'fro'), toc - tic))

tic = time.time()
loss_vectorized, grad_vectorized = svm.fast_loss_and_grad(X_dev, y_dev)
toc = time.time()
print('Vectorized loss / grad: {} / {} computed in {}'.format(loss_vectorized, np.linalg.norm(grad_vectorized, 'fro'), toc - tic))

# The losses should match but your vectorized implementation should be much faster.
print('difference in loss / grad: {} / {}'.format(loss - loss_vectorized, np.linalg.norm(grad - grad_vectorized)))

# You should notice a speedup with the same output, i.e., differences on the order of 1e-12

Normal loss / grad_norm: 15879.6858177 / 2182.00689622 computed in 0.0744769573212s
Vectorized loss / grad: 15879.6858177 / 2182.00689622 computed in 0.00919795036316s
difference in loss / grad: 1.27329258248e-11 / 3.77857077752e-12
```

Stochastic gradient descent


We now implement stochastic gradient descent. This uses the same principles of gradient descent we discussed in class, however, it calculates the gradient by only using examples from a subset of the training set (so each gradient calculation is faster).

In [15]: *# Implement svm.train() by filling in the code to extract a batch of data
and perform the gradient step.*

```
tic = time.time()
loss_hist = svm.train(X_train, y_train, learning_rate=5e-4,
                      num_iters=1500, verbose=True)
toc = time.time()
print('That took {}s'.format(toc - tic))

plt.plot(loss_hist)
plt.xlabel('Iteration number')
plt.ylabel('Loss value')
plt.show()
```

```
iteration 0 / 1500: loss 16557.3800019
iteration 100 / 1500: loss 4701.08945127
iteration 200 / 1500: loss 4017.33313794
iteration 300 / 1500: loss 3681.9226472
iteration 400 / 1500: loss 2732.6164374
iteration 500 / 1500: loss 2786.63784246
iteration 600 / 1500: loss 2837.03578428
iteration 700 / 1500: loss 2206.23486874
iteration 800 / 1500: loss 2269.03882412
iteration 900 / 1500: loss 2543.23781539
iteration 1000 / 1500: loss 2566.69213573
iteration 1100 / 1500: loss 2182.06890591
iteration 1200 / 1500: loss 1861.11822443
iteration 1300 / 1500: loss 1982.90138585
iteration 1400 / 1500: loss 1927.52041586
That took 5.89598894119s
```



Evaluate the performance of the trained SVM on the validation data.


```
In [16]: ## Implement svm.predict() and use it to compute the training and testing error.

y_train_pred = svm.predict(X_train)
print('training accuracy: {}'.format(np.mean(np.equal(y_train,y_train_pred)
, )))
y_val_pred = svm.predict(X_val)
print('validation accuracy: {}'.format(np.mean(np.equal(y_val, y_val_pred))
, ))

training accuracy: 0.285306122449
validation accuracy: 0.3
```

Optimize the SVM

Note, to make things faster and simpler, we won't do k-fold cross-validation, but will only optimize the hyperparameters on the validation dataset (X_val, y_val).

```
In [33]: # ===== #
# YOUR CODE HERE:
# Train the SVM with different learning rates and evaluate on the
# validation data.
# Report:
# - The best learning rate of the ones you tested.
# - The best VALIDATION accuracy corresponding to the best VALIDATION e
rror.
#
# Select the SVM that achieved the best validation error and report
# its error rate on the test set.
# Note: You do not need to modify SVM class for this section
# ===== #

learning_rates = [5e-2, 1e-2, 5e-3, 1e-3, 5e-4, 1e-4, 5e-5, 1e-5]
validation_scores = []

for i in np.arange(len(learning_rates)):
    svm.train(X_train, y_train, learning_rate=learning_rates[i],
              num_iters=1500, verbose=False)

    y_val_pred = svm.predict(X_val)
    validation_scores.append(np.mean(np.equal(y_val, y_val_pred)))

m_idx = np.argmax(validation_scores)

print validation_scores
print 'Learning rate of {} achieved the best validation rate of {}'.format(
learning_rates[m_idx], validation_scores[m_idx])

# ===== #
# END YOUR CODE HERE
# ===== #

[0.314, 0.275, 0.319, 0.267, 0.303, 0.271, 0.266, 0.214]
Learning rate of 0.005 achieved the best validation rate of 0.319
```