

Homework3 Report Template

Professor Pei-Yuan Wu
EE5184 - Machine Learning

姓名：馬咏治

學號：Ro7943123


Note: 1~3 題建議不要超過三頁

1. (1%) 請說明你實作的 CNN model，其模型架構、訓練過程和準確率為何？


| Layer (type) | Output Shape | Param # |
|---------------------------------------------|---------------------|---------|
| conv2d_1 (Conv2D) | (None, 48, 48, 64) | 640 |
| leaky_re_lu_1 (LeakyReLU) | (None, 48, 48, 64) | 0 |
| batch_normalization_1 (Batch Normalization) | (None, 48, 48, 64) | 256 |
| conv2d_2 (Conv2D) | (None, 48, 48, 64) | 36928 |
| leaky_re_lu_2 (LeakyReLU) | (None, 48, 48, 64) | 0 |
| batch_normalization_2 (Batch Normalization) | (None, 48, 48, 64) | 256 |
| max_pooling2d_1 (MaxPooling2D) | (None, 24, 24, 64) | 0 |
| dropout_1 (Dropout) | (None, 24, 24, 64) | 0 |
| conv2d_3 (Conv2D) | (None, 24, 24, 128) | 73856 |
| leaky_re_lu_3 (LeakyReLU) | (None, 24, 24, 128) | 0 |
| batch_normalization_3 (Batch Normalization) | (None, 24, 24, 128) | 512 |
| conv2d_4 (Conv2D) | (None, 24, 24, 128) | 147584 |
| leaky_re_lu_4 (LeakyReLU) | (None, 24, 24, 128) | 0 |
| batch_normalization_4 (Batch Normalization) | (None, 24, 24, 128) | 512 |
| max_pooling2d_2 (MaxPooling2D) | (None, 12, 12, 128) | 0 |
| dropout_2 (Dropout) | (None, 12, 12, 128) | 0 |
| conv2d_5 (Conv2D) | (None, 12, 12, 192) | 221376 |
| leaky_re_lu_5 (LeakyReLU) | (None, 12, 12, 192) | 0 |
| batch_normalization_5 (Batch Normalization) | (None, 12, 12, 192) | 768 |
| conv2d_6 (Conv2D) | (None, 12, 12, 192) | 331968 |
| leaky_re_lu_6 (LeakyReLU) | (None, 12, 12, 192) | 0 |
| batch_normalization_6 (Batch Normalization) | (None, 12, 12, 192) | 768 |
| max_pooling2d_3 (MaxPooling2D) | (None, 6, 6, 192) | 0 |

| | | |
|----------------------------------------------|-------------------|---------|
| dropout_3 (Dropout) | (None, 6, 6, 192) | 0 |
| conv2d_7 (Conv2D) | (None, 6, 6, 256) | 442624 |
| leaky_re_lu_7 (LeakyReLU) | (None, 6, 6, 256) | 0 |
| batch_normalization_7 (Batch Normalization) | (None, 6, 6, 256) | 1024 |
| conv2d_8 (Conv2D) | (None, 6, 6, 256) | 590080 |
| leaky_re_lu_8 (LeakyReLU) | (None, 6, 6, 256) | 0 |
| batch_normalization_8 (Batch Normalization) | (None, 6, 6, 256) | 1024 |
| max_pooling2d_4 (MaxPooling2D) | (None, 3, 3, 256) | 0 |
| dropout_4 (Dropout) | (None, 3, 3, 256) | 0 |
| conv2d_9 (Conv2D) | (None, 3, 3, 512) | 1180160 |
| leaky_re_lu_9 (LeakyReLU) | (None, 3, 3, 512) | 0 |
| batch_normalization_9 (Batch Normalization) | (None, 3, 3, 512) | 2048 |
| conv2d_10 (Conv2D) | (None, 3, 3, 512) | 2359808 |
| leaky_re_lu_10 (LeakyReLU) | (None, 3, 3, 512) | 0 |
| batch_normalization_10 (Batch Normalization) | (None, 3, 3, 512) | 2048 |
| max_pooling2d_5 (MaxPooling2D) | (None, 1, 1, 512) | 0 |
| dropout_5 (Dropout) | (None, 1, 1, 512) | 0 |
| flatten_1 (Flatten) | (None, 512) | 0 |
| dense_1 (Dense) | (None, 1024) | 525312 |
| dropout_6 (Dropout) | (None, 1024) | 0 |
| dense_2 (Dense) | (None, 7) | 7175 |
| Total params: 5,926,727 | | |
| Trainable params: 5,922,119 | | |
| Non-trainable params: 4,608 | | |

訓練過程：



準確率：68.737% (public)





2. (1%) 承上題，請用與上述 CNN 接近的參數量，實做簡單的 DNN model，其模型架構、訓練過程和準確率為何？試與上題結果做比較，並說明你觀察到了什麼？

| Layer (type) | Output Shape | Param # |
|-----------------------------|--------------|---------|
| flatten_1 (Flatten) | (None, 2304) | 0 |
| dense_1 (Dense) | (None, 512) | 1180160 |
| dropout_1 (Dropout) | (None, 512) | 0 |
| dense_2 (Dense) | (None, 1024) | 525312 |
| dropout_2 (Dropout) | (None, 1024) | 0 |
| dense_3 (Dense) | (None, 2048) | 2099200 |
| dropout_3 (Dropout) | (None, 2048) | 0 |
| dense_4 (Dense) | (None, 1024) | 2098176 |
| dropout_4 (Dropout) | (None, 1024) | 0 |
| dense_5 (Dense) | (None, 7) | 7175 |
| Total params: 5,910,023 | | |
| Trainable params: 5,910,023 | | |
| Non-trainable params: 0 | | |


訓練過程：

準確率：14.1%



使用 dnn 來 training 可以發現到 loss 和 accuracy 都一直在震盪，testing accuracy 一直保持在 14.1%，代表 nn 裡面的 weight 基本上已經穩定不會有大變動了。我想可能 dnn 在把圖片拉平後，讓圖片失去了一些局部的特性，是的這個被拉平的向量不具有太多的意義。

3. (1%) 觀察答錯的圖片中，哪些 class 彼此間容易用混？並說明你觀察到了什麼？[繪出 confusion matrix 分析]



根據我的觀察，Fear 和 Sad，Disgust 和 Angry 兩個 class 蠻容易混在一起的。在 779 個 Fear 照片中有 150 誤認為是 Sad，佔了 19%，而在 74 個 Disgust 照片中，有 20 張誤認為是 Angry。

會產生他們弄混的原因，我想是因為一般人很難單純以臉部標表情來判斷這個人的 emotion status，更何況是 Fear，Sad 和 Disgust，Angry 這幾個 class 的照片相似度這麼高，一個原因是 label 可能會標錯，或者是他們這幾個 class 之間並不好分辨，儘管是讓人類來分辨的話

-----Handwritten question-----

4. (1.5%, each 0.5%) CNN time/space complexity:

For a. b. Given a CNN model as

```
model = Sequential()
model.add(Conv2D(filters=6,
                  strides=(3, 3),
                  padding="valid",
                  kernel_size=(2,2),
                  input_shape=(8,8,5),
                  activation='relu'))
model.add(Conv2D(filters=4,
                  strides=(2, 2),
                  padding="valid",
                  kernel_size=(2,2),
                  activation='relu'))
```

And for the c. given the parameter as:
 kernel size = (k,k);
 channel size = c;
 filter size = f;
 input shape = (n,n);
 padding = 1;
 strides = (s,s);

- a. How many parameters are there in each layer(Hint: you may consider whether the number of parameter is related with)
 Layer A: 126
 Layer B: 100
- b. How many multiplications/additions are needed for a forward pass(each layer).
 Layer A: 1080/36
 Layer B: 96/4
- c. What is the time complexity of convolutional neural networks?(note: you must use big-O upper bound, and there are l layer, you can use $\square_0, \square_1, \dots, \square_{l-1}$ as lth and l-1th layer)

$$C_1: k^2 * c * f * \left(\frac{n}{s}\right)^2 + f$$

$$C_2: k^2 * f^2 * \left(\frac{n}{s^2}\right)^2 + f$$

.
.
.

$$C_l: k^2 * f^2 * \left(\frac{n}{s^l}\right)^2 + f$$

$$\text{Complexity} = C_1 * C_2 * \dots * C_l = O(ck^{2l}f^{2l-1}n^{2l}s^{-l(l+1)})$$

5. (1.5%,each 0.5%)PCA practice:Problem statement: Given 10 samples in 3D space.
 $(1,2,3), (4,8,5), (3,12,9), (1,8,5), (5,14,2), (7,4,1), (9,8,9), (3,8,1), (11,5,6), (10,11,7)$
 a. (1) What are the principal axes?

$$\mu = \begin{bmatrix} 5.4 \\ 8 \\ 4.8 \end{bmatrix}$$

$$\Sigma = \frac{1}{10} \sum_{i=1}^{10} (x_i - \mu)(x_i - \mu)^T$$

$$= \begin{bmatrix} 12.04 & 0.5 & 3.28 \\ 0.5 & 12.2 & 2.9 \\ 3.28 & 2.9 & 8.16 \end{bmatrix}$$

After Calculated Covariance Matrix, find the three eigenvector, which also is the principal axes

$$v_1 = \begin{bmatrix} -0.616595 \\ -0.588816 \\ -0.522596 \end{bmatrix} \quad v_2 = \begin{bmatrix} 0.678179 \\ -0.73439 \\ 0.0272856 \end{bmatrix} \quad v_3 = \begin{bmatrix} -0.399855 \\ -0.337589 \\ 0.852144 \end{bmatrix}$$

$$\lambda_1 = 15.2974, \lambda_2 = 11.6305, \lambda_3 = 5.47203$$

b. (2) Compute the principal components for each sample.

After Mapping to the principal axes (v_1, v_2, v_3) , the 10 sample are:

$$a_1 = \begin{bmatrix} -3.36 \\ -0.709 \\ 1.481 \end{bmatrix}, a_2 = \begin{bmatrix} -9.79 \\ -3.026 \\ -0.039 \end{bmatrix}, a_3 = \begin{bmatrix} -13.62 \\ -6.53 \\ 2.42 \end{bmatrix}, a_4 = \begin{bmatrix} -7.94 \\ -5.06 \\ 1.16 \end{bmatrix},$$

$$a_5 = \begin{bmatrix} -12.37 \\ -6.836 \\ -5.02 \end{bmatrix}, a_6 = \begin{bmatrix} -7.19 \\ 1.837 \\ -3.30 \end{bmatrix}, a_7 = \begin{bmatrix} -14.96 \\ 0.474 \\ 1.370 \end{bmatrix}$$

$$a_8 = \begin{bmatrix} -7.083 \\ -3.813 \\ -3.048 \end{bmatrix}, a_9 = \begin{bmatrix} -12.86 \\ 3.952 \\ -0.973 \end{bmatrix}, a_{10} = \begin{bmatrix} -16.301 \\ -1.106 \\ -1.747 \end{bmatrix}$$

c. (3) Reconstruction error if reduced to 2D.

(Calculate the L2-norm)

We reduce these 10 sample to v_1, v_2 since they have highest eigenvalue

After reconstruction,

$$a_1 = \begin{bmatrix} 1.591 \\ 2.499 \\ 1.737 \end{bmatrix}, a_2 = \begin{bmatrix} 3.984 \\ 7.987 \\ 5.034 \end{bmatrix}, a_3 = \begin{bmatrix} 3.970 \\ 12.815 \\ 6.940 \end{bmatrix}, a_4 = \begin{bmatrix} 1.464 \\ 8.391 \\ 4.011 \end{bmatrix},$$

$$a_5 = \begin{bmatrix} 2.991 \\ 12.304 \\ 6.278 \end{bmatrix}, a_6 = \begin{bmatrix} 5.680 \\ 2.885 \\ 3.808 \end{bmatrix}, a_7 = \begin{bmatrix} 9.546 \\ 8.461 \\ 7.831 \end{bmatrix}$$

$$a_8 = \begin{bmatrix} 1.781 \\ 6.971 \\ 3.598 \end{bmatrix}, a_9 = \begin{bmatrix} 10.610 \\ 4.670 \\ 6.828 \end{bmatrix}, a_{10} = \begin{bmatrix} 9.301 \\ 10.411 \\ 8.489 \end{bmatrix}$$

Next, we calculate the L2 Norm

$$L2(a_1) = |\Delta a_1|^2 = 2.1945$$

$$L2(a_2) = |\Delta a_2|^2 = 0.0016$$

$$L2(a_3) = |\Delta a_3|^2 = 5.8498$$

$$L2(a_4) = |\Delta a_4|^2 = 1.3459$$

$$L2(a_5) = |\Delta a_5|^2 = 25.2129$$

$$L2(a_6) = |\Delta a_6|^2 = 10.8715$$

$$L2(a_7) = |\Delta a_7|^2 = 1.8766$$

$$L2(a_8) = |\Delta a_8|^2 = 9.2911$$

$$L2(a_9) = |\Delta a_9|^2 = 0.9477$$

$$L2(a_{10}) = |\Delta a_{10}|^2 = 3.0521$$