

INTRO TO ARTIFICIAL INTELLIGENCE

---

# Assignment 1

Fast Trajectory Planning

---

*Authors:*

Brian LIN

Samuel YANG

*Supervisor:*

Dr. Abdeslam BOULARIAS



RUTGERS STATE UNIVERSITY OF NEW JERSEY

February 26, 2018

# Introduction

Your introduction goes here! Some examples of commonly used commands and features are listed below, to help you get started.

If you have a question, please use the support box in the bottom right of the screen to get in touch.

## Part 1 - Understanding the Methods

### A) - East vs North




Figure 1: Second Example Search Problem

The agent in the figure above begins its pathfinding without knowledge of which cells are blocked. From the perspective of being able to fully observe the maze, it appears clear that the best path for the agent is to move north to go around the obstacle. However, under the initial assumption that all cells are unblocked the shortest path from the current cell to the target is to move towards the east, as it has a direct path to the target cell. Only once the agent has moved to the cell to the east, will it observe the blocked cells that do not allow it to use that path and force the agent to find a new path to the target.

### B) - Proving Completeness

## Part 2 - The Effects of Ties

The figure above compares the total runtime using 3 different Repeated Forward A\* (RFAS) algorithms over 50 test cases. The blue line in




Figure 2: Effect of g-score based tie-breaking

the line graph represents the basic RFAS algorithm. The red line builds on the RFAS by breaking ties between states with the same smallest f-value by choosing the state with the higher g-score. The green line similarly impacts RFAS by adding in a tiebreaker but instead chooses the state with the lower g-score value. The data plotted in the figure can be observed in Table 1. Comparing the total compute times reveals that generally, RFAS implemented with some form of tiebreaker outperformed basic RFAS. To examine the differences and impact between using based a high g-score or a low g-score on the efficiency of the algorithm, examine Figure 3 and the computational times in Table 1. It is observed that for the majority of test cases, the computational time difference between tiebreakers emphasizing a higher g-score and those that chose a lower g-score were rather small. However, there is an overall trend of the higher g-score value actually outperforming the lower g-score value that was more observable when the algorithm and the paths were displayed. To understand the increase in speed and efficiency of the algorithm, recall that the f-score value is a sum of the g-score and the heuristic




Figure 3: Comparing tie-breaking based on higher g-scores vs lower g-scores




Figure 4: Repeated Forward A\* vs Repeated Backward A\*

cost for each cell. Cells with the same f-score, but having a lower g-score will therefore have a higher heuristic cost, meaning a higher estimate of the moves needed to reach the goal. Cells with a higher g-score would have a lower heuristic cost and ultimately provide a better path towards the goal cell. By choosing the higher g-score as a tiebreaker, the agent continues to move towards the target cell while reducing the future distance that would need to be traversed.

### Part 3 - Forward vs Backward

The data represented in the line graph above indicates that again, computational times were incredibly similar. This time, the comparisons are between Repeated Forward A\*, performing the algorithm from the agent cell to the target cell, and Repeated Backward A\* (RBAS), having the algorithm traverse the maze from the target cell to the agent. Examining the data more thoroughly, and observing the displayed output for both instances,

it begins to become possible to identify when each algorithm would outperform the other.



Figure 5: Test Case 26

1cm In the maze above, the agent cell encounters a heavily blocked off area along its prepared path soon after leaving the initial starting position. The shape of the blocked cells, rough resembles a wedge, where the agent will move towards the cells at the end of the funnel, as they will have the lowest f-score, but will eventually have to choose a different route as it discovers that there is no viable path through that area. In this instance, the RBAS algorithm outperformed the RFAS algorithm because when it encounters the blocked off cells that form this trap, it chooses a path that navigates around this obstacle, rather than first exploring it.

In other situations, RFAS is revealed to be the more efficient algorithm than RBAS. In Figure 6: Test Case 10, found below, one such example can be observed. This time, the target cell has a wedge-like formation of blocked cells that funnels the target cell into more blocked cells until the path would be deemed no longer viable and an alternative one would have to be taken.




Figure 6: Test Case 10

## Part 4 - Proving Heuristics in the Adaptive A\*

## Part 5 - Heuristics in the Adaptive A\*

The comparison of RFAS and Adaptive A\* proved to have the most significant differences




Figure 7: Comparing RFAS vs Adaptive A\*

in computational times, revealing the observable increase in efficiency that Adaptive A\* provides to the algorithm. During the examination of the various test cases, both algorithms started the initial repetitions at a similar speed. The speedup became evident as more and more repetitions of A\* were computed, as the agent moved away from the initial starting position. This correlates to the anticipated behavior of Adaptive A\* as the implementation of this algorithm means that future A\* searches do not have to spend time computing the heuristic costs of previously expanded cells. Rather, cells that had been expanded in previous iterations would have their heuristics be passed into the current search to reduce the overall computational time. As the agent moved closer to the target cell, the computational time continued to decrease in comparison to the RFAS. In all instances where the recorded time of RFAS was faster than the Adaptive A\*, the difference was negligible enough that other factors such as processor consistency could account for the time differences.

## Part 6 - Memory Issues

## Recorded Data

Testcase	R.Foward A*	RFAS HighG	RFAS LowG	R.Backward A*	Adaptive A*
1	0.18031	0.17805	0.17369	0.1801	0.16311
2	0.05316	0.1563	0.05501	0.04421	0.04815
3	0.01451	0.37243	0.01579	0.01735	0.01532
4	0.1154	0.05835	0.04682	0.03984	0.03901
5	0.02399	0.03725	0.02912	0.02909	0.02887
6	0.08087	0.0501	0.04396	0.04474	0.03894
7	0.00426	0.00272	0.00273	0.00274	0.0031
8	0.03738	0.03012	0.03074	0.02859	0.02917
9	0.23135	0.1988	0.22777	0.17702	0.1627
10	0.16354	0.17776	0.18004	0.19133	0.17266
11	0.01025	0.00971	0.00923	0.00969	0.0098
12	0.28907	0.20436	0.21727	0.19082	0.17869
13	0.68515	0.35616	0.34659	0.32296	0.3571
14	0.03878	0.03237	0.02349	0.02396	0.02264
15	0.18915	0.08623	0.08186	0.07736	0.07528
16	0.04573	0.02215	0.01864	0.01861	0.01785
17	0.53899	0.13428	0.14064	0.11699	0.1328
18	0.36806	0.27552	0.30568	0.31164	0.27548
19	0.08804	0.07818	0.08235	0.07921	0.0765
20	0.04013	0.03526	0.03576	0.03042	0.04663
21	0.12534	0.07269	0.05749	0.06926	0.06892
22	0.11665	0.12213	0.12065	0.12261	0.11285
23	0.0022	0.00142	0.0014	0.00141	0.00136
24	0.03575	0.03744	0.03721	0.03908	0.04306
25	0.03671	0.02363	0.02986	0.0337	0.02562



Testcase	R.Foward A*	RFAS HighG	RFAS LowG	R.Backward A*	Adaptive A*
25	0.03671	0.02363	0.02986	0.0337	0.02562
26	0.18862	0.24024	0.20164	0.213	0.21173
27	0.00122	0.00099	0.00111	0.00118	0.00114
28	0.06164	0.05404	0.05515	0.03637	0.04476
29	0.29145	0.12526	0.1081	0.11839	0.11472
30	0.16431	0.04679	0.05303	0.04632	0.05009
31	0.2099	0.23009	0.25453	0.21298	0.24917
32	0.003	0.00245	0.00244	0.00244	0.00246
33	0.03076	0.02806	0.03103	0.02944	0.02524
34	0.04988	0.05898	0.04902	0.04079	0.04513
35	0.02356	0.02285	0.02236	0.01885	0.01753
36	0.18883	0.06269	0.0526	0.056	0.05686
37	0.03722	0.05894	0.07305	0.05806	0.0586
38	0.13161	0.07622	0.07941	0.07465	0.06411
39	0.09456	0.09503	0.09055	0.08602	0.08135
40	0.06185	0.02452	0.02434	0.02521	0.0249
41	0.53071	0.28605	0.28678	0.28523	0.27768
42	0.20066	0.13528	0.11477	0.11826	0.1082
43	0.7402	0.10712	0.11034	0.10902	0.10043
44	0.09136	0.05433	0.05641	0.05744	0.06319
45	0.02809	0.01911	0.01862	0.01919	0.02032
46	0.063	0.03151	0.03352	0.04151	0.03259
47	0.01576	0.01462	0.01756	0.01589	0.01512
48	0.0051	0.00394	0.00393	0.00397	0.00373
49	0.09776	0.07013	0.05215	0.05897	0.06572
50	0.0003	0.00025	0.00039	0.00031	0.00023

Table 1: An example table.