

We reserve all rights in this document and in the information contained herein. Reproduction, use or disclosure to third parties without express authority is strictly forbidden. © Copyright 2003 ABB

Supplementary document	Doc. type	Document	Description
------------------------	-----------	----------	-------------

Ventilating hood

Ø 1000

Min 2200

315


475

Wall or fence  
with weld  
curtain

Följande standarder gäller för uppbyggnad av stationslayouter :  
EN 249, EN 349, EN775, EN 953, EN 999.  
Vid avvikelse från dessa skall separat riskbedömning ske enligt SS-EN 1050.

Following standards are valid for design of station layouts :  
EN 249, EN 349, EN775, EN 953, EN 999.  
In case of deviation from these standards separate risk assesment according to standard EN 1050 must be done.

- 1) Distance calculated according to EN 999  
 $S = V (T1 + T2) + C$   
S Safety distance (m)  
V Entering speed (1,6 m/s)  
T1 Stopping time for the positioner (s).  
See technical date in the product manual.  
T2 Response time for light beam (0,02s).  
C Reaching distance (0,85m).



IRB/Pedestal updated.

Latest Revision

Prepared	Responsible Department RO/PRMW	Description	SWD	Drawing	
Approved	Take over department	Layout IRBP R-300 IRB 2600			Sheet 1
Status Approved	ECO number 500000054387	Layout IRBP R-300 IRB 2600			No. of sh. 1
		Document no. 3HAC042305-013			Rev. ind. 01