

App Delivery Manager

Lab Guide

TechXchange 2023

Version 1

5/1/2023 7:57:01 AM

UDF Lab

Deploy the following UDF Blueprint in the region closest to you:

NMS ADM Lab TechXchange 2023



Maintained by Brett Wolmarans

F5, Sr. Product Management Engineer – NGINX Management Suite Modules Ecosystem

 Solution

 UDF

\$0.53
per hour

11
Deploys

 **DEPLOY**

 **COLLABORATORS (2)**

 **UNPUBLISH**

 Documentation

 Internal

 Components

 Revisions

 C

Summary

Welcome to the ADM Lab!

You are going to do all your work from the RDP Jumpbox.
Please have RDP client ready to go on your Windows or Mac.

1. Click on Components
2. Scroll to Ubuntu Jumpbox, click Access, and click XRDP
3. username is: ubuntu password is: UBUNTU123!@#

Please ctrl-Click here for the Lab Guide: [ADM_UDF_Lab.pdf](#)

Please ctrl-Click here for the ADM Lab Presentation slides: [ADM_UDF_Lab_Presentation.pdf](#)

Presentation Slides

The Lab Presentation Slides link can be found in the UDF deployment documentation.

Module 1 – Simple HTTP Deployment

Learn how to create a simple HTTP deployment that securely load balances between several apps including microservices apps

High Level Business Objective

- You work in the information technology department for a global drinks company, and you have been tasked with delivering the following critical business applications reliably, securely, and with high performance:
 - **Brewz**
 - **Juiceshop**


Brewz lives on **www.bigtechdojo.com** server, and consists of multiple microservices as shown here:

IMAGE	PORTS
spa-demo-app_recommendations	0.0.0.0:8001->8001/tcp
spa-demo-app_spa	0.0.0.0:8081->80/tcp,
spa-demo-app_inventory	0.0.0.0:8002->8002/tcp
spa-demo-app_api	0.0.0.0:8000->8000/tcp
spa-demo-app_checkout	0.0.0.0:8003->8003/tcp

Juiceshop also lives on **www.bigtechdojo.com**, is containerized, but is monolithic, deployed on a single port, but there are two instances of Juiceshop on ports **3000** and **3001** as shown here:


bkimminich/juice-shop	0.0.0.0:3001->3000/tcp
bkimminich/juice-shop	0.0.0.0:3000->3000/tcp

Diagram



List of Components

1. NMS - this is your NMS and ADM management platform. Creds are shown in the UDF deployment->NMS component->details
2. WEST-GW - this is one of your NGINX+ and NGINX-AGENT instances.
3. EAST-GW - this is another
4. WWW - this is a box of web servers, with one listening on port 80
5. UBUNTU - this is simply a jumpbox. creds are shown in the UDF deployment->Ubuntu component->details.
 1. Access via RDP, and then do all your work from the jumpbox.
 2. This box is faster, smoother, more fun and easier than a Windows Jumpbox. Don't worry it has Firefox on it.
 3. Pro Tip: When you download the RDP file, right-click and edit the file and set color depth to 16-bit, set the screen resolution to slightly less than your monitor, set the username to ubuntu, and enable saving username. Use Ctrl-Shift-V to paste.



Detailed Requirements & Information

- The platform infrastructure team has already configured the software and hardware for you, including NGINX Management Suite, App Delivery Manager, the NGINX instances, and the application servers.

You are the application delivery team, and in that role, you will consume the platform to deliver the application. The business wants the Juice application deployed in the West, and the Brewz application deployed in the East.

Apps need to be accessed securely over the Internet at the domains as shown in the diagram.

You will know you have succeeded when you can browse securely to the West gateway and use the Brewz app, and you can browse securely to the East gateway and use the Juice app.

You will do everything from the Ubuntu RDP jumpbox



Spoiler Alert – Do not proceed unless you want to see the step-by-step solution

Solution

In the NGINX Management Suite web interface, you access the App Delivery Manager (ADM) features by performing the following operations. **You will do everything from the Ubuntu RDP jumpbox.**

1. Log into the Ubuntu jumpbox via RDP: credentials can be found in UDF under “Ubuntu JumpBox RDP”, “Details” and then “Documentation” tab
2. Start Firefox on the Ubuntu jumpbox
3. Click on the “West Gateway” book mark link in Firefox, and notice nothing is there. This is because West Gateway is a totally unconfigured nginx instance.
4. Click on the NMS bookmark in the bookmark bar and login. Credentials can be found in UDF under “NMS-ADM”, “Details” and then “Documentation” tab
5. From the Launchpad, select the **NGINX Instance Manager** card to see your instances that have already been deployed for you.
 1. These have been put into two Instance Groups, region-1 and region-2.
 2. Click on one of the instance groups and click “edit config” to see the “blank” configuration.
6. Now, go back to the Launchpad and select the **App Delivery Manager** card

Create an Environment

The first resource you need to create, if one doesn’t already exist, is an Environment resource. This can be accomplished by taking the following steps:

1. Select **Environments** from the **App Delivery Manager** list in the left-hand sidebar. The list of existing environments will then display.
2. Select **Create Environment** on the right-hand side of the list. A panel will appear that allows you to configure the environment.
3. Enter the value **Production** for the **Name** field. This logical environment is not just for one app, but for all your internet-facing websites. You can take the defaults for all the other fields (this exercise does not require customized templates).
4. Select **Submit** to finish creating the environment.

Create a Gateway for Juice Shop

The gateway controls how traffic will route through an NGINX instance to get to the app workloads.

1. Select **Gateways** from the **App Delivery Manager** list in the left-hand sidebar. The list of existing gateways will then display.
2. Select **Create Gateway** on the right-hand side of the list. A panel will appear that allows you to configure the gateway.
3. From the Configuration page of **Create Gateway**, enter the gateway name as **West Gateway**. You can accept defaults for the next two fields.
4. For the environment field, select the environment **Production** that you previously created.
5. Select **Next** to get to the **Placements** page.
6. The platform team should have created an instance group **region-1**. Select **Add Placement** and from the Instance Group **Refs** dropdown, select **region-1**. Then click **Done**.


7. Select **Next** to get to the **Hostnames** page.
8. Select **Add Hostname** then enter **https://west-gw.bigtechdojo.com** for the Hostname.
9. In the Shared TLS Settings section, select **Create New**
10. In the **Create Certificate** page enter the name as **west-gw.bigtechdojo.com**
11. Select Import **PEM or PKCS12 files** and upload **ca-chain.pem**, **west-gw.bigtechdojo.com.crt** and **west-gw.bigtechdojo.com.key** found on the ubuntu Jumphost under /home/ubuntu
12. **Only** if you receive some error with the previous step (Do **NOT** do this if the browsing to /home/ubuntu step worked) download same certificates from the **Docker VM** in UDF by clicking on the **NGINX** access method. Again, no need to do this if the previous step already worked.



How would you like to add your key and certificates?


- ☒ Import PEM or PKCS12 files
- ☐ Copy and paste PEM text



PEM or PKCS12 files

Select or drag and drop a PKCS12 file.


Drag and drop your file here or [Browse](#) to upload

 ca-chain.pem 

 west-gw.bigtechdojo.com.crt

 west-gw.bigtechdojo.com.key 

13. Under **Associated Instances** select **west-gw.bigtechdojo.com**
14. Select **Submit** to create the certificate
15. Back to the **Create Gateway** page select **Submit** to complete the Gateway
16. When Gateway deployment is completed, Status will be shown as **Configured**

Create your Application for Juice Shop

Follow these steps to create the applications:

1. Select **Apps** from the **App Delivery Manager** list in the left-hand sidebar. The list of existing apps will then display.
2. Select **Create App** on the right-hand side of the list. A panel will appear that allows you to configure the app.
3. Enter the value **Juice** for the **Name** field. Select **Production** for the **Environment** field. You can take the defaults for all the other fields.
4. Select **Submit** to finish creating the app.
5. Status will be displayed as **Configured**

Create the Juice Shop Production Web Component

The app we just created is a wrapper that can be composed of multiple components, each potentially referencing a unique service or microservice. To create the production component, perform these steps:

1. You should be on the **Apps Overview** page at this point. Select the app that was just created in the list by clicking the app name.
2. The main display will now show basic metrics for the app. We are not, at this point, interested in the metrics, but from this page we can create a component. At the top of the page, select Web Components.
3. The list of web components will appear, but should be empty.
4. Select **Create Web Component** on the top right-hand side of the display. A panel will appear that allows you to configure the component. There will be several pages of configuration that will need to be performed.
5. On the first page (Configuration), enter the value **Juice** for the Name field.
6. The only other field that needs to be set on this page is the **Gateway Refs** field. Under this field, select **West Gateway**.
7. Click **Next** to advance to the URIs page.
8. Enter **/** for the URI (if you are not able to enter a value, click the pencil icon to edit the URI).
9. Click **Next** to proceed to the Workload Groups page and select **Add Workload Group**
 - a. In the **Workload Group Name** field, enter **Juice Servers**
 - b. In the Backend Workload URIs section, enter for the URI field and click Done:
http://www.bigtechdojo.com:3000
 - c. Select Add Backend Workload URI to add another workload, and enter:
http://www.bigtechdojo.com:3001
 - d. Click **Done**, then Click **Done** for the overall Workload Groups page.
10. Select the **Submit** button to complete the component configuration.
11. When the configuration is applied **Status** will be shown as **Configured**

Testing

1. Select the **West-gw** bookmark, or refresh the tab if you had one open, and you will see the application.
2. In NMS, navigate to Instance Manager, go to Instance group **region-1**, click on “Edit Config” and you will see the configuration that ADM has created.

Create a Gateway for Brewz

Follow the steps as shown above in the “Create a gateway for Juice Shop” section, with the following changes:

1. Configuration: name the gateway **East Gateway**
2. Placements: Place this gateway in **region-2** of the country, for low latency.
3. Hostnames: Enter **https://east-gw.bigtechdojo.com** for the **Hostname**, and then click **Done**.
4. Upload the correct cert and key (follow the instructions previously shown for the West Gateway) but this time choose **east-gw.bigtechdojo.com.pem** and **east-gw.bigtechdojo.com.key** respectively. Certificate name shall be **east-gw.bigtechdojo.com**

Create your Application for Brewz

Now that you have the hang of a simple monolithic application, you are going to deploy the microservices application Brewz. Brewz lives on the following ports:

IMAGE	PORTS
spa-demo-app_recommendations	0.0.0.0:8001->8001/tcp
spa-demo-app_spa	0.0.0.0:8081->80/tcp,
spa-demo-app_inventory	0.0.0.0:8002->8002/tcp
spa-demo-app_api	0.0.0.0:8000->8000/tcp
spa-demo-app_checkout	0.0.0.0:8003->8003/tcp


1. Create a new application
2. Enter **Brewz** for the **Name** field and select **Production** in the **Environment** field

The front-end of the Single-Page Application directs traffic to each of these containers based on the following routes:

URI	Port	Web Component
/	8081	Brewz Main
/recommendations	8001	Brewz Recommendations
/inventory	8002	Brewz Inventory
/api	8000	Brewz API
/images	8000	Brewz Images
/checkout	8003	Brewz Checkout

1. Create each of the 6 Brewz Web Components

You are going to create a web component for each Brewz microservice so that you end up with the following 6 web components:



The detailed steps are provided for the **/checkout** route, you are going to learn from these steps and create the other routes.

Follow the steps you did above for the Juice app, with the following changes:

12. On the first page (Configuration), enter the value **Brewz Checkout** for the **Name** field.
13. The only other field that needs to be set on this page is the **Gateway Refs** field. Under this field, select **East Gateway**. Then click **Next** to advance to the URIs page.
14. Enter **/checkout** for the URI (click the pencil icon to edit the URI).
15. Click **Done** to save the URI
16. Click **Next** to proceed to the Workload Groups page.
 - a. In the **Workload Group Name** field, enter **Brewz Checkout**
 - b. In the Backend Workload URIs section, enter for the URI field:
<http://www.bigtechdojo.com:8003>

c. Click **Done**, then click **Done** for the overall Workload Groups page.

17. Select the **Submit** button to complete the component configuration.

18. Create the remaining five routes to Brewz microservices as per the table above. Make sure the Backend Workload URI port is configured based on the table.

Testing

1. Select the **West-gw** bookmark, or refresh the tab if you had one open, and you will see the application.
2. In NMS, navigate to Instance Manager, go to Instance group **region-1**, click on “Edit Config” and you will see the configuration that ADM has created.

View Paths in Network Inspector

Inspector Console Debugger Network Style Editor Performance Memory Storage Accessibility Application		
Filter URLs		
Status	Method	URL
200	GET	https://west-gw.bigtechdojo.com/products
200	GET	https://west-gw.bigtechdojo.com/assets/index.6a1c8b32.js
200	GET	https://west-gw.bigtechdojo.com/assets/index.bf312d07.css
200	GET	https://west-gw.bigtechdojo.com/api/products
200	GET	https://west-gw.bigtechdojo.com/favicon.ico
200	GET	https://west-gw.bigtechdojo.com/images/tonys-coffee-upland-blend-medium-roast.png
200	GET	https://west-gw.bigtechdojo.com/images/puroast-bourbon-pecan-torte.png
200	GET	https://west-gw.bigtechdojo.com/images/peace-coffee-morning-glory.png
200	GET	https://west-gw.bigtechdojo.com/images/tim-hortons-original-blend-medium-roast.png
200	GET	https://west-gw.bigtechdojo.com/images/groundwork-organic-ethiopia-light-roast.png
200	GET	https://west-gw.bigtechdojo.com/images/first-colony-columbian-santa-marta.png
200	GET	https://west-gw.bigtechdojo.com/images/cafe-altura-organic-italian-style-dark-roast.png
200	GET	https://west-gw.bigtechdojo.com/images/equal-exchange-organic-breakfast-blend.png
200	GET	https://west-gw.bigtechdojo.com/images/illy-caffe-medium-roast.png
200	GET	https://west-gw.bigtechdojo.com/images/seattles-best-dark-intense.png
200	GET	https://west-gw.bigtechdojo.com/images/stumptown-coffee-organic-holler-mountain.png
200	GET	https://west-gw.bigtechdojo.com/images/community-coffee-breakfast-blend-medium-roast.png
200	GET	https://west-gw.bigtechdojo.com/api/products/123
200	GET	https://west-gw.bigtechdojo.com/images/tonys-coffee-upland-blend-medium-roast.png
200	GET	https://west-gw.bigtechdojo.com/api/users/12345/cart
200	GET	https://west-gw.bigtechdojo.com/api/inventory
200	GET	https://west-gw.bigtechdojo.com/api/recommendations/123
200	GET	https://west-gw.bigtechdojo.com/images/community-coffee-breakfast-blend-medium-roast.png

Critical Analytics

In the ADM module select **Apps** then **Juice** and open the **Critical Analytics** tab. **Select** Breakout By: HTTP URI and select **Last 30 minutes**



Last 6 hours

Compare to:


Prev day

Breakout By:

HTTP URI

Bytes In (SUM)


71.67 KB



● all, Baseline ● /assets/index.bf312d07.css, Baseline
● /assets/index.6a1c8b32.js, Baseline ● /products, Baseline
● /images/community-coffee-breakfast-blend-medium-roast....
● /images/cafe-altura-organic-italian-style-dark-roast.png, B...
● other, Baseline

Bytes Out (SUM)

47.25 MB



● all, Baseline ● /assets/index.6a1c8b32.js, Baseline
● /images/puroast-bourbon-pecan-torte.png, Baseline
● /assets/index.bf312d07.css, Baseline
● /images/tonys-coffee-upland-blend-medium-roast.png, Ba...
● /images/lily-caffe-medium-roast.png, Baseline
● other, Baseline


Module 2 - Templates

Templates allow a customer to extend ADM. In this module, you are going to enable existing templates. After that, you will install new templates into ADM that professional services has created to enable remote syslog logging to a rsyslog server.

Enabling Templates

You are going to enable the Caching, Health Monitoring, and Server TLS templates.

1. Edit your **Production** environment (click on the three dots) and select **Use Cases** templates and select the following templates:



2. From the **Gateways** menu **Edit** your **West Gateway** and select **Custom Extensions** and enable the following Server TLS settings:

1. Caching Response Codes: 200 and Caching Time: 10s
2. TLS Options Proxy SSL Protocols: TLSv1.1 and TLSv1.2
3. TLS Options Proxy SSL Ciphers : HIGH:!aNULL:!MD5

The screenshot shows the 'Edit Gateway' form with the 'Custom Extensions' tab selected. The left sidebar lists 'BASIC' settings: Configuration, Placements, Hostnames, and Custom Extensions (highlighted). The main content area is divided into two sections: 'Cache valid configuration' and 'TLS Options'. The 'Cache valid configuration' section has a 'Response Codes' field with the value '200' and a 'Caching time' field with the value '10s'. The 'TLS Options' section has a 'Proxy SSL Protocols' field with the value 'TLSv1.1 TLSv1.2' and a 'Proxy SSL Ciphers' field with the value 'HIGH:!aNULL:!MD5'. There are also fields for 'SSL Prefer Server Ciphers' and 'SSL Session Cache'.

3. Click **Submit**
4. From the **Apps** menu select **Juice** and the **Web components** tab. Edit your **Juice Shop** web component by clicking on the three dots and select **Custom Extension**
5. Configure the Health Check **Interval** to 10 **Jitter** to 1, and click **Submit**.

The screenshot shows the 'Edit Web Component' form with the 'Custom Extensions' tab selected. The left sidebar lists 'BASIC' settings: Configuration, URIs, Workload Groups, and Custom Extensions (highlighted). The main content area is divided into two sections: 'Caching' and 'Health check configuration'. The 'Caching' section has a 'Cache settings for components applicable to web client requests' field. The 'Health check configuration' section has a 'Health check settings for components applicable to web client requests' field. Below these are fields for 'Interval' (value: 10) and 'Jitter' (value: 1). There is also a 'Failed health checks' section.

6. View the resulting configuration in Instance Manager by selecting the **Instance Groups** section and opening **region-1**

Look for **health_check** to see configuration lines added by the template.

```
08 # Created by Gateway: west-gw(d2d0b917-2d84-4dcf-9b15-3c43ab1d4a78)
09 server {
10     server_name west-gw.bigtechdojo.com;
11     listen 443 ssl reuseport;
12     proxy_cache_valid 200 10s;
13     # Usecase: builtin-server-tls-v1
14     # Template: server-gateway.tmpl
15     # Gateway name: West GW
16     proxy_ssl_protocols TLSv1.1 TLSv1.2;
17     proxy_ssl_ciphers HIGH:!aNULL:!MD5;
18     ssl_certificate /etc/nginx/aux/west-gw.bigtechdojo.com.crt;
19     ssl_certificate_key /etc/nginx/aux/west-gw.bigtechdojo.com.key;
20     status_zone d2d0b917-2d84-4dcf-9b15-3c43ab1d4a78;
21     f5_metrics_marker environment 18af103e-fda0-4470-af81-1b4c320c4bc2;
22     f5_metrics_marker gateway d2d0b917-2d84-4dcf-9b15-3c43ab1d4a78;
23     location = /_health_check_b9ca5f77-0b84-4df4-9ad9-6e6ac0cdd6f4 {
24         internal;
25         proxy_set_header Host $host;
26         health_check jitter=1 interval=10 fails=1 passes=1 uri=/;
27         proxy_pass http://b9ca5f77-0b84-4df4-9ad9-6e6ac0cdd6f4;
28     }
29     # Generated by web component jjj(b9ca5f77-0b84-4df4-9ad9-6e6ac0cdd6f4)
30     location / {
31         status_zone b9ca5f77-0b84-4df4-9ad9-6e6ac0cdd6f4;
32         proxy_set_header X-Forwarded-For $remote_addr;
33         proxy_set_header Host $host;
34         proxy_set_header Connection "";
35         proxy_http_version 1.1;
36         proxy_pass http://b9ca5f77-0b84-4df4-9ad9-6e6ac0cdd6f4;
37         # metrics
38         f5_metrics_marker app a5391940-57d4-480f-ba55-2c6cb91594fa;
39         f5_metrics_marker component b9ca5f77-0b84-4df4-9ad9-6e6ac0cdd6f4;
40     }
}
```

Installing Custom Templates

Here you are in the role of the SE helping the Platform Team, so you are going to touch the NMS at the Operating System level.


Imagine that your customer has a requirement for a feature that is not included in the product, but can be enabled with Templates.

In this example, the templates have already created by F5 professional services or F5 SA, and are located on your jumpbox in the /home/ubuntu directory.

You just need to help the customer Platform Team install them and configure them in ADM.

1. Open a terminal window on the jumpbox
2. In this terminal window, SCP copy the **gateway.json** and **server-gateway.tmpl** to the NMS system, and then SSH to the NMS system (ssh keys are already set up) (you can copy and paste (On a Windows system, use CTRL-SHIFT-V to paste into the RDP window)

```
scp gateway.json nms.bigtechdojo.com:
scp server-gateway.tmpl nms.bigtechdojo.com:
```

A terminal window screenshot showing the execution of SCP and SSH commands. The user is on a jumpbox and copies files to the NMS system. After SSHing, the terminal displays system information, update notifications, and login details.

```
File Edit View Search Terminal Help
ubuntu@jumpbox:~$ scp gateway.json nms.bigtechdojo.com:
gateway.json
ubuntu@jumpbox:~$ scp server-gateway.tmpl nms.bigtechdojo.com:
server-gateway.tmpl
ubuntu@jumpbox:~$ ssh nms.bigtechdojo.com
Welcome to Ubuntu 20.04.2 LTS (GNU/Linux 5.4.0-66-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

System information as of Wed May  3 06:38:39 UTC 2023

System load:  0.0               Processes:            136
Usage of /:   11.5% of 33.75GB   Users logged in:     1
Memory usage: 4%               IPv4 address for ens5: 10.1.1.5
Swap usage:   0%

 * Strictly confined Kubernetes makes edge and IoT secure. Learn how MicroK8s
   just raised the bar for easy, resilient and secure K8s cluster deployment.

https://ubuntu.com/engage/secure-kubernetes-at-the-edge

263 updates can be installed immediately.
188 of these updates are security updates.
To see these additional updates run: apt list --upgradable

New release '22.04.2 LTS' available.
Run 'do-release-upgrade' to upgrade to it.

Last login: Wed May  3 05:50:30 2023 from 10.1.1.1
ubuntu@nms:~$
ubuntu@nms:~$
ubuntu@nms:~$
ubuntu@nms:~$
```

3. SSH to the NMS system by running **ssh nms** in the terminal window

4. Enter exactly the following commands **one-by-one** on the NMS system (On a Windows system, use CTRL-SHIFT-V to paste then **one-by-one** into the RDP window. Do not copy all the lines and paste them at once, you can copy and paste them **one-by-one**)

```
sudo bash
cd /etc/nms/modules/adm/templates/usecases
mkdir builtin-logging-v1
cd builtin-logging-v1
cp /home/ubuntu/gateway.json .
cp /home/ubuntu/server-gateway.tmpl .
chown nms *
chgrp nms *
ls -altr
exit
exit
```



```
root@nms:/etc/nms/modules/adm/templates/usecases/builtin-logging-v1# ls -altr
total 16
-rw-r--r--  1 nms  nms  4086 May  4 05:17 gateway.json
drwxr-xr-x 13 root root 4096 May  4 05:17 ..
-rw-r--r--  1 nms  nms   753 May  4 05:17 server-gateway.tmpl
drwxr-xr-x  2 root root 4096 May  4 05:17 .
root@nms:/etc/nms/modules/adm/templates/usecases/builtin-logging-v1#
```

5. That is the end of the work for the Platform team.
6. In your jumpbox Terminal window, fully exit out of your SSH session to NMS by typing exit so you are back to your jumpbox prompt.
7. In your jumpbox terminal window, type

```
tail -f /var/log/syslog
```

8. Send web traffic to your gateway by refreshing the browser, and notice you do not yet see HTTP requests in your syslog on the jumpbox
9. Now, go back to your **Browser** window. In the ADM section go to your **Production** environment, select **Edit** from the “...” link on the right side of the screen. Click on the **Templates** section and select your **builtin-logging-v1** template in the **Use Cases** section, then **Submit** all changes

☐ builtin-listen-options-v1
☒ builtin-logging-v1
☐ builtin-server-tls-v1
☐ builtin-uri-rewrites-redirects-v1
☐ Select All

builtin-logging-v1 X

10. Edit your **West Gateway**

11. Select the **edit** button to modify the **Hostname**.

12. You will see new **Server block access_log** and **Server block error_log** fields, from the template.

13. Enter the following for the **Access Log** field:

```
syslog:server=jumpbox.bigtechdojo.com:514,facility=local7,tag=nginx,severity=info
```

14. Enter the following for the **Error Log** field:

```
syslog:server=jumpbox.bigtechdojo.com:514,facility=local7,tag=nginx,severity=error
```

Form API Spec Reset All Fields

Edit Gateway

WASHC

- Configuration
- Placements
- Hostnames**
- Custom Extensions

TLS SETTINGS

☐ CUSTOMIZE FOR THIS URI

CUSTOM EXTENSIONS

Server block access_log directive
For example: syslog:server=10.11.4-514,facility=local7,tag=nginx,severity=info

Local Access Log arguments (Optional)
syslog:server=10.11.4-514,facility=local7,tag=nginx,severity=info

Access Log description

Server block error_log directive
For example: syslog:server=10.11.4-514,facility=local7,tag=nginx,severity=error

Local Error Log arguments (Optional)
syslog:server=10.11.4-514,facility=local7,tag=nginx,severity=error

Error Log description

Cancel Done

Shared TLS Settings

Cancel and Exit Submit Next

15. Click **Submit**

16. View the resulting configuration in Instance Manager, you will see your `access_log` and `error_log` directives created under the `Server` block.

17. On your jumpbox, tail -f /var/log/syslog, send web traffic to your gateway by refreshing the browser, and make sure you see nginx access log entries in your syslog

```
ubuntu@jumpbox: ~  
File Edit View Search Terminal Help  
.bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:25:01 jumpbox CRON[3059]: (ubuntu) CMD (~/.ddns/ddns.sh >/dev/null 2>&1)  
May  4 18:25:01 west-gw.bigtechdojo.com CRON[2895]: (ubuntu) CMD (~/.ddns/ddns.sh >/dev/null 2>&1)  
May  4 18:25:09 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:25:09 +0000] "GET /socket.io/?EI0=4&transp  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:25:09 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:25:09 +0000] "POST /socket.io/?EI0=4&trans  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:25:34 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:25:34 +0000] "GET /socket.io/?EI0=4&transp  
w.bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:25:34 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:25:34 +0000] "POST /socket.io/?EI0=4&trans  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:25:59 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:25:59 +0000] "GET /socket.io/?EI0=4&transp  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:25:59 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:25:59 +0000] "POST /socket.io/?EI0=4&trans  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:26:01 jumpbox CRON[3065]: (ubuntu) CMD (~/.ddns/ddns.sh >/dev/null 2>&1)  
May  4 18:26:01 west-gw.bigtechdojo.com CRON[2917]: (ubuntu) CMD (~/.ddns/ddns.sh >/dev/null 2>&1)  
May  4 18:26:24 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:26:24 +0000] "GET /socket.io/?EI0=4&transp  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:26:24 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:26:24 +0000] "POST /socket.io/?EI0=4&trans  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:26:49 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:26:49 +0000] "GET /socket.io/?EI0=4&transp  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"  
May  4 18:26:49 west-gw.bigtechdojo.com nginx: 10.1.1.4 - - [04/May/2023:18:26:49 +0000] "POST /socket.io/?EI0=4&trans  
bigtechdojo.com/" "Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:109.0) Gecko/20100101 Firefox/112.0"
```