

A Fast and Accurate Zebra Finch Syllable Detector

Ben Pearre^{1,a,✉}, L. Nathan Perkins^{1,b}, Jeffrey E. Markowitz^{1,c}, Timothy J. Gardner^{1,d}

¹ Department of Biology, Boston University, Boston, Massachusetts, United States of America

Author ^a contributed the original Matlab and LabView implementations and most of the manuscript. ^b contributed the Swift implementation and its description herein, helped debug the training code, and measured the timing for most of the detectors. ^c wrote several types of filterbank software against which we compared, made suggestions for the neural network detector, and prepared the final version of the Matlab code for distribution. ^d provided a stream of suggested techniques, metrics, and goals.

✉ Corresponding author: bwpearre@gmail.com (BP)

Abstract

The song of the adult male zebra finch is strikingly stereotyped. Efforts to understand motor output, pattern generation, and learning have taken advantage of this consistency by investigating the bird's ability to modify specific parts of song under external cues, and by examining timing relationships between neural activity and vocal output. Such experiments require that precise moments during song be identified in real time as the bird sings. Various syllable-detection methods exist, but many require special hardware, software, and know-how, and details on their implementation and performance are scarce. We present an accurate, versatile, and fast syllable detector that can control hardware at precisely timed moments during zebra finch song. Many moments during song can be isolated and detected with false negative and false positive rates well under 0.5% and 0.01% respectively. The detector can run on a stock Mac Mini with triggering delay of less than a millisecond and a jitter of $\sigma \approx 2$ milliseconds.

1 Introduction

The adult zebra finch (*Taeniopygia guttata*) sings a song made up of 2–6 syllables, with longer songs taking on the order of a second. The song may be repeated hundreds of times per day, is almost identical each time, and several brain areas reflect this consistency in highly stereotyped neural firing patterns. This consistency makes the zebra finch one of the most popular models for the study of the neural basis of learning, audition, and control.

This consistency allows a variety of experiments if precise moments in song can reliably be detected quickly enough to trigger other apparatus during singing. A common area of study with this song-triggering technique is the anterior forebrain pathway (AFP), a homologue of mammalian basal ganglia consisting of a few distinct brain areas concerned with the acquisition and learning of song. For example, [1] stimulated the lateral magnocellular nucleus of the anterior nidopallium (LMAN)—the output nucleus of the AFP—at precisely timed moments during song and showed that this area repeatably controls specific variables in song output. [2] played a disruptive sound during renditions of a syllable that were slightly above (or below) its average pitch, and showed that AFP produces a corrective signal to bias song away from those disruptions. [3] showed that that AFP transfers this signal to the robust nucleus of the arcopallium (RA) using NMDA-receptor-mediated glutamatergic transmission. By looking at song recovery after applying the same pitch-shift paradigm, [4] showed that the caudal medial nidopallium is implicated in memorising or recalling a recent song target, but for neither auditory processing nor directed motor learning.

Despite the power and versatility of such experiments, there is no standard syllable detector. Considerations include:

Accuracy: How often does the system produce false positives or false negatives?

Latency: The average delay between the target syllable being sung and the detection.

Jitter: The amount that latency changes from instance to instance of song. Our measure of jitter is the standard deviation σ of latency.

Versatility: Is detection possible at “difficult” syllables?

Ease of use: How automated is the process of programming a detector?

Cost: What are the hardware and software requirements?

A variety of syllable-triggering systems have been used, but few have been documented or characterised in detail. In 1999, [5] used groups of IIR filters with hand-tuned logical operators. Their system had a latency of 50 or 100 milliseconds (ms), and they do not report on jitter or accuracy. As access to computational resources has improved, approaches have changed: in 2009, [2] still used hand-tuned filters, but ran them on a Tucker-Davis Technologies digital signal processor. They report a latency of around 4 ms, but as with other filter bank techniques, it is not strictly a syllable detector but rather a pitch and timbre detector—it cannot identify a frequency sweep, or distinguish a short chirp from a long one—and thus requires careful selection of target syllables. Furthermore, the method is neither inexpensive nor, based on our experience with a similar technique, accurate. [6] applied a neural network to a spectral image of song. It reported a latency of 4.3 ms, but further implementation and performance details are not available. In 2011, [3] matched spectral templates to stable portions of syllables in 8-ms segments. It reported a jitter of 4.5 ms, and false-negative and false-positive rates of up to 2% and 4%, respectively. Hardware requirements and ease of use were not reported. In 2013, [7] described in detail a system that matches spectral images of template syllables using a correlation coefficient. With a fast desktop (Intel i7 six-core) running Linux and equipped with a National Instruments data acquisition card, it boasts a hardware-only (not accounting for the time taken to compute a match with a syllable) latency and jitter of just a few microseconds, and the detection computation they use should not much increase that. Drawbacks are that some hand-tuning is still required, and that they report false-negative rates around 4% and 7% for zebra finches and Bengalese finches respectively, measured on a small dataset. In much other work, an allusion is made to a syllable detector, but no further information is provided.

We developed a standalone detector that learns to match moments in the song using a neural network applied to the song spectrogram, and outputs a TTL pulse at the chosen moment. The approach consists of three steps:

1. Record and align a corpus of training songs. The technique has been published in [8].

2. Choose one or more instants in the song that should create a trigger event, and train a neural network to recognise them. This step is carried out offline. While any neural network software would produce equivalent results, we used Matlab 2015b's neural network toolbox.
3. Once trained and saved, the neural network is used by a realtime detection program that listens to an audio signal and indicates detection of the target syllables via a TTL pulse. We present three implementations that trade off hardware requirements, ease of maintenance, and performance.

This method makes the following contributions:

- Fast: sub-millisecond latencies, with jitter around 2 ms.
- Accurate: false positive rates under 0.02% and false negative rates under 0.5% for a variety of syllables. Balancing these rates depends on a single relative-cost parameter.
- State-of-the-art performance with default parameters.
- Runs on inexpensive hardware.
- Described in detail here, with reference implementations provided and benchmarked.

2 Materials and Methods

2.1 Learning a detector

We begin with a few hundred time-aligned recordings of a given bird's song. Time-alignment is described in [8].

The spectrogram is computed at regular intervals—the useful range seems to be roughly 1–5 milliseconds, which we refer to as the frame interval t_f . The target frame interval may not line up with the sample rate, especially on consumer audio hardware that operates at 44.1 kHz, so the actual frame interval may be different from the target. For example, at 44.1 kHz a 1 ms target frame interval requires a new FFT every 44.1 samples. This is rounded to 44 samples, resulting in $t_f = \lfloor 44.1 \rfloor / 44.1 \approx 0.9977$ ms.

One or more moments during the song must be chosen. Our interface presents the time-aligned spectrogram averaged over training songs, and requires manual input of the target times. Then we assemble the training set from the song data, train the network, compute optimal output unit thresholds, and save the network object and an audio test file.

Recognition region The neural network uses a contiguous set of the most recent timesteps (frames) from the song spectrogram. The frequencies F and duration T of this recognition region may be chosen in order to contain unique features of the target syllable and surrounding areas. We have found that a 30-ms time window of frequencies spanning 1–8 kHz works well for most syllables.

Building the training set The training set is created in the typical fashion: the rectangular $|F| \times |T|$ recognition region in the spectrogram is simply reshaped into a vector of length $|F||T|$. The frequency range is constant, and every possible time interval of length $|T|$ at time t is converted into a training input vector x_t .

Training targets y_t are vectors with one element for each desired detection syllable. That element is, roughly, 1 if the input vector comes from the target time ($t = t^*$), 0 otherwise, for each target syllable (of which there may be any number, although they increase training time, and in our implementations the number of distinct output pulses is constrained by hardware). Since the song alignment may not be perfect, due to sample aliasing, and because the song spectrogram appears not to vary faster than the frame rate we chose, a strict binary target may ask the network to learn that practically identical samples should have opposite targets. Thus it is preferable to spread the target in time, such that at the target moment it is 1, and at neighbouring moments it is nonzero. We found that a Gaussian smoothing kernel around the target time with $\sigma \approx 2$ ms serves well.

With inputs well outside the space on which a neural network has been trained, its outputs will be essentially random. In order to reduce the false positive rate it is useful to provide negative training examples that include silence, cage noise, non-song vocalisations, and perhaps songs from other birds. We have found that training with as low as a 1:1 ratio of non-song to song yields excellent results, although this will

depend on the makeup of the non-song data.

Normalisation To accommodate differences in amplitude due to changes in the relative position between the microphone and bird or other variations in recording, the incoming signal is normalised in order to ensure that the detector is sensitive only to the relative spectral content. We settled upon the following two-step normalisation scheme. First, each spectral time-frequency window x_t is normalised (referred to here as \hat{x}_t) so that the content of that window has mean $\mu_{\hat{x}_t} = 0$ and standard deviation $\sigma_{\hat{x}_t} = 1$: after each time-frequency window is reshaped into a vector x_t , it is normalised using Matlab's `zscore` function $\hat{x}_t = (x_t - \mu_{x_t})/\sigma_{x_t}$. This eliminates relative differences in song amplitude due to microphone position or line levels. Next, each element of the time-frequency window vector \hat{x}_t^i —one time-frequency point \hat{x}_t^i —is scaled to ξ^i in the same way, so that the values of that point across the whole training set have mean $\mu_{\xi^i} = 0$ and standard deviation $\sigma_{\xi^i} = 1$. In training, this is accomplished by setting Matlab's neural network toolbox training set normalisation scheme to `mapstd`, and this scaling factor is saved as part of the network object used by the realtime detector so that it may be applied to unseen data during runtime. These two normalisation steps provide a set of inputs that are more robust to outliers and less likely to produce false positives during silence when evaluated against other normalisation schemes, such as linear or L_2 normalisation.

Neural Networks While any learned classifier might suffice, we chose a two-layer feedforward neural network. In brief, our network takes an input vector ξ_t —as described above—to an output vector y_t , and when any element of y_t is above a threshold (described below), the detector reports a detection event. The network uses two matrices of weights, W_0 and W_1 . The first takes the input ξ_t to an intermediate stage—the “hidden layer” vector. To each element of this vector is applied a nonlinear squashing function such as `tanh`, and then the second weight matrix W_1 is applied. This produces output y_t :

$$y_t = W_2 \cdot \tanh(W_1 \cdot \xi_t)$$

The elements of each matrix are learned by back-propagation of errors over a training set. A more detailed explanation of neural networks may be found in [9].

Essentially, after training, the network is available in the form of the two matrices W_0 and W_1 , and running the network consists of two matrix multiplications and the application of the squashing function.

I've left out bias terms and some other details. Ok?

Training the network The network is trained using Matlab's neural network toolbox. We tried a variety of feedforward neural network geometries, from simple 1-layer perceptrons to geometries with many hidden nodes, as well as autoencoders. Perhaps surprisingly, even the former yields excellent results on many syllables, but a 2-layer perceptron with a very small hidden layer—with a unit count 4 times the number of target syllables, or even fewer—was a good compromise between accuracy and training speed. Various other neural network geometries could be tried, as well as any other classifier that executes quickly. For more variable songs, deep structure-preserving networks may be more appropriate, but they are slow to train and unnecessary for zebra finch song.

Matlab's neural network toolbox defaults to Levenburg-Marquardt training. This is a fast algorithm, but is memory-intensive, so many target syllables or high FFT frame rates require a large amount of RAM and increase training time to hours. Other training algorithms that use less RAM are much slower, and by default they will often terminate prematurely due to their performance gradient going to 0.

Computing optimal output thresholds After the network is trained, outputs of the network for any input are now available, and will be in (or, due to noisy inputs and imperfect training, close to) the interval $(0, 1)$. We must choose a threshold above which the output is considered a positive detection. Finding the optimal threshold requires two choices. The first is the relative cost of false negatives to false positives, C_n . The second is the acceptable time interval: if the true event occurs at time t , and the detector triggers at any time $t \pm \Delta t$, then it is considered a correct detection. Then the optimal detection threshold τ is the one that minimises $[\text{false positives}] + C_n \cdot [\text{false negatives}]$ over the training set, using the definitions of false positives and negatives given in Section 2.3. Since large portions of the cost function are flat, hillclimbing is ineffective. Random-restart hillclimbing would work, but a brute-force search requires fractions of a second. For the results presented here,

we have used $C_n = 1$ and $\Delta t = 10$ ms.

De-bouncing Since the network may produce above-threshold responses to nearby frames, after the first response, subsequent responses are suppressed for 100 ms. However, for the accuracy figures presented here, we used the un-de-bounced network response.

Our parameter choices We used an FFT of size 256; a Hamming window; and chose a target spectrogram frame interval of $t_f = 1.5$ milliseconds, resulting in a true frame interval of $t_f = \lfloor 1.5 \cdot 44.1 \rfloor / 44.1 \approx 1.4966$ ms. We set the network's input space to 30 ms long, and to span frequencies from 1–8 kHz, which contains the fundamentals and several overtones of most zebra finch vocalisations.

We found these parameters to work well across a variety of target syllables, but various other parameter sets yield results similar to those presented here. Some of the parameters trade off detection accuracy or temporal precision vs. training time. For example, detection latency and jitter cannot be much less than the frame interval, but increasing the frame rate increases the size of the training set and thus the training resources required and the detection latency.

2.2 Realtime detection

The architecture of the realtime detector requires that the most recent $|T|/t_f$ spectrograms be fed to the neural network every frame interval. Audio samples from the microphone are appended to a circular buffer. Every t_f seconds a new spectrogram is calculated by applying the Hamming window to the contents of the buffer, performing an FFT, and extracting the power. Outputs of the spectrogram from the target frequency band are appended to a second circular buffer. The spectrograms are sent to a static implementation of the previously trained neural network.

We tested three implementations of the realtime detector. For all of these tests, we ran the detector processes under the operating systems' default schedulers and process priorities, running typical operating system daemon processes but no user loads. The computers had ample memory resources.

Swift This detector uses the Swift programming language and Core Audio interface included in Apple’s operating systems.

The Core Audio frameworks provide an adjustable buffer size for reading from and writing to audio hardware. Tuning this buffer size provides a tradeoff between the jitter in the detection and the processor usage needed to run the detector. We settled on a buffer size of 32 samples (0.7 ms at 44.1 kHz), as this created minimal system load while achieving detection within the desired lag and jitter.

Vector operations—applying the Hamming window, the FFT, input normalisation, matrix multiplication, and the neural network’s transfer functions—are performed using the Accelerate framework (vDSP and vecLib), which use modern vector-oriented processor instructions to perform calculations.

When the neural network detects a match, it instructs the computer to generate a TTL pulse that can be used to trigger downstream hardware. This pulse can be either written to the computer’s audio output buffer (again, in 32-sample or 0.7-ms chunks) or sent to a microcontroller (Arduino) via a USB serial interface. Sending the trigger pulse via the serial interface and microcontroller is noticeably faster (2.2 ms lower latency), likely due to the fact that the audio buffer goes through hardware mixing and filtering prior to output.

The above code can be run on multiple channels of audio on consumer hardware (such as a 2014 Mac Mini) with little impact on CPU usage (< 15%). Depending on the experimental needs, latency can be further decreased (at the expense of processor usage) by adjusting the audio buffer sizes.

LabView This implementation requires special software and hardware: LabView from National Instruments, and a data acquisition card—we use the National Instruments PCI-6251 card on a PC with an Intel Core i5-4590 processor at 3.7GHz (a relatively low-end machine) with 32 gigabytes of RAM, running Microsoft Windows 8.1 Pro.

This implementation has several drawbacks: it requires Windows and expensive hardware and software, it requires Matlab savefile versions no more recent than ‘v7’, and due to the programming language it is difficult to modify and debug—indeed, a persistent bug in our implementation currently renders it substantially less accurate

than the other detector implementations on some syllables. However, our test configuration usually achieved excellent performance, and further gains should be possible if the implementation were retargeted onto FPGA hardware—which would have the additional benefit of providing deterministic “hard realtime” guarantees—or just run on a faster desktop system.

Matlab This detector uses the built-in audio input and output hardware on a compatible computer. We tested on a 2014 Mac Mini and 2015 Mac Pro. The Mac Pro does not have an audio input jack, so input was through an M-Audio MobilePre external USB audio interface. Despite the faster processor, the latter system did not achieve higher performance than the former, perhaps due to USB data transfer overhead.

Because of how Matlab’s DSP toolbox interfaces with audio hardware, there is a double buffer both reading from and writing to audio hardware. As a result, much of the code focuses on a lightweight audio hardware interface, in order to have the smallest achievable audio buffer. To help achieve this, the Matlab implementation spreads data acquisition and processing across two threads, due to the higher computational overhead of the interpreted programming language.

The most versatile implementation, Matlab runs on a variety of hardware and operating systems, and is perhaps the easiest to modify. While it did not perform as well on our test system as the other implementations, the convenience may outweigh the slight timing performance penalty for some experiments. Key to minimising jitter is the size of the audio buffer: on a 2014 Mac Mini running Matlab 2015b the smallest buffer size that did not result in read overruns was about 4 ms.

2.3 Quantification

We divided the data into training and test sets. For the results reported in the following section, the training set consisted of 1000 instances of the song of one bird and 1000 instances of non-song data. Our test set consisted of an additional 1818 iterations of the bird’s song and 1818 more instances of non-song data.

The Matlab neural network toolbox further divides our “training” set into internal training, validation, and test sets. We did not stray from the toolbox’s default values,

and do not discuss Matlab's internal subdivision of our training set.

Because the dataset consists of temporally aligned songs, ground truth is available for each song, and thus the detector can be checked by presenting the recorded training songs as well as the canonical detection events. To this end, besides the trained network object, our learning code produces an audio file consisting of all of the training data on the left audio channel and a delta function at each aligned moment of target syllable presentation on the right channel. Thus, when played on any audio player, the left channel may be provided as input to the detector, and the the detector's output pulses may be compared against the right channel.

Accuracy We define the accuracy of the network based on its classification performance per frame. In order to avoid the apparent problem of every non-detected non-syllable counting as a true negative, we also tried defining accuracy on a per-song basis, such that a song without the target syllable counted as a single true negative. Computing the optimal output thresholds on a per-frame basis resulted in higher thresholds and thus a lower false-positive rate, with minimal consequences to the false-negative rate, while also providing a valid definition of false-positive rate for data streams that had not been segmented into songs.

The accuracy as defined above is used for computing the optimal thresholds above which the network's output should be interpreted as a match on the training data as described in Section 2.1, for evaluation of the detectors on the training songs, and while live.

Timing We evaluate the time taken from the presentation of the target syllable to the firing of the detector's TTL pulse. While playing the audio test file from any audio playback device, the TTL output from the ground-truth channel of the audio output may be used as the trigger pulse for an oscilloscope, and compared to the TTL pulse produced by the detector implementation, which sees only the birdsong channel of the audio file. For this purpose we used a pulse generator (Philips PM 5715, with a listed latency of 50 ns, jitter of $\leq 0.1\%$ or 50 ps, whichever is greater) to widen the detector's output spike to a number much larger than the jitter (~ 100 ms). This obviates pulse length variability in the output device by essentially discarding the falling edge of the

output pulse. The oscilloscope is then set to averaging mode (128-trigger average) in order to collect timing data. The canonical signal is the trigger at $t = 0$, and the average of the detector's detection events will be seen as a low-to-high transition with form approximating the cumulative probability distribution function (CDF) of the detector's output in response to the chosen song event.

Mean latency is then given as the halfway point of that detection sigmoid. It is a helpful number, but not a critical one, since a detector with high but constant latency can often be trained to trigger at a point somewhat before the true moment of interest, especially given the stereotypy of zebra finch song. Often more important is latency jitter: how much random variability is there in the latency?

We obtain both of these numbers by performing a maximum-likelihood fit of a Gaussian distribution to the timing data obtained from the oscilloscope. We refer to the distribution's mean as latency and its standard deviation as jitter.

When measuring timing, it is useful to compare against a theoretical optimal, in order to control for any imprecision in the song extraction and alignment of our real data inherent in the method we use (described in [8]). We propose two measures thereof:

First we test the "ideal" latency and jitter in the time shift used in calculating new columns of the spectrogram. By passing a recorded audio sequence into the detector offline, and assuming no input or output latency, we compare how many additional audio samples beyond the syllable are needed before the spectrogram can match the inputs needed to trigger the neural network. This latency reflects the FFT size used for calculating the spectrogram, the FFT time shift between columns in the spectrogram, and the width of the Gaussian smoothing kernel applied to the ground truth data when training the neural network, but ignores computation times, audio buffers, and other operating system overhead.

Next we use a " δ -syllable" consisting of a δ function in the time domain, and train the network to trigger 5 ms after this pulse. This song is fed into the live detector. The results for this measurement show the latency and jitter inherent in the complete detector including audio read and write buffers, classifier computation, and FFT time shift aliasing, but excluding imprecision in the song alignment as well as detection timing effects due to differences between instances of the bird's song.




Figure 1. This image was made by superposing the spectra of our 2818 aligned songs. The detection points are shown as red lines, with the recognition regions ($30 \text{ ms} \times 1\text{--}8 \text{ kHz}$) marked as rectangles.

Finally, we measure latency on real bird song aligned as in [8]. This extracts and aligns the centres of the sampled songs, and the canonical signal is given with respect to that alignment. These timing measurements reflect not only detector performance, but also the variability of the bird's song.

3 Results

Fig. 1 shows the song for which we present results. Six example target syllables are shown, at 150, 200, 250, 300, 350, and 400 milliseconds after the beginning of the aligned samples, as indicated by the red lines. The rectangles show the recognition window (30 ms , $1\text{--}8 \text{ kHz}$) for each instant in the song.

The first two triggers, at 150 and 200 ms, are far from pure tones, but are closer to coloured noise. They would be difficult for a harmonic-stack filterbank to detect, and especially to pinpoint in time. The third and sixth triggers (at 250 and 400 ms) are rich in overtones and contain downward slides with changing timbres. The fourth trigger, at 300 ms, is a more typical harmonic stack amenable to a variety of recognition techniques, although consistently detecting a point partway through the syllable demands a detector that can use multiple timesteps. The fifth trigger, at 350 ms, shows a steady pitch followed by a complex changing tone structure.

The detector's output for three of these syllables is shown in Fig. 2. By sorting according to time of each syllable's detection, the rest of the song is shown in the context of the timing for that moment, giving an intuition of the variability of intrasong timing.




Figure 2. Each plot shows one network output unit's responses to all 2818 presentations of the song shown in Fig. 1. For simplicity, we show only the syllables at 200, 300, and 400 ms. The horizontal axis is time relative to the beginning of the aligned song, and the vertical axis is an index for the 2818 single song presentations. The grey shading shows the total audio energy of song Y at time X. The bar on the left is the same width as the detection window, and its colour code shows training songs adjacent to cyan regions and unseen test songs adjacent to red regions. For visualisation of the distribution, songs have been stably sorted by the time of detection events; thus, each of the three detection graphs shows the songs in a different order.

3.1 Accuracy

We allowed our training software to allocate our default of 4 hidden units per syllable, and sampled a new FFT every 1.5 ms. Because our timing test files are designed for our stereo playback software, allowing only one channel for the ground-truth pulse, we trained one detector for each syllable for the following results—but note that accuracy is generally slightly higher if one network is trained on multiple syllables. In order to eliminate the large number of variables involved in microphone, cage, playback and re-digitising, we evaluated the neural network’s accuracy directly on the digitised recording. When training and runtime data are gathered on the same hardware setup, this is the digital signal that the detector will see—only the non-song data may be different. Typical confusion matrices for these syllables are:

At 150 ms	True	
	pos	neg
Detected pos	99.96451%	0.000298%
neg	0.0355%	99.99970%

At 200 ms	True	
	pos	neg
Detected pos	99.92903%	0.000596%
neg	0.0710%	99.99940%

At 250 ms	True	
	pos	neg
Detected pos	99.68062%	0.00194%
neg	0.319%	99.99806%

At 300 ms	True	
	pos	neg
Detected pos	99.82257%	0.00239%
neg	0.177%	99.99761%




Figure 3. Timing varies as the FFT frame interval changes. Here we show results for the ideal detector and the LabView and Swift+serial implementations, for the constructed δ -syllable and for the real bird song at 300 ms.

At 350 ms	True	
	pos	neg
Detected pos	99.78708%	0
neg	0.213%	100%

At 400 ms	True	
	pos	neg
Detected pos	99.71611%	0.00552%
neg	0.284%	99.99448%

The accuracies for the synthetic δ -function songs were always 100%.

3.2 Timing

We evaluate variability in timing performance across three variables: FFT frame interval; syllable choice; and detector implementation.




Figure 4. Timing data for our 6 test syllables, for the ideal and the Swift+serial detectors, with an FFT frame rate of 1.5 ms.

FFT Frame Interval Detector latency and jitter depend on the FFT frame rate. Our 1.5-ms-frame default is a compromise: shorter frames increase the precision of timing, but also increase computational requirements both during training and at runtime. Fig. 3 shows how these numbers vary over a useful range of frame rates on our ideal detector, the Swift detector with serial output, and for the LabView detector, for both the δ -syllable and for the real bird song at the 300-ms detection point.

Syllable choice Syllable choice impacts detector performance, but despite the variety of syllables chosen here, performance was fairly stable across syllables. Fig. 4 shows measured timing data for the Swift+serial detector compared to the ideal, with $t_f = 1.5$ ms. Given the variety of the test syllables, the variability is surprisingly low, and is summarised here with 95% confidence intervals (with $n=6$):

Detector	Latency	Jitter
Ideal	-0.8 ± 0.3 s	2.1 ± 0.1 s
Swift+serial	0.0 ± 0.6 s	2.0 ± 0.1 s

The negative latency is due to the way in which the network responds to the song through time: as the recognition region looks increasingly similar to the trained match, the network's evaluation of similarity rises, and will generally cross the triggering threshold before it reaches its maximum value.

By choosing easy syllables, jitter can be reduced, although it will never be much less than t_f .




Figure 5. The different detectors for the constructed δ -syllable and for the real bird song at 300 ms.




Figure 6. Raw timing curves for all detectors measured during detection of the syllable at 300 ms, using 1.5-ms frames.

Detector Implementations Again exploring our 1.5-ms FFT frame interval, Fig. 5 shows latency and jitter across all detector implementations for the δ -syllable and for our bird syllable at 300 ms.

Fig. 6 gives a more detailed view of what the timing curves look like for the five implementations of our detector trained on our test bird, for the syllable at 300 ms, using an FFT frame rate of 1.5 ms. The maximum-likelihood estimates of the mean μ (latency) and standard deviation σ (jitter) on this syllable are as follows:

Detector	δ -syllable		Bird: 300 ms	
	Latency	Jitter	Latency	Jitter
Ideal	0.66	0.38	-1.0	2.0
LabView	1.5	0.69	-0.18	2.4
Swift+serial	0.88	1.6	-0.075	2.0
Swift+audio	5.89	2.6	1.24	4.9
Matlab+serial	8.1	2.3	3.8	2.0
Matlab+audio	12.5	5.9	8.4	5.9

4 Discussion

This syllable detector is appropriate for zebra finch song, and although our tests were carried out on songs from that species, it is also likely to work well for Bengalese finches. It offers the following benefits:

- The detector is accurate. False negative and false positive rates can be well under 0.5% and 0.01% respectively, and trading these two numbers off against each other is through a single relative-cost parameter.
- Latency is generally under a millisecond, with jitter around 2 ms.
- Works on a wide range of target syllables using the default values described here, generally eliminating the need for hand-tuning.
- Runs easily fast enough for syllable-modification experiments on inexpensive consumer-grade hardware, although we recommend that the training phase be run on a fast desktop system with 32 GB of RAM.
- A single detector can generate different target pulses for multiple syllables at almost no additional computational cost during runtime, although training time will increase.

Although there are differences, the Swift+serial detector and the LabView implementation are roughly comparable in performance. We prefer the Swift implementation due to its lower hardware and software requirements and the difficulty

of debugging LabView programmes. With serial output, Matlab's performance is good, 408
although its buffer handling is sensitive to system load. 409

Due to the randomness of neural network initialisation and training song 410
presentation, multiple training runs yield different networks. We found that for 411
difficult syllables, the training process would sometimes yield a network that 412
performed unusually poorly, but that it was easy to spot these networks by their 413
performance on the test audio file, and re-train when necessary. 414

A common experimental paradigm requires detecting the frequency of syllables. 415
Many pitch detection techniques rely on the spectrum, which incurs no additional 416
computational cost here since it is already available. For example, [4] achieved good 417
results with the Harmonic Product Spectrum algorithm [10]. 418

In order to monitor syllable duration, the beginning and end of a syllable may be 419
detected by looking at the ratio of total energy in the singing frequency band to the 420
total energy, over some small time window. Any syllable thus identified that also 421
contains a trigger event may be monitored for duration. Alternatively, the network 422
can be trained to recognise both the beginning and the end of the syllable of interest. 423

In feedback experiments such as frequency- or duration-shifting, vocal output 424
changes over the course of the experiment. The neural network excels at identifying 425
syllables close to its training set, so as vocal output changes the detector may not 426
recognise a match. If the detector must be robust to this shift, it may be retrained as 427
often as necessary as the bird learns, or data consisting of synthetically pitch-shifted 428
or duration-shifted target syllables over the recognition region may be added to the 429
training set. We will test these approaches in future work. 430

5 Acknowledgments 431

We would like to thank William A. Liberti for his improvements to the draft. This 432
work was funded by someone. 433

But by whom?

PLOS doesn't really say where such things should go.

Cleanup: mostly done. But it would be nice to move all this to the lab's github group.

A Resources

Song alignment: Last we checked, Jeff Markowitz's song alignment software could be found at <https://github.com/jmarkow>.

Training the neural network: Our implementation of the syllable detector training code is available under the GNU GPL at: <https://github.com/bwpearre/>

Runtime: The Matlab, Swift, and Labview implementations for executing the trained network: <https://github.com/nathanntg/syllable-detector>

References

1. Kao MH, Doupe AJ, Brainard MS. Contributions of an avian basal ganglia-forebrain circuit to real-time modulation of song. *Letters to Nature*. 2005 February;433:638–643. Available from: <http://www.nature.com/nature/journal/v433/n7026/abs/nature03127.html>.
2. Andalman AS, Fee MS. A basal ganglia-forebrain circuit in the songbird biases motor output to avoid vocal errors. *Proceedings of the National Academy of Sciences of the United States of America*. 2009 July;106(30):12518–12523. Available from: <http://www.ncbi.nlm.nih.gov/pmc/articles/PMC2709669/>.
3. Warren TL, Tumer EC, Charlesworth JD, Brainard MS. Mechanisms and time course of vocal learning and consolidation in the adult songbird. *Journal of Neurophysiology*. 2011 October;106(4):1806–1821. Available from: <http://jn.physiology.org/content/106/4/1806.full>.
4. Canopoli A, Herbst JA, Hahnloser RHR. A Higher Sensory Brain Region Is Involved in Reversing Reinforcement-Induced Vocal Changes in a Songbird. *The Journal of Neuroscience*. 2014;34(20):7018–7026. Available from: <http://www.jneurosci.org/content/34/20/7018.full>.

5. Leonardo A, Konishi M. Decrystallization of adult birdsong by perturbation of
auditory feedback. *Nature*. 1999 June;(399):466–470. Available from:
<http://www.nature.com/nature/journal/v399/n6735/abs/399466a0.html>.
6. Keller GB, Hahnloser RHR. Neural processing of auditory feedback during
vocal practice in a songbird. *Nature*. 2009 January;(457):187–190. Available from:
<http://www.nature.com/nature/journal/v457/n7226/abs/nature07467.html>.
7. Skocik M, Kozhevnikov A. Real-time system for studies of the effects of
acoustic feedback on animal vocalizations. *Frontiers in Neural Circuits*. 2013
January;6(111). Available from:
<http://www.ncbi.nlm.nih.gov/pmc/articles/PMC3539774/>.
8. Poole B, Markowitz JE, Gardner TJ. The Song Must Go On: Resilience
of the Songbird Vocal Motor Pathway. *PLOS One*. 2012 June;7(6). Available from:
<http://journals.plos.org/plosone/article?id=10.1371/journal.pone.0038173>.
9. Hertz JA, Krogh AS, Palmer RG. Introduction to the Theory of Neural
Computation. Perseus Books; 1991.
10. Noll AM. Pitch determination of human speech by the harmonic product
spectrum, the harmonic sum spectrum, and a maximum likelihood estimate;
1970. .