

Architectural Particular Specification

INDOOR MATERIAL QUALITY

SECTION 8.1

Rev	Date	Description
0	14 APR 2022	First Issue

SECTION 8.1

INDOOR MATERIAL QUALITY

PART 1 GENERAL

1.01 SUMMARY OF WORK

- A. This specification shall apply to the following building materials/products which usually involve formaldehyde emissions:-
1. Plywood panels, particle boards, medium-density fibreboards (MDF) and other pressed-wood products involving adhesives;
 2. Paints & Varnishes;
 3. Wall coverings;
 4. Flooring materials, e.g., bamboo / wood-based flooring, etc.
 5. Carpets.

1.02 REFERENCES (NOT USED)

1.03 QUALITY ASSURANCE (NOT USED)

1.04 PERFORMANCE REQUIREMENTS

- A. All indoor decorating & refurbishing materials as well as fixtures shall be in compliance with the following standards or equivalent:-
1. European E0 emission standard.
 2. HKGLS (Hong Kong Green Label Scheme), wherever available.

1.05 ENVIRONMENTAL REQUIREMENTS (NOT USED)

1.06 SUBMITTALS (NOT USED)

1.07 DELIVERY, STORAGE, AND HANDLING (NOT USED)

1.08 MOCK-UPS (NOT USED)

1.09 TESTING (NOT USED)

1.10 WARRANTY (NOT USED)

1.11 SPARE PARTS (NOT USED)

PART 2 PRODUCTS

2.01 MATERIALS

A. Adhesive for Wood / Resin for MDF Panel

All urea formaldehyde bonded MDF (Medium Density Fibreboard) panels and MUF (Moisture resistant panel) mouldings, etc. shall be manufactured with low emission resins conforming to European E0 emission standard unless otherwise approved by the Architect. Stainless Steel Sheets, Strips, Bars and Plates: BS 1449: Part 2: 1983, and BS 4360. Type 316 with 2.5% Molybdenum minimum. Provide sheet of minimum 3.0 mm nominal thickness for exterior work.

B. Wood Chipboard

1. To be low formaldehyde emission wood chipboard (European E0 emission standard), or polyurethane-based chipboard with zero formaldehyde emission.
2. To BS 5669 and BS 1142, or the latest relevant codes.

C. Paints / Varnishes / Coatings

1. All coatings not to be formulated or manufactured with formaldehyde, halogenated or aromatic solvents or heavy metals such as mercury, lead, cadmium and chromium.
2. Water-based, wherever possible.
3. To contain no lead and possess low volatile organic content (VOCs).
4. The VOC content, in grams per litre, of all paints applied on surfaces of building fabrics, building elements and any installations/equipment inside semi-enclosed / enclosed areas of the building shall NOT exceed:-
 - a. Type of Internal Paint
 - Water-based paint: 80 g/litre
 - Solvent-based paint: 450 g/litre
 - b. Type of External Paint
 - Water-based paint: 100 g/litre
 - Solvent-based paint: 450 g/litre
 - c. The VOC content of paint shall be determined either by recognized method of calculation or laboratory testing. Welding Materials: BS 639: 1986 and BS 5135: 1984, type required for materials being welded.
 - d. To HKGLS GL-005-003, European E0 emission standard, or acceptable equivalent.
 - e. With zero formaldehyde emission.
5. Wall Coverings

To be in compliance with the following standards or equivalent, wherever applicable:-

 - a. HKGLS GL-008-003.
 - b. European E0 emission standard.

D. Flooring Materials (Bamboo / Wood-based Flooring, etc. except Carpets)

1. To be in compliance with the following standards or equivalent, wherever applicable:-
 - a. HKGLS GL-088-002.
 - b. European E0 emission standard

PART 3 EXECUTION

3.01 EXAMINATION / INSPECTION
(NOT USED)

3.02 PREPARATION
(NOT USED)

3.03 INSTALLATION
(NOT USED)

3.04 CLEANING
(NOT USED)

3.05 PROTECTION
(NOT USED)

END OF SECTION