

TWO TASKS. ONE SYSTEM.

Test networks with helium — without unnecessary intervention.

No complete draining

Measurable even through PE casing

Free, no-obligation quote →



LEAK LOCATION

Pinpoint the defect

- ✓ during operation
- ✓ no complete draining
- ✓ no exploratory excavation

Even the smallest leaks are detected



TIGHTNESS CONTROL

Assess a test section

- ✓ new and existing networks
- ✓ documented test procedure
- ✓ evidence by prior agreement

Agree criteria before testing starts

HOW THE METHOD WORKS

- 1 Define test section**
Review data and select injection point
- 2 Inject helium**
Bubble-free into the liquid medium
- 3 Measure the route**
Detect and narrow down the release
- 4 Issue the report**
Document findings and assessment

WHY HELIUM? THE PRINCIPLE.

The patented injection unit introduces helium **bubble-free** into the test medium – inside the closed network it stays bound in the medium. Only at the leak does it escape with the medium: on contact with ambient air the helium is released as gas and rises to the surface – **even through PE casings**. At the surface we measure the smallest increases above the natural helium background and pinpoint the leak.

FREE & NO-OBLIGATION QUOTE

Basic site data is all we need – you receive a clear assessment and a no-obligation quote.

Proven method in line with recognized standards (DIN EN ISO 20485 · DIN EN 1779 · AGFW FW 602) · Drinking water: helium listed in Germany's Section 20 list for leak detection.

Mark Schwarze · +49 156 79799100 · info@helium-leckortung.de

helium-leckortung.de · Alter Postweg 80 · 26607 Aurich · Germany